
MyTardis Documentation

Release 4.0.2

Aug 02, 2019

Contents

1	Overview	3
2	Key features for users	5
3	Key features for instrument facilities	7
4	Developing for MyTardis	9
5	Find out more	11
6	Known deployments	13
7	Related projects and repositories	15
8	Releases	17
9	Reporting Bugs	19
10	Contributing	21
11	Documentation	23
11.1	User Guide	23
11.2	Configuration and Administration	42
11.3	Development	62
11.4	Documentation for included Apps	238
11.5	Releases	246
12	Indices and tables	253
	Python Module Index	255
	Index	261

CHAPTER 1

Overview

MyTardis began at Monash University to solve the problem of users needing to store large datasets and share them with collaborators online. Its particular focus is on integration with scientific instruments, instrument facilities and research storage and computing infrastructure; to address the challenges of data storage, data access, collaboration and data publication.

[Read more...](#)

CHAPTER 2

Key features for users

The MyTardis data management platform is a software solution that manages research data and the associated meta-data. MyTardis handles the underlying storage to ensure that data is securely archived and provides access to the data through a web portal. Data hosted in MyTardis can also be accessed via SFTP.

[Read more...](#)

Key features for instrument facilities

MyTardis takes care of distributing data to your users. Its instrument integration technology takes care of securely and automatically shifting data from instrument to repository and makes it accessible by the right users.

[Read more...](#)

CHAPTER 4

Developing for MyTardis

MyTardis is mostly written in the [Python programming language](#) and is built on top of the [Django web framework](#). A complete installation of the service also includes an [Elasticsearch](#) index, a [RabbitMQ](#)-based task queue, an [Nginx](#) server, and a [PostgreSQL](#) database.

To set up and manage these services we employ the [SaltStack](#) orchestration software and cloud technologies.

[Read more...](#)

CHAPTER 5

Find out more

Project homepage <http://mytardis.org>

The source code is hosted at <https://github.com/mytardis/mytardis>

Documentation at <http://mytardis.readthedocs.org> includes

- User documentation
- Administrator documentation
- Developer documentation

The wiki at <https://github.com/mytardis/mytardis/wiki> includes

- Links to MyTardis add-ons, including apps and post-save filters
- Information about MyTardis community events

CHAPTER 6

Known deployments

- **Store.Synchrotron:** <https://store.synchrotron.org.au/>
- **Store.Monash:** <https://store.erc.monash.edu>
- **NIF ImageTrove:** <https://imagetrove.cai.uq.edu.au/>
- **MHTP Medical Genomics:** <https://mhtp-seq.erc.monash.edu/>
- **ANSTO:** <https://tardis.nbi.ansto.gov.au/>
- **Monash MyTardis Demo:** <https://mytardisdemo.erc.monash.edu/>

Related projects and repositories

- **MyData:** <https://github.com/mytardis/mydata>
 - A desktop application for managing uploads to MyTardis
- **NIF ImageTrove:** <https://github.com/NIF-au/imagetrove>
 - A tool for ingesting and archiving NIF datasets, including
 - * Web front end: [MyTardis](#)
 - * A DICOM server: [DICOM ToolKit](#)
 - * A dataset uploader: [imagetrove-uploader](#)
 - * Federated authentication with the Australian Access Federation’s [Rapid Connect](#) service
- **NIF ImageTrove Docker deployment:** <https://github.com/UWA-FoS/docker-mytardis>
 - For ease of deployment, all of ImageTrove’s components are packaged into a Docker container.
- **NIF Trusted Data Repositories:** <https://github.com/NIF-au/TDR>
 - Delivering durable, reliable, high-quality image data

CHAPTER 8

Releases

The default branch on GitHub is `develop`. This is the cutting edge development version. Please DO NOT use this in production, as it may have bugs that eat your data.

The `master` branch is the current stable release with all the latest bugfixes included. It will move to newer versions automatically. Follow this branch if you want to stay up to date in a production environment.

Each version has its own branch named by version number. At the time of writing, the latest release is `4.0.0`, tagged from the `series-4.0` branch. Follow this branch for your production installation and perform version upgrades manually.

Each bugfix or set of fixes bumps the minor version and each new release is tagged, eg. `4.0.1`. Use tagged releases if you are paranoid about changes to the code you have not tested yourself.

To follow development, please see the contributing section below.

CHAPTER 9

Reporting Bugs

Bug reports and feature requests can be made via our [public issue tracker](#).

CHAPTER 10

Contributing

New contributors are always welcome, however all developers should review the [pull-request checklist](#) before making pull requests.

For any wishes, comments, praise etc. either open a GitHub issue or contact us.

Active developers are also welcome to join our Slack team.

Contact details can be found on mytardis.org.

11.1 User Guide

11.1.1 Basics

Organising Data

Data Structure Overview

Data in MyTardis is organised into a uniform hierarchy, which includes Experiments, Datasets and Data Files. Experiments are at the top of the hierarchy and can contain multiple Datasets. Similarly, Datasets can contain multiple Data Files. The hierarchy can be thought of like a directory structure on a typical PC (Fig. 1) in which a the Experiment directory contains multiple Dataset directories, which in turn contain multiple Data Files.

Creating Experiments

1. Navigate to the **My Data** page.
2. Click on the **Create** button to the right of the page.

MyTardis Home About **My Data** Public Data Stats Help

Experiments

1 Experiment You Own

[+ Create](#)

[Collapse all](#) [Expand all](#)

Test Experiment	yesterday	1	0	Private
Download data as .tar				
Peter Capaldi				
Microscopy experiment				
Latest dataset in this experiment				
Dataset 1				

3. Fill in the 'Create Experiment' form. Requires at least a Title and one author.




Fig. 1: Fig. 1. Data hierarchy in MyTardis

MyTardis

HomeAboutMy DataPublic DataStatsHelp

thedoctor

Create Experiment

Title

Test Experiment

Authors

Peter Capaldi

Comma-separated authors and optional emails/URLs

Institution name

Monash University

Description

Microscopy experiment

Save

Cancel

Powered by MyTardis

4. Click **Save**.

Adding Datasets

Datasets always have at least one parent Experiment. To add a dataset to an Experiment:

1. Navigate to the Experiment page into which you would like to add a dataset.
2. Click the **+ Add New** button to the right of the page.

The screenshot shows the 'Test Experiment' page in MyTardis. The top navigation bar includes 'MyTardis', 'Home', 'About', 'My Data', 'Public Data', 'Stats', and 'Help'. The experiment details on the left include 'Microscopy experiment', 'Description', 'Metadata', 'Sharing', and 'Transfer Datasets'. The dataset list on the right shows '1 Dataset' with a search bar and a '+ Add New' button highlighted by a red box.

3. Fill in the 'Add new dataset' form. Note: The 'Description' field is actually the name of the dataset.

The screenshot shows the 'Add new dataset' form. It has three input fields: 'Description' (containing 'Dataset 1'), 'Directory', and 'Instrument'. A 'Save' button is at the bottom.

4. Click **Save**.

Adding Data Files

Data Files can be added to a particular Dataset from the Dataset page.

1. Navigate to the Dataset into which you want to add new files.
2. Click the green **Add files...** button to the right of the page.

MyTardis
Home
About
My Data
Public Data
Stats
Help
thedocter

Dataset
Dataset 1
From the experiment: [Test Experiment](#)

Edit Dataset Description

1 0 0 bytes

Datafile Information
Click the button next to any file to view details and actions.

Dataset Metadata
There is no metadata for this dataset.

Other Experiments
This dataset doesn't appear in any other experiments.

0 Files
Download Dataset: [TAR](#) [SFTP](#) [MD5](#)
Add files...
Search: Enter part or all of a filename, then press ↵
Select: [All](#) / [None](#) [Download Selected Files](#)

Powered by MyTardis

3. Select the files you want to add from the file selector dialog and Click **Open**. You can add multiple files by holding the “Shift” or “Ctrl” keys to select multiple files in the dialog.

Accessing Data

Download a Data File

Individual Data Files can be downloaded as follows:

1. Navigate to the Dataset containing the Data File you want to download.
2. Click the **Download** button on the Data File you want to download.

MyTardis
Home
About
My Data
Public Data
Stats
Help
thedocter

Dataset
Dataset 1
From the experiment: [Test Experiment](#)

Edit Dataset Description

1 4 3.1 GB

Preview Images

cell5_deskewed_C2_T0.ome.tif

4 Files
Download Dataset: [TAR](#) [SFTP](#) [MD5](#)
Add files...
Search: Enter part or all of a filename, then press enter.
Select: [All](#) / [None](#) [Download Selected Files](#)

☐	cell5_deskewed.companion.ome (292.2 KB)			
☐	cell5_deskewed_C0_T0.ome.tif (1.0 GB)			
☐	cell5_deskewed_C1_T0.ome.tif (1.0 GB)			
☐	cell5_deskewed_C2_T0.ome.tif (1.0 GB)			

Datafile Information
Click the button next to any file to view details and actions.

Dataset Metadata
There is no metadata for this dataset.

Download a Dataset

Entire Datasets can be downloaded as a tar archive.

1. Navigate to the Dataset you want to download.
2. Click the **tar** button to the right of the page.

The screenshot shows the MyTardis interface for 'Dataset 1'. The top navigation bar includes 'MyTardis', 'Home', 'About', 'My Data', 'Public Data', 'Stats', and 'Help'. The user 'thedoctor' is logged in. The dataset is from the experiment 'Test Experiment'. It contains 4 files totaling 3.1 GB. The 'Preview Images' section shows a thumbnail of a file named 'cell5_deskewed_C2_T0.ome.tif'. The 'Datafile Information' section has a note: 'Click the [icon] button next to any file to view details and actions.' The 'Dataset Metadata' section states 'There is no metadata for this dataset.' On the right, the '4 Files' section shows download options: 'TAR' (highlighted), 'SFTP', and 'MD5'. Below this is a search bar and a list of files: 'cell5_deskewed.companion.ome' (292.2 KB), 'cell5_deskewed_C0_T0.ome.tif' (1.0 GB), 'cell5_deskewed_C1_T0.ome.tif' (1.0 GB), and 'cell5_deskewed_C2_T0.ome.tif' (1.0 GB). Each file has a checkbox, a download icon, a plus icon, and a list icon.

Note: *tar* is an archive format like *zip* that may not be familiar to Windows users and a default Windows installation may not have the appropriate software to expand *tar* archives. We suggest that users install [7-zip](#) to expand *tar* archives from MyTardis.

Download an Experiment

Entire Experiments can be downloaded as a tar archive.

1. Navigate to the Experiment you want to download.
2. Click the **tar** button under the 'Description' section of the page.

MyTardis Home About My Data Public Data Stats Help thedoctor

Experiment
Test Experiment
Peter Capaldi

Create publication Edit Experiment

1 4 3.1 GB 5th December 2017 Private

Microscopy experiment

Description Metadata Sharing Transfer Datasets

Institution Monash University
Licensing Unspecified
Administrators thedoctor

Download All **TAR** SFTP

1 Dataset **Dataset 1** 3.1 GB

Powered by MyTardis

Note: *tar* is an archive format like *zip* that may not be familiar to Windows users and a default Windows installation may not have the appropriate software to expand *tar* archives. We suggest that users install [7-zip](#) to expand *tar* archives from MyTardis.

Sharing and Publishing Data

MyTardis provides 3 primary mechanisms for sharing your data:

- Sharing with another MyTardis user.
- Sharing via a temporary (obfuscated) link.
- Making data public.

Data sharing is done at the Experiment level and you can find the options to share an Experiment under the **Sharing** tab on the left side of an Experiment page.

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#)[Metadata](#)[Sharing](#)[Transfer Datasets](#)

Public Access

Current Public Access Settings

Private

Current License

Unspecified

[⚙️ Change Public Access](#)

Sharing

Users

Users who have a share in this experiment:

Username	Name
thedoctor	none

[↗️ Change User Sharing](#)

Groups

Groups who have a share in this experiment:

There are currently no groups with access to this experiment.[↗️ Change Group Sharing](#)

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined

[Create New Temporary Link](#)

Sharing Data with Another MyTardis User

To share an Experiment with another MyTardis user:

1. Navigate to the Experiment you want to share.
2. Click on the **Sharing** tab on the left side of the page.
3. Click the **Change User Sharing** button.

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#)[Metadata](#)[Sharing](#)[Transfer Datasets](#)

Public Access

Current Public Access Settings

[Private](#)

Current License

[Unspecified](#)[⚙️ Change Public Access](#)

Sharing

Users

Users who have a share in this experiment:

Username	Name
thedoctor	none

[↪️ Change User Sharing](#)

Groups

Groups who have a share in this experiment:

There are currently no groups with access to this experiment.[↪️ Change Group Sharing](#)

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined

[Create New Temporary Link](#)

4. Enter the **Username** of the user with which you want to share the data.

User Sharing

Current User Permissions

[thedoctor] (doctor@tardis.org) Read Edit Owner Edit Delete

Add new user

Username:

Permissions:

Owners have the ability to change access controls and share experiments with others.

+ Add User

Note: Entering the users name or email address with activate autocomplete, which helps to find the username of the user.

5. Select the permissions you'd like to give the user from the **Permissions** dropdown.
6. Click the **+Add User** button.
7. You should now see a new entry under the **Current User Permissions** section showing the user you've shared the Experiment with and the permissions you've given them.

User Sharing ×

Current User Permissions

[thedoctor] (doctor@tardis.org)	Read	Edit	Owner	Edit	Delete
[rosetyler] (rosetyler@tardis.org)	Read	Edit		Edit	Delete

Add new user

Username:

Permissions:

Owners have the ability to change access controls and share experiments with others.

[+ Add User](#)

Sharing Data via a Temporary Link

You can also share Data in an Experiment via a temporary (obfuscated) link. Temporary links expire after 1 month or can be deleted manually. Note: temporary links are not protected (i.e., anybody with the link can access the data); however, they are obfuscated and are thus difficult to find without prior knowledge of the link.

To share an Experiment via a temporary link:

1. Navigate to the Experiment you want to share.
2. Click on the **Sharing** tab on the left of the page.
3. Click the **Create New Temporary Link** button in the links section.

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared for direct access.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined

[Create New Temporary Link](#)

4. You should now see a new entry in the **Links** section. The new entry will provide links to both the Experiment page and a direct download link. These can be copied to the clipboard using the relevant buttons. These can then be shared with collaborators using email etc.

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared for direct access.

Temporary access links provide full access to recipients regardless of an experiment's public status.

Temporary Link	Archive direct download	Expiry	Granted By
Page link  Copy to clipboard	Archive link  Copy to clipboard	10th January 2018	thedoctor  Delete
Create New Temporary Link			

Publishing Data

Access to an Experiment in MyTardis is set to “private” by default and no license is attached to the data; however, MyTardis allows data from an Experiment to be made publicly available with an appropriate license. To make an Experiment publicly available:

1. Navigate to the Experiment you wish to publish and activate the **Sharing** tab to the left of the page.
2. Click the **Change Public Access** button. This will activate the Public Access dialog and display the current status of the data.
3. Select **Public** in the “Public access” dropdown menu.
4. Select an appropriate license from the list of licenses presented. In the following screenshot, a “Creative Commons Attribution” license is selected; however, your choices may be different as licenses are configured by your service provider.

Public Access

Step 1: Change Public Access:

Public access

Public

Step 2: Select a license:

Creative Commons Attribution 3.0 Australia (CC BY 3.0)

This licence lets others distribute, remix, tweak, and build upon your work, even commercially, as long as they credit you for the original creation. This is the most accommodating of licences offered under Creative Commons.


[Reselect License](#)

Step 3: Accept The Legal Agreement:

Monash University (ABN 12 377 614 012) ("University") maintains a digital repository ("Repository") in which it stores and makes available various works via the Internet or other electronic means.

By submitting material for the Repository ("Work") the person(s) submitting the Work ("Depositor") agree to the following terms and conditions:

5. Agree to the "Terms of Publishing" of your service provider.
6. Click **Confirm**

11.1.2 SFTP Access

SFTP is a secure and convenient way to access, browse and download large Experiments, Datasets and Files in MyTardis. Importantly, the SFTP interface to MyTardis is read only i.e., it is a mechanism to access data in MyTardis but does **not** allow adding data to MyTardis.

Prerequisites for accessing data via SFTP

In order to access data on MyTardis via SFTP, you will first need to install an SFTP client. There are many free and commercial SFTP clients for you to choose from; however, we recommend [Cyberduck \(Win & Mac\)](#), [FileZilla \(All platforms\)](#) or [WinSCP \(Win only\)](#) for the majority of users. The instructions here will focus on [Cyberduck \(Win & Mac\)](#).

Registering and managing SSH keys in MyTardis

MyTardis uses SSH key pairs to authenticate you when connecting via SFTP. Using SSH keys to authenticate is more secure and private than password-based authentication. SSH keys generally come in a pair: (1) a private part and (2) a public part. Key-based authentication typically requires you to share your public key with the service, again which you use your private key to authenticate. Never share your private key!

MyTardis provide to mechanism for registering a public key:


1. *Adding an existing public SSH key to MyTardis*
2. *Have MyTardis to generate an SSH key pair*

Adding an existing public SSH key to MyTardis


If you have an existing SSH keypair, you can register the public key in MyTardis. For instructions on how to create an SSH key pair, Gitlab provide some nice documentation on how to do so [here](#).

To register a public key in MyTardis:

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the + *Add Key* button:



3. Fill in the *Add SSH Keys* form by entering a name for the key and the public key text. The public key text should be in OpenSSH format e.g., `ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQADYznXpTP6e/BsQw+...`

Add SSH Keys ✕

Add your own public SSH Key using the form below. **Important:** Don't add your private key.

Device Name:

Public Key:

```
ssh-rsa
AAAAB3NzaC1vc2EAAAADAQABAAQBAQDYZYnXpTP6e/BsQw+QEVdtpvdKJV2pxc9Q
DlSipqsV464bxerFs7+deNSHlpJiHy7zBO4zbzGd2vE2wuxXa02tGRwKqhQm3/fFRH6ZL4
pfJ/tkasYd7i5sAIKlkh0tPVVU+6HYbNbNjN+riIYh16ECrp7+YmtwPwVieeiTn69cSTkG+way
TFXwO6M3dolb/SMY8zE5JMotVnqxBJTwNwpQZHmQW4eh87eIHbv7QrtRF7ws/Ph6ME
Bpy1A9V118ysBKMG4YxybxGuwOOMDAOI/2RhqMGV1MPXlulshIOAy9vrYCeS40AukYjE
```

Close Add Key

4. Click the *Add Key* button.

If successful you should get a new entry in the SSH keys table.

MyTardis Home About My Data Public Data Stats Help

SSH Keys

Add and manage your public SSH keys for accessing MyTardis via SFTP.

+ Add key + Generate key

Key
massive Delete Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-07


Have MyTardis to generate an SSH key pair

Creating SSH key pairs can be a bit of a challenge, particularly on Windows systems. For this reason, MyTardis provides another you another option for registering a public keys. In this case, MyTardis will generate the key pair for


you, store the public part of the key and provide you with a one time opportunity to download the private part of the key.

It is important to note that MyTardis never stores your private key. If you lose/delete it, MyTardis cannot recover it for you. This isn't really a problem, since MyTardis can always generate another key pair for you; however, you should revoke the public key associated to the lost private key in your account to ensure that no one who gains access to your private key can access your data. See [Deleting previously registered public keys in MyTardis](#).

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the + *Generate key* button:



3. Give the key a name and click the *Generate & Download* button. The server will generate an SSH key pair, register the public key and trigger your browser to download the private key.

SFTP:

Generate an SSH key pair ×

MyTardis can generate an SSH key pair for you. Only the public part of the key pair will be stored by MyTardis and you will be provided with a one time opportunity to download the private part of the key pair.

Name:

Important: Keep your private key in a safe place. Anyone with access to the private key will be able to access your data on MyTardis.

- The SSH keys table will be updated with your newly registered public key.

MyTardis
Home
About
My Data
Public Data
Stats
Help

SSH Keys


Add and manage your public SSH keys for accessing MyTardis via SFTP.

Key
massive Delete Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-07
TestKey Delete Type: SSH-RSA Fingerprint: 3c4c3c3eb293d274fbeb687cc46aff76 Date added: 2018-08-07

Deleting previously registered public keys in MyTardis

Removing a previously registered public SSH key from MyTardis is straightforward.

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the *Delete* button on the key you wish to remove.

MyTardis Home About My Data Public Data Stats Help

SSH Keys

Add and manage your public SSH keys for accessing MyTardis via SFTP.

[+ Add key](#) [+ Generate key](#)

Key	
massive Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-08	Delete
TestKey Type: SSH-RSA Fingerprint: e27936d5ccac5b7e5af83cefb29f01f0 Date added: 2018-08-09	Delete


Attempting to connect to MyTardis via SFTP using the private sister key to the deleted key will no longer work.

Connecting to MyTardis via SFTP

1. Open your SFTP client and create a new connection with the following configuration:

Parameter	Value
Server:	<i>URL for your MyTardis deployment e.g. https://store.erc.monash.edu</i>
Port:	<i>Port on which SFTP server is running</i>
Username:	<i>Your MyTardis username</i>
Password:	<i>Leave this blank</i>
SSH Private Key	<i>Path to a private SSH key¹</i>

Note: substitute your credentials and details for your MyTardis deployment for the *italicised* values. If you are unsure about any of these value, please contact your system admin should be able to provide these to you.



2. Click **Connect**

3. Upon successful connection you will be presented with a file browser showing all your data on MyTardis.

Data is organised according to the Experiment/Dataset/Data File hierarchy/structure described in the [Organising Data](#) section.

Browse and/or Download a Specific Experiment or Dataset

MyTardis also provides a convenient way to access/browse a particular Experiment or Dataset via SFTP.

1. Navigate to the Experiment or Dataset page that you want to access via SFTP using your web browser.
2. There is an **SFTP** button in the *Download* section on both the Experiment and Dataset views.

¹ You must register the public key in MyTardis first, see [Registering and managing SSH keys in MyTardis](#)

Experiment View

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#) [Metadata](#) [Sharing](#) [Transfer Datasets](#)

Institution Monash University

Licensing Unspecified

Administrators Peter Capaldi

Download All [TAR](#) [SFTP](#)

Dataset View

4 Files

Download Dataset: [TAR](#) [SFTP](#) [MD5](#)[Add files...](#)

Search: Enter part or all of a filename, then press enter.

Select: [All](#) / [None](#)[Download Selected Files](#)

☐	cell5_deskewed.companion.ome (292.2 KB)	Download + List
☐	cell5_deskewed_C0_T0.ome.tif (1.0 GB)	Download + List
☐	cell5_deskewed_C1_T0.ome.tif (1.0 GB)	Download + List
☐	cell5_deskewed_C2_T0.ome.tif (1.0 GB)	Download + List

- Clicking the **SFTP** button at either of these two locations will redirect you to a page with instructions and links for starting an SFTP session for a specific experiment or dataset.

11.2 Configuration and Administration

11.2.1 Installation

The sections through to Extended Configuration below provide a Quick Start guide for getting a basic MyTardis installation up and running. The following section provides additional information on advanced configuration and add-on capabilities of MyTardis.

Prerequisites

Ubuntu (18.04 LTS is recommended)

Run the script:

```
sudo bash install-ubuntu-requirements.sh
```

It will install required packages with this command:

```
# for Ubuntu 16.04 or 18.04
# sudo bash install-ubuntu-requirements.sh

apt-get update
apt-get install git libldap2-dev libmagickwand-dev libsasl2-dev \
  libssl-dev libxml2-dev libxslt1-dev libmagic-dev curl gnupg \
  python-dev python-pip python-virtualenv virtualenvwrapper \
  zlib1g-dev libfreetype6-dev libjpeg-dev

curl -sL https://deb.nodesource.com/setup_10.x | sudo -E bash -
sudo apt-get install -y nodejs
```

Download

To get the most recent stable release:

```
git clone -b master https://github.com/mytardis/mytardis.git
cd mytardis
```

This clones the repository as read-only.

Or, to get the current development branch:

```
git clone -b develop git://github.com/mytardis/mytardis.git
cd mytardis
```

Quick configuration

It is recommended that you use a virtualenv. The list of packages above includes the `virtualenvwrapper` toolkit. Set up your environment with these commands:

Ubuntu 18.04:

```
source /etc/bash_completion.d/virtualenvwrapper
```

For Ubuntu 16.04:

```
source /usr/share/virtualenvwrapper/virtualenvwrapper.sh
```

Then create the mytardis virtual environment

```
mkvirtualenv mytardis
pip install -U pip
```

Note: the next time you want to work with this virtualenv, run the appropriate `source` command and then use the command: `workon mytardis`

MyTardis dependencies are then installed with pip:

```
pip install -U -r requirements.txt
```

To install minimal Javascript dependencies for production:

```
npm install --production
```

To install Javascript dependencies for production and for testing:

```
npm install && npm test
```

Configuring MyTardis is done through a standard Django *settings.py* file. MyTardis comes with a set of default settings in its `tardis/default_settings/` package. You can import this as the basis of your own config file - options defined here will override the relevant options in `default_settings/*.py`.

Create a new file `tardis/settings.py` containing the following:

```
from .default_settings import *

# Add site specific changes here.
```

(continues on next page)

(continued from previous page)

```
# Turn on django debug mode.
DEBUG = True

# Use the built-in SQLite database for testing.
# The database needs to be named something other than "tardis" to avoid
# a conflict with a directory of the same name.
DATABASES['default']['ENGINE'] = 'django.db.backends.sqlite3'
DATABASES['default']['NAME'] = 'tardis_db'
```

In addition you will need to create a new SECRET_KEY for your installation. This is important for security reasons.

A convenient method is to run the following command in your mytardis installation location:

```
python -c "import os; from random import choice; key_line = '%sSECRET_KEY=\"%s\"' % ('from .default_settings import * \n\n' if not os.path.
↳ isfile('tardis/settings.py') else '', ''.join([choice(
↳ 'abcdefghijklmnopqrstuvwxyz0123456789@#%^&*(_+=)') for i in range(50)])); f=open(
↳ 'tardis/settings.py', 'a+'); f.write(key_line); f.close()"
```

This is the minimum set of changes required to successfully run the server in development mode. You can make any other site-specific changes as necessary.

Initialisation

Create and configure the database:

```
python manage.py migrate
python manage.py createcachetable default_cache
python manage.py createcachetable celery_lock_cache
```

This avoids creating a superuser before the MyTardis specific `UserProfile` table has been created. More information about the migrate commands can be found at [Configuration and Administration](#).

Next, create a superuser:

```
python manage.py createsuperuser
```

MyTardis can now be executed in its simplest form using:

```
python manage.py runserver
```

This will start the Django web server at <http://localhost:8000/>.

Extended configuration

See below for some extra configuration options that are specific to MyTardis.

An automatically generated documentation of the settings can be found in *tardis package*.

Essential Production Settings

When deploying to production, you should read Django's [deployment checklist](#).

Warning: MyTardis’s built-in default settings don’t include all of the settings required to run a secure (HTTPS) deployment. Django provides a check command which you can run on your production (or pre-production) server to help you to identify missing settings related to security:

```
./manage.py check --deploy
```

The following settings are essential if you want to run MyTardis in production.

DEBUG

This must be set to False for production, otherwise your users will see tracebacks containing sensitive information when they encounter an unhandled exception (Internal Server Error).

Warning: After setting DEBUG to False, unhandled exceptions will trigger Internal Server Error emails to **ADMINS** which does not scale well. Django suggests “using an error monitoring system such as Sentry before your inbox is flooded by reports”.

SECRET_KEY

This key needs to be unique per installation and, as the name implies, be kept secret.

A new one can be conveniently generated with the command:

```
echo "SECRET_KEY=`python manage.py generate_secret_key`" >> tardis/settings.py
```

ALLOWED_HOSTS

ALLOWED_HOSTS is a list of hostnames and/or IP addresses under which the server is accessible. If this is not set you will get a 500 Error for any request, due to Django raising a SuspiciousOperation exception. For more information, see: <https://docs.djangoproject.com/en/1.11/ref/settings/#allowed-hosts>

Database

tardis.default_settings.DATABASE_ENGINE

The database server engine that will be used to store the MyTardis metadata, possible values are *postgresql_psycopg2*, *postgresql*, *mysql*, *sqlite3* or *oracle*.

tardis.default_settings.DATABASE_NAME

The name of the database to used to store the data, this is the path to the database if you are using the SQLite storage engine.

tardis.default_settings.DATABASE_USER

The user name used to authenticate to the database. If you are using SQLite this field is not used.

tardis.default_settings.DATABASE_PASSWORD

The password used to authenticate to the database. If you are using SQLite this field is not used.

tardis.default_settings.DATABASE_HOST

The host name of the machine hosting the database service. If this is empty then localhost will be used. If you are using SQLite then this field is ignored.

tardis.default_settings.DATABASE_PORT

The port the database is running on. If this is empty then the default port for the database engine will be used. If you are using SQLite then this field is ignored.

LDAP

For further information see [LDAP authentication](#)

Repository

`tardis.default_settings.DEFAULT_STORAGE_BASE_DIR`

The path to the default MyTardis storage location. This is where files will be stored to if you do not provide any other location explicitly through “StorageBox”es.

`tardis.default_settings.REQUIRE_DATAFILE_CHECKSUMS`

If True, a Datafile requires an MD5 or SHA-512 checksum from the time it is first recorded in the MyTardis database. This enables a model-level constraint check each time a Datafile record is saved. Defaults to True. Datafile record is saved.

`tardis.default_settings.REQUIRE_DATAFILE_SIZES`

If True, a Datafile require a size from the time it is first recorded in the MyTardis database. This enables a model-level constraint check each time a Datafile record is saved. Defaults to True.

`tardis.default_settings.REQUIRE_VALIDATION_ON_INGESTION`

If True, ingestion of a Datafile is only permitted if the Datafile matches its supplied size and/or checksums. Defaults to True.

Access Rights & Licensing

Licences

By default, no licences are loaded. A user can make metadata public without assigning a licence, but they cannot allow public access to their data.

Creative Commons licences (for Australia) are available in `tardis/tardis_portal/fixtures/cc_licenses.json`. You can load them with `python manage.py loaddata`.

You can use the admin interface to add other licences. Please ensure `allows_distribution` is set to the correct value to ensure the licence appears in conjunction with suitable public access types.

Legal Notice

When changing the public access rights or licence for an experiment, a legal notice is displayed. You can override it by either:

1. creating a new app (probably your site theme) and putting your legal text in `tardis/apps/<app_name>/static/publishing_legal.txt`, or
2. directly making changes to `tardis/tardis_portal/static/publishing_legal.txt`.

Filters

`tardis.default_settings.POST_SAVE_FILTERS`

This contains a list of post save filters that are execute when a new data file is created.

The `POST_SAVE_FILTERS` variable is specified like:

```
POST_SAVE_FILTERS = [
    ("tardis.tardis_portal.filters.exif.EXIFFilter", ["EXIF", "http://exif.schema
↪"]),
]
```

For further details please see the *Filter Setup* section.

Archive Organizations

tardis.default_settings.DEFAULT_ARCHIVE_FORMATS.

This is a prioritized list of download archive formats to be used in contexts where only one choice is offered to the user; e.g. the “download selected” buttons. (The list allows for using different archive formats depending on the user’s platform.)

tardis.default_settings.DEFAULT_PATH_MAPPER.

This gives the default archive “organization” to be used. Organizations are defined via the next attribute.

tardis.default_settings.DOWNLOAD_PATH_MAPPERS.

This is a hash that maps archive organization names to Datafile filename mapper functions. These functions are responsible for generating the archive pathnames used for files written to “tar” and “zip” archives by the downloads module.

The **DOWNLOAD_PATH_MAPPERS** variable is specified like:

```
DOWNLOAD_PATH_MAPPERS = {
    'test': ('tardis.apps.example.ExampleMapper',),
    'test2': ('tardis.apps.example.ExampleMapper', {'foo': 1})
}
```

The key for each entry is the logical name for the organization, and the value is a tuple consisting of the function’s pathname and a set of optional keyword arguments to be passed to the function. At runtime, the function is called with each Datafile as a positional argument, and an additional ‘rootdir’ keyword argument. The function should compute and return a (unique) pathname based on the Datafile and associated objects. If the function returns **None**, this tells the archive builder to leave out the file.

By default, the archive builder uses the built-in “deep-storage” mapper which gives pathnames that try to use directory information to rebuild a file tree.

Storage Locations (**StorageBox** es)

A MyTardis instance can be configured to support multiple locations (**StorageBox** es) for storing data files. Each location holds copies (**DataFileObject** s) of **DataFile** s that are recorded in the MyTardis database.

The **StorageBox** architecture is compatible with the [Django File Storage API](#). This makes it relatively easy to support a number of different storage backends such as cloud storage or SFTP servers. Please refer to the *StorageBox documentation* for more detailed information.

Single Search

Instructions on installing and configuring Elasticsearch for advanced search are available from *Setting Up Search*.

Additional Tabs

Additional and custom tabs may be configured in MyTardis on a per-installation basis. The tabs are implemented as separate Django applications with a single view (index), listed in the `TARDIS_APPS` configuration item and either linked to, or installed in the `TARDIS_APP_ROOT` directory, by default `tardis/apps`.

Documentation on the additional tabs is available from [Apps and Contextual Views](#).

Additional Views

Custom views may be configured in MyTardis on a per-installation basis. The tabs are implemented as separate Django applications with a single view function listed in the `*_VIEWS` configuration item and added to the `INSTALLED_APPS` list.

Refer to the [views documentation](#) for further information.

Site Customisations

Some settings that allow customised messages and styles.

```
PUBLICATION_INTRODUCTION = """
<p><strong>... introduction and publication agreement ...</strong></p>
"""
SITE_STYLES = '' # should be CSS

# if either GA setting is empty, GA is disabled
GOOGLE_ANALYTICS_ID = '' # whatever Google provides
GOOGLE_ANALYTICS_HOST = '' # the host registered with Google

# these refer to any template finder findable location, e.g. APPDIR/templates/...
CUSTOM_ABOUT_SECTION_TEMPLATE = 'tardis_portal/about_include.html'
CUSTOM_USER_GUIDE = 'user_guide/index.html'
```

Deployment

Collecting Static Files

For performance reasons you should avoid static files being served via the application, and instead serve them directly through the webserver.

To collect all the static files to a single directory:

```
python manage.py collectstatic
```

`tardis.default_settings.STATIC_ROOT`

This contains the location to deposit static content for serving.

`tardis.default_settings.STATIC_URL`

The path static content will be served from. (eg. `/static` or `http://mytardis-resources.example.com/`)

See also:

`collectstatic`, `STATIC_ROOT`, `STATIC_URL`

Serving with Nginx + Gunicorn

In this configuration, Nginx serves static files and proxies application requests to a Gunicorn server:



Nginx should then be configured to send requests to the server. Here is an example configuration (SSL part from Mozilla SSL configurator). Please amend for your own needs and understand the settings before deploying it.:

```

upstream mytardis {
    server unix:/var/run/gunicorn/mytardis/socket;
    server 127.0.0.1:8000 backup;
}
server {
    listen 80 default_server;
    server_name demo.mytardis.org;
    return 301 https://$server_name$request_uri;
}

server {
    listen 443 default_server ssl;
    server_name demo.mytardis.org;

    # certs sent to the client in SERVER HELLO are concatenated in ssl_certificate
    ssl_certificate /path/to/signed_cert_plus_intermediates;
    ssl_certificate_key /path/to/private_key;
    ssl_session_timeout 5m;
    ssl_session_cache shared:SSL:50m;

    # Diffie-Hellman parameter for DHE ciphersuites, recommended 2048 bits
    ssl_dhparam /path/to/dhparam.pem;

    # intermediate configuration. tweak to your needs.
    ssl_protocols TLSv1.1 TLSv1.2;
    ssl_ciphers 'ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-
↪AES256-GCM-SHA384:ECDHE-ECDSA-AES256-GCM-SHA384:DHE-RSA-AES128-GCM-SHA256:DHE-DSS-
↪AES128-GCM-SHA256:kEDH+AESGCM:ECDHE-RSA-AES128-SHA256:ECDHE-ECDSA-AES128-
↪SHA256:ECDHE-RSA-AES128-SHA:ECDSA-AES128-SHA:ECDSA-AES128-SHA:ECDSA-AES256-SHA384:ECDHE-
↪ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA:ECDSA-AES256-SHA:DHE-RSA-AES128-
↪SHA256:DHE-RSA-AES128-SHA:DHE-DSS-AES128-SHA256:DHE-RSA-AES256-SHA256:DHE-DSS-
↪AES256-SHA:DHE-RSA-AES256-SHA:DES-CBC3-SHA:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!
↪PSK:!aECDH:!EDH-DSS-DES-CBC3-SHA:!EDH-RSA-DES-CBC3-SHA:!KRB5-DES-CBC3-SHA';
    ssl_prefer_server_ciphers on;

    # HSTS (ngx_http_headers_module is required) (15768000 seconds = 6 months)
    add_header Strict-Transport-Security max-age=15768000;

    # OCSP Stapling ---
    # fetch OCSP records from URL in ssl_certificate and cache them
    ssl_stapling on;
    ssl_stapling_verify on;

    ## verify chain of trust of OCSP response using Root CA and Intermediate certs
    ssl_trusted_certificate /path/to/root_CA_cert_plus_intermediates;

```

(continues on next page)

(continued from previous page)

```
resolver <IP DNS resolver>;

client_max_body_size 4G;
keepalive_timeout 5;

gzip off; # security reasons
gzip_proxied any;
# MyTardis generates uncompressed archives, so compress them in transit
gzip_types application/x-javascript text/css;
gzip_min_length 1024;
gzip_vary on;

location / {
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header X-Forwarded-Proto $scheme;
    proxy_set_header Host $http_host;
    proxy_redirect off;
    proxy_pass http://mytardis;
    client_max_body_size 4G;
    client_body_buffer_size 8192k;
    proxy_connect_timeout 2000;
    proxy_send_timeout 2000;
    proxy_read_timeout 2000;
}

location /static/ {
    expires 7d;
    alias /srv/static_files/;
}
}
```

The X-Forwarded-Proto header is explained in <http://docs.gunicorn.org/en/stable/deploy.html#id5>:

It is recommended to pass protocol information to Gunicorn. Many web frameworks use this information to generate URLs. Without this information, the application may mistakenly generate ‘http’ URLs in ‘https’ responses, leading to mixed content warnings or broken applications.

To tell MyTardis to set this header in its HTTP requests and redirects, you’ll need the following in your `settings.py`:

```
SECURE_PROXY_SSL_HEADER = ('HTTP_X_FORWARDED_PROTO', 'https')
```

For more information, including warnings on the risks of misconfiguring this setting, see: <https://docs.djangoproject.com/en/1.11/ref/settings/#secure-proxy-ssl-header>

Don’t forget to create the static files directory and give it appropriate permissions. The location is set in the `settings.py` file.

```
# Collect static files to ``settings.STATIC_ROOT``
python manage.py collectstatic
# Allow Nginx read permissions
setfacl -R -m user:nginx:rx static_dir
```

See also:

[Django with Gunicorn](#)

Serving with Apache HTTPD + mod_wsgi

We do not support the use of Apache. If you need this and want to support this use case, we welcome your contribution of any relevant documentation.

Creating Systemd Services for Gunicorn and Celery

Gunicorn is a Python WSGI HTTP Server which is suitable for production (when combined with NGINX). Gunicorn is typically run from a Systemd service (on Ubuntu 16.04 or Ubuntu 18.04), saved in */etc/systemd/system/gunicorn.service*:

```
[Unit]
Description=gunicorn daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/gunicorn \
  -c gunicorn_settings.py -b unix:/tmp/gunicorn.socket \
  -b 127.0.0.1:8000 \
  --log-syslog \
  wsgi:application

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Gunicorn service would be configured in */etc/supervisor/conf.d/gunicorn.conf*:

```
[program:gunicorn]
command=/home/mytardis/.virtualenvs/mytardis/bin/gunicorn
  -c /home/mytardis/mytardis/gunicorn_settings.py
  -b unix:/tmp/gunicorn.socket
  -b 127.0.0.1:8000
  --log-syslog
  wsgi:application
user=mytardis
stdout_logfile=/var/log/gunicorn.log
redirect_stderr=true
```

A single server MyTardis deployment requires only one Gunicorn service, but MyTardis can be installed on multiple web nodes, each running NGINX and Gunicorn to accomodate load balancing and high availability using HAProxy.

The Celery workers which run MyTardis asynchronous tasks also require a service configuration, which is typically implemented with Systemd (on Ubuntu 16.04 or Ubuntu 18.04), saved in */etc/systemd/system/celeryworker.service*:

```
[Unit]
Description=celeryworker daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
```

(continues on next page)

(continued from previous page)

```
Environment=DJANGO_SETTINGS_MODULE=tardis.settings
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/celery worker \
  -A tardis.celery.tardis_app \
  -c 2 -Q celery,default -n "allqueues.%%h"

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Celery worker service would be configured in */etc/supervisor/conf.d/celeryworker.conf*:

```
[program:celeryd]
environment=
  DJANGO_SETTINGS_MODULE=tardis.settings
command=/home/mytardis/.virtualenvs/mytardis/bin/celery worker
  -A tardis.celery.tardis_app
  -c 2 -Q celery,default -n "allqueues.%%h"
user=mytardis
directory=/home/mytardis/mytardis
stdout_logfile=/var/log/celeryd.log
redirect_stderr=true
killasgroup=true
stopwaitsecs=600
```

For tasks scheduled by Celerybeat, the Systemd service configuration (for Ubuntu 16.04 or Ubuntu 18.04), is saved in */etc/systemd/system/celerybeat.service*:

```
[Unit]
Description=celerybeat daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
Environment=DJANGO_SETTINGS_MODULE=tardis.settings
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/celery beat \
  -A tardis.celery.tardis_app --loglevel INFO

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Celerybeat service would be configured in */etc/supervisor/conf.d/celerybeat.conf*:

```
[program:celerybeat]
environment=
  DJANGO_SETTINGS_MODULE=tardis.settings
command=/home/mytardis/.virtualenvs/mytardis/bin/celery beat
  -A tardis.celery.tardis_app --loglevel INFO
user=mytardis
directory=/home/mytardis/mytardis
stdout_logfile=/var/log/celerybeat.log
redirect_stderr=true
```

11.2.2 Authentication Methods

Users

MyTardis supports several sources of authentication and identity, referred to as user providers.

In the *settings.py* user providers are activated by specifying them within the **USER_PROVIDERS** variable:

```
USER_PROVIDERS = ('tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider',)
```

Groups

MyTardis also supports several sources for group membership information, referred to as group providers.

In the *settings.py* group providers are activated by specifying them within the **GROUP_PROVIDERS** variable:

```
GROUP_PROVIDERS = ('tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider',
                   'tardis.tardis_portal.auth.vbl_auth.VblGroupProvider',)
```

Included Auth Plugins

HTTP Basic Endpoint Authentication

`tardis.tardis_portal.auth.httpbasicendpoint_auth`

HTTP Basic Endpoint authentication uses access to a HTTP resource (or endpoint) to determine if authentication should be allowed.

To use HTTP Basic Endpoint authentication, you'll need a HTTP resource protected by HTTP Basic Auth which is accessible from the MyTardis server.

In the *settings.py* add the following to **AUTH_PROVIDERS** with an appropriate name. eg.

```
AUTH_PROVIDERS = (
    ('acls', 'acls', 'tardis.tardis_portal.auth.httpbasicendpoint_auth.
↪HttpBasicEndpointAuth'),
)
```

On each request, MyTardis will attempt to use basic authentication with the provided credentials to access the HTTP resource. If it fails, access is denied.

Endpoint to use in HTTP Basic Endpoint Auth. eg.

```
HTTP_BASIC_AUTH_ENDPOINT = 'https://test.example/endpoint'
```

LDAP Authentication

`tardis.tardis_portal.auth.ldap_auth`

To enable LDAP you'll need to specify which components of the LDAP authentication backend are enabled. In the *settings.py* add the following to either Authentication, User Provider, Group Provider slugs.:

```
'tardis.tardis_portal.auth.ldap_auth.ldap_auth'
```

This is a wrapper function that allows initialisation of the LDAP provider using *settings.py* values.

ldap_auth() Function

The following are configuration settings that are used when initialising the LDAP backend.

`tardis.default_settings.LDAP_TLS`

Enable TLS connections.

`tardis.default_settings.LDAP_URL`

Set the URL of the LDAP server, e.g. `ldap://localhost:389/`

`tardis.default_settings.LDAP_USER_LOGIN_ATTR`

Set the login attribute of the users, usually this will be either *cn* or *uid*

`tardis.default_settings.LDAP_USER_ATTR_MAP`

The LDAP user attribute map is used to map internal identifiers like *first_name*, *last_name* and *email* to their LDAP equivalents e.g. `{"givenName": "first_name", "sn": "last_name", "mail": "email"}`

`tardis.default_settings.LDAP_GROUP_ID_ATTR`

This is where you specify the group identifier from LDAP, usually it will be *cn*.

`tardis.default_settings.LDAP_GROUP_ATTR_MAP`

This map is used to map internal identifiers like *display* e.g. `{"description": "display"}`

`tardis.default_settings.LDAP_BASE`

Sets the search base of the LDAP queries *dc=example, dc=com*

`tardis.default_settings.LDAP_USER_BASE`

Sets the suffix to append to the user RDN (e.g. *uid=jsmith*) to construct the DN e.g. `"ou=People, " + LDAP_BASE`

`tardis.default_settings.LDAP_GROUP_BASE`

Sets the suffix to append to the group RDN (e.g. *cn=group1*) to construct the DN e.g. `"ou=Group, " + LDAP_BASE`

Temporary Token Authentication

`tardis.tardis_portal.auth.token_auth`

To use token authentication, you'll need to specify the following *settings.py*

`'tardis.tardis_portal.auth.token_auth.TokenGroupProvider',`

`TOKEN_EXPIRY_DAYS = 30`

`TOKEN_LENGTH = 30`

`TOKEN_USERNAME = 'tokenuser'`

and create a user with

`bin/django createtokenuser`

Cleaning up

`bin/django cleanuptokens`

It is recommended that you schedule regular purging of expired tokens. Set a cronjob to run `bin/django cleanuptokens`

Expiry

Token auth works by hijacking the group provider system.

MyTardis groups are calculated and cached when a user logs in.

This means that if a session is active, and a token becomes invalid (either through deletion or expiry) that access will still be granted. To mitigate this, when a token user logs in, an explicit expiry is set on their session - the earlier of 4am the next day, or the session expiry date (the end of the day)

This forces the user to attempt to log in again, and be denied access.

- `tardis.tardis_portal.auth.ip_auth`

The *tardis.tardis_portal.auth* package module contains the authentication specific code.

11.2.3 Filter Setup

filters

Filters are called once an object has been saved to the database. They build on the [Django Signals Infrastructure](#).

In the *settings.py* file filters are activated by specifying them within the `POST_SAVE_FILTERS` variable, for example

```
POST_SAVE_FILTERS = [
    ("tardis.tardis_portal.filters.exif.EXIFFilter",
     ["EXIF", "http://exif.schema"]),
]
```

The format they are specified in is

```
(<filter class path>, [args], {kwargs})
```

Where `args` and `kwargs` are both optional.

11.2.4 Database

Initialising

When creating a new database the `migrate` command will need to be called to initialise the schema and insert the initial data fixtures.

Usage

```
python manage.py migrate
```

Migrating

Some of the upgrades to MyTardis will require that the database schema be upgraded to match the internal data model. The `migrate` command migrates data from old database schemas to the current one. It detects which version of the database you are currently running and will automatically migrate to the current version.

In certain cases it is also necessary to update the permissions table.

Usage

```
python manage.py migrate
```

If the model changes require it, run:

```
python manage.py update_permissions
```

creating superuser

After success of database initialization or migration, please use a command line utility called `createsuperuser` to create an administrator account using the admin site which is hooked to the URL `/admin/`.

Usage

```
python manage.py createsuperuser
```

Backup

Previous versions of MyTardis included a `backupdb` management command but it has been removed in 4.0. Please use the recommended backup tool for your database engine, e.g. `pg_dump` or `mysqldump`.

11.2.5 Schema and Parameter Sets

MyTardis stores metadata as *Parameters*, which are grouped in to *Parameter Sets*, which are defined by a *Schema*.

Managing Schema

Schema are managed through the Django administrative interface. The administrative interface is normally accesible from a link similar to:

```
http://domain.com:8000/admin/
```

Selecting “Schemas” in the adminstrative interface will display a list of the installed schemas. Clicking on a schema displays the editor for that schema.

Schema definitions are the combination of two tables, *Schema* and *ParameterName*.

The *Schema* fields are:

Namespace The namespace uniquely identifies the schema. When exporting an experiment as a METS file the namespace is used as an XML Namespace, and thus must follow the XML standard, i.e. in the form of a URL.

The MyTardis naming convention is:

```
http://domain.com/localidentifiers/schemaname/version
```

Name The display name of the schema.

Type Experiment, Dataset or Datafile.

Subtype Used to group and identify schema for forms based searching.

The *ParameterName* fields are:

Schema The namespace of the schema which this parameter belongs to.

Name The identifier used to ingest parameters.

Full Name The display name of the parameter.

Units The display name of the units for numerical values.

Data Type One of:

- Numeric
- String
- Longstring
- URL
- Filename
- Datetime
- Link

Strings use the input field widget for editing, while longstrings use a textarea widget.

Immutable If true, no user editing of the parameter is allowed, regardless of access.

Comparison Type The type of search to be performed with Forms Based Search. Not used by Advanced Search.

Is Searchable Flag whether this parameter is searchable.

Choices If defined, a drop down list of values is displayed.

Order The display order of the parameters within the schema. Sorting is by Order, then alphabetically.

11.2.6 Setting Up Search

Tardis comes with a single search option which provides users with a search field that returns a list of matching Experiments, Datasets and Datafiles.

The single search box uses Elasticsearch, with a django-haystack frontend, and accordingly requires some setup. The single search box is disabled by default.

Setting up Elasticsearch

Elasticsearch doesn't work out of the box with MyTardis. It is not currently installed with pip and requires a number of manual steps to get working.

Elasticsearch can be found here: <https://www.elastic.co/products/elasticsearch>

The following are a very simple list of steps that will get everything up and running. It is advisable to follow up with the person responsible for overseeing security policy at your home institution to see if any extra setup is necessary.

Django Configuration

Enabling Single Search

A list of default settings for Single Search are already in `default_settings.py` in the MyTardis repository. Single search is enabled by setting the `SINGLE_SEARCH_ENABLED` option to `True`.

Other settings are shown below:

HAYSTACK_CONNECTIONS

The default value is

```
HAYSTACK_CONNECTIONS = {
    'default': {
        'ENGINE': 'haystack.backends.elasticsearch_backend.'
                  'ElasticsearchSearchEngine',
        'URL': 'http://127.0.0.1:9200/',
        'INDEX_NAME': 'haystack',
    },
}
```

HAYSTACK_SIGNAL_PROCESSOR

This setting determines when the information in Elasticsearch is updated. The default value updates it in real time with db changes

```
HAYSTACK_SIGNAL_PROCESSOR = 'haystack.signals.RealtimeSignalProcessor'
```

A more performant implementation would trigger an update task on each db change.

Please see django-haystack documentation for further information: <http://haystacksearch.org>

Updating Indexes

Once Elasticsearch is set up, and Single Search is enabled (i.e. the `SINGLE_SEARCH_ENABLED` option in settings is set to True) Haystack will automatically register the addition of and changes to models and reflect these in the search index. That is, as soon as a new instance of a model is added to the database, or changes are made to an existing instance, these changes will be searchable.

If you're adding search to an existing deployment of Django then you'll need to manually trigger a rebuild of the indexes (automatic indexing only happens through signals when models are added or changed).

Haystack registers a number of management commands with the Django framework, the important one here being the *rebuild_index* command. To rebuild, navigate to your checkout and call the following command

```
python manage.py rebuild_index
```

Haystack will then ask you to confirm your decision (Note: Rebuilding will destroy your existing indexes, and will take a while for large datasets, so be sure), and then start rebuilding.

11.2.7 Storage Options and Architecture in MyTardis

Database layout for storage

The storage for each DataFile is configured individually. A “way to store data” is called StorageBox. Each file has one or many related DataFileObjects, which link a DataFile with a StorageBox. A DataFile can have several copies stored in different StorageBoxes via several DataFileObjects.

StorageBoxes

StorageBoxes contain all the information needed to store a file except an id unique to the file and storagebox.

Each StorageBox points to a class that implements the Django storage API via a python module path as string.

Optional instantiation parameters for each StorageBox can be stored in StorageBoxOptions. These are used as parameters to the storage class set in the `django_storage_class` attribute of a StorageBox

These parameters are string types by default. However, by setting the optional parameter `value_type` to `'pickle'`, any pickleable object can be stored here and hence used for instantiation of the storage class.

Optional classification and other metadata can be stored in StorageBoxAttributes.

A special case is where someone registers a file and wants to put it into location themselves but needs to be given the place to put it (via the API). Such situation can only be resolved with StorageBoxes that implement the `“build_save_location”` function. Such StorageBoxes need to have a StorageBoxAttribute with key `“staging”` and value `“True”`.

DataFiles

DataFiles are the logical representation of the file. They contain information about the name, size, checksum, dates etc.

DataFileObjects

DataFileObjects point to the DataFile they belong to and the StorageBox they reside in. They also have an identifier that the StorageBox uses to find the actual file. DataFileObjects also have a date, and a state-flag.

Available backends

Django storage API compatible backends are available for example at <https://github.com/jschneier/django-storages>

We have tested the following backends with MyTardis:

- File on disk or any other system mounted storage
- SFTP
- SWIFT Object Storage

Documented backends

S3 compatible storage

S3 and S3 compatible storage backends are supported by the `django-storages` package.

To use the S3 storage backend, you will need to install the following:

```
pip install django-storages
pip install boto3
```

The `S3Boto3Storage` storage backend provided by `django-storages` can be used to configure an S3 storage box, or it can be used to store static assets in S3, as described at <https://django-storages.readthedocs.io/en/latest/backends/amazon-S3.html>

To configure an S3 storage box, set the storage box's `django_storage_class` field to `storages.backends.s3boto3.S3Boto3Storage`

Configuration

The following options can be set as `StorageBoxOption` on your S3 storage box or system wide in your Django settings (a default of * labels mandatory settings):

StorageBoxOption	Django Setting	Default
access_key	AWS_S3_ACCESS_KEY_ID AWS_ACCESS_KEY_ID	*
secret_key	AWS_S3_SECRET_ACCESS_KEY AWS_SECRET_ACCESS_KEY	*
file_overwrite	AWS_S3_FILE_OVERWRITE	True
headers	AWS_HEADERS	{}
bucket_name	AWS_STORAGE_BUCKET_NAME	*
auto_create_bucket	AWS_AUTO_CREATE_BUCKET	False
default_acl	AWS_DEFAULT_ACL	public-read
bucket_acl	AWS_BUCKET_ACL	default_acl
querystring_auth	AWS_QUERYSTRING_AUTH	True
querystring_expire	AWS_QUERYSTRING_EXPIRE	3600
reduced_redundancy	AWS_REDUCED_REDUNDANCY	False
location	AWS_LOCATION	' '
encryption	AWS_S3_ENCRYPTION	False
custom_domain	AWS_S3_CUSTOM_DOMAIN	None
calling_format	AWS_S3_CALLING_FORMAT	SubdomainCallingFormat()
secure_urls	AWS_S3_SECURE_URLS	True
file_name_charset	AWS_S3_FILE_NAME_CHARSET	'utf-8'
gzip	AWS_IS_GZIPPED	False
preload_metadata	AWS_PRELOAD_METADATA	False
gzip_content_types	GZIP_CONTENT_TYPES	('text/css', 'text/javascript', 'application/javascript', 'application/x-javascript', 'image/svg+xml')
url_protocol	AWS_S3_URL_PROTOCOL	http:
host	AWS_S3_HOST	S3Connection.DefaultHost
use_ssl	AWS_S3_USE_SSL	True
port	AWS_S3_PORT	None
proxy	AWS_S3_PROXY_HOST	None
proxy_port	AWS_S3_PROXY_PORT	None
The max amount of memory a returned file can take up before being rolled over into a temporary file on disk. Default is 0: Do not roll over.		
max_memory_size	AWS_S3_MAX_MEMORY_SIZE	0

Appendix: Conversion of ‘Replicas’

Replicas used to be the method of file storage abstraction in MyTardis versions 3.x. The StorageBoxes replace this. For pain-free upgrading, a conversion has been included with the database migrations that works as follows:

All ‘Locations’ that are local are converted to default (folder on disk) StorageBoxes. All ‘Locations’ that are not local are converted to dummy ‘link only’ StorageBoxes with the corresponding name. These can be upgraded manually to a StorageBox with an appropriate backend after the migration has taken place.

Max size is set to size of disk, hence for multiple locations on the same disk this number provides no protection. This also should be set to reasonable values manually after the migration.

Each ‘Replica’ of a file will be converted to a DataFileObject pointing to the relevant StorageBox.

All files are manually reverified, so that unverified entries can be checked for errors.


11.2.8 Facility Overview

Introduction

The Facility Overview included with MyTardis allows facility administrators to monitor the output of connected instruments, highlighting unverified files, dataset size, file counts and file listings.

Setup

In order for datasets to appear in the Facility Overview, each dataset must be associated with an Instrument, which is itself associated with a Facility. The Facility object will reference a facility administrator’s group, members of which may view the Facility Overview.



The facility managers, facility manager groups, facilities and instruments may be configured via the django admin interface. MyData, the desktop uploader client for the MyTardis server, can be configured to assign the appropriate instrument to uploaded datasets at the point of ingestion.

It should be noted that the dataset visibility within the facility overview is limited to dataset and datafile listings only. Access to the experiment and dataset views, as well as raw data, is still controlled via the [ACL framework](#).

Usage

Members of the facility manager groups for one or more facilities will see the “Facility Overview” menu item in the MyTardis web portal. After opening the facility overview, a list of recently ingested datasets will be displayed from the facility being managed. If a user manages multiple facilities, a blue drop-down selector will also appear on the

right-hand side of the page. As the facility overview is designed to give a snapshot of recently uploaded datasets, older data is not immediately accessible; MyTardis' *search feature* is better suited to this.

In addition to simply listing the most recent datasets, the datasets can be grouped by instrument or by owner, and filtered by username, experiment name and instrument name. Note that while filters are active, it may appear as though no new pages are loaded by clicking “Load more”, since the additional datasets fetched from the server might not match the active filters.

11.3 Development

11.3.1 Architecture

This page describes the architecture of MyTardis.

MyTardis is built on the Django web framework, which itself is built on Python, thus MyTardis follows the architectural model of Django.

Component Architecture

Web Server MyTardis is typically deployed with the standard [Nginx](#) + [Gunicorn](#) + [Django](#) + [Python](#) stack.

RDBMS Ideally, use PostgreSQL. MySQL or MariaDB may be usable but it is not as well tested.

Data Storage Local disk, network mounted disks as well as S3 and SFTP are supported.

Ingestion Ingestion is normally site specific. A desktop application is available (MyData).

Functional Architecture

MyTardis follows the standard Django architecture.

The major functional modules in MyTardis are:

API A RESTful API provides anonymous and authenticated access to most of the stored data.

Auth Authentication and Authorisation.

Download Data download functionality.

Filters Processing of metadata as data is uploaded, e.g. extract EXIF metadata from JPEG files.

Management Additional commands for the Django CLI. The backup utility is implemented as a Django command.

Migrations Database migration code.

Publish RIF-CS metadata publication.

Search Provides a searchable and authorisation enabled index for quickly finding data.

SFTP server Provides read access to data in MyTardis via the SFTP protocol

Information on the individual modules is available from the modindex.

Scalability Model

At the component / module level, performance and Scalability within MyTardis is achieved by:

- Allowing long lived or compute intensive operations to be hosted on separate machines from the main web server.
 - E.g. by running multiple web servers and sending long lived operations, such as ingestion, to a server reserved for such operations.
- Performance and Scalability of the database is achieved by a combination of 1) optimising the SQL requests issued by MyTardis, and 2) database specific scalability, please refer to the appropriate database documentation.
- Performance and Scalability of the web server is provided through the normal mechanisms for nginx / wsgi hosted python applications, e.g.:
 - Increasing individual Server capability
 - * Individual Server performance / utilization may be managed by controlling the number of python (django) processes active at any one time.
 - Deploying multiple web servers
 - * Multiple web servers may be deployed using standard mechanisms, e.g. load balancers. State (session) information is distributed using Django's standard session model.
- The Data Archive is a normal file system, e.g. NFS, SAMBA, etc., with performance and scalability dependent on the implementation and deployment.
- Extraction and formatting of metadata for ingestion is up to the client and may be distributed across any number of machines.

SQL Scalability Notes

The datafileparameter table is expected to be the single largest table by an order of magnitude, in the hundreds of millions of records (at the Australian Synchrotron).

For Postgres, this will probably be addressed by table partitioning. In this case using a date field to partition is often recommended. Dates may be introduced as part of the support for annotations, raw data, versioned data and derived data.

Persistence and Data Architecture

Django provides an Object-Relational-Model that maps Django Models to the underlying relational database.

The Django Models are defined in `tardis.tardis_portal.models`.

Security Model

Authentication

Access to data catalogued by MyTardis may be either public, i.e. anonymous access allowed, or private, requiring authentication. The Authentication Framework is documented in [ref-authframework](#).

Authorisation

MyTardis includes an extensible authorisation engine, documented in `ref-authframework` and *Authorisation Framework*.

Class Diagram

Unless the application has a very rich business model (which MyTardis does not), a class diagram doesn't convey much information in Django applications (it ends up being a flat list of classes). To understand the context in which the MyTardis classes are created, please refer to the Django documentation, <http://docs.djangoproject.com/> on the responsibilities of models, views, managers and templates.

Source Code

This section describes the top level layout of the source code in the [GitHub repository](#).

- docs
 - MyTardis User and Administrative documentation
- tardis
 - apps
 - * **Contains all the optional functionality and installation specific** functionality. Examples include the optional ANDS Register (`ands_register`) and Related Info (`related_info`) tabs, and the ANSTO (`mecat-anso`) and Australian Synchrotron (`mecat-as`) installation specific modules.
 - * **Some applications are part of the main code base, others can be added** at installation time.
 - search
 - * Search related code
 - tardis_portal
 - * This is the main django application that contains most of the core MyTardis functionality

11.3.2 Authorisation Framework

Django Authorisation

Django has a built-in authorisation/permission mechanism that is in use by default. It is enabled in MyTardis in `default_settings.py` together with the custom object level permission framework described below.

```
AUTHENTICATION_BACKENDS = (  
    'django.contrib.auth.backends.ModelBackend',  
    'tardis.tardis_portal.auth.authorisation.ACLAwareBackend',  
)
```

The Django default permissions are automatically available for each Model. The verbs are `add`, `change`, `delete`, and they can be queried on the user object as follows:

```
user.has_perm('tardis_portal.add_experiment')  
user.has_perm('tardis_portal.add_dataset')  
user.has_perm('tardis_portal.change_experiment')  
user.has_perm('tardis_portal.delete_datasetparameterset')
```

There is a function in `tardis.tardis_portal.auth.authservice` called `_set_user_from_dict` that adds the following permissions for each new user created using custom methods:

```
'add_experiment'
'change_experiment'
'change_group'
'change_userauthentication'
'change_experimentacl'
```

These permissions apply in general and are augmented by ACLs

Object Level Permissions and Access Control Lists

The main purpose of the ACL system is to manage per experiment permissions. The architecture allows for future expansion to more fine grained permission management. However, at this stage only the Experiment level is supported by the user interface.

Permissions are applied with a few predefined roles:

read read permission allows individuals and groups access to view an experiment.

write write permissions cover addition of new datasets and datafiles and also deletion of datafile.

delete delete permission allows deletion of datasets and experiments.

Roles are applied through the web using the *Control Panel* and can be applied to either users or groups.

To make an experiment public requires an explicit publish action.

The ACL permissions can be queried on the user object just like standard permissions, however, with the addition of the object in question:

```
user.has_perm('tardis_acls.change_experiment', experiment)
```

Verbs currently available are `change`, `view`, `delete`, `owns`, `share`.

The translation of ACLs to `has_perm` verbs is defined in a function in `tardis.tardis_portal.auth.authorisation`.

To allow for querying on any object related to experiments, extra logic was added to some of the models. To support the logic, in addition to ACLs, `has_perm` calls model functions named `_has_VERB_perm`, which allows model-specific permission logic.

The current policy is that if those functions return `True` or `False` then that result is returned without further checking. If they return an object, permissions will be checked for this object thereby allowing delegation.

11.3.3 RESTful API for MyTardis

The data and metadata stored in MyTardis instances is made accessible through a RESTful API.

Not all functionality has been exposed via the API at this time. This documentation reflects what is available and tested.

The API version `v1` is built on the Tastypie framework.

The RESTful API can also be explored via the automatically generated Swagger documentation at <http://mytardis-example.com/api/v1/swagger/>.

See swagger.io for details on the Swagger standard.

API accessible models

- Experiment
- ExperimentParameterSet
- ExperimentParameter
-
- Dataset
- DatasetParameterSet
- DatasetParameter
-
- DataFile
- DatafileParameterSet
- DatafileParameter
-
- StorageBox
- StorageBoxOption
- StorageBoxAttribute
-
- Schema
- ParameterName
-
- User
- Group
-
- Facility
- Instrument
-
- ObjectACL

Authentication

Currently implemented are Basic Auth, to be used via HTTPS only, and SessionAuth which queries Django sessions.

Due to our desire to provide information to users without any login, eg. for public data, the Basic Auth mechanism is slightly non-standard.

The standard sends an anonymous request, awaits a WWW-Authenticate header, then sends authentication credentials. Instead, this API sends public data for anonymous requests.

Using `curl` or the `requests` library this poses no problem. However, using `urllib2` or web browser without a Django session is not going to work out of the box.

Here is a snippet (found here: <http://stackoverflow.com/questions/4628610/does-urllib2-support-preemptive-authentication-authentication>) that makes urllib2 work, should you want to use this library:

```
class PreemptiveBasicAuthHandler(urllib2.BaseHandler):

    def __init__(self, password_mgr=None):
        if password_mgr is None:
            password_mgr = urllib2.HTTPPasswordMgrWithDefaultRealm()
        self.passwd = password_mgr
        self.add_password = self.passwd.add_password

    def http_request(self, req):
        uri = req.get_full_url()
        user, pw = self.passwd.find_user_password(None, uri)
        if pw is None:
            return req

        raw = "%s:%s" % (user, pw)
        auth = 'Basic %s' % base64.b64encode(raw).strip()
        req.add_unredirected_header('Authorization', auth)
        return req

auth_handler = PreemptiveBasicAuthHandler()
auth_handler.add_password(realm=None,
                          uri=url,
                          user='mytardis',
                          passwd='mytardis')
opener = urllib2.build_opener(auth_handler)
# ...and install it globally so it can be used with urlopen.
urllib2.install_opener(opener)
```

Querying the database (GET)

All endpoints support querying lists and individual records via GET requests. Some support more complex queries via GET parameters as well.

Creating objects, adding files (POST)

The creation of Experiments, Datasets and Dataset_Files via POSTs with the option to include metadata/parametersets has been implemented and tested.

The following examples demonstrate how to go about it.

In all except the file attachment case the POST data should be a JSON string, the Content-Type header needs to be set to application/json and the Accept header as well. Other response formats may be made available in the future.

In all cases the URI of the created object is returned in the Location header of the response.

Experiments

Example JSON input

```
{
  "title": "API-created Experiment #1",
  "description": "Wow, all automatic!",
  "institution_name": "Monash University",
  "parameter_sets": [
    {
      "schema": "http://institution.com/my/schema",
      "parameters": [
        {
          "name": "important_parameter_1",
          "value": "Test16"
        },
        {
          "name": "important_parameter_3",
          "value": "57.136"
        }
      ]
    },
    {
      "schema": "http://company.com/some/other/schema",
      "parameters": [
        {
          "name": "meaningful_name",
          "value": "Test17"
        },
        {
          "name": "meaningless_name",
          "value": "1234"
        }
      ]
    }
  ]
}
```

This creates an experiment with two parametersets with two parameters each.

Alternative to Schema namespaces and Parameter names, you can also specify the URIs to each. Until the querying of Schemas and Parameters is documented this is discouraged.

Datasets

Example JSON input:

```
{
  "description": "API-created Dataset",
  "experiments": [
    "/api/v1/experiment/1/",
    "/api/v1/experiment/2/"
  ],
  "immutable": false,
  "parameter_sets": [
    {
      "parameters": [
        {
          "name": "obscure-instrument-setting-52",
          "value": "awesome dataset api POST"
        }
      ]
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "name": "temperature",
      "value": "301"
    }
  ],
  "schema": "http://datasets.com/need/schemas/too"
},
{
  "parameters": [
    {
      "name": "someotherparameter",
      "value": "some other value"
    }
  ],
  "schema": "http://better-datasets.com/offers/better/schemas"
}
]
}

```

DataFiles

There are three ways to add a file to MyTardis via the API.

Via multipart form POST

This works for single files at the moment.

The key is to send a multipart-form instead of 'application/json'. This can be accomplished with the requests library as shown in the following example.

To use requests you need to install it first, eg. `pip install requests`.

Also, for this to work, the POST data needs to be sent with the JSON string called 'json_data' and the file called 'attached_file'.

Example JSON input:

```

{
  "dataset": "/api/v1/dataset/1/",
  "filename": "mytestfile.txt",
  "md5sum": "c858d6319609d6db3c091b09783c479c",
  "size": "12",
  "mimetype": "text/plain",
  "parameter_sets": [{
    "schema": "http://datafileshop.com/fileinfo/v1",
    "parameters": [{
      "name": "fileparameter1",
      "value": "123"
    }],
    {
      "name": "fileparameter2",
      "value": "1234"
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```
    ]]  
}
```

Example requests script:

```
import requests  
from requests.auth import HTTPBasicAuth  
  
url = "http://localhost:8000/api/v1/dataset_file/"  
headers = {'Accept': 'application/json'}  
response = requests.post(url, data={"json_data": data}, headers=headers,  
                        files={'attached_file': open(filename, 'rb')},  
                        auth=HTTPBasicAuth(username, password)  
                        )
```

Via staging location

Another way to add a file is to create the database entry first without providing a storage location. This will return back a location on the server that you are assumed to have access to. Once the file appears there, for example when you copy it there, it will be moved to its permanent storage location managed by MyTardis.

The full file path that you should copy/move the file to is returned as the content of the response.

Example JSON input:

```
{  
  "dataset": "/api/v1/dataset/1/",  
  "filename": "mytestfile.txt",  
  "md5sum": "c858d6319609d6db3c091b09783c479c",  
  "size": "12",  
  "mimetype": "text/plain",  
  "parameter_sets": [{  
    "schema": "http://datafileshop.com/fileinfo/v1",  
    "parameters": [{  
      "name": "fileparameter1",  
      "value": "123"  
    },  
    {  
      "name": "fileparameter2",  
      "value": "1234"  
    }  
  ]  
}]  
}
```

Via shared permanent storage location

This method assumes that there exists a storage that is shared between MyTardis and you. The registered file will remain in this location.

For this to work you need to get a `Location` (internal MyTardis settings) name to submit with your metadata.

Examples JSON:

```
{
  "dataset": "/api/v1/dataset/1/",
  "filename": "mytestfile.txt",
  "md5sum": "c858d6319609d6db3c091b09783c479c",
  "size": "12",
  "mimetype": "text/plain",
  "replicas": [{
    "url": "mytestfile.txt",
    "location": "local",
    "protocol": "file"
  }],
  "parameter_sets": [{
    "schema": "http://datafileshop.com/fileinfo/2",
    "parameters": [{
      "name": "fileparameter1",
      "value": "123"
    },
    {
      "name": "fileparameter2",
      "value": "123"
    }
  ]
}]
}
```

urllib2 POST example script

Replace MODEL with one of the available model names in lower case. data is the JSON as a string.

```
import urllib2
url = "http://localhost:8000/api/v1/MODEL/"
headers = {'Accept': 'application/json',
           'Content-Type': 'application/json'}
auth_handler = urllib2.HTTPBasicAuthHandler()
auth_handler.add_password(realm="django-tastypie",
                          uri=url,
                          user=username,
                          passwd=password)
opener = urllib2.build_opener(auth_handler)
urllib2.install_opener(opener)
myrequest = urllib2.Request(url=url, data=data,
                            headers=headers)
myrequest.get_method = lambda: 'POST'
output = "error"
output = urllib2.urlopen(myrequest)
print output.headers["Location"]
```

11.3.4 Tests

Running the Test Suite

Run this command to run the unit tests:

```
./test.py
```

If you want to specify any options or specific tests to run, the test argument is required first:

```
./test.py test --some-argument
```

You can choose to run the test suite with different options (e.g. with coverage, with different verbosity, etc.). To see the full list of options, run the same command with the `--help` flag.

Running Individual Unit Tests

The unit tests reside in the `tardis/tardis_portal/tests` directory. To run the unit tests individually, you can use this command:

```
./test.py test <test_module_name_here>
```

Note that the test module name argument should be the relative file path with “.” as folder separator. For example, if you want to run the test “`test_authentication.py`”, then your command to execute this test would be:

```
./test.py test tardis.tardis_portal.tests.test_authentication
```

Other options

You can choose to include different options when running the unit tests (e.g. run in verbose mode, print out a traceback, etc.). Run the test or django test command with `--help` flag to see the full list of options:

```
./test.py test --help
```

Running BDD tests

To run BDD (Behaviour Driven Development) tests with the default settings and headless Chrome, download ChromeDriver from <http://chromedriver.chromium.org/downloads> and make it available in your PATH (e.g. in `/usr/local/bin/`) and run:

```
./test.py behave
```

Running QUnit tests

The QUnit tests reside in the `js_tests/` directory.

`package.json` contains `devDependencies` required for running these tests.

Running `npm install` will install everything you need, whereas `npm install --production` will skip the `devDependencies`.

You will need PhantomJS to run the QUnit tests, which can be installed with:

```
npm install -g phantomjs-prebuilt
```

You can run the QUnit tests with:

```
npm test
```

Or by running a web server:

```
python -m SimpleHTTPServer
```

and opening http://127.0.0.1:8000/js_tests/tests.html in your browser.

11.3.5 tardis

tardis package

Subpackages

tardis.analytics package

Submodules

tardis.analytics.apps module

```
class tardis.analytics.apps.AnalyticsConfig(app_name, app_module)
    Bases: django.apps.config.AppConfig
    name = 'tardis.analytics'
    verbose_name = 'Analytics framework'
```

tardis.analytics.ga module

Google analytics tracking

```
tardis.analytics.ga.track_download(label, session_id, ip, user, total_size=None,
                                     num_files=None, ua=None)
tardis.analytics.ga.track_login(label, session_id, ip, user)
tardis.analytics.ga.track_logout(label, session_id, ip, user)
```

tardis.analytics.tracker module

Generic tracking and analytics interface Supports Google Analytics through ga.py, others may follow

```
class tardis.analytics.tracker.IteratorTracker(iterator, tracker_data=None)
    Bases: object
    wraps file iterator to track successful and incomplete downloads
    close()
    next()
```

```
tardis.analytics.tracker.service = <module 'tardis.analytics.ga' from '/home/docs/checkout...
```

This can become a setting to other service in the future

Module contents

tardis.apps package

Subpackages

tardis.apps.deep_storage_download_mapper package

Submodules

tardis.apps.deep_storage_download_mapper.mapper module

File mapper that works for files stored in deep directory structures. It recreates the structure as stored in the datafile directory

```
tardis.apps.deep_storage_download_mapper.mapper.deep_storage_mapper(obj,  
                                                                    root-  
                                                                    dir=None)
```

If rootdir is None, just return a filesystem-safe representation of the object, e.g. “DatasetDescription_123” or “strange %2F filename.txt”

For now, only DataFiles are supported when rootdir is not None.

Parameters

- **obj** (`DataFile`, `Dataset` or `Experiment`) – The model instance (`DataFile`, `Dataset` or `Experiment`) to generate a path for.
- **rootdir** (`basestring`) – The top-level directory name, or None

Returns Filesystem-safe path for the object in the archive or SFTP view.

Return type `basestring`

Raises

- `Exception` –
- `NotImplementedError` –

tardis.apps.deep_storage_download_mapper.urls module

Module contents

tardis.apps.dl_mapper_df_dir_only package

Submodules

tardis.apps.dl_mapper_df_dir_only.mapper module

File mapper that works for files stored in deep directory structures. It recreates the structure as stored in the datafile directory

```
tardis.apps.dl_mapper_df_dir_only.mapper.df_dir_only(datafile, rootdir)
```

tardis.apps.dl_mapper_df_dir_only.urls module

Module contents

tardis.apps.equipment package

Subpackages

tardis.apps.equipment.migrations package

Submodules

tardis.apps.equipment.migrations.0001_initial module

```
class tardis.apps.equipment.migrations.0001_initial.Migration(name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0002_auto_20150528_1128')]

    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'key', <django.db.models.fields.CharField>)]>]
```

Module contents

tardis.apps.equipment.south_migrations package

Submodules

tardis.apps.equipment.south_migrations.0001_initial module

Module contents

Submodules

tardis.apps.equipment.admin module

tardis.apps.equipment.forms module

```
class tardis.apps.equipment.forms.EquipmentSearchForm(data=None, files=None,
    auto_id=u'id_%s', pre-
    fix=None, initial=None,
    error_class=<class
    'django.forms.utils.ErrorList'>,
    label_suffix=None,
    empty_permitted=False,
    field_order=None,
    use_required_attribute=None,
    renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'description': <django.forms.fields.CharField object>, 'key': <django.forms.fields.CharField object>}
```

```
declared_fields = {'description': <django.forms.fields.CharField object>, 'key': <dj
media
```

tardis.apps.equipment.models module

```
class tardis.apps.equipment.models.Equipment(id, key, description, make, model, type, se-
rial, comm, decomm, url)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

comm

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

dataset

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

decomm

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

make

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

model

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
objects = <django.db.models.manager.Manager object>
```

serial

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.apps.equipment.tests module

tests.py <http://docs.djangoproject.com/en/dev/topics/testing/>

class tardis.apps.equipment.tests.**EquipmentTestCase** (*methodName='runTest'*)

Bases: django.test.testcases.TestCase

fixtures = ['initial_data.json']

setUp()

Hook method for setting up the test fixture before exercising it.

testEquipmentDetail()

testEquipmentList()

testSearchEquipmentForm()

testSearchEquipmentResult()

tardis.apps.equipment.tests.**suite()**

tardis.apps.equipment.urls module**tardis.apps.equipment.views module**

tardis.apps.equipment.views.**index**(*request*)

tardis.apps.equipment.views.**search**(*request*)

tardis.apps.equipment.views.**view_id**(*request, object_id*)

tardis.apps.equipment.views.**view_key**(*request, object_key*)

Module contents**tardis.apps.filepicker package****Submodules****tardis.apps.filepicker.filepicker_settings module****tardis.apps.filepicker.urls module**

tardis.apps.filepicker.utils module

taken from https://raw.githubusercontent.com/Filepicker/django-filepicker/master/django_filepicker/utils.py on 11 Apr 2013

```
class tardis.apps.filepicker.utils.FilepickerFile (url)
    Bases: object

    cleanup ()
        Removes any downloaded objects and closes open files.

    filepicker_url_regex = <_sre.SRE_Pattern object>

    get_file ()
        Downloads the file from filepicker.io and returns a Django File wrapper object
```

tardis.apps.filepicker.views module

Filepicker.io button view and upload handler

Module contents

tardis.apps.oaipmh package

Subpackages

tardis.apps.oaipmh.provider package

Submodules

tardis.apps.oaipmh.provider.base module

```
class tardis.apps.oaipmh.provider.base.BaseProvider (site)
    Bases: oaipmh.interfaces.IOAI, object

    A base provider which roughly implements the PyOAI interface for OAI-PMH servers.

    Extend this if you're writing your own provider for a new type or a different metadata format.

    getRecord (metadataPrefix, identifier)
        Get a record for a metadataPrefix and identifier.
```

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **identifier** (*string*) –
 - repository-unique identifier of record

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is unknown or not supported by identifier.
- **oaipmh.error.IdDoesNotExistError** – if identifier is unknown or illegal.

Returns a header, metadata, about tuple describing the record.

identify()

Retrieve information about the repository.

Returns an Identify object describing the repository.

listIdentifiers (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return headers in set
- **from** (*datetime*) – only retrieve headers from **from_** date forward (in naive UTC)
- **until** (*datetime*) – only retrieve headers with dates up to and including until date (in naive UTC)

Raises

- **error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of headers.

listMetadataFormats (*identifier=None*)

List metadata formats supported by repository or record.

Parameters **identifier** (*string*) – identify record for which we want to know all supported metadata formats. If absent, list all metadata formats supported by repository.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record.

Returns an iterable of metadataPrefix, schema, metadataNamespace tuples (each entry in the tuple is a string).

listRecords (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header, metadata and about information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return records in set
- **from** (*datetime*) – only retrieve records from **from_** date forward (in naive UTC)
- **until** (*datetime*) – only retrieve records with dates up to and including until date (in naive UTC)

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **oaipmh.error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of header, metadata, about tuples.

listSets()

Get a list of sets in the repository.

Raises `error.NoSetHierarchyError` – if the repository does not support sets.

Returns an iterable of `setSpec`, `setName` tuples (strings).

writeMetadata(*element*, *metadata*)

Create XML elements under the given element, using the provided metadata.

Should avoid doing any model-lookups, as they should be done when creating the metadata.

Parameters

- **element** (`lxml.etree.Element`) – element to put all content under (as `SubElements`)
- **metadata** (`oaipmh.common.Metadata`) – metadata to turn into XML

Raises `NotImplementedError` – not implemented

tardis.apps.oaipmh.provider.experiment module

class `tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider` (*site*)

Bases: `tardis.apps.oaipmh.provider.base.BaseProvider`

NS_CC = 'http://www.tardis.edu.au/schemas/creative_commons/2011/05/17'

getRecord(*metadataPrefix*, *identifier*)

Return record if we handle it.

static get_id(*obj*)

listIdentifiers(*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Return identifiers in range, provided we handle this metadata prefix.

listRecords(*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Return records in range, provided we handle this metadata prefix.

listSets()

No support for sets.

class `tardis.apps.oaipmh.provider.experiment.DcExperimentProvider` (*site*)

Bases: `tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider`

listMetadataFormats(*identifier=None*)

Return metadata format if no identifier, or identifier is a valid experiment.

class `tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` (*site*)

Bases: `tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider`

class `ExperimentWriter` (*root*, *metadata*, *site*)

write()

writeRegistryObjectsWrapper()

writeRelatedAuthor(*element*, *obj*, *relation*)

writeRelatedInfo(*element*, *obj*)

writeRelatedUser(*element*, *obj*, *relation*)

writeSubject(*element*, *obj*)

```

static get_rifcs_id (id_, site_=None)
listMetadataFormats (identifier=None)
    Return metadata format if no identifier, or identifier is a valid experiment.
static writeExperimentMetadata (element, metadata, site=None, writer=None)
    Wrapper around experiment writer.
static writeUserMetadata (element, metadata, site=None)

```

Module contents

tardis.apps.oaipmh.tests package

Subpackages

tardis.apps.oaipmh.tests.provider package

Submodules

tardis.apps.oaipmh.tests.provider.test_base module

```

class tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testGetRecord ()
        Default behaviour should be to not handle the identifier.

    testIdentify ()
        There can be only one provider that responds. By default, don't.

    testListIdentifiers ()
        By default a provider cannot handle the given metadata prefix.

    testListMetadataFormats ()
        By default a provider handles no metadata formats.

    testListRecords ()
        By default a provider cannot handle the given metadata prefix.

    testListSets ()
        By default a provider does not implement sets.

```

tardis.apps.oaipmh.tests.provider.test_experiment module

```

class tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTC
    Bases: object

    setUp ()

    tearDown ()

```

```
testGetRecordHandlesInvalidIdentifiers ()
testIdentify ()
    There can be only one provider that responds. This one does not.
testListIdentifiers ()
testListIdentifiersDoesNotHandleSets ()
testListMetadataFormats ()
testListSets ()
class tardis.apps.oaipmh.tests.provider.test_experiment.DcExperimentProviderTestCase (method
    Bases: tardis.apps.oaipmh.tests.provider.test_experiment.
    AbstractExperimentProviderTC, django.test.testcases.TestCase
testGetRecord ()
testListRecords ()
class tardis.apps.oaipmh.tests.provider.test_experiment.RifCsExperimentProviderTestCase (met
    Bases: tardis.apps.oaipmh.tests.provider.test_experiment.
    AbstractExperimentProviderTC, django.test.testcases.TestCase
tearDown ()
    Hook method for deconstructing the test fixture after testing it.
testGetRecord ()
testListRecords ()
```

Module contents

Submodules

tardis.apps.oaipmh.tests.test_oai module

```
class tardis.apps.oaipmh.tests.test_oai.EndpointTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase
setUp ()
    Hook method for setting up the test fixture before exercising it.
tearDown ()
    Hook method for deconstructing the test fixture after testing it.
testGetRecord ()
testIdentify ()
testListIdentifiers ()
testListMetadataFormats ()
testListRecords ()
```

Module contents

Submodules

tardis.apps.oaipmh.models module**tardis.apps.oaipmh.server module**

class tardis.apps.oaipmh.server.**ProxyingMetadataRegistry** (*providers*)

Bases: oaipmh.metadata.MetadataRegistry

A registry that only writes, and does so by proxying to Providers.

hasReader (*metadata_prefix*)

hasWriter (*metadata_prefix*)

readMetadata (*metadata_prefix, element*)

Turn XML into metadata object.

element - element to read in

returns - metadata object

registerReader (*metadata_prefix, reader*)

registerWriter (*metadata_prefix, writer*)

writeMetadata (*metadata_prefix, element, metadata*)

Write metadata as XML.

element - ElementTree element to write under metadata - metadata object to write

class tardis.apps.oaipmh.server.**ProxyingServer** (*providers*)

Bases: oaipmh.interfaces.IOAI

getRecord (*metadataPrefix, identifier*)

Get a record for a metadataPrefix and identifier.

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if no provider returns a result, but at least one provider responds with **oaipmh.error.CannotDisseminateFormatError** (meaning the identifier exists)
- **oaipmh.error.IdDoesNotExistError** – if all providers fail with **oaipmh.error.IdDoesNotExistError**

Returns first successful provider response

Return type response

identify ()

Retrieve information about the repository.

Returns an **oaipmh.common.Identify** object describing the repository.

Return type **oaipmh.common.Identify**

listIdentifiers (*metadataPrefix, **kwargs*)

Lists identifiers from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if *metadataPrefix* is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set`. Set of headers.

Return type `set`

listMetadataFormats (***kwargs*)

List metadata formats from all providers in a single set.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record, but it does exist.

Returns a *frozenset* of `metadataPrefix`, `schema`, `metadataNamespace` tuples (each entry in the tuple is a string).

Return type `frozenset`

listRecords (*metadataPrefix*, ***kwargs*)

Lists records from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set`. Set of header, metadata, about tuples.

Return type `set`

listSets ()

List sets.

Raises `oaipmh.error.NoSetHierarchyError` – because set hierarchies are currently not implemented

`tardis.apps.oaipmh.server.get_server` (*current_site*)

tardis.apps.oaipmh.urls module

tardis.apps.oaipmh.views module

`tardis.apps.oaipmh.views.endpoint` (*request*)

Module contents

tardis.apps.openid_migration package

Subpackages

tardis.apps.openid_migration.migrations package

Submodules

tardis.apps.openid_migration.migrations.0001_initial module

```
class tardis.apps.openid_migration.migrations.0001_initial.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0012_userauthentication_approved'), (u'auth', u'_
    initial = True
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'ac
```

Module contents**tardis.apps.openid_migration.tests package****Submodules****tardis.apps.openid_migration.tests.test_forms module**

Tests related to OpenID migration forms

```
class tardis.apps.openid_migration.tests.test_forms.OpenIDMigrationFormTestCase(methodName='
    Bases: django.test.testcases.TestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    test_init()
```

tardis.apps.openid_migration.tests.test_migration module

Tests related to OpenID migration

```
class tardis.apps.openid_migration.tests.test_migration.OpenIDMigrationTestCase(methodName='
    Bases: django.test.testcases.TestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    test_do_migration()
```

tardis.apps.openid_migration.tests.test_models module

```
class tardis.apps.openid_migration.tests.test_models.ModelTestCase(methodName='runTest')
    Bases: django.test.testcases.TestCase
    create_OpenidUserMigration()
    setUp()
        Hook method for setting up the test fixture before exercising it.
    test_OpenidUserMigration_creation()
```

tardis.apps.openid_migration.tests.test_views module

Tests related to OpenID migration views

```
class tardis.apps.openid_migration.tests.test_views.OpenIDMigrationViewTestCase(methodName=
    Bases: django.test.testcases.TestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    test_migrate_accounts()
```

Module contents

Submodules

tardis.apps.openid_migration.apps module

```
class tardis.apps.openid_migration.apps.OpenidMigrationConfig(app_name,
    app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig
    name = 'tardis.apps.openid_migration'
    verbose_name = 'OpenID migrations'
```

tardis.apps.openid_migration.context_processors module

```
tardis.apps.openid_migration.context_processors.openid_migration_processor(request)
    adds context for openid_migration
```

tardis.apps.openid_migration.default_settings module

tardis.apps.openid_migration.email_text module

```
tardis.apps.openid_migration.email_text.email_migration_success(user,
    new_username,
    auth_method)
tardis.apps.openid_migration.email_text.interpolate_template(template_name,
    **kwargs)
```

tardis.apps.openid_migration.forms module

```
tardis.apps.openid_migration.forms.openid_user_migration_form()
    Create a user migration form with username and password field.
```

tardis.apps.openid_migration.migration module

```
tardis.apps.openid_migration.migration.acl_migration(userIdToBeReplaced,
    replacementUserId,
    user_migration_record)
```

```
tardis.apps.openid_migration.migration.confirm_migration(request)
```

```
tardis.apps.openid_migration.migration.do_migration(request)
```

Migrating account from the account that the logged in user has provided in the Authentication Form. Migration involve relinking the UserAuthentication table entries, transferring ObjectACL entries to the migrated account, changing the Group memberships and making the old account inactive.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains request.user’s new list of authentication methods

Return type `HttpResponse`

```
tardis.apps.openid_migration.migration.getSupportedAuthMethods()
```

Return the list of authentication methods.

```
tardis.apps.openid_migration.migration.get_api_key(user)
```

```
tardis.apps.openid_migration.migration.get_matching_auth_provider(backend)
```

```
tardis.apps.openid_migration.migration.migrate_api_key(old_user, new_user)
```

```
tardis.apps.openid_migration.migration.migrate_user_permissions(old_user,
                                                                new_user)
```

```
tardis.apps.openid_migration.migration.openid_migration_method(request)
```

tardis.apps.openid_migration.models module

```
class tardis.apps.openid_migration.models.OpenidACLMigration(id, user_migration,
                                                            acl_id)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

acl_id

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

acl_id_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

user_migration

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_migration_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.apps.openid_migration.models.OpenidACLMigrationAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    list_display = ['user_migration_obj', 'acl_id']
    media
    user_migration_obj(obj)

class tardis.apps.openid_migration.models.OpenidUserMigration(id, old_user,
    old_user_auth_method,
    new_user,
    new_user_auth_method,
    migration_timestamp,
    migration_status)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

get_next_by_migration_timestamp (**morekwargs)

get_previous_by_migration_timestamp (**morekwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

migration_status

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

migration_timestamp

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

new_user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

new_user_auth_method

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

new_user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

old_user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

old_user_auth_method

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

old_user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

openidaclmigration_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.apps.openid_migration.models.OpenidUserMigrationAdmin(model, admin_site)
```

Bases: django.contrib.admin.options.ModelAdmin

```
list_display = ['__unicode__', 'old_user', 'old_user_auth_method', 'new_user_id', 'new_media']
```

tardis.apps.openid_migration.tasks module**tardis.apps.openid_migration.urls module****tardis.apps.openid_migration.user_menu_modifiers module**

```
tardis.apps.openid_migration.user_menu_modifiers.add_migrate_account_menu_item(request, user_menu)
```

Add a 'Migrate My Account' item to the user menu

Parameters

- **request** (`django.http.HttpRequest`) – an HTTP Request instance
- **user_menu** (`list`) – user menu context to modify

Returns user_menu list

Return type `list`

tardis.apps.openid_migration.utils module

`tardis.apps.openid_migration.utils.rollback_migration` (*user_migration_obj*)

tardis.apps.openid_migration.views module

`tardis.apps.openid_migration.views.migrate_accounts` (*request, *args, **kwargs*)
Manage user migration using AJAX.

Module contents

tardis.apps.push_to package

Subpackages

tardis.apps.push_to.migrations package

Submodules

tardis.apps.push_to.migrations.0001_initial module

```
class tardis.apps.push_to.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'auth', u'__first__'), (u'auth', u'0006_require_contenttypes_0002')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'key_type',
```

tardis.apps.push_to.migrations.0002_auto_20160518_1953 module

```
class tardis.apps.push_to.migrations.0002_auto_20160518_1953.Migration (name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'push_to', u'0001_initial')]
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'key_type',
```

Module contents

tardis.apps.push_to.tests package

Submodules

tardis.apps.push_to.tests.test_models module

```
class tardis.apps.push_to.tests.test_models.ModelsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_credential_generation()

    test_get_allowed_signing_services()

    test_keys_from_private_key_only()

    test_pkey_to_credential()
```

Module contents

Submodules

tardis.apps.push_to.apps module

```
class tardis.apps.push_to.apps.PushToConfig (app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.push_to'

    verbose_name = 'Push To'
```

tardis.apps.push_to.exceptions module

```
exception tardis.apps.push_to.exceptions.NoSuitableCredential
    Bases: exceptions.Exception

    This exception is thrown when attempting to find a suitable credential for a remote host but none is found
```

tardis.apps.push_to.models module

```
class tardis.apps.push_to.models.Credential (*args, **kwargs)
    Bases: tardis.apps.push_to.models.KeyPair

    A credential that may contain a password and/or key. The auth method chosen depends on the credentials
    available, allowed auth methods, and priorities defined by the SSH client.

    exception DoesNotExist
        Bases: django.core.exceptions.ObjectDoesNotExist
```

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

static generate_keypair_credential (*tardis_user*, *remote_user*, *remote_hosts*,
bit_length=2048)

Generates and saves an RSA key pair credential. Credentials returned by this method are intended to be registered on remote systems before being used. @type tardis_user: User @type remote_user: str @type bit_length: int @type remote_hosts: list[RemoteHost] :return: the generated credential :rtype: object

get_client_for_host (*remote_host*)

Attempts to establish a connection with the remote_host using this credential object. The remote_host may be any host, but only those in the remote_hosts field are expected to work. @type remote_host: RemoteHost :return: a connected SSH client :rtype: SSHClient

static get_suitable_credential (*tardis_user*, *remote_host*, *remote_user=None*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

password

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

remote_hosts

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

remote_user

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verify_remote_access (*remote_host=None*)

@type remote_host: RemoteHost

```

class tardis.apps.push_to.models.CredentialAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    form
        alias of CredentialForm

    media

class tardis.apps.push_to.models.CredentialForm(data=None, files=None,
        auto_id=u'id_%s', prefix=None,
        initial=None, error_class=<class
        'django.forms.utils.ErrorList'>,
        label_suffix=None,
        empty_permitted=False,
        instance=None,
        use_required_attribute=None)

    Bases: django.forms.models.ModelForm

    class Meta

        fields = '__all__'

        model
            alias of Credential

        widgets = {'password': <django.forms.widgets.PasswordInput object>}

    base_fields = {'key_type': <django.forms.fields.CharField object>, 'password': <djan

    declared_fields = {}

    media

class tardis.apps.push_to.models.DBHostKeyPolicy
    Bases: paramiko.client.MissingHostKeyPolicy

    Host key verification policy based on the host key stored in the database.

    missing_host_key(client, hostname, key)
        @type key: PKey

class tardis.apps.push_to.models.KeyPair(*args, **kwargs)
    Bases: django.db.models.base.Model

    A key pair

    class Meta

        abstract = False

    key

        Returns a subclass of PKey of the appropriate key type

        Return type PKey

        Raises ValidationError –

    key_type
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

```

private_key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

public_key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

save (*args, **kwargs)

class tardis.apps.push_to.models.OAuthSSHCertSigningService(*args, **kwargs)

Bases: django.db.models.base.Model

Connection parameters for an OAuth2 SSH certificate signing service. Supports certificate signing server available here: <https://github.com/monash-merc/ssh-authz>

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

allow_for_all

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

allowed_groups

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

allowed_remote_hosts

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

allowed_users

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

cert_signing_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

static get_available_signing_services (*user*)

Gets all SSH cert signing services available for a given user :param User user: User :return: allowed signing services :rtype: User

static get_oauth_service (*user, service_id*)

@type user: User @type service_id: int

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

nickname

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_authorize_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_check_token_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_client_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_client_secret

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_token_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

class tardis.apps.push_to.models.RemoteHost (*args, **kwargs)

Bases: *tardis.apps.push_to.models.KeyPair*

A remote host that may be connected to via SSH

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

administrator

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOne-ToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

administrator_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

credential_set

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

host_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

logo_img

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

nickname

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauthsshcertsigningservice_set

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

objects = <django.db.models.manager.Manager object>

port

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.apps.push_to.models.RemoteHostAdmin(model, admin_site)
```

Bases: `django.contrib.admin.options.ModelAdmin`

Hides the private key field, which is not necessary for host keys

```
fields = ['nickname', 'administrator', 'host_name', 'port', 'key_type', 'public_key',
media
```

tardis.apps.push_to.oauth_tokens module

`tardis.apps.push_to.oauth_tokens.get_token(request, oauth_service)`

Returns the OAuth2 token from the current session :param Request request: django session object :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Returns

Return type string

`tardis.apps.push_to.oauth_tokens.get_token_data(oauth_service, token)`

Gets the OAuth2 user attributes using the supplied token :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Parameters `token` (*basestring*) – an OAuth2 token

Returns a json object of user attributes

Return type dict

`tardis.apps.push_to.oauth_tokens.set_token(request, oauth_service, token)`

Stores the OAuth2 token in the current session :param Request request: django request object :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Parameters `token` (*basestring*) – the OAuth2 token

tardis.apps.push_to.ssh_authz module

`tardis.apps.push_to.ssh_authz.sign_certificate(credential, token, url)`

An interface to the OAuth2 SSH certificate signing service @type credential: models.Credential

tardis.apps.push_to.tasks module

`tardis.apps.push_to.tasks.do_file_copy(credential_id, remote_host_id, datafile_map, base_dir=None)`

`tardis.apps.push_to.tasks.make_dirs(sftp_client, dir_list)`

`tardis.apps.push_to.tasks.notify_user(user_id, remote_host_id, success=True)`

tardis.apps.push_to.urls module

tardis.apps.push_to.utils module

```
tardis.apps.push_to.utils.bytes_available (ssh_client, path)
tardis.apps.push_to.utils.can_copy (ssh_client, object_type, object_id, path)
tardis.apps.push_to.utils.get_default_push_location (sftp_client)
tardis.apps.push_to.utils.get_object_size (type, id)
tardis.apps.push_to.utils.is_directory (sftp_client, path)
tardis.apps.push_to.utils.list_subdirectories (sftp_client, path, show_hidden=False)
tardis.apps.push_to.utils.shell_escape (s)
```

tardis.apps.push_to.views module

```
tardis.apps.push_to.views.authorize_remote_access (request, *args, **kwargs)
    Generates an SSH certificate using an OAuth2 SSH signing service :param Request request: request object
    :param basestring remote_host_id: remote host id :param basestring service_id: OAuth2 SSH certificate signing
    service id :return: an error message or OAuth2 redirects :rtype: HttpResponseRedirect

tardis.apps.push_to.views.get_accessible_hosts (request, *args, **kwargs)
    Retrieves all accessible hosts (i.e. hosts for which the user already has credentials for) including push-to trigger
    URLs if the object type and id are supplied :param Request request: request object :param object obj_type: data
    type to be copied
    (experiment, dataset or datafile)

    Parameters push_obj_id (int) – the database object id

    Returns json object with accessible hosts

    Return type HttpResponse

tardis.apps.push_to.views.get_credential (request, remote_host)
    Fetches a suitable credential for the remote host, or raises an exception if none found :param Request request:
    request object :param RemoteHost remote_host: the RemoteHost for which a credential
    should be found

    Returns the credential

    Return type object

    Raises NoSuitableCredential – raised when no credential is found

tardis.apps.push_to.views.get_push_url_for_host (remote_host, obj_type, push_obj_id)
    Constructs a push-to URL to trigger data transfer :param RemoteHost remote_host: the RemoteHost to which
    data should be copied :param obj_type: data type to be copied (experiment, dataset or datafile) :type obj_type:
    object :param int push_obj_id: the database object id :return: a push-to URL :rtype: basestring

tardis.apps.push_to.views.get_signing_services (request, *args, **kwargs)
    Retrieves all certificate signing services and associated hosts including push-to trigger URLs if the object type
```

and id are supplied :param Request request: request object :param class obj_type: data type to be copied (experiment, dataset or datafile) :param int push_obj_id: the database object id :return: json object with signing services and hosts :rtype: HttpResponse

`tardis.apps.push_to.views.oauth_callback(request, *args, **kwargs)`

OAuth2 callback endpoint to continue the SSH certificate signing process :param Request request: request object :return: error message or redirect to the signing service with access token :rtype: HttpResponse

`tardis.apps.push_to.views.oauth_callback_url(request)`

Builds the oauth callback URL :param Request request: request object :return: callback URL :rtype: basestring

`tardis.apps.push_to.views.render_error_message(request, message, status=500)`

`tardis.apps.push_to.views.render_success_message(request, message, status=200)`

`tardis.apps.push_to.views.validate_remote_path(request, *args, **kwargs)`

Module contents

`tardis.apps.related_info` package

Subpackages

`tardis.apps.related_info.tests` package

Submodules

`tardis.apps.related_info.tests.test_oaipmh` module

```
class tardis.apps.related_info.tests.test_oaipmh.RifCSTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testExistsInOaipmh ()
```

`tardis.apps.related_info.tests.tests` module

```
class tardis.apps.related_info.tests.tests.CreateTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanCreate ()

    testDetectsBadInput ()

    testMustHaveWrite ()

class tardis.apps.related_info.tests.tests.DeleteTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.
```

```
testCanDelete()
testMustHaveWrite()
class tardis.apps.related_info.tests.tests.GetTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    testHandlesFound()
    testHandlesNotFound()
class tardis.apps.related_info.tests.tests.ListTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    testHandlesEmptySet()
    testHandlesMultipleEntries()
    testHandlesSingleEntry()
class tardis.apps.related_info.tests.tests.TabTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    testAccessWithReadPerms()
    testAccessWithoutReadPerms()
class tardis.apps.related_info.tests.tests.UpdateTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase
    setUp()
        Hook method for setting up the test fixture before exercising it.
    testDetectsBadInput()
    testMustHaveWrite()
```

Module contents

Submodules

tardis.apps.related_info.forms module

```

class tardis.apps.related_info.forms.RelatedInfoForm(data=None,      files=None,
                                                    auto_id=u'id_%s',      pre-
                                                    fix=None,      initial=None,
                                                    error_class=<class
                                                    'django.forms.utils.ErrorList'>,
                                                    label_suffix=None,
                                                    empty_permitted=False,
                                                    field_order=None,
                                                    use_required_attribute=None,
                                                    renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'identifier': <django.forms.fields.URLField object>, 'notes': <django
    declared_fields = {'identifier': <django.forms.fields.URLField object>, 'notes': <dj
    media

```

tardis.apps.related_info.models module**tardis.apps.related_info.settings module****tardis.apps.related_info.urls module****tardis.apps.related_info.views module****Module contents****tardis.apps.sftp package****Subpackages****tardis.apps.sftp.management package****Subpackages****tardis.apps.sftp.management.commands package****Submodules****tardis.apps.sftp.management.commands.sftpd module**

```

class tardis.apps.sftp.management.commands.sftpd.Command(stdout=None,
                                                            stderr=None,
                                                            no_color=False)

    Bases: django.core.management.base.BaseCommand

    add_arguments(parser)

    handle(*args, **options)

```

Module contents

Module contents

tardis.apps.sftp.migrations package

Submodules

tardis.apps.sftp.migrations.0001_initial module

```
class tardis.apps.sftp.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0011_auto_20160505_1643'), (u'auth', u'__first__')]
    initial = True
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'na
```

Module contents

tardis.apps.sftp.tests package

Submodules

tardis.apps.sftp.tests.test_sftp module

```
class tardis.apps.sftp.tests.test_sftp.SFTPDManagementTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testSFTPDWithoutHostKey ()
        Attempting to start the SFTPD service without a host key should raise an SSHException

class tardis.apps.sftp.tests.test_sftp.SFTPTTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_cyberduck_connection_window ()

    test_sftp ()

    test_sftp_dynamic_docs_dataset ()

    test_sftp_dynamic_docs_experiment ()

    test_sftp_key_connect ()
```

Module contents

Submodules

tardis.apps.sftp.admin module

tardis.apps.sftp.api module

```
class tardis.apps.sftp.api.SFTPAclAuthorization
```

```
    Bases: tastypie.authorization.Authorization
```

```
    create_detail (object_list, bundle)
```

```
    delete_detail (object_list, bundle)
```

```
    read_detail (object_list, bundle)
```

```
    read_list (object_list, bundle)
```

```
class tardis.apps.sftp.api.SFTPPublicKeyAppResource (api_name=None)
```

```
    Bases: tastypie.resources.ModelResource
```

```
    Tastypie model resource for SFTPPublicKey model
```

```
    class Meta
```

```
        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
```

```
        authorization
```

```
        detail_allowed_methods = ['get', 'delete']
```

```
        filtering = {'id': ('exact',), 'name': ('exact',)}
```

```
        list_allowed_methods = ['get', 'post']
```

```
        object_class
```

```
            alias of tardis.apps.sftp.models.SFTPPublicKey
```

```
        queryset
```

```
        resource_name = 'sftp/key'
```

```
        validation = <tastypie.validation.FormValidation object>
```

```
    base_fields = {'added': <tastypie.fields.DateField object>, u'id': <tastypie.fields.
```

```
    declared_fields = {}
```

```
    dehydrate (bundle)
```

```
    hydrate (bundle)
```

tardis.apps.sftp.apps module

```
class tardis.apps.sftp.apps.SFTPConfig (app_name, app_module)
```

```
    Bases: tardis.app_config.AbstractTardisAppConfig
```

```
    name = 'tardis.apps.sftp'
```

```
    verbose_name = 'SFTP'
```

tardis.apps.sftp.default_settings module

`tardis.apps.sftp.default_settings.REQUIRE_SSL_TO_GENERATE_KEY = True`

Require a secure connection (i.e., HTTPS) to allow key generation.

`tardis.apps.sftp.default_settings.SFTP_USERNAME_ATTRIBUTE = 'email'`

The attribute from the User model ('email' or 'username') used to generate the SFTP login example on the sftp_access help page.

tardis.apps.sftp.forms module

```
class tardis.apps.sftp.forms.KeyAddForm(data=None, files=None, auto_id=u'id_%s', pre-  
                                       fix=None, initial=None, error_class=<class  
                                       'django.forms.utils.ErrorList'>, la-  
                                       bel_suffix=None, empty_permitted=False,  
                                       field_order=None, use_required_attribute=None,  
                                       renderer=None)
```

Bases: `django.forms.forms.Form`

```
base_fields = {'key_type': <django.forms.fields.CharField object>, 'name': <django.f
```

```
clean()
```

```
declared_fields = {'key_type': <django.forms.fields.CharField object>, 'name': <djan
```

```
media
```

```
class tardis.apps.sftp.forms.KeyGenerateForm(data=None, files=None,  
                                              auto_id=u'id_%s', prefix=None,  
                                              initial=None, error_class=<class  
                                              'django.forms.utils.ErrorList'>,  
                                              label_suffix=None,  
                                              empty_permitted=False, field_order=None,  
                                              use_required_attribute=None, ren-  
                                              derer=None)
```

Bases: `django.forms.forms.Form`

```
base_fields = {'name': <django.forms.fields.CharField object>}
```

```
declared_fields = {'name': <django.forms.fields.CharField object>}
```

```
media
```

tardis.apps.sftp.models module

```
class tardis.apps.sftp.models.SFTPPublicKey(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

Model for associated SFTP public keys with users

Parameters

- **user** (*ForeignKey for User*) – user who owns this public key
- **name** (*string*) – name for this public key
- **public_key** (*string*) – OpenSSH formatted public key
- **added** (*date*) – date the public key was added (Optional)

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

added

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_next_by_added (***morekwargs*)

get_previous_by_added (***morekwargs*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

public_key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.apps.sftp.sftp module**SFTP Server**

class `tardis.apps.sftp.sftp.DynamicTree` (*host_obj=None*)

Bases: `object`

add_child (*name, obj=None*)

add_path (*path*)

add_path_elems (*elems*)

clear_children ()

```
get_leaf (path, update=False)
update_all_files ()
update_dataset_files ()
update_datasets ()
update_experiments ()
update_nothing ()
```

class tardis.apps.sftp.sftp.**MyTSFTPHandle** (*df, flags=0, optional_args=None*)
Bases: paramiko.sftp_handle.SFTPHandle
SFTP File Handle

stat ()
Return an L{SFTPAttributes} object referring to this open file, or an error code. This is equivalent to L{SFTPServerInterface.stat}, except it's called on an open file instead of a path.

@return: an attributes object for the given file, or an SFTP error code (like L{SFTP_PERMISSION_DENIED}). @rtype: L{SFTPAttributes} I{or error code}

class tardis.apps.sftp.sftp.**MyTSFTPRequestHandler** (*request, client_address, server*)
Bases: SocketServer.BaseRequestHandler

auth_timeout = 60
handle ()
handle_timeout ()
setup ()
timeout = 60

class tardis.apps.sftp.sftp.**MyTSFTPServer** (**args, **kwargs*)
Bases: paramiko.sftp_server.SFTPServer
override SFTPServer to provide channel information to the SFTP subsystem

class tardis.apps.sftp.sftp.**MyTSFTPServerInterface** (*server, *args, **kwargs*)
Bases: paramiko.sftp_si.SFTPServerInterface
MyTardis data via SFTP

canonicalize (*path*)
Return the canonical form of a path on the server.

experiments

list_folder (*path*)
Returns a list of files within a given folder. The C{path} will use posix notation (C{"/"} separates folder names) and may be an absolute or relative path.

The list of files is expected to be a list of L{SFTPAttributes} objects, which are similar in structure to the objects returned by C{os.stat}. In addition, each object should have its C{filename} field filled in, since this is important to a directory listing and not normally present in C{os.stat} results.

In case of an error, you should return one of the C{SFTP_*} error codes, such as L{SFTP_PERMISSION_DENIED}.

@param path: the requested path (relative or absolute) to be listed. @type path: str @return: a list of the files in the given folder, using L{SFTPAttributes} objects. @rtype: list of L{SFTPAttributes} I{or error code}

lstat (*path*)

symbolic links are not supported

open (*path, flags, attr*)

Open a file on the server and create a handle for future operations on that file. On success, a new object subclassed from L{SFTPHandle} should be returned. This handle will be used for future operations on the file (read, write, etc). On failure, an error code such as L{SFTP_PERMISSION_DENIED} should be returned.

C{flags} contains the requested mode for opening (read-only, write-append, etc) as a bitset of flags from the C{os} module:

- C{os.O_RDONLY}
- C{os.O_WRONLY}
- C{os.O_RDWR}
- C{os.O_APPEND}
- C{os.O_CREAT}
- C{os.O_TRUNC}
- C{os.O_EXCL}

(One of C{os.O_RDONLY}, C{os.O_WRONLY}, or C{os.O_RDWR} will always be set.)

The C{attr} object contains requested attributes of the file if it has to be created. Some or all attribute fields may be missing if the client didn't specify them.

@note: The SFTP protocol defines all files to be in "binary" mode. There is no equivalent to python's "text" mode.

Parameters

- **path** (*basestring*) – the requested datafile path
- **flags** (*int*) – flags or'd together from the C{os} module indicating the requested mode for opening the file.
- **attr** (*SFTPAttributes*) – requested attributes of the file if it is newly created.

Returns a new L{SFTPHandle} I{or error code}.

Return type SFTPHandle

session_ended ()

run cleanup on exceptions or disconnection. idea: collect stats and store them in this function

session_started ()

run on connection initialisation

stat (*path*)

Return an L{SFTPAttributes} object for a path on the server, or an error code. If your server supports symbolic links (also known as "aliases"), you should follow them. (L{lstat} is the corresponding call that doesn't follow symlinks/aliases.)

@param path: the requested path (relative or absolute) to fetch file statistics for. @type path: str

@return: an attributes object for the given file, or an SFTP error code (like L{SFTP_PERMISSION_DENIED}). @rtype: L{SFTPAttributes} I{or error code}

```
class tardis.apps.sftp.sftp.MyTSFTPTCPServer (address, host_key, RequestHandler-  
                                              Class=None)
```

Bases: SocketServer.TCPServer

```
allow_reuse_address = True
```

```
close_request(request)
```

```
shutdown_request(request)
```

```
class tardis.apps.sftp.sftp.MyTServerInterface
```

```
    Bases: paramiko.server.ServerInterface
```

```
    check_auth_interactive(username, submethods)
```

Begin an interactive authentication challenge, if supported. You should override this method in server mode if you want to support the "keyboard-interactive" auth type, which requires you to send a series of questions for the client to answer.

Return `AUTH_FAILED` if this auth method isn't supported. Otherwise, you should return an *InteractiveQuery* object containing the prompts and instructions for the user. The response will be sent via a call to *check_auth_interactive_response*.

The default implementation always returns `AUTH_FAILED`.

Parameters

- **username** (*str*) – the username of the authenticating client
- **submethods** (*str*) – a comma-separated list of methods preferred by the client (usually empty)

Returns `AUTH_FAILED` if this auth method isn't supported; otherwise an object containing queries for the user

Return type `int` or *InteractiveQuery*

```
    check_auth_interactive_response(responses)
```

Continue or finish an interactive authentication challenge, if supported. You should override this method in server mode if you want to support the "keyboard-interactive" auth type.

Return `AUTH_FAILED` if the responses are not accepted, `AUTH_SUCCESSFUL` if the responses are accepted and complete the authentication, or `AUTH_PARTIALLY_SUCCESSFUL` if your authentication is stateful, and this set of responses is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

If you wish to continue interactive authentication with more questions, you may return an *InteractiveQuery* object, which should cause the client to respond with more answers, calling this method again. This cycle can continue indefinitely.

The default implementation always returns `AUTH_FAILED`.

Parameters **responses** – list of *str* responses from the client

Returns `AUTH_FAILED` if the authentication fails; `AUTH_SUCCESSFUL` if it succeeds; `AUTH_PARTIALLY_SUCCESSFUL` if the interactive auth is successful, but authentication must continue; otherwise an object containing queries for the user

Return type `int` or *InteractiveQuery*

```
    check_auth_password(username, password)
```

Determine if a given username and password supplied by the client is acceptable for use in authentication.

Return `AUTH_FAILED` if the password is not accepted, `AUTH_SUCCESSFUL` if the password is accepted and completes the authentication, or `AUTH_PARTIALLY_SUCCESSFUL` if your authentication is stateful, and this key is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

The default implementation always returns `AUTH_FAILED`.

Parameters

- **username** (*str*) – the username of the authenticating client.
- **password** (*str*) – the password given by the client.

Returns `AUTH_FAILED` if the authentication fails; `AUTH_SUCCESSFUL` if it succeeds; `AUTH_PARTIALLY_SUCCESSFUL` if the password auth is successful, but authentication must continue.

Return type `int`

check_auth_publickey (*username, key*)

Determine if a given key supplied by the client is acceptable for use in authentication. You should override this method in server mode to check the username and key and decide if you would accept a signature made using this key.

Return `AUTH_FAILED` if the key is not accepted, `AUTH_SUCCESSFUL` if the key is accepted and completes the authentication, or `AUTH_PARTIALLY_SUCCESSFUL` if your authentication is stateful, and this password is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

Note that you don't have to actually verify any key signature here. If you're willing to accept the key, Paramiko will do the work of verifying the client's signature.

The default implementation always returns `AUTH_FAILED`.

Parameters

- **username** (*str*) – the username of the authenticating client
- **key** (*PKey*) – the key object provided by the client

Returns `AUTH_FAILED` if the client can't authenticate with this key; `AUTH_SUCCESSFUL` if it can; `AUTH_PARTIALLY_SUCCESSFUL` if it can authenticate with this key but must continue with authentication

Return type `int`

check_channel_request (*kind, chanid*)

Determine if a channel request of a given type will be granted, and return `OPEN_SUCCEEDED` or an error code. This method is called in server mode when the client requests a channel, after authentication is complete.

If you allow channel requests (and an ssh server that didn't would be useless), you should also override some of the channel request methods below, which are used to determine which services will be allowed on a given channel:

- *check_channel_pty_request*
- *check_channel_shell_request*
- *check_channel_subsystem_request*
- *check_channel_window_change_request*
- *check_channel_x11_request*
- *check_channel_forward_agent_request*

The `chanid` parameter is a small number that uniquely identifies the channel within a `.Transport`. A `.Channel` object is not created unless this method returns `OPEN_SUCCEEDED` – once a `.Channel` object is created, you can call `.Channel.get_id` to retrieve the channel ID.

The return value should either be `OPEN_SUCCEEDED` (or 0) to allow the channel request, or one of the following error codes to reject it:

- `OPEN_FAILED_ADMINISTRATIVELY_PROHIBITED`
- `OPEN_FAILED_CONNECT_FAILED`
- `OPEN_FAILED_UNKNOWN_CHANNEL_TYPE`
- `OPEN_FAILED_RESOURCE_SHORTAGE`

The default implementation always returns `OPEN_FAILED_ADMINISTRATIVELY_PROHIBITED`.

Parameters

- **kind** (*str*) – the kind of channel the client would like to open (usually "session").
- **chanid** (*int*) – ID of the channel

Returns an *int* success or failure code (listed above)

`get_allowed_auths` (*username*)

Return a list of authentication methods supported by the server. This list is sent to clients attempting to authenticate, to inform them of authentication methods that might be successful.

The “list” is actually a string of comma-separated names of types of authentication. Possible values are "password", "publickey", and "none".

The default implementation always returns "password".

Parameters **username** (*str*) – the username requesting authentication.

Returns a comma-separated *str* of authentication types

`myt_auth` (*username, password*)

`tardis.apps.sftp.sftp.start_server` (*host=None, port=None, keyfile=None*)

The `SFTP_HOST_KEY` setting is required for configuring SFTP access. The `SFTP_PORT` setting defaults to 2200.

See: `tardis/default_settings/sftp.py`

tardis.apps.sftp.urls module

tardis.apps.sftp.user_menu_modifiers module

`tardis.apps.sftp.user_menu_modifiers.add_ssh_keys_menu_item` (*request, user_menu*)

Add a ‘Manage SSH Keys’ item to the user menu

Parameters

- **request** (`django.http.HttpRequest`) – an HTTP Request instance
- **user_menu** (*list*) – user menu context to modify

Returns `user_menu` list

Return type *list*

tardis.apps.sftp.views module

`tardis.apps.sftp.views.cybderduck_connection_window(request, *args, **kwargs)`

`tardis.apps.sftp.views.sftp_access(request, *args, **kwargs)`

Show dynamically generated instructions on how to connect to SFTP :param Request request: HttpRequest
:return: HttpResponse :rtype: HttpResponse

`tardis.apps.sftp.views.sftp_keys(request, *args, **kwargs)`

Generate an RSA key pair for a user.

Generates a key pair, stores the public part of the key and provides a one time opportunity for the user to download the private part of the key.

Parameters `request` (*HttpRequest*) – http request

Returns either returns form on GET request or private key download on POST request

Return type `HttpResponse`

Module contents

tardis.apps.social_auth package

Subpackages

tardis.apps.social_auth.auth package

Submodules

tardis.apps.social_auth.auth.authorisation module

tardis.apps.social_auth.auth.social_auth module

`tardis.apps.social_auth.auth.social_auth.add_authentication_method(**kwargs)`

Creates an authentication record for OpenID authenticated user

`tardis.apps.social_auth.auth.social_auth.add_migration_permission(**kwargs)`

Adds permission to migrate account for OpenID authenticated user

`tardis.apps.social_auth.auth.social_auth.add_user_permissions(**kwargs)`

Adds default permission to OpenID authenticated user

`tardis.apps.social_auth.auth.social_auth.approve_user_auth(**kwargs)`

Sets approved status to True in user authentication This will add user permissions as well.

`tardis.apps.social_auth.auth.social_auth.get_auth_method(authenticatedBackendName)`

Return matching user authentication method from list of authentication methods in settings

`tardis.apps.social_auth.auth.social_auth.is_openid_migration_enabled()`

`tardis.apps.social_auth.auth.social_auth.migrate_user_message(**kwargs)`

Automatically detects if a user has an account with the same email address and prompts user to perform migration.

`tardis.apps.social_auth.auth.social_auth.requires_admin_approval(authenticationBackend)`

```
tardis.apps.social_auth.auth.social_auth.send_admin_email(**kwargs)
```

Sends MyTardis admins an email for approving account

Module contents

Submodules

`tardis.apps.social_auth.apps` module

```
class tardis.apps.social_auth.apps.SocialAuthConfig(app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.social_auth'
    verbose_name = 'Social Auth'
```

`tardis.apps.social_auth.default_settings` module

`tardis.apps.social_auth.urls` module

Module contents

Module contents

`tardis.default_settings` package

Submodules

`tardis.default_settings.admins` module

```
tardis.default_settings.admins.ADMINS = []
```

A list of all the people who get code error notifications. When `DEBUG=False` and `AdminEmailHandler` is configured in `LOGGING` (done by default), Django emails these people the details of exceptions raised in the request/response cycle.

Each item in the list should be a tuple of (Full name, email address). Example:

```
[('John', 'john@example.com'), ('Mary', 'mary@example.com')]
```

`tardis.default_settings.analytics` module

`tardis.default_settings.apps` module

```
tardis.default_settings.apps.USER_MENU_MODIFIERS = ['tardis.apps.sftp.user_menu_modifiers...]
```

A list of methods which can modify the user menu defined in `tardis.tardis_portal.context_processors.user_menu_processor`. The modifications will be applied in order, so it is possible for one app to overwrite changes made by another app whose modifier method is earlier in the list.

Each modifier method should take a `django.http.HttpRequest` object and a list of user menu items, and return a modified list of user menu items.

An example from the SFTP app is below:

```
USER_MENU_MODIFIERS.extend([
    'tardis.apps.sftp.user_menu_modifiers.add_ssh_keys_menu_item'
])
```

tardis.default_settings.auth module

`tardis.default_settings.auth.AUTOGENERATE_API_KEY = False`

Generate a tastypie API key with user post_save (`tardis/tardis_portal/models/hooks.py`)

`tardis.default_settings.auth.REGISTRATION_OPEN = True`

Enable/disable the self-registration link and form in the UI. Note - this does not actually disable the URL endpoints for registration. You must also remove the *registration* app from *INSTALLED_APPS* to disable registration.

tardis.default_settings.caches module

`tardis.default_settings.caches.CACHES = {'celery-locks': {'BACKEND': 'django.core.cache.backends.memcached.MemcachedBackend'}}`
change the CACHES setting to memcached if you prefer. Requires additional dependencies.

tardis.default_settings.celery_settings module

tardis.default_settings.custom_views module

`tardis.default_settings.custom_views.DATASET_VIEWS = []`

Dataset view overrides ('contextual views') are specified as tuples mapping a Schema namespace to a class-based view (or view function). See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#dataset-and-experiment-views

e.g.:

```
DATASET_VIEWS = [
    ('http://example.org/schemas/dataset/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomDatasetViewSubclass'),
]
```

`tardis.default_settings.custom_views.EXPERIMENT_VIEWS = []`

Experiment view overrides ('contextual views') are specified as tuples mapping a Schema namespace to a class-based view (or view function). See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#dataset-and-experiment-views

e.g.:

```
EXPERIMENT_VIEWS = [
    ('http://example.org/schemas/expt/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomExptViewSubclass'),
]
```

`tardis.default_settings.custom_views.INDEX_VIEWS = {}`

A custom index page override is defined in as dictionary mapping a class-based view (or view function) to a Django Site, specified by `SITE_ID` (an integer) or the domain name of the incoming request. See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#custom-index-view

e.g.:

```
INDEX_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomIndexSubclass',
    'store.example.com': 'tardis.apps.myapp.AnotherCustomIndexSubclass'
}
```

`tardis.default_settings.custom_views.LOGIN_VIEWS = {}`

A custom login page override is defined in as dictionary mapping a class-based view (or view function) to a Django Site, specified by `SITE_ID` (an integer) or the domain name of the incoming request. See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#custom-login-view

e.g.:

```
LOGIN_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomLoginSubclass',
    'store.example.com': 'tardis.apps.myapp.AnotherCustomLoginSubclass'
}
```

tardis.default_settings.database module

tardis.default_settings.debug module

`tardis.default_settings.debug.ALLOWED_HOSTS = ['*']`

For security reasons this needs to be set to your hostname and/or IP address in production.

`tardis.default_settings.debug.DEBUG = True`

Set to false for production use

`tardis.default_settings.debug.INTERNAL_IPS = ('127.0.0.1',)`

A list of IP addresses, as strings, that: Allow the `debug()` context processor to add some variables to the template context.

tardis.default_settings.downloads module

`tardis.default_settings.downloads.DEFAULT_ARCHIVE_FORMATS = ['tar']`

Site's preferred archive types, with the most preferred first other available option: 'tgz'. Add to list if desired

tardis.default_settings.email module

`tardis.default_settings.email.DEFAULT_FROM_EMAIL = 'webmaster@localhost'`

This can be set as : “MyTardis Admins <admins@mytardis.org>”

`tardis.default_settings.email.EMAIL_HOST = 'localhost'`

Set this to your local SMTP server, e.g. 'smtp.example.edu' or to a remote SMTP server, e.g. 'smtp.gmail.com'

`tardis.default_settings.email.EMAIL_HOST_PASSWORD = ''`

When using a local SMTP server, you probably don't need to authenticate, so you can leave this blank.

If using a remote SMTP server, this can be set to the password used to authenticate.

```
tardis.default_settings.email.EMAIL_HOST_USER = ''
```

When using a local SMTP server, you probably don't need to authenticate, so you can leave this blank.

If using a remote SMTP server, this can be set to the email address used to authenticate, e.g. 'bob@bobmail.com'

```
tardis.default_settings.email.EMAIL_PORT = 25
```

Some SMTP servers require a different port, e.g. 587. Django's default value for this setting is 25.

```
tardis.default_settings.email.EMAIL_USE_TLS = False
```

Some SMTP servers require this to be set to True. Django's default value for this setting is False.

tardis.default_settings.filters module

tardis.default_settings.frontend module

```
tardis.default_settings.frontend.BLEACH_ALLOWED_ATTRIBUTES = {'a': ['href', 'title'], 'ab
```

These are the default bleach values and shown here as an example.

```
tardis.default_settings.frontend.BLEACH_ALLOWED_TAGS = ['a', 'abbr', 'acronym', 'b', 'bloc
```

These are the default bleach values and shown here as an example.

tardis.default_settings.i18n module

tardis.default_settings.localisation module

tardis.default_settings.logging module

tardis.default_settings.middlewares module

tardis.default_settings.publication module

tardis.default_settings.search module

tardis.default_settings.sharing module

tardis.default_settings.site_customisations module

```
tardis.default_settings.site_customisations.SITE_TITLE = 'MyTardis'
```

customise the title of your site

```
tardis.default_settings.site_customisations.SPONSORED_TEXT = None
```

add text to the footer to acknowledge someone

tardis.default_settings.static_files module

tardis.default_settings.storage module

```
tardis.default_settings.storage.METADATA_STORE_PATH = '/home/docs/checkouts/readthedocs.org
```

storage path for image paths stored in parameters. Better to set to another location if possible

tardis.default_settings.templates module

tardis.default_settings.uploads module

tardis.default_settings.uploads.UPLOAD_METHOD = False

Old version: UPLOAD_METHOD = “uploadify”. This can be changed to an app that provides an upload_button function, eg. “tardis.apps.filepicker.views.upload_button” to use a fancy commercial uploader. To use filepicker, please also get an API key at <http://filepicker.io>

tardis.default_settings.urls module

Module contents

tardis.default_settings.get_git_version()

tardis.search package

Submodules

tardis.search.datafile_index module

search indexes for single search

```
class tardis.search.datafile_index.DataFileIndex
    Bases: haystack.indexes.SearchIndex, haystack.constants.Indexable
    datafile_filename = <haystack.fields.CharField object>
    dataset_id_stored = <haystack.fields.IntegerField object>
    experiment_id_stored = <haystack.fields.MultiValueField object>
    fields = {'datafile_filename': <haystack.fields.CharField object>, 'dataset_id_stored': <haystack.fields.IntegerField object>}
    get_model()
    objects = <haystack.manager.SearchIndexManager object>
    prepare_experiment_id_stored(obj)
    prepare_text(obj)
    text = <haystack.fields.CharField object>
```

tardis.search.forms module

```
class tardis.search.forms.GroupedSearchForm(*args, **kwargs)
    Bases: haystack.forms.ModelSearchForm
    base_fields = {'q': <django.forms.fields.CharField object>}
    declared_fields = {'q': <django.forms.fields.CharField object>}
    media
    search(*args, **kwargs)
```

tardis.search.search_indexes module

search indexes for single search

```
class tardis.search.search_indexes.DatasetIndex
    Bases: haystack.indexes.SearchIndex, haystack.constants.Indexable

    dataset_description = <haystack.fields.CharField object>
    dataset_id_stored = <haystack.fields.IntegerField object>
    experiment_id_stored = <haystack.fields.MultiValueField object>
    fields = {'dataset_description': <haystack.fields.CharField object>, 'dataset_id_stor
    get_model()

    objects = <haystack.manager.SearchIndexManager object>
    prepare_experiment_id_stored(obj)
    prepare_text(obj)
        Elasticsearch's standard tokenizer won't split on underscores, as it uses the Unicode Text Segmentation
        algorithm, as specified in the Unicode Standard Annex #29. Some MyTardis users replace spaces with
        underscores in folder names, because their instrument data collection software won't allow spaces in paths,
        so we replace underscores with spaces in the search index, but they will still appear as underscores in the
        search results.

    text = <haystack.fields.CharField object>
```

```
class tardis.search.search_indexes.ExperimentIndex
    Bases: haystack.indexes.SearchIndex, haystack.constants.Indexable

    experiment_author = <haystack.fields.MultiValueField object>
    experiment_created_time = <haystack.fields.DateTimeField object>
    experiment_creator = <haystack.fields.CharField object>
    experiment_description = <haystack.fields.CharField object>
    experiment_end_time = <haystack.fields.DateTimeField object>
    experiment_id_stored = <haystack.fields.IntegerField object>
    experiment_institution_name = <haystack.fields.CharField object>
    experiment_start_time = <haystack.fields.DateTimeField object>
    experiment_title = <haystack.fields.CharField object>
    experiment_update_time = <haystack.fields.DateTimeField object>
    fields = {'experiment_author': <haystack.fields.MultiValueField object>, 'experiment_
    get_model()

    index_queryset(using=None)
        Used when the entire index for model is updated.

    objects = <haystack.manager.SearchIndexManager object>
    prepare_experiment_creator(obj)
    prepare_experimentauthor(obj)
```

prepare_text (*obj*)

Elasticsearch's standard tokenizer won't split on underscores, as it uses the Unicode Text Segmentation algorithm, as specified in the Unicode Standard Annex #29. Some MyTardis users replace spaces with underscores in folder names, because their instrument data collection software won't allow spaces in paths, so we replace underscores with spaces in the search index, but they will still appear as underscores in the search results.

text = <haystack.fields.CharField object>

tardis.search.urls module

tardis.search.utils module

class tardis.search.utils.**SearchQueryString** (*query_string*)

Bases: `object`

Class to manage switching between space separated search queries and '+' separated search queries (for addition to urls)

TODO This would probably be better handled with filters

query_string ()

url_safe_query ()

tardis.search.views module

views relevant to search

class tardis.search.views.**ExperimentSearchView** (***kwargs*)

Bases: `haystack.generic_views.SearchView`

create_response ()

extra_context ()

class tardis.search.views.**SingleSearchView** (***kwargs*)

Bases: `haystack.generic_views.SearchView`

form_class

alias of `tardis.search.forms.GroupedSearchForm`

form_valid (*form*)

If the form is valid, redirect to the supplied URL.

template_name = 'search/search.html'

tardis.search.views.**search_experiment** (*request*)

Either show the search experiment form or the result of the search experiment query.

tardis.search.views.**search_quick** (*request*)

Module contents

tardis.tardis_portal package

Subpackages

tardis.tardis_portal.auth package

Submodules

tardis.tardis_portal.auth.authentication module

A module containing helper methods for the `manage_auth_methods` function in `views.py`.

`tardis.tardis_portal.auth.authentication.add_auth_method(request)`

Add a new authentication method to `request.user`'s existing list of authentication methods. This method will ask for a confirmation if the user wants to merge two accounts if the authentication method he provided already exists as a method for another user.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.edit_auth_method(request)`

Change the local DB (Django) password for `request.user`.

`tardis.tardis_portal.auth.authentication.list_auth_methods(request)`

Generate a list of authentication methods that `request.user` uses to authenticate to the system and send it back in a `HttpResponse`.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.merge_auth_method(request)`

Merge the account that the user is logged in as and the account that he provided in the Authentication Form. Merging accounts involve relinking the `UserAuthentication` table entries, transferring `ObjectACL` entries to the merged account, changing the Group memberships and deleting the unneeded account.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.remove_auth_method(request)`

Removes the non-local DB auth method from the `UserAuthentication` model.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

tardis.tardis_portal.auth.authorisation module

Object-level authorisation backend

class `tardis.tardis_portal.auth.authorisation.ACLAwareBackend`

Bases: `object`

```
app_label = 'tardis_acls'

authenticate(request)
    do not use this backend for authentication

get_perm_bool(verb)
    relates ACLs to permissions

has_perm(user_obj, perm, obj=None)
    main method, calls other methods based on permission type queried

supports_anonymous_user = True

supports_object_permissions = True
```

tardis.tardis_portal.auth.authservice module

models.py

```
class tardis.tardis_portal.auth.authservice.AuthService(settings=<LazySettings
                                                         "tardis.test_settings">)
```

The AuthService provides an interface for querying the auth(nl) framework within MyTardis. The auth service works by reading the class path to plugins from the settings file.

Parameters **settings** (`django.conf.settings`) – the settings object that contains the list of user and group plugins.

authenticate (*authMethod*, ***credentials*)

Try and authenticate the user using the auth type he/she specified to use and if authentication didn't work using that

Parameters

- **authMethod** (*string*) – the shortname of the auth method.
- **credentials** (*kwargs*) – the credentials as expected by the auth plugin

Returns authenticated User or None

Return type User or `None`

getGroups (*user*)

Parameters **user** (*User*) – User

Returns a list of tuples containing pluginname and group id

Return type `list`

getGroupsForEntity (*entity*)

Return a list of the groups an entity belongs to

Parameters **entity** (*string*) – the entity to search for, user or group.

Returns groups

Return type Group

The groups will be returned as a list similar to:

```
[{'name': 'Group 456', 'id': '2'},
 {'name': 'Group 123', 'id': '1'}]
```

getUser (*authMethod, user_id, force_user_create=False*)

Return a user model based on the given auth method and user id.

This function is responsible for creating the user within the Django DB and returning the resulting user model.

getUsernameByEmail (*authMethod, email*)

Return a username given the auth method and email address of a user.

get_or_create_user (*user_obj_or_dict, authMethod=None*)

refactored out for external use by AAF and possibly others

searchEntities (*filter*)

Return a list of users and/or groups

searchGroups (***kw*)

basestring id: the value of the id to search for basestring name: the value of the displayname to search for int max_results: the maximum number of elements to return basestring sort_by: the attribute the users should be sorted on basestring plugin: restrict the search to the specific group provider

returns: a list of users and/or groups rtype: list

searchUsers (*filter*)

Return a list of users and/or groups

tardis.tardis_portal.auth.decorators module

tardis.tardis_portal.auth.decorators.**datafile_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_download_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_write_permissions_required** (*f*)

tardis.tardis_portal.auth.decorators.**delete_permissions_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_download_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_ownership_required** (*f*)

A decorator for Django views that validates if a user is an owner of an experiment or ‘superuser’ prior to further processing the request. Unauthenticated requests are redirected to the login page. If the user making the request satisfies none of these criteria, an error response is returned.

Parameters *f* (*types.FunctionType*) – A Django view function

Returns A Django view function

Return type *types.FunctionType*

tardis.tardis_portal.auth.decorators.**get_accessible_datafiles_for_user** (*request*)

tardis.tardis_portal.auth.decorators.**get_accessible_experiments** (*request*)

tardis.tardis_portal.auth.decorators.**get_accessible_experiments_for_dataset** (*request, dataset_id*)

tardis.tardis_portal.auth.decorators.**get_owned_experiments** (*request*)

tardis.tardis_portal.auth.decorators.**get_shared_experiments** (*request*)

`tardis.tardis_portal.auth.decorators.group_ownership_required(f)`

A decorator for Django views that validates if a user is a group admin or 'superuser' prior to further processing the request. Unauthenticated requests are redirected to the login page. If the user making the request satisfies none of these criteria, an error response is returned.

Parameters *f* (*types.FunctionType*) – A Django view function

Returns A Django view function

Return type *types.FunctionType*

`tardis.tardis_portal.auth.decorators.has_datafile_access(request, datafile_id)`

`tardis.tardis_portal.auth.decorators.has_datafile_download_access(request, datafile_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_access(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_download_access(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_ownership(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_write(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_delete_permissions(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_access(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_download_access(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_ownership(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_write(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_read_or_owner_ACL(request, experiment_id)`

Check whether the user has read access to the experiment - this means either they have been granted read access, or that they are the owner.

NOTE: This does not check whether the experiment is public or not, which means even when the experiment is public, this method does not automatically returns true.

As such, this method should NOT be used to check whether the user has general read permission.

`tardis.tardis_portal.auth.decorators.has_write_permissions(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.is_group_admin(request, *args, **kwargs)`

`tardis.tardis_portal.auth.decorators.upload_auth(f)`

`tardis.tardis_portal.auth.decorators.write_permissions_required(f)`

tardis.tardis_portal.auth.fix_circular module

`tardis.tardis_portal.auth.fix_circular.getGroups(user)`

tardis.tardis_portal.auth.interfaces module

class tardis.tardis_portal.auth.interfaces.**AuthProvider**

authenticate (*request*)

from a request authenticate try to authenticate the user. return a user dict if successful.

getUsernameByEmail (*email*)

returns the username (format string) from the auth domain

Implementing this function is optional- it is needed for resolving experiment owner email addresses to usernames during ingestion.

get_user (*user_id*)

class tardis.tardis_portal.auth.interfaces.**GroupProvider**

getGroupById (*id*)

return the group associated with the id

getGroups (*user*)

return an iteration of the available groups.

getGroupsForEntity (*id*)

return a list of groups associated with a particular entity id

searchGroups (***filter*)

return a list of groups that match the filter

class tardis.tardis_portal.auth.interfaces.**UserProvider**

getUserById (*id*)

return the user dictionary in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

getUsernameByEmail (*email*)

returns the username (format string) from the auth domain needed for resolving experiment owners during ingestion

searchUsers (***filter*)

return a list of user descriptions from the auth domain.

each user is in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

tardis.tardis_portal.auth.ldap_auth module

tardis.tardis_portal.auth.localdb_auth module

Local DB Authentication module.

class tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend

Bases: *tardis.tardis_portal.auth.interfaces.AuthProvider*

Authenticate against Django's Model Backend.

authenticate (*request*)

authenticate a user, this expect the user will be using form based auth and the *username* and *password* will be passed in as **POST** variables.

Parameters **request** (*django.http.HttpRequest*) – a HTTP Request instance

Returns authenticated User

Return type User

get_user (*user_id*)

class tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider

Bases: *tardis.tardis_portal.auth.interfaces.GroupProvider*

getGroupById (*id*)

return the group associated with the id:

```
{ "id": 123,
```

```
  "display": "Group Name", }
```

getGroups (*user*)

return an iteration of the available groups.

name = u'django_group'

searchGroups (***filter*)

class tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider

Bases: *tardis.tardis_portal.auth.interfaces.UserProvider*

getUserById (*id*)

return the user dictionary in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

name = u'django_user'

tardis.tardis_portal.auth.token_auth module

token authentication module

class tardis.tardis_portal.auth.token_auth.TokenAuthMiddleware (*get_response*)

Bases: *object*

adds tokens to the user object and the session from a GET query

process_request (*request*)

```
class tardis.tardis_portal.auth.token_auth.TokenGroupProvider
    Bases: tardis.tardis_portal.auth.interfaces.GroupProvider

    Transforms tokens into auth groups

    getGroups (user)

    name = u'token_group'

    searchGroups (**kwargs)
        return nothing because these are not groups in the standard sense
```

tardis.tardis_portal.auth.utils module

Created on 15/03/2011

@author: gerson

```
tardis.tardis_portal.auth.utils.configure_user (user)
    Configure a user account that has just been created by adding the user to the default groups and marking it as a
    not a Django account.
```

Parameters *user* (*User*) – the User instance for the newly created account

Returns User profile for user

Return type *UserProfile*

```
tardis.tardis_portal.auth.utils.create_user (auth_method, user_id, email="")
```

```
tardis.tardis_portal.auth.utils.get_or_create_user (auth_method, user_id, email="")
```

Module contents

tardis.tardis_portal.filters package

Submodules

tardis.tardis_portal.filters.jeolsem module

```
class tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter
    Bases: object
```

This filter collects metadata from JEOL SEM text files.

param name: the short name of the schema. type name: string param schema: the name of the schema to load the EXIF data into. type schema: string

```
ATTR_PREFIXES = ('$CM_', '$$SM_')
```

```
SCHEMA = 'http://www.jeol.com/#jeol-sem-schema'
```

```
get_file_contents (datafile)
```

```
get_metadata (schema, filedata)
```

```
is_already_processed (datafile)
```

```
is_jeol_sem_metadata (filedata)
```

```
is_text_file (datafile)
```

```
save_metadata (datafile, schema, metadata)
```

Module contents

```
__init__.py
```

```
class tardis.tardis_portal.filters.FilterInitMiddleware (get_response,          fil-
                                                         ters=None)
    Bases: object
```

tardis.tardis_portal.management package

Subpackages

tardis.tardis_portal.management.commands package

Submodules

tardis.tardis_portal.management.commands.createuser module

Management utility to create regular users.

```
class tardis.tardis_portal.management.commands.createuser.Command (stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)
    Bases: django.core.management.base.BaseCommand
    add_arguments (parser)
    handle (*args, **options)
    help = 'Used to create a MyTardis user.'
tardis.tardis_portal.management.commands.createuser.is_valid_email (value)
```

tardis.tardis_portal.management.commands.dumpschemas module

Command for dumping soft schema definitions

```
class tardis.tardis_portal.management.commands.dumpschemas.Command (stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)
    Bases: django.core.management.base.BaseCommand
    add_arguments (parser)
    args = '[namespace...]'
    handle (*args, **options)
    help = 'Dump soft schema definitions. No namespace = dump all schemas'
```

tardis.tardis_portal.management.commands.loadschemas module

Command for loading soft schema definitions

```
class tardis.tardis_portal.management.commands.loadschemas.Command(stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)

    Bases: django.core.management.base.BaseCommand

    add_arguments (parser)

    args = 'schema [schema ...]'

    handle (*args, **options)

    help = 'Load soft schema definitions'
```

tardis.tardis_portal.management.commands.rmexperiment module

Management command to delete the specified experiment and its associated datasets, datafiles and parameters.

The operation is atomic, either the entire experiment is deleted, or nothing.

rmexperiment was introduced due to the Oracle DISTINCT workaround causing sql delete cascading to fail. The current implementation of rmexperiment still relies on some cascading.

```
class tardis.tardis_portal.management.commands.rmexperiment.Command(stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)

    Bases: django.core.management.base.BaseCommand

    add_arguments (parser)

    args = '<MyTardis Exp ID>'

    handle (*args, **options)

    help = 'Delete the supplied MyTardis Experiment ID'
```

tardis.tardis_portal.management.commands.runfilters module

Management command to (re-)run the ingestion filters by hand.

```
class tardis.tardis_portal.management.commands.runfilters.Command(stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)

    Bases: django.core.management.base.BaseCommand

    add_arguments (parser)

    args = ' [<filter-no>] ... '

    handle (*args, **options)

    help = "Run selected ingestion filters on all Datafiles.\nNote that a typical ingestion filter will be run on all datafiles in the system."

    instantiateFilters (filterIds)

    listFilters ()

    runFilters (filters, dryRun=False)
```

Module contents

Module contents

tardis.tardis_portal.migrations package

Submodules

tardis.tardis_portal.migrations.0001_initial module

```
class tardis.tardis_portal.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'contenttypes', u'0002_remove_content_type_name'), (u'auth', u'__first__')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'first_name', <django.db.models.fields.CharField>), (u'last_name', <django.db.models.fields.CharField>), (u'email', <django.db.models.fields.CharField>), (u'password', <django.db.models.fields.CharField>), (u'is_staff', <django.db.models.fields.BooleanField>), (u'is_superuser', <django.db.models.fields.BooleanField>), (u'groups', <django.db.models.fields.related.ManyToManyField>), (u'user_permissions', <django.db.models.fields.related.ManyToManyField>), (u'profile', <django.db.models.fields.related.OneToOneField>)]>]
```

tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643 module

```
class tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'contenttypes', u'0002_remove_content_type_name'), (u'auth', u'__first__')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'first_name', <django.db.models.fields.CharField>), (u'last_name', <django.db.models.fields.CharField>), (u'email', <django.db.models.fields.CharField>), (u'password', <django.db.models.fields.CharField>), (u'is_staff', <django.db.models.fields.BooleanField>), (u'is_superuser', <django.db.models.fields.BooleanField>), (u'groups', <django.db.models.fields.related.ManyToManyField>), (u'user_permissions', <django.db.models.fields.related.ManyToManyField>), (u'profile', <django.db.models.fields.related.OneToOneField>)]>, <ReplaceModel model=tardis_portal.Profile>]
    replaces = [(u'tardis_portal', u'0001_initial'), (u'tardis_portal', u'0002_auto_20150528_1128')]
tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643.cast_string_to_integer
```

tardis.tardis_portal.migrations.0002_auto_20150528_1128 module

```
class tardis.tardis_portal.migrations.0002_auto_20150528_1128.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0001_initial')]
    operations = [<AlterField field=<django.db.models.fields.related.OneToOneField>, name=tardis_portal.Profile, to_type=django.db.models.fields.related.OneToOneField>]
```

tardis.tardis_portal.migrations.0003_auto_20150907_1315 module

```
class tardis.tardis_portal.migrations.0003_auto_20150907_1315.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0002_auto_20150528_1128')]
    operations = [<AlterField field=<django.db.models.fields.IntegerField>, name=tardis_portal.Profile.data_type, to_type=django.db.models.fields.IntegerField>]
```

tardis.tardis_portal.migrations.0004_storageboxoption_value_type module

```
class tardis.tardis_portal.migrations.0004_storageboxoption_value_type.Migration(name,
                                         app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0003_auto_20150907_1315')]
    operations = [<AddField field=<django.db.models.fields.CharField>, name=u'value_type',
```

tardis.tardis_portal.migrations.0005_datafile_add_size_int_column module

```
class tardis.tardis_portal.migrations.0005_datafile_add_size_int_column.Migration(name,
                                         app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0004_storageboxoption_value_type')]
    operations = [<AddField field=<django.db.models.fields.BigIntegerField>, name=u'_size'
tardis.tardis_portal.migrations.0005_datafile_add_size_int_column.cast_string_to_integer(ap
sc
```

tardis.tardis_portal.migrations.0006_datafile_remove_size_string_column module

```
class tardis.tardis_portal.migrations.0006_datafile_remove_size_string_column.Migration(name,
                                         app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0005_datafile_add_size_int_column')]
    operations = [<RemoveField name=u'size', model_name=u'datafile'>, <RenameField new_name
```

tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index module

```
class tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index.Migration(name,
                                         app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0006_datafile_remove_size_string_column')]
    operations = [<AlterField field=<django.db.models.fields.TextField>, name=u'string_val
```

tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres module

```
class tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres.Migration(name,
                                         app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0007_remove_parameter_string_value_index')]
    operations = []
```

tardis.tardis_portal.migrations.0009_auto_20160128_1119 module

```
class tardis.tardis_portal.migrations.0009_auto_20160128_1119.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0008_string_value_partial_index_postgres')]  
    operations = [<AlterUniqueTogether unique_together=set([(u'name', u'facility')]), name=
```

tardis.tardis_portal.migrations.0010_auto_20160503_1443 module

```
class tardis.tardis_portal.migrations.0010_auto_20160503_1443.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0009_auto_20160128_1119')]  
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'mimetype',
```

tardis.tardis_portal.migrations.0011_auto_20160505_1643 module

```
class tardis.tardis_portal.migrations.0011_auto_20160505_1643.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0010_auto_20160503_1443')]  
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'directory'
```

tardis.tardis_portal.migrations.0012_userauthentication_approved module

```
class tardis.tardis_portal.migrations.0012_userauthentication_approved.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0011_auto_20160505_1643')]  
    operations = [<AddField field=<django.db.models.fields.BooleanField>, name=u'approved'
```

tardis.tardis_portal.migrations.0013_auto_20181002_1136 module

```
class tardis.tardis_portal.migrations.0013_auto_20181002_1136.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0012_userauthentication_approved')]  
    operations = [<AlterModelOptions options={u'ordering': (u'name',), u'verbose_name_plu
```

tardis.tardis_portal.migrations.0014_auto_20181002_1154 module

```
class tardis.tardis_portal.migrations.0014_auto_20181002_1154.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration
```

```
dependencies = [(u'tardis_portal', u'0013_auto_20181002_1136')]
operations = [<AlterField field=<django.db.models.fields.BigIntegerField>, name=u'max_
```

tardis.tardis_portal.migrations.0015_dataset_created_time module

```
class tardis.tardis_portal.migrations.0015_dataset_created_time.Migration(name,
                                                                           app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0014_auto_20181002_1154')]
    operations = [<AddField field=<django.db.models.fields.DateTimeField>, name=u'created_
```

tardis.tardis_portal.migrations.0016_add_timestamps module

```
class tardis.tardis_portal.migrations.0016_add_timestamps.Migration(name,
                                                                       app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0015_dataset_created_time')]
    operations = [<AddField field=<django.db.models.fields.DateTimeField>, name=u'created_
```

Module contents

tardis.tardis_portal.models package

Submodules

tardis.tardis_portal.models.access_control module

```
class tardis.tardis_portal.models.access_control.GroupAdmin(*args, **kwargs)
    Bases: django.db.models.base.Model
```

GroupAdmin links the Django User and Group tables for group administrators

Attribute user a foreign key to the `django.contrib.auth.models.User`

Attribute group a foreign key to the `django.contrib.auth.models.Group`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

group

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

group_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class tardis.tardis_portal.models.access_control.**ObjectACL**(*args, **kwargs)

Bases: django.db.models.base.Model

The ObjectACL (formerly ExperimentACL) table is the core of the [Tardis Authorisation framework](#)

Attribute pluginId the the name of the auth plugin being used

Attribute entityId a foreign key to auth plugins

Attribute object_type a foreign key to ContentType

Attribute object_id the primary key/id of the object_type

Attribute canRead gives the user read access

Attribute canWrite gives the user write access

Attribute canDelete gives the user delete permission

Attribute isOwner the experiment owner flag.

Attribute effectiveDate the date when access takes into effect

Attribute expiryDate the date when access ceases

Attribute aclOwnershipType system-owned or user-owned.

System-owned ACLs will prevent users from removing or editing ACL entries to a particular experiment they own. User-owned ACLs will allow experiment owners to remove/add/edit ACL entries to the experiments they own.

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

OWNER_OWNED = 1

SYSTEM_OWNED = 2

aclOwnershipType

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canDelete

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canRead

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canWrite

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

content_object

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

content_type

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

content_type_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

effectiveDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

entityId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

expiryDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_aclOwnershipType_display (***kwargs*)

classmethod get_effective_query ()

get_related_object ()

If possible, resolve the pluginId/entityId combination to a user or group object.

get_related_object_group ()

If possible, resolve the pluginId/entityId combination to a user or group object.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isOwner

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

object_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

openidaclmigration_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

pluginId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.access_control.UserAuthentication(id, user-
                                                                    Profile,
                                                                    user-
                                                                    name,
                                                                    authen-
                                                                    tication-
                                                                    Method,
                                                                    ap-
                                                                    proved)
```

Bases: django.db.models.base.Model

CHOICES = ()

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

approved

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

authenticationMethod

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getAuthMethodDescription()

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

save (*args, **kwargs)

userProfile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

userProfile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

username

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.access_control.UserProfile(*args, **kwargs)
Bases: django.db.models.base.Model
```

UserProfile class is an extension to the Django standard user model.

Attribute isDjangoAccount is the user a local DB user

Attribute user a foreign key to the `django.contrib.auth.models.User`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

ext_groups

getUserAuthentications()

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isDjangoAccount

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isValidPublicContact()

Checks if there's enough information on the user for it to be used as a public contact.

Note: Last name can't be required, because people don't necessarily have a last (or family) name.

objects = <django.db.models.manager.Manager object>

rapidConnectEduPersonTargetedID

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a one-to-one relation.

In the example:

```
class Restaurant(Model):
    place = OneToOneField(Place, related_name='restaurant')
```

`restaurant.place` is a `ForwardOneToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

userauthentication_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
tardis.tardis_portal.models.access_control.create_user_api_key(sender,
                                                                **kwargs)
```

Auto-create ApiKey objects using Tastypie's `create_api_key`

```
tardis.tardis_portal.models.access_control.create_user_profile(sender, instance, created,
                                                                **kwargs)
```

tardis.tardis_portal.models.datafile module

```
class tardis.tardis_portal.models.datafile.DataFile(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

A `DataFile` is a record of a file which includes its filename, its size in bytes, its relative directory, and various other meta-data. Each `DataFile` belongs to a `Dataset` which usually represents the files from one folder on an instrument PC.

The physical copy (or copies) of a file are described by distinct `DataFileObject` records.

Attribute dataset The foreign key to the `tardis.tardis_portal.models.Dataset` the file belongs to.

Attribute filename The name of the file, excluding the path.

Attribute size The size of the file.

Attribute created_time Should be populated with the file's creation time from the instrument PC.

Attribute modification_time Should be populated with the file's last modification time from the instrument PC.

Attribute mimetype For example 'application/pdf'

Attribute md5sum Digest of length 32, containing only hexadecimal digits

Attribute sha512sum Digest of length 128, containing only hexadecimal digits

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

cache_file()**created_time**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

dataset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

dataset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

deleted

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

deleted_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

directory

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

file_object**file_objects**

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

filename

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getParameterSets (*schemaType=None*)

Return datafile parametersets associated with this datafile.

get_absolute_filepath ()**get_as_temporary_file** (***kws*)

Returns a traditional file-system-based file object that is a copy of the original data. The file is deleted when the context is destroyed.

Parameters **directory** (*basestring*) – the directory in which to create the temp file

Returns the temporary file object

Return type NamedTemporaryFile

get_default_storage_box ()

try to guess appropriate box from files, dataset or experiment

get_download_url ()**get_file** (*verified_only=True*)

Returns the file as a readable file-like object from the best available storage box.

If *verified_only=False*, the return of files without a verified checksum is allowed, otherwise *None* is returned for unverified files.

Parameters **verified_only** (*bool*) – if *False* return files without verified checksums

Returns Python file object

Return type Python File object

get_image_data ()**get_mimetype** ()**get_preferred_dfo** (*verified_only=True*)**get_receiving_storage_box** ()**get_size** ()**get_view_url** ()**has_image** ()**id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_image ()

returns *True* if it's an image and not an x-icon and not an img the image/img mimetype is made up though and may need revisiting if there is an official img mimetype that does not refer to diffraction images

is_local ()**is_online**

return *False* if a file is on tape. At this stage it checks it returns *true* for no file objects, because those files are offline through other checks

is_public ()

md5sum

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

mimetype

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

modification_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

save (*args, **kwargs)

sha512sum

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

size

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

status

returns information about the status of the file. States are defined in StorageBox

classmethod sum_sizes (datafiles)

Takes a query set of datafiles and returns their total size.

update_mimetype (mimetype=None, force=False, save=True)

verified

verify (reverify=False)

version

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class tardis.tardis_portal.models.datafile.DataFileObject (*args, **kwargs)

Bases: django.db.models.base.Model

The physical copy (or copies) of a *DataFile* are described by distinct *DataFileObject* records.

Attribute datafile The *DataFile* record which this DataFileObject is storing a copy of.

Attribute storage_box The *StorageBox* containing this copy of the file. The StorageBox could represent a directory on a mounted filesystem, or a bucket in an Object Store.

Attribute uri The relative path of the file location within the the *StorageBox*, e.g. dataset1-12345/file1.txt for a copy of a *DataFile* with filename file1.txt which belongs to a *Dataset* with a description of dataset1 and an ID of 12345.

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

cache_file ()

copy_file (dest_box=None, verify=True)

copies verified file to new storage box checks for existing copy triggers async verification if not disabled

:param StorageBox dest_box: StorageBox instance :param bool verify: :returns: DataFileObject of copy
:rtype: DataFileObject

create_set_uri (*force=False, save=False*)

sets the uri as well as building it :param bool force: :param bool save: :return: :rtype: basestring

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

datafile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

delete_data()

file_object

A set of accessor functions that convert the file information to a standard Python file object for reading and copy the contents of an existing file_object into the storage backend.

Returns a file object

Return type Python File object

get_full_path()

get_next_by_created_time (***kwargs*)

get_previous_by_created_time (***kwargs*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

last_verified_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

modified_time

move_file (*dest_box=None*)

moves a file copies first, then synchronously verifies deletes file if copy is true copy and has been verified

Parameters **dest_box** (StorageBox) – StorageBox instance

Returns moved file dfo

Return type *DataFileObject*

objects = <django.db.models.manager.Manager object>

save (**args, **kwargs*)

storage_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

storage_type

Returns storage_box type

Return type StorageBox type constant

uri

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verified

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verify (add_checksums=True, add_size=True)

```
tardis.tardis_portal.models.datafile.compute_checksums (file_object,           com-
                                                         pute_md5=True,       com-
                                                         pute_sha512=True,
                                                         close_file=True)
```

Computes checksums for a python file object

Parameters

- **file_object** (*object*) – Python File object
- **compute_md5** (*bool*) – whether to compute md5 default=True
- **compute_sha512** (*bool*) – whether to compute sha512, default=True
- **close_file** (*bool*) – whether to close the file_object, default=True

Returns the checksums as {'md5sum': result, 'sha512sum': result}

Return type dict

```
tardis.tardis_portal.models.datafile.delete_dfo (sender, instance, **kwargs)
Deletes the actual file / object, before deleting the database record
```

tardis.tardis_portal.models.dataset module

```
class tardis.tardis_portal.models.dataset.Dataset (*args, **kwargs)
```

Bases: django.db.models.base.Model

A dataset represents a collection files usually associated with a folder on an instrument PC. Each file within the dataset is represented by a tardis.tardis_portal.models.DataFile record. A dataset can appear in one or more *Experiment* records. Access controls are configured at the Experiment level by creating

ObjectACL records. Each dataset can be associated with an *Instrument* record, but it is possible to create a dataset without specifying an instrument.

Attribute experiment A foreign key to the one or more *Experiment* records which contain this dataset

Attribute instrument The foreign key to the instrument that generated this data

Attribute description Description of this dataset, which usually corresponds to the folder name on the instrument PC

Attribute immutable Whether this dataset is read-only

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafile_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

directory

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

equipment_set

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experiments

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

`getParameterSets (schemaType=None)`

Return the dataset parametersets associated with this experiment.

`get_absolute_url (**kwargs)`

Return the absolute url to the current Dataset

`get_all_storage_boxes_used ()`

`get_datafiles ()`

`get_download_urls ()`

`get_edit_url (**kwargs)`

Return the absolute url to the edit view of the current Dataset

`get_first_experiment ()`

`get_images ()`

`get_path ()`

`get_size ()`

`get_thumbnail_url ()`

`id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`image`

`immutable`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`instrument`

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

instrument_id
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_online

modified_time
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<tardis.tardis_portal.managers.OracleSafeManager object>`

save (*force_insert=False, force_update=False, using=None, update_fields=None*)

`tardis.tardis_portal.models.experiment` module

class `tardis.tardis_portal.models.experiment.Experiment` (**args, **kwargs*)
Bases: `django.db.models.base.Model`

An `Experiment` is a collection of `Dataset` records. A `Dataset` record can appear in multiple `Experiment` records. Access controls are configured at the `Experiment` level by creating `ObjectACL` records.

Attribute url An optional URL associated with the data collection

Attribute approved An optional field indicating whether the collection is approved

Attribute title The title of the experiment.

Attribute description The description of the experiment.

Attribute institution_name The name of the institution who created the experiment.

Attribute start_time Undocumented

Attribute end_time Undocumented

Attribute created_time Undocumented

Attribute handle Undocumented

Attribute public Whether the experiment is publicly accessible

Attribute objects Default model manager

Attribute safe ACL aware model manager

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

`PUBLICATION_DETAILS_SCHEMA` = `'http://www.tardis.edu.au/schemas/publication/details/'`

`PUBLICATION_DRAFT_SCHEMA` = `'http://www.tardis.edu.au/schemas/publication/draft/'`

`PUBLICATION_SCHEMA_ROOT` = `'http://www.tardis.edu.au/schemas/publication/'`

`PUBLIC_ACCESS_CHOICES` = ((1, 'No public access (hidden)'), (25, 'Ready to be released'))

`PUBLIC_ACCESS_EMBARGO` = 25

`PUBLIC_ACCESS_FULL` = 100

PUBLIC_ACCESS_METADATA = 50

PUBLIC_ACCESS_NONE = 1

approved

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

created_by

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

created_by_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datasets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

end_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentauthor_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

experimentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

getParameterSets (*schemaType=None*)

Return the experiment parametersets associated with this experiment.

get_absolute_url (***kwargs*)

Return the absolute url to the current Experiment

get_create_token_url (***kwargs*)

Return the absolute url to the create token view of the current Experiment

get_ct ()**get_datafiles** ()**get_download_urls** ()**get_edit_url** (***kwargs*)

Return the absolute url to the edit view of the current Experiment

get_groups ()**get_images** ()**get_next_by_created_time** (***morekwargs*)**get_next_by_update_time** (***morekwargs*)**get_or_create_directory** ()**get_owners** ()**get_previous_by_created_time** (***morekwargs*)**get_previous_by_update_time** (***morekwargs*)**get_public_access_display** (***morekwargs*)**get_size** ()**handle**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

institution_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_publication ()**is_publication_draft** ()

license

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

license_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

locked

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objectacIs

Accessor to the related objects manager on the one-to-many relation created by GenericRelation.

In the example:

```
class Post(Model):
    comments = GenericRelation(Comment)
```

post.comments is a ReverseGenericManyToOneDescriptor instance.

objects = <tardis.tardis_portal.managers.OracleSafeManager object>

public_access

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

classmethod public_access_implies_distribution (*public_access_level*)

Determines if a level of public access implies that distribution should be allowed, or alternately if it should not be allowed. Used to prevent free-distribution licences for essentially private data, and overly-restrictive licences for public data.

public_download_allowed ()

instance method version of 'public_access_implies_distribution'

safe = <tardis.tardis_portal.managers.ExperimentManager object>

save (*args, **kwargs)

start_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

title

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

token_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

update_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.experiment.ExperimentAuthor(id, experiment,  
author, institu-  
tion, email, order,  
url)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

author

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

email

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):  
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

institution

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

order

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

save (**args, **kwargs*)

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.facility module

class tardis.tardis_portal.models.facility.**Facility**(*args, **kwargs)

Bases: django.db.models.base.Model

Represents a facility that produces data.

Each *Instrument* record must belong to exactly one facility. Many *Instrument* records can be associated with the same facility.

Attribute name The name of the facility, e.g. “Test Facility”

Attribute manager_group The group of users who can access the Facility Overview for this facility.

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrument_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

manager_group

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

manager_group_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

modified_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

save()

`tardis.tardis_portal.models.facility.facilities_managed_by(user)`

Returns a list of facilities managed by a user

`tardis.tardis_portal.models.facility.is_facility_manager(user)`

Returns true if the user manages one or more facilities

tardis.tardis_portal.models.hooks module

`tardis.tardis_portal.models.hooks.post_save_experiment(sender, **kwargs)`

`tardis.tardis_portal.models.hooks.post_save_experiment_parameter(sender, **kwargs)`

`tardis.tardis_portal.models.hooks.post_save_experimentauthor(sender, **kwargs)`

`tardis.tardis_portal.models.hooks.publish_public_expt_rifcs(experiment)`

tardis.tardis_portal.models.instrument module

class `tardis.tardis_portal.models.instrument.Instrument(*args, **kwargs)`

Bases: `django.db.models.base.Model`

Represents an instrument belonging to a facility that produces data

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

dataset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

facility

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

facility_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getParameterSets (*schemaType=None*)

Return the instrument parametersets associated with this instrument.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

modified_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

save ()

tardis.tardis_portal.models.jti module

class tardis.tardis_portal.models.jti.**JTI** (*id, jti, created_time*)

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`get_next_by_created_time (**morekwargs)`

`get_previous_by_created_time (**morekwargs)`

`id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`jti`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`objects = <django.db.models.manager.Manager object>`

`tardis.tardis_portal.models.license` module

class `tardis.tardis_portal.models.license.License (*args, **kwargs)`

Bases: `django.db.models.base.Model`

Represents a licence for experiment content.

Instances should provide enough detail for both researchers to select the licence, and for the users of their data to divine correct usage of experiment content.

(Non-US developers: We're using US spelling in the code.)

exception `DoesNotExist`

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception `MultipleObjectsReturned`

Bases: `django.core.exceptions.MultipleObjectsReturned`

allows_distribution

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experiment_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

classmethod `get_none_option_license()`

classmethod `get_suitable_licenses (public_access_method=None)`

`id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

image_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

internal_description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_active

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.parameters module

```
class tardis.tardis_portal.models.parameters.DatafileParameter(id, name,
                                                                string_value,
                                                                numeri-
                                                                cal_value,
                                                                datetime_value,
                                                                link_id, link_ct,
                                                                parameterset)
```

Bases: *tardis.tardis_portal.models.parameters.Parameter*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to ForwardManyToOneDescriptor) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameter_type = 'Datafile'

parameterset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.DatafileParameterSet(id, schema,
                                                                    datafile)
```

Bases: `tardis.tardis_portal.models.parameters.ParameterSet`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

datafile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

datafile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of *DatafileParameter*

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

```
class tardis.tardis_portal.models.parameters.DatasetParameter(id, name,
                                                             string_value,
                                                             numerical_value,
                                                             datetime_value,
                                                             link_id, link_ct,
                                                             parameterset)
```

Bases: *tardis.tardis_portal.models.parameters.Parameter*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameter_type = 'Dataset'**parameterset**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.DatasetParameterSet(id, schema,
                                                                    dataset)
```

Bases: `tardis.tardis_portal.models.parameters.ParameterSet`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

dataset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

dataset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datasetparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of `DatasetParameter`

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.ExperimentParameter(id, name,
                                                                string_value,
                                                                numeri-
                                                                cal_value,
                                                                date-
                                                                time_value,
                                                                link_id,
                                                                link_ct, pa-
                                                                rameterset)
```

Bases: `tardis.tardis_portal.models.parameters.Parameter`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the content_type and object_id fields.

This class also doubles as an accessor to the related object (similar to ForwardManyToOneDescriptor) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameter_type = 'Experiment'**parameterset**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

save (*args, **kwargs)

```
class tardis.tardis_portal.models.parameters.ExperimentParameterSet(id,
                                                                    schema,
                                                                    experi-
                                                                    ment)
```

Bases: *tardis.tardis_portal.models.parameters.ParameterSet*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of *ExperimentParameter*

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.FreeTextSearchField(id, parameter_name)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

parameter_name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameter_name_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.InstrumentParameter(id, name,
                                                                string_value,
                                                                numeri-
                                                                cal_value,
                                                                date-
                                                                time_value,
                                                                link_id,
                                                                link_ct, pa-
                                                                rameterset)
```

Bases: `tardis.tardis_portal.models.parameters.Parameter`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameter_type = 'Instrument'**parameterset**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.InstrumentParameterSet(id,
                                                                    schema,
                                                                    instru-
                                                                    ment)
```

Bases: *tardis.tardis_portal.models.parameters.ParameterSet*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrument

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

instrument_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of *InstrumentParameter*

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.Parameter(*args, **kwargs)
    Bases: django.db.models.base.Model
```

class Meta

abstract = False

app_label = 'tardis_portal'

ordering = ['name']

datetime_value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get()

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

link_ct_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

link_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_url

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

name_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

numerical_value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects

parameter_type = 'Abstract'

set_value (value)

Sets the parameter value, converting into the appropriate data type. Deals with date/time strings that are timezone naive or aware, based on the `USE_TZ` setting.

Parameters `value` (*basestring*) – a string (or string-like) repr of the value

Raises `SuspiciousOperation` –

string_value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.ParameterName(id, schema, name,
                                                            full_name, units,
                                                            data_type, immutable,
                                                            comparison_type,
                                                            is_searchable,
                                                            choices, order)
```

Bases: `django.db.models.base.Model`

CONTAINS_COMPARISON = 8

DATETIME = 6

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

EXACT_VALUE_COMPARISON = 1

FILENAME = 5

GREATER_THAN_COMPARISON = 4

GREATER_THAN_EQUAL_COMPARISON = 5

JSON = 8

LESS_THAN_COMPARISON = 6

LESS_THAN_EQUAL_COMPARISON = 7

LINK = 4

LONGSTRING = 7

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

NOT_EQUAL_COMPARISON = 2

NUMERIC = 1

RANGE_COMPARISON = 3

STRING = 2

URL = 3

choices

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

comparison_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

data_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experimentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

freetextsearchfield_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

full_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getUniqueShortName()**get_comparison_type_display** (***morekwargs*)**get_data_type_display** (***morekwargs*)**id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

immutable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

isDateTime()

isFilename()

isLink()

isLongString()

isNumeric()

isString()

isURL()

is_json()

is_searchable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

natural_key()

objects = <`tardis.tardis_portal.managers.ParameterNameManager` object>

order

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

schema_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

units

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.ParameterSet(*args, **kwargs)
    Bases: django.db.models.base.Model, tardis.tardis_portal.models.parameters.
    ParameterSetManagerMixin
```

```
class Meta
```

```
    abstract = False
```

```
    app_label = 'tardis_portal'
```

```
    ordering = ['id']
```

```
parameter_class = None
```

```
save(*args, **kwargs)
```

```
schema
```

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

```
schema_id
```

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
storage_box
```

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

```
class tardis.tardis_portal.models.parameters.ParameterSetManagerMixin(parameterset=None,
                                                                    par-
                                                                    en-
                                                                    tOb-
                                                                    ject=None,
                                                                    schema=None)
```

Bases: *tardis.tardis_portal.ParameterSetManager.ParameterSetManager*

for clarity's sake and for future extension this class makes ParameterSetManager local to this file. At the moment its only function is increasing the line count

```
class tardis.tardis_portal.models.parameters.Schema(id, namespace, name, type, sub-
                                                    type, immutable, hidden)
```

Bases: *django.db.models.base.Model*

```
DATAFILE = 3
```

```
DATASET = 2
```

```
exception DoesNotExist
```

Bases: *django.core.exceptions.ObjectDoesNotExist*

```
EXPERIMENT = 1
```

INSTRUMENT = 5

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

NONE = 4

exception UnsupportedType (*msg*)

Bases: `exceptions.Exception`

datafileparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experimentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

classmethod getNamespaces (*type_, subtype=None*)

Return the list of namespaces for equipment, sample, and experiment schemas.

classmethod getSubTypes ()

classmethod get_schema_type_name (*schema_type, short=False*)

get_type_display (***morekwargs*)

hidden

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

immutable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

namespace

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

natural_key()

objects = <tardis.tardis_portal.managers.SchemaManager object>

parametername_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

subtype

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.storage module

class `tardis.tardis_portal.models.storage.StorageBox(*args, **kwargs)`

Bases: `django.db.models.base.Model`

table that holds storage boxes of any type. to extend to new types, add fields if necessary

Attribute **max_size** max size in bytes

BUNDLE = 6

CACHE = 3

DISK = 1

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

TAPE = 2

TEMPORARY = 4

TYPES = {'bundle': 6, 'cache': 3, 'disk': 1, 'receiving': 4, 'tape': 2}

TYPE_UNKNOWN = 5

attributes

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

autocache

Whether to automatically copy data into faster storage

Returns True if data should be automatically cached

Return type `bool`

cache_box

Get cache box if set up

cache_files()

Copy all files to faster storage.

This can be used to copy data from a Vault cache (containing data which will soon be pushed to tape) to Object Storage, so that the data can always be accessed quickly from Object Storage, and the Vault can be used for disaster recovery if necessary.

child_boxes

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

copy_files (*dest_box=None*)

copy_to_master()

classmethod create_local_box (*location=None*)

datafileparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

django_storage_class

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

file_objects

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

classmethod `get_default_storage` (*location=None, user=None*)

gets default storage box or get local storage box with given base location or create one if it doesn't exist.

policies: Have a StorageBoxAttribute: key='default', value=True find a storage box where location is DEFAULT_STORAGE_BASE_DIR create a default storage box at DEFAULT_STORAGE_BASE_DIR lowest id storage box is default no storage box defined, use hard coded default for now TODO: consider removing this

Would be nice: get largest free space one, test for authorisation

get_initialised_storage_instance ()

get_options_as_dict ()

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

master_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

master_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

max_size

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

move_files (*dest_box=None*)

move_to_master ()

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

offline_types = [2]

online_types = [3, 1, 4, 6]

options

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

status

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

storage_type

type_order = [3, 6, 1, 2, 4, 5]

```
class tardis.tardis_portal.models.storage.StorageBoxAttribute(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

Can hold attributes/metadata about different storage locations.

Attribute key The key used to look up the attribute (e.g. “type”).

Attribute value The value of the attribute e.g. “cache”.

The “type” key has three values support by the core MyTardis code: “permanent”, “receiving” and “cache”.

Adding an attribute with key “type” and value “permanent” preserves the default behaviour of a storage box, i.e. it is equivalent to not adding the attribute.

Adding an attribute with key “type” and value “receiving” means that the storage box will be treated as a staging area which receives files intended to be transferred to a permanent storage box. If a storage box has the “type: receiving” attribute, it must link to a permanent storage box (via its `master_box` foreign key).

Adding an attribute with key “type” and value “cache” means that the storage box will be used to copy data from slow-access storage to fast-access storage. If a storage box has the “type: cache” attribute, it must link to a permanent storage box (via its `master_box` foreign key).

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

storage_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.storage.StorageBoxOption(*args, **kwargs)
```

Bases: django.db.models.base.Model

holds the options passed to the storage class defined in StorageBox. key->value store with support for typed values through pickling when value_type is set to 'pickle'

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

PICKLE = 'pickle'

STRING = 'string'

TYPE_CHOICES = (('string', 'String value'), ('pickle', 'Pickled value'))

get_value_type_display(**morekwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

storage_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

unpickled_value**value**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

value_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.token module

class tardis.tardis_portal.models.token.**Token** (*id, token, experiment, expiry_date, user*)

Bases: django.db.models.base.Model

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

expiry_date

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_next_by_expiry_date (***morekwargs*)

get_previous_by_expiry_date (***morekwargs*)

get_session_expiry ()

A token login should expire at the earlier of a) tomorrow at 4am b) the (end of) the token's expiry date

It is the responsibility of token_auth to set the session expiry

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_expired ()

objects = <tardis.tardis_portal.managers.OracleSafeManager object>

save_with_random_token ()

token

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

Module contents

`models/__init__.py`

`tardis.tardis_portal.publish` package

Subpackages

`tardis.tardis_portal.publish.provider` package

Submodules

`tardis.tardis_portal.publish.provider.rifcsprovider` module

```
class tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider
    Bases: object
    can_publish(experiment)
    get_rifcs_context(experiment)
    get_template(experiment)
    is_schema_valid(experiment)
```

Module contents

Submodules

`tardis.tardis_portal.publish.publishservice` module

```
class tardis.tardis_portal.publish.publishservice.PublishService(providers, ex-
                                                                    periment)

    get_context()
    get_template()
    manage_rifcs(oaipath)
```

Module contents

tardis.tardis_portal.storage package

Submodules

tardis.tardis_portal.storage.file_system module

class tardis.tardis_portal.storage.file_system.**MyTardisLocalFileSystemStorage** (*location=None, base_url=None*)

Bases: `django.core.files.storage.FileSystemStorage`

Simply changes the FileSystemStorage default store location to the MyTardis file store location. Makes it easier to migrate 2.5 installations.

Module contents

class tardis.tardis_portal.storage.**DummyStorage**

Bases: `django.core.files.storage.Storage`

Does nothing except serve as a place holder for Storage classes not implemented yet

exception tardis.tardis_portal.storage.**MisconfiguredStorageError**

Bases: `exceptions.Exception`

tardis.tardis_portal.template_tags package

Submodules

tardis.tardis_portal.template_tags.approved_user_tags module

tardis.tardis_portal.template_tags.approved_user_tags.**check_if_user_not_approved** (*request*)
Custom template filter to identify whether a user account is approved.

tardis.tardis_portal.template_tags.approved_user_tags.**get_matching_authmethod** (*backend*)

tardis.tardis_portal.template_tags.basiccomparisonfilters module

tardis.tardis_portal.template_tags.basiccomparisonfilters.**gt** (*value, arg*)
Returns a boolean of whether the value is greater than the argument.

tardis.tardis_portal.template_tags.basiccomparisonfilters.**gte** (*value, arg*)
Returns a boolean of whether the value is greater than or equal to the argument.

tardis.tardis_portal.template_tags.basiccomparisonfilters.**length_gt** (*value, arg*)
Returns a boolean of whether the value's length is greater than the argument.

tardis.tardis_portal.template_tags.basiccomparisonfilters.**length_gte** (*value, arg*)
Returns a boolean of whether the value's length is greater than or equal to the argument.

`tardis.tardis_portal.templatetags.basiccomparisonfilters.length_lt` (*value*,
arg)

Returns a boolean of whether the value's length is less than the argument.

`tardis.tardis_portal.templatetags.basiccomparisonfilters.length_lte` (*value*,
arg)

Returns a boolean of whether the value's length is less than or equal to the argument.

`tardis.tardis_portal.templatetags.basiccomparisonfilters.lt` (*value*, *arg*)

Returns a boolean of whether the value is less than the argument.

`tardis.tardis_portal.templatetags.basiccomparisonfilters.lte` (*value*, *arg*)

Returns a boolean of whether the value is less than or equal to the argument.

`tardis.tardis_portal.templatetags.bleach_tag` module

`tardis.tardis_portal.templatetags.bleach_tag.bleach_value` (*value*)

`tardis.tardis_portal.templatetags.capture` module

class `tardis.tardis_portal.templatetags.capture.CaptureNode` (*odelist*, *varname*)
Bases: `django.template.base.Node`

render (*context*)

`tardis.tardis_portal.templatetags.capture.capture` (*parser*, *token*)
{% capture as [foo] %}

`tardis.tardis_portal.templatetags.dataset_tags` module

`tardis.tardis_portal.templatetags.dataset_tags.dataset_datafiles_badge` (*dataset=None*,
count=None)

Displays an badge with the number of datafiles for this experiment

`tardis.tardis_portal.templatetags.dataset_tags.dataset_experiments_badge` (*dataset*)
Displays an badge with the number of datasets for this experiment

`tardis.tardis_portal.templatetags.dataset_tags.dataset_size_badge` (*dataset=None*,
size=None)

Displays an badge with the total size of the files in this experiment

`tardis.tardis_portal.templatetags.dataset_tags.dataset_tiles` (*experiment*, *in-*
clude_thumbnails)

`tardis.tardis_portal.templatetags.dynurl` module

class `tardis.tardis_portal.templatetags.dynurl.DynUrlNode` (**args*)
Bases: `django.template.base.Node`

render (*context*)

`tardis.tardis_portal.templatetags.dynurl.dynurl` (*parser*, *token*)

tardis.tardis_portal.templatetags.experiment_tags module

`tardis.tardis_portal.templatetags.experiment_tags.experiment_browse_item` (*experiment*,
***kwargs*)

Displays an experiment for a browsing view.

`tardis.tardis_portal.templatetags.experiment_tags.experiment_datafiles_badge` (*experiment*)

Displays an badge with the number of datafiles for this experiment

`tardis.tardis_portal.templatetags.experiment_tags.experiment_datasets_badge` (*experiment*)

Displays an badge with the number of datasets for this experiment

`tardis.tardis_portal.templatetags.experiment_tags.experiment_last_updated_badge` (*experiment*)

`tardis.tardis_portal.templatetags.experiment_tags.experiment_public_access_badge` (*experiment*)

Displays an badge the level of public access for this experiment

`tardis.tardis_portal.templatetags.experiment_tags.experiment_size_badge` (*experiment*)

Displays an badge with the total size of the files in this experiment

tardis.tardis_portal.templatetags.experimentstats module

`tardis.tardis_portal.templatetags.experimentstats.experiment_file_count` (*value*)

tardis.tardis_portal.templatetags.facility_tags module

`tardis.tardis_portal.templatetags.facility_tags.check_if_facility_manager` (*request*)

Custom template filter to identify whether a user is a facility manager.

tardis.tardis_portal.templatetags.feed module

`tardis.tardis_portal.templatetags.feed.todatetime` (*value*)

tardis.tardis_portal.templatetags.formfieldfilters module

This module holds filters that can be used in postprocessing a form field.

@author: Gerson Galang

`tardis.tardis_portal.templatetags.formfieldfilters.parametername_form` (*value*)

Removes all values of arg from the given string

`tardis.tardis_portal.templatetags.formfieldfilters.sanitize_html` (*html*,
bad_tags=['body'])

Removes identified malicious HTML content from the given string.

`tardis.tardis_portal.templatetags.formfieldfilters.size` (*value*, *actualSize*)

Add the size attribute to the text field.

tardis.tardis_portal.templatetags.lookupfilters module

`tardis.tardis_portal.templatetags.lookupfilters.get_item` (*dictionary*, *key*)

Returns a value from a dictionary.

tardis.tardis_portal.template_tags.pagination module

tardis.tardis_portal.template_tags.pagination.**pagination** (*data_list*, *paginator*,
page_num, *query_string*)

Generates the series of links to the pages in a paginated list.

tardis.tardis_portal.template_tags.pagination.**paginator_number** (*data_list*, *paginator*, *page_num*,
query_string,
page_index)

Generates an individual page index link in a paginated list.

tardis.tardis_portal.template_tags.xml_date module

tardis.tardis_portal.template_tags.xml_date.**toxml_datetime** (*value*)

Module contents

tardis.tardis_portal.tests package

Subpackages

tardis.tardis_portal.tests.api package

Submodules

tardis.tardis_portal.tests.api.test_auth module

Testing authentication and authorization in the Tastypie-based MyTardis REST API

```
class tardis.tardis_portal.tests.api.test_auth.ACLAuthorizationTest (methodName='runTest')
    Bases: django.test.testcases.TestCase
```

```
class tardis.tardis_portal.tests.api.test_auth.MyTardisAuthenticationTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_apikey_authentication()
    test_bad_credentials()
```

tardis.tardis_portal.tests.api.test_datafile_metadata_resources module

Testing the DatafileParameter and DatafileParameterSet resources in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_datafile_metadata_resources.DatafileParameterRes
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_datafile_metadata_resources.DatafileParameterSet
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_datafile_resource module

Testing the DataFile resource in MyTardis's Tastypie-based REST API

```

class tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_download_file ()
        Doesn't actually check the content downloaded yet Just checks if the download API endpoint responds
        with 200

    test_post_single_file ()

    test_shared_fs_many_files ()
        tests sending many files with known permanent location (useful for Australian Synchrotron ingestions)

    test_shared_fs_single_file ()

```

tardis.tardis_portal.tests.api.test_dataset_metadata_resources module

Testing the DatasetParameter and DatasetParameterSet resources in MyTardis's Tastypie-based REST API

```

class tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterSetResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

```

tardis.tardis_portal.tests.api.test_dataset_resource module

Testing the Dataset resource in MyTardis's Tastypie-based REST API

```

class tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_get_dataset_filter_instrument ()

    test_get_dataset_no_instrument ()

    test_get_dataset_with_instrument ()

    test_post_dataset ()

```

tardis.tardis_portal.tests.api.test_experiment_metadata_resources module

Testing the ExperimentParameter and ExperimentParameterSet resources in MyTardis's Tastypie-based REST API

```

class tardis.tardis_portal.tests.api.test_experiment_metadata_resources.ExperimentParameterResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_experiment_metadata_resources.ExperimentParameterSetResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

```

tardis.tardis_portal.tests.api.test_experiment_resource module

Testing the Experiment resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTest (method=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_get_experiment()

    test_post_experiment()
```

tardis.tardis_portal.tests.api.test_facility_resource module

Testing the Facility resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_facility_resource.FacilityResourceTest (methodName=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_facility_by_id()

    test_get_facility_by_manager_group_id()
        This type of query can be used to iterate through a user's groups, and use each group's id to de-
        termine which facilities a user manages, i.e. a way to obtain the functionality implemented by
        facilities_managed_by() via the API

    test_get_facility_by_name()
```

tardis.tardis_portal.tests.api.test_group_resource module

Testing the Group resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_group_resource.GroupResourceTest (methodName='runTest
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_group_by_id()

    test_get_group_by_name()
```

tardis.tardis_portal.tests.api.test_instrument_resource module

Testing the Instrument resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTest (method=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_instrument_by_id()

    test_get_instrument_by_name()

    test_post_instrument()

    test_rename_instrument()

    test_unauthorized_instrument_access_attempt()
```

tardis.tardis_portal.tests.api.test_location_resource module

Testing the Location resource in MyTardis's Tastypie-based REST API

“Location” was the old name for what is now known as a StorageBox in MyTardis. The API v1 endpoint is still /api/v1/location/

```
class tardis.tardis_portal.tests.api.test_location_resource.LocationResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_replica_resource module

Testing the Replica resource in MyTardis's Tastypie-based REST API

“Replica” was the old name for what is now known as a DataFileObject in MyTardis. The API v1 endpoint is still /api/v1/replica/

```
class tardis.tardis_portal.tests.api.test_replica_resource.ReplicaResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_schema_resource module

Testing the Schema resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_schema_resource.SchemaResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_serializer module

Testing the serializer in the Tastypie-based MyTardis REST API

```
class tardis.tardis_portal.tests.api.test_serializer.SerializerTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_debug_serializer()
    test_pretty_serializer()
```

Module contents

Testing the tastypie-based mytardis api

```
class tardis.tardis_portal.tests.api.MyTardisResourceTestCase (methodName='runTest')
    Bases: tastypie.test.ResourceTestCaseMixin, django.test.testcases.TestCase

    abstract class without tests to combine common settings in one place

    get_apikey_credentials()
    get_credentials()
    setUp()
        Hook method for setting up the test fixture before exercising it.
```

tardis.tardis_portal.tests.auth package

Module contents

tardis.tardis_portal.tests.filters package

Submodules

tardis.tardis_portal.tests.filters.test_jeolsem module

```
class tardis.tardis_portal.tests.filters.test_jeolsem.JEOLSEMFilterTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testJEOLComplex()

    testJEOLSimple()
```

tardis.tardis_portal.tests.filters.test_middleware module

```
class tardis.tardis_portal.tests.filters.test_middleware.Filter1

    classmethod getTuples()

    tuples = []

class tardis.tardis_portal.tests.filters.test_middleware.Filter2

    classmethod getTuples()

    tuples = []

class tardis.tardis_portal.tests.filters.test_middleware.FilterInitTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testFiltering()

class tardis.tardis_portal.tests.filters.test_middleware.RunFiltersTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    testAll()
        Just test that we can run ./manage.py runfilters --all without any runtime exceptions

    testDryRun()
        Just test that we can run ./manage.py runfilters --dryRun without any runtime exceptions
```

```
testList()
```

Just test that we can run ./manage.py runfilters --list without any runtime exceptions

Module contents

Submodules

tardis.tardis_portal.tests.ldap_ldif module

tardis.tardis_portal.tests.mock_vbl_auth module

Created on 24/01/2011

@author: gerson

```
class tardis.tardis_portal.tests.mock_vbl_auth.MockBackend
```

Authenticate against the VBL SOAP Webservice. It is assumed that the request object contains the username and password to be provided to the VBLgetExpIDs function.

a new local user is created if it doesn't already exist

if the authentication succeeds, the session will contain a VBL session key used for downloads as well as the user's EPN list

```
authenticate(request)
```

```
get_user(user_id)
```

tardis.tardis_portal.tests.mock_vbl_download module

```
tardis.tardis_portal.tests.mock_vbl_download.download_datafile(request, *args,
                                                                **kwargs)
```

Dummy view for vbl download tests

tardis.tardis_portal.tests.slapd module

Utilities for starting up a test slapd server and talking to it with ldapsearch/ldapadd.

```
class tardis.tardis_portal.tests.slapd.Slapd
```

Controller class for a slapd instance, OpenLDAP's server.

This class creates a temporary data store for slapd, runs it on a private port, and initialises it with a top-level dc and the root user.

When a reference to an instance of this class is lost, the slapd server is shut down.

```
PATH_LDAPADD = None
```

```
PATH_LDAPSEARCH = None
```

```
PATH_SCHEMA_DIR = '/home/docs/checkouts/readthedocs.org/user_builds/mytardis/checkouts
```

```
PATH_SLAPD = None
```

```
PATH_SLAPTEST = None
```

```
PATH_TMPDIR = '/tmp/tmpgF410E'
```

```
TEST_UTILS_DIR = '/home/docs/checkouts/readthedocs.org/user_builds/mytardis/checkouts/'

classmethod check_paths ()
    Checks that the configured executable paths look valid. If they don't, then logs warning messages (not
    errors).

configure (cfg)
    Appends slapd.conf configuration lines to cfg. Also re-initializes any backing storage. Feel free to subclass
    and override this method.

get_address ()
get_dn_suffix ()
get_root_dn ()
get_root_password ()
get_tmpdir ()
get_url ()
ldapadd (ldif, extra_args=[])
    Runs ldapadd on this slapd instance, passing it the ldif content
ldapsearch (base=None, filter='(objectClass=*)', attrs=[], scope='sub', extra_args=[])
restart ()
    Restarts the slapd server; ERASING previous content. Starts the server even it if isn't already running.
set_debug ()
set_dn_suffix (dn)
set_port (port)
set_root_cn (cn)
set_root_password (pw)
set_slapd_debug_level (level)
set_tmpdir (path)
start ()
    Starts the slapd server process running, and waits for it to come up.
started ()
    This method is called when the LDAP server has started up and is empty. By default, this method adds the
    two initial objects, the domain object and the root user object.
stop ()
    Stops the slapd server, and waits for it to terminate
wait ()
    Waits for the slapd process to terminate by itself.

tardis.tardis_portal.tests.slapd.delete_directory_content (path)
tardis.tardis_portal.tests.slapd.find_available_tcp_port (host='127.0.0.1')
tardis.tardis_portal.tests.slapd.mkdirs (path)
    Creates the directory path unless it already exists
tardis.tardis_portal.tests.slapd.quote (s)
    Quotes the " and characters in a string and surrounds with "..."
```

`tardis.tardis_portal.tests.slapped.which` (*executable*)

`tardis.tardis_portal.tests.test_authentication` module

Created on 19/01/2011

```
class tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCreateNewAccount ()

    testManageAuthMethods ()

    testSimpleAuthenticate ()

    test_djangoauth ()
```

`tardis.tardis_portal.tests.test_authorisation` module

```
class tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testCantEditLockedExperiment ()

    testChangeUserPermissions ()

    testOwnedExperiments ()

    testReadAccess ()

    testWriteAccess ()

    urls = 'tardis.urls'
```

`tardis.tardis_portal.tests.test_authservice` module

```
class tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testAuthenticate ()

    testGetGroupsForEntity ()

    testGroupProvider ()

    testGroupSearch ()
```

```
    testInitialisation()

class tardis.tardis_portal.tests.test_authservice.MockAuthProvider

    authenticate(request)

class tardis.tardis_portal.tests.test_authservice.MockGroupProvider
    Bases: tardis.tardis_portal.auth.interfaces.GroupProvider

    getGroupById(id)

    getGroups(user)

    getGroupsForEntity(id)

    searchGroups(**filter)

class tardis.tardis_portal.tests.test_authservice.MockRequest
    Bases: django.http.request.HttpRequest

    setPost(field, value)

class tardis.tardis_portal.tests.test_authservice.MockSettings
    Bases: object
```

tardis.tardis_portal.tests.test_collectstatic module

```
class tardis.tardis_portal.tests.test_collectstatic.CollectstaticTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_collectstatic()
```

tardis.tardis_portal.tests.test_createuser module

```
class tardis.tardis_portal.tests.test_createuser.CreateUserTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testInteractive()
        Just test that we can run ./manage.py createuser without any runtime exceptions by mocking the raw_input
        username and email entry

    testNoInput()
        Just test that we can run ./manage.py createuser --username testuser1 --email testuser1@example.com
        --noinput without any runtime exceptions
```

tardis.tardis_portal.tests.test_download module

```
class tardis.tardis_portal.tests.test_download.DownloadTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.
```

```

tearDown()
    Hook method for deconstructing the test fixture after testing it.

testDatasetFile()

testDownload()

testView()

```

```
tardis.tardis_portal.tests.test_download.get_size_and_sha512sum(testfile)
```

tardis.tardis_portal.tests.test_download_apikey module

```

class tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTestCase (methodName='runTest')
    Bases: tastypie.test.ResourceTestCaseMixin, django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_download_apikey()

```

tardis.tardis_portal.tests.test_dumpschemas module

```

class tardis.tardis_portal.tests.test_dumpschemas.DumpSchemasTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    testDumpSchemas()
        Just test that we can run ./manage.py dumpschemas without any runtime exceptions

```

tardis.tardis_portal.tests.test_facility_overview module

Tests relating to facility overview

```

class tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_facility_overview_datafile_list()

    test_facility_overview_experiments()
        Despite the name of the test_facility_overview_experiments method, it actually returns a JSON list of
        datasets (not experiments)

```

tardis.tardis_portal.tests.test_forms module

test_models.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.test_forms.RightsFormTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_ensures_suitable_license ()

    test_needs_confirmation ()
```

tardis.tardis_portal.tests.test_iiif module

```
class tardis.tardis_portal.tests.test_iiif.ExtraTestCases (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testImageCacheControl ()

    testImageHasEtags ()

    testInfoHasEtags ()

class tardis.tardis_portal.tests.test_iiif.Level0TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanGetInfoAsJSON ()

    testCanGetInfoAsXML ()

    testCanGetOriginalImage ()

class tardis.tardis_portal.tests.test_iiif.Level1TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanGetJpegFormat ()

    testHandleRegions ()

    testHandleRotation ()

    testHandleSizing ()

class tardis.tardis_portal.tests.test_iiif.Level2TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html
```

```

setUp()
    Hook method for setting up the test fixture before exercising it.

testCanGetRequiredFormats()

testHandleSizing()

```

tardis.tardis_portal.tests.test_ldap module

```

class tardis.tardis_portal.tests.test_ldap.LDAPErrorTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_search()

class tardis.tardis_portal.tests.test_ldap.LDAPTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_authenticate()

    test_getgroupbyid()

    test_getgroups()

    test_getgroupsforentity()

    test_getuserbyid()

    test_search()

    test_searchgroups()

```

tardis.tardis_portal.tests.test_loadschemas module

```

class tardis.tardis_portal.tests.test_loadschemas.LoadSchemasTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testLoadSchemas()
        Test that we can run ./manage.py loadschemas tardis/tardis_portal/fixtures/jeol_metadata_schema.json

```

tardis.tardis_portal.tests.test_models module

```

test_models.py http://docs.djangoproject.com/en/dev/topics/testing/

class tardis.tardis_portal.tests.test_models.ModelTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_authors()

    test_create_user_automatically_generate_api_key()

    test_datafile()

```

```
test_dataset ()
test_deleting_dfo_without_uri ()
test_experiment ()
test_instrument ()
test_parameter ()
```

tardis.tardis_portal.tests.test_parametersets module

test_parametersets.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.test_parametersets.EditParameterSetTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_add_datafile_params ()
    test_add_dataset_params ()
    test_add_experiment_params ()
    test_edit_datafile_params ()
    test_edit_dataset_params ()
    test_edit_experiment_params ()

class tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_existing_parameterset ()
    test_link_parameter_type ()
        Test that Parameter.link_gfk (GenericForeignKey) is correctly assigned after using Parameter.set_value(some_url) for a LINK Parameter.
    test_link_parameter_type_extra ()
    test_new_parameterset ()
    test_tz_aware_date_handling ()
        Ensure that dates are handling in a timezone-aware way.
    test_tz_naive_date_handling ()
        Ensure that dates are handling in a timezone-aware way.
    test_unresolvable_link_parameter ()
        Test that LINK Parameters that can't be resolved to a model (including non-URL values) still work.
```

tardis.tardis_portal.tests.test_publishservice module

```

class tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider
    Bases: tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider

    get_beamline (experiment)

    get_license_uri (experiment)

    get_rifcs_context (experiment)

    get_template (experiment)

    is_schema_valid (experiment)

class tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testContext ()

    testInitialisation ()

    testInitialisationNoProvider ()

    testManageRifCsCheckContent ()

    testManageRifCsCreateAndRemove ()

```

tardis.tardis_portal.tests.test_rmexperiment module

```

class tardis.tardis_portal.tests.test_rmexperiment.RmExperimentTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testList ()

    testRemove ()

```

tardis.tardis_portal.tests.test_storage module

test_storage.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```

class tardis.tardis_portal.tests.test_storage.ModelTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_get_receiving_box ()

    test_storageboxoption ()

```

tardis.tardis_portal.tests.test_tar_download module

```
class tardis.tardis_portal.tests.test_tar_download.TarDownloadTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_tar_experiment_download()
```

tardis.tardis_portal.tests.test_tasks module

```
class tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testLocalFile()

    test_wrong_size_verification()
```

tardis.tardis_portal.tests.test_tokens module

test_tokens.py

```
class tardis.tardis_portal.tests.test_tokens.FrozenTime (*args, **kwargs)

    classmethod freeze_time (time)

    classmethod now ()

class tardis.tardis_portal.tests.test_tokens.TokenTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_create_token()

    test_default_expiry()

    test_get_session_expiry()

    test_get_session_expiry_expired_token()

    test_get_session_expiry_near_expiry()

    test_is_expired()

    test_retrieve_access_list_tokens()

    test_save_with_random_token()
```

```

test_save_with_random_token_failures()
test_save_with_random_token_gives_up()
test_token_delete()
urls = 'tardis.tardis_portal.tests.urls'

```

tardis.tardis_portal.tests.test_views module

test_views.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```

class tardis.tardis_portal.tests.test_views.ContextualViewTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        setting up essential objects, copied from tests above

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    testDetailsDisplay()
        test display of view for an existing schema and no display for an undefined one.

class tardis.tardis_portal.tests.test_views.ExperimentListsTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        setting up essential objects, copied from tests above

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_mydata_view()
        Test My Data view

    test_shared_view()
        Test Shared view

class tardis.tardis_portal.tests.test_views.ExperimentTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testCreateAndEdit()

    testDatasetJson()

class tardis.tardis_portal.tests.test_views.ManageAccountTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testManageAccount()

class tardis.tardis_portal.tests.test_views.RightsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testRightsRequireValidOwner()

class tardis.tardis_portal.tests.test_views.UploadTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

```

```
tearDown ()
    Hook method for deconstructing the test fixture after testing it.

testFileUpload ()

testUploadComplete ()

class tardis.tardis_portal.tests.test_views.UserListTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    User lists are used for autocompleting the user-to-share-with field when granting access to an experiment

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testGetUserList ()

class tardis.tardis_portal.tests.test_views.ViewTemplateContextsTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        setting up essential objects, copied from tests above

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testDatasetView ()
        test some context parameters for a dataset view

    testExperimentView ()
        test some template context parameters for an experiment view

class tardis.tardis_portal.tests.test_views.listTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testGetGroupList ()

    testGetUserList ()
```

tardis.tardis_portal.tests.tests module

tests.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.tests.SearchTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testSearchExperimentAuthentication (**kwargs)

    testSearchExperimentForm (**kwargs)
```

```

    testSearchExperimentResults (**kwargs)
class tardis.tardis_portal.tests.tests.UserInterfaceTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase
    test_login()
    test_root()
    test_search_urls (**kwargs)
    test_urls()
    test_urls_with_some_content()
tardis.tardis_portal.tests.tests.suite()

```

tardis.tardis_portal.tests.urls module

Module contents

tardis.tardis_portal.views package

Submodules

tardis.tardis_portal.views.ajax_actions module

views that perform some action and don't return anything very useful

tardis.tardis_portal.views.ajax_json module

views that return JSON data

```
tardis.tardis_portal.views.ajax_json.retrieve_licenses(request)
```

tardis.tardis_portal.views.ajax_pages module

views that return HTML that is injected into pages

```
tardis.tardis_portal.views.ajax_pages.experiment_public_access_badge(request,
                                                                    experi-
                                                                    ment_id)
```

```
tardis.tardis_portal.views.ajax_pages.retrieve_owned_exps_list(request, *args,
                                                                **kwargs)
```

```
tardis.tardis_portal.views.ajax_pages.retrieve_shared_exps_list(request, *args,
                                                                **kwargs)
```

tardis.tardis_portal.views.authentication module

views that have to do with authentication

```
tardis.tardis_portal.views.authentication.create_user(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.authentication.login(request, *args, **kwargs)
    handler for login page
tardis.tardis_portal.views.authentication.logout(request)
tardis.tardis_portal.views.authentication.manage_auth_methods(request, *args,
                                                                **kwargs)
    Manage the user's authentication methods using AJAX.
tardis.tardis_portal.views.authentication.manage_user_account(request, *args,
                                                                **kwargs)
tardis.tardis_portal.views.authentication.rcauth(*args, **kwargs)
```

tardis.tardis_portal.views.authorisation module

views that have to do with authorisations

```
tardis.tardis_portal.views.authorisation.create_group(*args, **kwargs)
tardis.tardis_portal.views.authorisation.manage_groups(request, *args, **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_access_list_group_readonly(request,
                                                                              *args,
                                                                              **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_access_list_user_readonly(request,
                                                                              *args,
                                                                              **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_list(request, *args,
                                                                **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_list_by_user(request,
                                                                        *args,
                                                                        **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_userlist_readonly(request,
                                                                              *args,
                                                                              **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_user_list(request, *args,
                                                                **kwargs)
tardis.tardis_portal.views.authorisation.share(request, experiment_id)
    Choose access rights and licence.
tardis.tardis_portal.views.authorisation.token_delete(request, *args, **kwargs)
```

tardis.tardis_portal.views.facilities module

views relevant for facilities and the facility view

```
tardis.tardis_portal.views.facilities.dataset_aggregate_info(dataset)
tardis.tardis_portal.views.facilities.datetime_to_us(dt)
    The datetime objects are kept as None if they aren't set, otherwise they're converted to milliseconds so AngularJS can format them nicely.
```

```
tardis.tardis_portal.views.facilities.facility_overview_data_count (request,
                                                                    *args,
                                                                    **kwargs)
```

returns the total number of datasets for pagination in json format

```
tardis.tardis_portal.views.facilities.facility_overview_datafile_list (dataset)
```

```
tardis.tardis_portal.views.facilities.facility_overview_dataset_detail (request,
                                                                    *args,
                                                                    **kwargs)
```

```
tardis.tardis_portal.views.facilities.facility_overview_experiments (request,
                                                                    *args,
                                                                    **kwargs)
```

json facility datasets

```
tardis.tardis_portal.views.facilities.facility_overview_facilities_list (request,
                                                                    *args,
                                                                    **kwargs)
```

json list of facilities managed by the current user

tardis.tardis_portal.views.images module

views that return images or route to images

```
tardis.tardis_portal.views.images.load_datafile_image (request, parameter_id)
```

```
tardis.tardis_portal.views.images.load_dataset_image (request, parameter_id)
```

```
tardis.tardis_portal.views.images.load_experiment_image (request, parameter_id)
```

```
tardis.tardis_portal.views.images.load_image (request, *args, **kwargs)
```

tardis.tardis_portal.views.machine module

views that return data useful only to other machines (but not JSON)

```
tardis.tardis_portal.views.machine.site_settings (request)
```

tardis.tardis_portal.views.pages module

views that render full pages

```
class tardis.tardis_portal.views.pages.DatasetView (**kwargs)
```

Bases: `django.views.generic.base.TemplateView`

```
find_custom_view_override (request, dataset)
```

Determines if any custom view overrides have been defined in settings.DATASET_VIEWS and returns the view function if a match to one the schemas for the dataset is found. (DATASET_VIEWS is a list of (schema_namespace, view_function) tuples).

Parameters

- **request** –
- **dataset** –

Returns

Return type

get (*request*, **args*, ***kwargs*)
View an existing dataset.

This default view can be overridden by defining a dictionary DATASET_VIEWS in settings.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **args** (*list*) –
- **kwargs** (*dict*) –

Returns The Django response object

Return type `django.http.HttpResponse`

get_context_data (*request*, *dataset*, ***kwargs*)
Prepares the values to be passed to the default dataset view, respecting authorization rules. Returns a dict of values (the context).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **dataset** (`tardis.tardis_portal.models.dataset.Dataset`) – the Dataset model instance
- **kwargs** (*dict*) –

Returns A dictionary of values for the view/template.

Return type `dict`

`template_name = 'tardis_portal/view_dataset.html'`

class `tardis.tardis_portal.views.pages.ExperimentView` (***kwargs*)
Bases: `django.views.generic.base.TemplateView`

find_custom_view_override (*request*, *experiment*)

get (*request*, **args*, ***kwargs*)
View an existing experiment.

This default view can be overridden by defining a dictionary EXPERIMENT_VIEWS in settings.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP Request instance
- **args** (*list*) –
- **kwargs** (*dict*) – In kwargs: param int `experiment_id`: the ID of the experiment

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

get_context_data (*request*, *experiment*, ***kwargs*)
Prepares the values to be passed to the default experiment view, respecting authorization rules. Returns a dict of values (the context).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **experiment** (`tardis.tardis_portal.models.experiment.Experiment`) – the experiment model instance

- **kwargs** (*dict*) – kwargs

Returns A dictionary of values for the view/template.

Return type `dict`

```
template_name = 'tardis_portal/view_experiment.html'
```

```
class tardis.tardis_portal.views.pages.IndexView (**kwargs)
    Bases: django.views.generic.base.TemplateView
```

```
get (request, *args, **kwargs)
```

The index view, intended to render the front page of the MyTardis site listing recent experiments.

This default view can be overridden by defining a dictionary `INDEX_VIEWS` in settings which maps `SITE_ID`'s or domain names to an alternative view function (similar to the `DATASET_VIEWS` or `EXPERIMENT_VIEWS` overrides).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **args** (*list*) –
- **kwargs** (*dict*) –

Returns The Django response object

Return type `django.http.HttpResponse`

```
get_context_data (*args, **kwargs)
```

```
template_name = 'tardis_portal/index.html'
```

```
tardis.tardis_portal.views.pages.about (request)
```

```
tardis.tardis_portal.views.pages.add_dataset (request, *args, **kwargs)
```

```
tardis.tardis_portal.views.pages.control_panel (request, *args, **kwargs)
```

```
tardis.tardis_portal.views.pages.create_experiment (request, *args, **kwargs)
```

Create a new experiment view.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP Request instance
- **template_name** (*string*) – the path of the template to render

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

```
tardis.tardis_portal.views.pages.edit_dataset (request, *args, **kwargs)
```

```
tardis.tardis_portal.views.pages.facility_overview (request, *args, **kwargs)
    summary of experiments in a facility
```

```
tardis.tardis_portal.views.pages.my_data (request, *args, **kwargs)
    show owned data with credential-based access
```

```
tardis.tardis_portal.views.pages.public_data (request)
    list of public experiments
```

```
tardis.tardis_portal.views.pages.shared (request, *args, **kwargs)
    show shared data with credential-based access
```

```
tardis.tardis_portal.views.pages.site_routed_view(request, _default_view,
                                                    _site_mappings, *args, **kwargs)
```

Allows a view to be overridden based on the Site (eg domain) for the current request. Takes a default fallback view (`_default_view`) and a dictionary mapping Django Sites (domain name or int `SITE_ID`) to views. If the current request matches a Site in the dictionary, that view is used instead of the default.

The intention is to define `{site: view}` mappings in `settings.py`, and use this wrapper view in `urls.py` to allow a single URL to be routed to different views depending on the Site in the request.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **_default_view** (`types.FunctionType` | `str`) – The default view if no Site in `_site_mappings` matches the current Site.
- **_site_mappings** (`dict`) – A dictionary mapping Django sites to views (sites are specified as either a domain name `str` or int `SITE_ID`).
- **args** –
- **kwargs** –

Returns A view function

Return type `types.FunctionType`

```
tardis.tardis_portal.views.pages.stats(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.pages.use_rapid_connect(fn)
```

A decorator that adds AAF Rapid Connect settings to a `get_context_data` method.

Parameters **fn** (`types.FunctionType`) – A `get_context_data` function/method.

Returns A `get_context_data` function that adds `RAPID_CONNECT_*` keys to its output context.

Return type `types.FunctionType`

```
tardis.tardis_portal.views.pages.user_guide(request)
```

tardis.tardis_portal.views.parameters module

views to do with metadata, parameters etc. Mostly ajax page inclusions

```
tardis.tardis_portal.views.parameters.add_datafile_par(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.parameters.add_dataset_par(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.parameters.add_experiment_par(request, *args,
                                                            **kwargs)
```

```
tardis.tardis_portal.views.parameters.add_par(request, parentObject, otype, stype)
```

```
tardis.tardis_portal.views.parameters.edit_datafile_par(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.parameters.edit_dataset_par(request, *args, **kwargs)
```

```
tardis.tardis_portal.views.parameters.edit_experiment_par(request, *args,
                                                            **kwargs)
```

```
tardis.tardis_portal.views.parameters.edit_parameters(request, parameterset, otype)
```

tardis.tardis_portal.views.upload module

views for uploading files via HTTP

```
tardis.tardis_portal.views.upload.upload_complete(request,
                                                    template_name='tardis_portal/upload_complete.html')
```

The ajax-loaded result of a file being uploaded

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP Request instance
- **template_name** (`string`) – the path of the template to render

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

tardis.tardis_portal.views.utils module

helper functions used by other views

```
class tardis.tardis_portal.views.utils.HttpResponseMethodNotAllowed(*args,
                                                                    **kwargs)
```

Bases: `django.http.response.HttpResponse`

status_code = 303

```
class tardis.tardis_portal.views.utils.HttpResponseSeeAlso(redirect_to, *args,
                                                            **kwargs)
```

Bases: `django.http.response.HttpResponseRedirect`

status_code = 303

```
tardis.tardis_portal.views.utils.feedback(request)
```

```
tardis.tardis_portal.views.utils.get_dataset_info(dataset, include_thumbnail=False,
                                                    exclude=None)
```

```
tardis.tardis_portal.views.utils.remove_csrf_token(request)
rather than fixing the form code that loops over all POST entries indiscriminately, I am removing the csrf token
with this hack. This is only required in certain form code and can be removed should this ever be fixed
```

Module contents

importing all views files here, so that any old code will work as expected, when importing from `tardis.tardis_portal.views`

Submodules

tardis.tardis_portal.ParameterSetManager module

```
class tardis.tardis_portal.ParameterSetManager.ParameterSetManager(parameterset=None,
                                                                    parentOb-
                                                                    ject=None,
                                                                    schema=None)
```

Bases: `object`

```
blank_param = None
delete_all_params()
delete_params(parname)
get_param(parname, value=False)
get_params(parname, value=False)
get_schema()
new_param(parname, value, fullparname=None)
parameters = None
parameterset = None
set_param(parname, value, fullparname=None, example_value=None)
set_param_list(parname, value_list, fullparname=None)
set_params_from_dict(dict)
```

tardis.tardis_portal.admin module

```
class tardis.tardis_portal.admin.DataFileObjectInline(parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline
```

```
    extra = 0
```

```
    form
        alias of DataFileObjectInlineForm
```

```
    media
```

```
    model
        alias of tardis.tardis_portal.models.datafile.DataFileObject
```

```
class tardis.tardis_portal.admin.DataFileObjectInlineForm(data=None, files=None,
    auto_id=u'id_%s', pre-
    fix=None, initial=None,
    error_class=<class
    'django.forms.utils.ErrorList'>,
    label_suffix=None,
    empty_permitted=False,
    instance=None,
    use_required_attribute=None)
```

```
Bases: django.forms.models.ModelForm
```

```
class Meta
```

```
    fields = '__all__'
```

```
    model
        alias of tardis.tardis_portal.models.datafile.DataFileObject
```

```
    widgets = {'uri': <django.forms.widgets.TextInput object>}
```

```
    base_fields = {'datafile': <django.forms.models.ModelChoiceField object>, 'last_verif
```

```
    declared_fields = {}
```

```
    media
```

```

class tardis.tardis_portal.admin.DatafileAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    form
        alias of DatafileAdminForm

    inlines = [<class 'tardis.tardis_portal.admin.DataFileObjectInline'>]

    media

    search_fields = ['filename', 'id']

class tardis.tardis_portal.admin.DatafileAdminForm(data=None,          files=None,
                                                    auto_id=u'id_%s', prefix=None,
                                                    initial=None, error_class=<class
                                                    'django.forms.utils.ErrorList'>,
                                                    label_suffix=None,
                                                    empty_permitted=False,
                                                    instance=None,
                                                    use_required_attribute=None)

    Bases: django.forms.models.ModelForm

    class Meta

        fields = '__all__'

        model
            alias of tardis.tardis_portal.models.datafile.DataFile

        widgets = {'directory': <django.forms.widgets.TextInput object>}

    base_fields = {'created_time': <django.forms.fields.DateTimeField object>, 'dataset':

    declared_fields = {}

    media

class tardis.tardis_portal.admin.DatasetAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    media

    search_fields = ['description', 'id']

class tardis.tardis_portal.admin.ExperimentAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    inlines = [<class 'tardis.tardis_portal.admin.ObjectACLInline'>]

    media

    search_fields = ['title', 'id']

class tardis.tardis_portal.admin.ExperimentParameterInline(parent_model,      ad-
                                                            min_site)
    Bases: django.contrib.admin.options.TabularInline

    extra = 0

    formfield_overrides = {<class 'django.db.models.fields.TextField'>: {'widget': <clas

    media

    model
        alias of tardis.tardis_portal.models.parameters.ExperimentParameter

```

```
class tardis.tardis_portal.admin.ExperimentParameterSetAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    inlines = [<class 'tardis.tardis_portal.admin.ExperimentParameterInline'>]
    media

class tardis.tardis_portal.admin.FacilityAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media
    search_fields = ['name']

class tardis.tardis_portal.admin.FreeTextSearchFieldAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media

class tardis.tardis_portal.admin.InstrumentAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media
    search_fields = ['name']

class tardis.tardis_portal.admin.InstrumentParameterInline(parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline
    extra = 0
    media
    model
        alias of tardis.tardis_portal.models.parameters.InstrumentParameter

class tardis.tardis_portal.admin.InstrumentParameterSetAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    inlines = [<class 'tardis.tardis_portal.admin.InstrumentParameterInline'>]
    media

class tardis.tardis_portal.admin.ObjectACLAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    list_display = ['__str__', 'pluginId', 'entityId', 'canRead', 'canWrite', 'canDelete',
    media
    search_fields = ['content_type', 'object_id']

class tardis.tardis_portal.admin.ObjectACLInline(parent_model, admin_site)
    Bases: django.contrib.contenttypes.admin.GenericTabularInline
    extra = 0
    media
    model
        alias of tardis.tardis_portal.models.access_control.ObjectACL

class tardis.tardis_portal.admin.ParameterNameAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
```

```

    media

    search_fields = ['name', 'schema__id']

class tardis.tardis_portal.admin.ParameterNameInline (parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline

    extra = 0

    media

    model
        alias of tardis.tardis_portal.models.parameters.ParameterName

class tardis.tardis_portal.admin.SchemaAdmin (model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    inlines = [<class 'tardis.tardis_portal.admin.ParameterNameInline'>]

    media

    search_fields = ['name', 'namespace']

class tardis.tardis_portal.admin.StorageBoxAdmin (model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    form
        alias of StorageBoxForm

    inlines = [<class 'tardis.tardis_portal.admin.StorageBoxOptionInline'>, <class 'tardis
    media

    search_fields = ['name']

class tardis.tardis_portal.admin.StorageBoxAttributeInline (parent_model,      ad-
                                                                min_site)
    Bases: django.contrib.admin.options.TabularInline

    extra = 0

    form
        alias of StorageBoxAttributeInlineForm

    media

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

class tardis.tardis_portal.admin.StorageBoxAttributeInlineForm (data=None,
                                                                files=None,
                                                                auto_id=u'id_%s',
                                                                pre-
                                                                fix=None,    ini-
                                                                tial=None,   er-
                                                                ror_class=<class
                                                                'django.forms.utils.ErrorList'>,
                                                                la-
                                                                bel_suffix=None,
                                                                empty_permitted=False,
                                                                instance=None,
                                                                use_required_attribute=None)

    Bases: django.forms.models.ModelForm

```

```
class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

    widgets = {'key': <django.forms.widgets.TextInput object>, 'value': <django.forms
base_fields = {'key': <django.forms.fields.CharField object>, 'storage_box': <django
declared_fields = {}

media

class tardis.tardis_portal.admin.StorageBoxForm(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
instance=None,
use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBox

    widgets = {'description': <django.forms.widgets.TextInput object>, 'django_storage
base_fields = {'description': <django.forms.fields.CharField object>, 'django_storage
declared_fields = {}

media

class tardis.tardis_portal.admin.StorageBoxOptionInline(parent_model, ad-
min_site)

Bases: django.contrib.admin.options.TabularInline

extra = 0

form
    alias of StorageBoxOptionInlineForm

media

model
    alias of tardis.tardis_portal.models.storage.StorageBoxOption
```

```

class tardis.tardis_portal.admin.StorageBoxOptionInlineForm(data=None,
                                                         files=None,
                                                         auto_id=u'id_%s',
                                                         prefix=None,    ini-
                                                         tial=None,        er-
                                                         ror_class=<class
                                                         'django.forms.utils.ErrorList'>,
                                                         label_suffix=None,
                                                         empty_permitted=False,
                                                         instance=None,
                                                         use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxOption

    widgets = {'key': <django.forms.widgets.TextInput object>, 'value': <django.forms
base_fields = {'key': <django.forms.fields.CharField object>, 'storage_box': <django
declared_fields = {}

media

class tardis.tardis_portal.admin.UserAuthenticationAdmin(model, admin_site)
Bases: django.contrib.admin.options.ModelAdmin

media

search_fields = ['username', 'authenticationMethod', 'UserProfile__user__username']

```

tardis.tardis_portal.api module

RESTful API for MyTardis models and data. Implemented with Tastypie.

```

class tardis.tardis_portal.api.ACLAuthorization
Bases: tastypie.authorization.Authorization

Authorisation class for Tastypie.

create_detail(object_list, bundle)

create_list(object_list, bundle)

delete_detail(object_list, bundle)

delete_list(object_list, bundle)

read_detail(object_list, bundle)

read_list(object_list, bundle)

update_detail(object_list, bundle)
    Latest TastyPie requires update_detail permissions to be able to create objects. Rather than duplicating
    code here, we'll just use the same authorization rules we use for create_detail.

update_list(object_list, bundle)

```

```
class tardis.tardis_portal.api.DataFileResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        filtering = {'dataset': 2, 'directory': ('exact', 'startswith'), 'filename': ('exact', 'startswith')}
        object_class
            alias of tardis.tardis_portal.models.datafile.DataFile
        ordering = ['filename', 'modification_time']
        queryset
        resource_name = 'dataset_file'

    base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'datafile': <tastypie.fields.FileField object>}
    declared_fields = {'datafile': <tastypie.fields.FileField object>, 'dataset': <tastypie.fields.IntegerField object>}
    deserialize (request, data, format=None)
        from https://github.com/toastdriven/django-tastypie/issues/42 modified to deserialize json sent via POST.
        Would fail if data is sent in a different format. uses a hack to get back pure json from request.POST
    download_file (request, **kwargs)
        curl needs the -J switch to get the filename right auth needs to be added manually here
    hydrate (bundle)
    obj_create (bundle, **kwargs)
        Creates a new DataFile object from the provided bundle.data dict.

        If a duplicate key error occurs, responds with HTTP Error 409: CONFLICT
    post_list (request, **kwargs)
    prepend_urls ()
    put_detail (request, **kwargs)
        from https://github.com/toastdriven/django-tastypie/issues/42
    temp_url = None
    verify_file (request, **kwargs)
        triggers verification of file, e.g. after non-POST upload complete

class tardis.tardis_portal.api.DatafileParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        object_class
            alias of tardis.tardis_portal.models.parameters.DatafileParameter
        queryset

    base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, 'id': <tastypie.fields.IntegerField object>}
    declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.DatafileParameterSetResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterSetResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
```

```

    object_class
        alias of tardis.tardis_portal.models.parameters.DatafileParameterSet

    queryset

base_fields = {'datafile': <tastypie.fields.ForeignKey object>, u'id': <tastypie.fie
declared_fields = {'datafile': <tastypie.fields.ForeignKey object>, 'parameters': <t

class tardis.tardis_portal.api.DatasetParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.DatasetParameter

        queryset

base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, u'id': <tas
declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.DatasetParameterSetResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterSetResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.DatasetParameterSet

        queryset

base_fields = {'dataset': <tastypie.fields.ForeignKey object>, u'id': <tastypie.fiel
declared_fields = {'dataset': <tastypie.fields.ForeignKey object>, 'parameters': <ta

class tardis.tardis_portal.api.DatasetResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        always_return_data = True

        filtering = {'description': ('exact',), 'directory': ('exact',), 'experiments':

        object_class
            alias of tardis.tardis_portal.models.dataset.Dataset

        ordering = ['description']

        queryset

base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'description':
declared_fields = {'experiments': <tastypie.fields.ToManyField object>, 'instrument':
get_datafiles (request, **kwargs)
prepend_urls ()

class tardis.tardis_portal.api.ExperimentParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

```

```
class Meta
    Bases: tardis.tardis_portal.api.Meta

    object_class
        alias of tardis.tardis_portal.models.parameters.ExperimentParameter

    queryset

    base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, u'id': <tas
    declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}
```

class `tardis.tardis_portal.api.ExperimentParameterSetResource` (*api_name=None*)
Bases: *tardis.tardis_portal.api.ParameterSetResource*
API for ExperimentParameterSets

```
class Meta
    Bases: tardis.tardis_portal.api.Meta

    object_class
        alias of tardis.tardis_portal.models.parameters.ExperimentParameterSet

    queryset

    base_fields = {'experiment': <tastypie.fields.ForeignKey object>, u'id': <tastypie.f
    declared_fields = {'experiment': <tastypie.fields.ForeignKey object>, 'parameters':
```

class `tardis.tardis_portal.api.ExperimentResource` (*api_name=None*)
Bases: *tardis.tardis_portal.api.MyTardisModelResource*
API for Experiments also creates a default ACL and allows ExperimentParameterSets to be read and written.
TODO: catch duplicate schema submissions for parameter sets

```
class Meta
    Bases: tardis.tardis_portal.api.Meta

    always_return_data = True

    filtering = {'id': ('exact',), 'title': ('exact',)}

    object_class
        alias of tardis.tardis_portal.models.experiment.Experiment

    ordering = ['title', 'created_time', 'update_time']

    queryset

    base_fields = {'approved': <tastypie.fields.BooleanField object>, 'created_by': <tas
    declared_fields = {'created_by': <tastypie.fields.ForeignKey object>, 'parameter_sets
    dehydrate (bundle)

    hydrate_m2m (bundle)
        create ACL before any related objects are created in order to use ACL permissions for those objects.

    obj_create (bundle, **kwargs)
        experiments need at least one ACL to be available through the ExperimentManager (Experiment.safe)
        Currently not tested for failed db transactions as sqlite does not enforce limits.
```

class `tardis.tardis_portal.api.FacilityResource` (*api_name=None*)
Bases: *tardis.tardis_portal.api.MyTardisModelResource*

```

class Meta
    Bases: tardis.tardis_portal.api.Meta
    always_return_data = True
    filtering = {'id': ('exact',), 'manager_group': 2, 'name': ('exact',)}
    object_class
        alias of tardis.tardis_portal.models.facility.Facility
    queryset

base_fields = {'created_time': <tastypie.fields.DateTimeField object>, u'id': <tastypie.fields.IntegerField object>}
declared_fields = {'manager_group': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.GroupResource (api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta
        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        filtering = {'id': ('exact',), 'name': ('exact',)}
        object_class
            alias of django.contrib.auth.models.Group
        queryset

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'name': <tastypie.fields.CharField object>}
declared_fields = {}

class tardis.tardis_portal.api.InstrumentResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        always_return_data = True
        filtering = {'facility': 2, 'id': ('exact',), 'name': ('exact',)}
        object_class
            alias of tardis.tardis_portal.models.instrument.Instrument
        queryset

base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'facility': <tastypie.fields.ForeignKey object>}
declared_fields = {'facility': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.LocationResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        object_class
            alias of tardis.tardis_portal.models.storage.StorageBox
        queryset

```

```
base_fields = {'description': <tastypie.fields.CharField object>, 'django_storage_cla
declared_fields = {}

class tardis.tardis_portal.api.MyTardisAuthentication
    Bases: object
    custom tastypie authentication that works with both anonymous use and a number of available auth mechanisms.

    get_identifier(request)
    is_authenticated(request, **kwargs)
        handles backends explicitly so that it can return False when credentials are given but wrong and return
        Anonymous User when credentials are not given or the session has expired (web use).

class tardis.tardis_portal.api.MyTardisModelResource(api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        object_class = None
        serializer = <tardis.tardis_portal.api.PrettyJSONSerializer object>
        base_fields = {'u'resource_uri': <tastypie.fields.CharField object>}
        declared_fields = {}
        lookup_kwargs_with_identifiers(bundle, kwargs)

class tardis.tardis_portal.api.ObjectACLResource(api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        filtering = {'entityId': ('exact',), 'pluginId': ('exact',)}
        object_class
            alias of tardis.tardis_portal.models.access_control.ObjectACL
        queryset

        base_fields = {'aclOwnershipType': <tastypie.fields.IntegerField object>, 'canDelete'
        declared_fields = {'content_object': <tastypie.contrib.contenttypes.fields.GenericFor
        hydrate(bundle)

class tardis.tardis_portal.api.ParameterNameResource(api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
```

```

    filtering = {'schema': 2}
    object_class
        alias of tardis.tardis_portal.models.parameters.ParameterName
    queryset

base_fields = {'choices': <tastypie.fields.CharField object>, 'comparison_type': <ta
declared_fields = {'schema': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.ParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    base_fields = {'name': <tastypie.fields.ForeignKey object>, u'resource_uri': <tastyp
    declared_fields = {'name': <tastypie.fields.ForeignKey object>, 'value': <tastypie.f
    hydrate (bundle)
        sets the parametername by uri or name if untyped value is given, set value via parameter method, otherwise
        use modelresource automatisms

class tardis.tardis_portal.api.ParameterSetResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    base_fields = {u'resource_uri': <tastypie.fields.CharField object>, 'schema': <tastyp
    declared_fields = {'schema': <tastypie.fields.ForeignKey object>}
    hydrate_schema (bundle)

class tardis.tardis_portal.api.PrettyJSONSerializer (formats=None,          con-
                                                tent_types=None,          date-
                                                time_formatting=None)

    Bases: tastypie.serializers.Serializer

    json_indent = 2
    to_json (data, options=None)

class tardis.tardis_portal.api.ReplicaResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'url': ('exact', 'startswith'), 'verified': ('exact',)}
        object_class
            alias of tardis.tardis_portal.models.datafile.DataFileObject
        queryset

        base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'datafile': <
        declared_fields = {'datafile': <tastypie.fields.ForeignKey object>}
        dehydrate (bundle)
        hydrate (bundle)

class tardis.tardis_portal.api.SchemaResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'id': ('exact',), 'namespace': ('exact',)}
```

```
    object_class
        alias of tardis.tardis_portal.models.parameters.Schema

    queryset

base_fields = {'hidden': <tastypie.fields.BooleanField object>, u'id': <tastypie.fie
declared_fields = {}

lookup_kwargs_with_identifiers (bundle, kwargs)

class tardis.tardis_portal.api.StorageBoxAttributeResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

        queryset

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'key': <tastypie.fields
declared_fields = {'storage_box': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.StorageBoxOptionResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBoxOption

        queryset

accessible_keys = ['location']

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'key': <tastypie.fields
declared_fields = {'storage_box': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.StorageBoxResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBox

        queryset

base_fields = {'attributes': <tastypie.fields.ToManyField object>, 'description': <t
declared_fields = {'attributes': <tastypie.fields.ToManyField object>, 'options': <t

class tardis.tardis_portal.api.UserResource (api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta

        allowed_methods = ['get']

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
```

```

authorization
    Authorisation class for Tastypie.

fields = ['username', 'first_name', 'last_name', 'email']

filtering = {'email': ('iexact',), 'username': ('exact',)}

object_class
    alias of django.contrib.auth.models.User

queryset

serializer = <tardis.tardis_portal.api.PrettyJSONSerializer object>

base_fields = {'email': <tastypie.fields.CharField object>, 'first_name': <tastypie.

declared_fields = {'groups': <tastypie.fields.ManyToManyField object>}

dehydrate (bundle)
    use cases:

```

```

public user:
    anonymous:
        name, uri, email, id
    authenticated:
        other user:
            name, uri, email, id [, username if facility manager]
        same user:
            name, uri, email, id, username
private user:
    anonymous:
        none
    authenticated:
        other user:
            name, uri, id [, username, email if facility manager]
        same user:
            name, uri, email, id, username

```

`tardis.tardis_portal.api.lookup_by_unique_id_only` (*resource*)
 returns custom lookup function. initialise with resource type

tardis.tardis_portal.constants module

constants.py

@author: Gerson Galang

tardis.tardis_portal.context_processors module

`tardis.tardis_portal.context_processors.global_contexts` (*request*)

`tardis.tardis_portal.context_processors.google_analytics` (*request*)
 adds context for portal_template.html

`tardis.tardis_portal.context_processors.registration_processor` (*request*)

`tardis.tardis_portal.context_processors.single_search_processor` (*request*)

`tardis.tardis_portal.context_processors.user_details_processor` (*request*)

```
tardis.tardis_portal.context_processors.user_menu_processor(request)
```

tardis.tardis_portal.creativecommonshandler module

Creative Commons Handler

A wrapper for creative commons interactions on a ParameterSet

```
class tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler(experiment_id=None,  
                                                                           create=  
                                                                           ate=True)
```

```
    experiment_id = None
```

```
    get_or_create_cc_parameterset (create=True)
```

Gets the creative commons parameterset for the experiment :param create: If true, creates a new parameterset object to hold the cc license if one doesn't exist :type create: boolean :return: The parameterset manager for the cc parameterset :rtype: tardis.tardis_portal.ParameterSetManager.ParameterSetManager

```
    has_cc_license ()
```

Returns True if there's a cc license parameterset for the experiment

Return type boolean

```
    psm = None
```

```
    save_license (request)
```

Saves a license parameterset with the POST variables from the creative commons form :param request: a HTTP Request instance :type request: `django.http.HttpRequest`

```
    schema = 'http://www.tardis.edu.au/schemas/creative_commons/2011/05/17'
```

tardis.tardis_portal.deprecations module

Deprecation warnings

```
exception tardis.tardis_portal.deprecations.RemovedInMyTardis41Warning
```

Bases: `exceptions.DeprecationWarning`

Used to raise warnings about deprecated functionality.

Usage:

```
import warnings

warnings.warn(
    "This method will be removed in MyTardis 4.1. "
    "Please use method2 instead.",
    RemovedInMyTardis41Warning
)
```

```
exception tardis.tardis_portal.deprecations.RemovedInMyTardis42Warning
```

Bases: `exceptions.PendingDeprecationWarning`

Used to raise warnings about deprecated functionality.

Usage:

```
import warnings

warnings.warn(
    "This method will be removed in MyTardis 4.2. "
    "Please use method2 instead.",
    RemovedInMyTardis42Warning
)
```

tardis.tardis_portal.download module

download.py

```
class tardis.tardis_portal.download.UncachedTarStream(mapped_file_objs, filename,
                                                    do_gzip=False, buffer-
                                                    size=131072, comp_level=6,
                                                    http_buffersize=65535)
```

Bases: `tarfile.TarFile`

Stream files into a compressed tar stream on the fly

close_gzip()

compress(buf)

compute_size()

get_response(tracker_data=None)

make_tar()

main tar generator. until python 3 needs to be in one function because ‘yield’s don’t bubble up.

prepare_output(uc_buf, remainder)

tarinfo_for_df(df, name)

tardis.tardis_portal.download.classic_mapper(rootdir)

tardis.tardis_portal.download.download_api_key(request, *args, **kwargs)

tardis.tardis_portal.download.download_datafile(request, datafile_id)

tardis.tardis_portal.download.get_download_organizations()

tardis.tardis_portal.download.make_mapper(organization, rootdir)

tardis.tardis_portal.download.streaming_download_datafiles(request)

takes string parameter “comptype” for compression method. Currently implemented: “tgz” and “tar” The datafiles to be downloaded are selected using “datafile”, “dataset” or “url” parameters. An “expid” parameter may be supplied for use in the download archive name. If “url” is used, the “expid” parameter is also used to limit the datafiles to be downloaded to a given experiment.

tardis.tardis_portal.download.view_datafile(request, datafile_id)

tardis.tardis_portal.email module

tardis.tardis_portal.email.build_template_html(template_filename, context)

tardis.tardis_portal.email.build_template_text(template_filename, context)

tardis.tardis_portal.email.email_user(subject, template_filename, context, user)

tardis.tardis_portal.errors module

Created on 02/09/2010

```
exception tardis.tardis_portal.errors.ParameterChoicesFormatError(msg)
    Bases: exceptions.Exception

exception tardis.tardis_portal.errors.SearchQueryTypeUnprovidedError(msg)
    Bases: exceptions.Exception

exception tardis.tardis_portal.errors.UnsupportedSearchQueryTypeError(msg)
    Bases: exceptions.Exception
```

tardis.tardis_portal.fields module

```
class tardis.tardis_portal.fields.MultiValueCommaSeparatedField(fields=(),
                                                                *args,
                                                                **kwargs)

    Bases: django.forms.fields.MultiValueField

    compress (data_list)
```

tardis.tardis_portal.forms module

forms module

```
class tardis.tardis_portal.forms.AddGroupPermissionsForm(data=None, files=None,
                                                         auto_id=u'id_%s', pre-
                                                         fix=None, initial=None,
                                                         error_class=<class
                                                         'django.forms.utils.ErrorList'>,
                                                         label_suffix=None,
                                                         empty_permitted=False,
                                                         field_order=None,
                                                         use_required_attribute=None,
                                                         renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'addgroup': <django.forms.fields.CharField object>, 'authMethod': <dj
    declared_fields = {'addgroup': <django.forms.fields.CharField object>, 'authMethod':
    media

class tardis.tardis_portal.forms.AddUserPermissionsForm(data=None, files=None,
                                                         auto_id=u'id_%s', pre-
                                                         fix=None, initial=None,
                                                         error_class=<class
                                                         'django.forms.utils.ErrorList'>,
                                                         label_suffix=None,
                                                         empty_permitted=False,
                                                         field_order=None,
                                                         use_required_attribute=None,
                                                         renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'authMethod': <django.forms.fields.CharField object>, 'autocomp_user':
```

```

        declared_fields = {'authMethod': <django.forms.fields.CharField object>, 'autocomp_us
media
class tardis.tardis_portal.forms.ChangeGroupPermissionsForm(data=None,
                                                            files=None,
                                                            auto_id=u'id_%s',
                                                            prefix=None,    ini-
                                                            tial=None,        er-
                                                            ror_class=<class
                                                            'django.forms.utils.ErrorList'>,
                                                            label_suffix=None,
                                                            empty_permitted=False,
                                                            field_order=None,
                                                            use_required_attribute=None,
                                                            renderer=None)

Bases: django.forms.forms.Form

base_fields = {'canDelete': <django.forms.fields.BooleanField object>, 'canRead': <d
declared_fields = {'canDelete': <django.forms.fields.BooleanField object>, 'canRead':
media
class tardis.tardis_portal.forms.ChangeUserPermissionsForm(data=None,
                                                            files=None,
                                                            auto_id=u'id_%s',
                                                            prefix=None,    ini-
                                                            tial=None,        er-
                                                            ror_class=<class
                                                            'django.forms.utils.ErrorList'>,
                                                            label_suffix=None,
                                                            empty_permitted=False,
                                                            instance=None,
                                                            use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

```

```
class ObjectACL(*args, **kwargs)
```

Bases: django.db.models.base.Model

The ObjectACL (formerly ExperimentACL) table is the core of the [Tardis Authorisation framework](#)

Attribute pluginId the the name of the auth plugin being used

Attribute entityId a foreign key to auth plugins

Attribute object_type a foreign key to ContentType

Attribute object_id the primary key/id of the object_type

Attribute canRead gives the user read access

Attribute canWrite gives the user write access

Attribute canDelete gives the user delete permission

Attribute isOwner the experiment owner flag.

Attribute effectiveDate the date when access takes into effect

Attribute expiryDate the date when access ceases

Attribute aclOwnershipType system-owned or user-owned.

System-owned ACLs will prevent users from removing or editing ACL entries to a particular experiment they own. User-owned ACLs will allow experiment owners to remove/add/edit ACL entries to the experiments they own.

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

OWNER_OWNED = 1

SYSTEM_OWNED = 2

aclOwnershipType

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canDelete

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canRead

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canWrite

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

content_object

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

content_type

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

content_type_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

effectiveDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

entityId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

expiryDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_aclOwnershipType_display (**morekwarg)

classmethod get_effective_query()

get_related_object()

If possible, resolve the pluginId/entityId combination to a user or group object.

get_related_object_group()

If possible, resolve the pluginId/entityId combination to a user or group object.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isOwner

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

object_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

openidaclmigration_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

pluginId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

fields = ['canDelete', 'canRead', 'canWrite', 'effectiveDate', 'expiryDate', 'isOwner']

model

alias of `tardis.tardis_portal.models.access_control.ObjectACL`

widgets = {'effectiveDate': <django.forms.widgets.SelectDateWidget object>, 'expiryDate': <django.forms.widgets.SelectDateWidget object>, 'isOwner': <django.forms.widgets.BooleanField object>, 'canDelete': <django.forms.widgets.BooleanField object>, 'canRead': <django.forms.widgets.BooleanField object>, 'canWrite': <django.forms.widgets.BooleanField object>}

base_fields = {'canDelete': <django.forms.fields.BooleanField object>, 'canRead': <django.forms.fields.BooleanField object>, 'canWrite': <django.forms.fields.BooleanField object>, 'effectiveDate': <django.forms.fields.DateField object>, 'expiryDate': <django.forms.fields.DateField object>, 'isOwner': <django.forms.fields.BooleanField object>}

declared_fields = {}

media

```
class tardis.tardis_portal.forms.CreateGroupPermissionsForm(data=None,
    files=None,
    auto_id=u'id_%s',
    prefix=None,
    initial=None,
    error_class=<class
'django.forms.utils.ErrorList'>,
    label_suffix=None,
    empty_permitted=False,
    field_order=None,
    use_required_attribute=None,
    renderer=None)
```

Bases: `django.forms.forms.Form`

```
base_fields = {'addgroup': <django.forms.fields.CharField object>, 'adduser': <django.forms.fields.CharField object>
declared_fields = {'addgroup': <django.forms.fields.CharField object>, 'adduser': <django.forms.fields.CharField object>
media

class tardis.tardis_portal.forms.CreateUserPermissionsForm(data=None,
                                                           files=None,
                                                           auto_id=u'id_%s',
                                                           prefix=None, initial=None,
                                                           error_class=<class 'django.forms.utils.ErrorList'>,
                                                           label_suffix=None,
                                                           empty_permitted=False,
                                                           field_order=None,
                                                           use_required_attribute=None,
                                                           renderer=None)

Bases: tardis.tardis_portal.forms.RegistrationForm

base_fields = {'authMethod': <django.forms.fields.CharField object>, 'email': <django.forms.fields.CharField object>
declared_fields = {'authMethod': <django.forms.fields.CharField object>, 'email': <django.forms.fields.CharField object>
media

class tardis.tardis_portal.forms.DatasetForm(data=None,
                                              files=None,
                                              auto_id=u'id_%s', prefix=None,
                                              initial=None, error_class=<class 'django.forms.utils.ErrorList'>,
                                              label_suffix=None,
                                              empty_permitted=False, instance=None,
                                              use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = ['description', 'directory', 'instrument']
    model = tardis.tardis_portal.models.dataset.Dataset
    alias of tardis.tardis_portal.models.dataset.Dataset

base_fields = {'description': <django.forms.fields.CharField object>, 'directory': <django.forms.fields.CharField object>
declared_fields = {'description': <django.forms.fields.CharField object>}
media

class tardis.tardis_portal.forms.ExperimentAuthor(data=None,
                                                  files=None,
                                                  auto_id=u'id_%s', prefix=None,
                                                  initial=None, error_class=<class 'django.forms.utils.ErrorList'>,
                                                  label_suffix=None,
                                                  empty_permitted=False,
                                                  instance=None,
                                                  use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = ['author', 'institution', 'email', 'order', 'url']
```

```

    model
        alias of tardis.tardis_portal.models.experiment.ExperimentAuthor

    base_fields = {'author': <django.forms.fields.CharField object>, 'email': <django.f.fo
    declared_fields = {}

    media

class tardis.tardis_portal.forms.ExperimentForm(data=None,          files=None,
        auto_id='%s',    prefix=None,    ini-
        tial=None,      error_class=<class
        'django.forms.utils.ErrorList'>,
        label_suffix=':',
        empty_permitted=False,          in-
        stance=None, extra=0)

Bases: django.forms.models.ModelForm

This handles the complex experiment forms.

All internal datasets forms are prefixed with dataset_, and all internal dataset file fields are prefixed with file_.
These are parsed out of the post data and added to the form as internal lists.

class FullExperiment (**kwargs)
    Bases: UserDict.UserDict

    This is a dict wrapper that store the values returned from the tardis.tardis_portal.forms.
    ExperimentForm.save() function. It provides a convenience method for saving the model objects.

    save_m2m()
        {'experiment': experiment, 'experiment_authors': experiment_authors, 'authors': authors, 'datasets':
        datasets, 'datafiles': datafiles}

class Meta

    fields = ('title', 'institution_name', 'description')

    model
        alias of tardis.tardis_portal.models.experiment.Experiment

    base_fields = {'description': <django.forms.fields.CharField object>, 'institution_na
    declared_fields = {'url': <django.forms.fields.CharField object>}

    is_valid()
        Test the validity of the form, the form may be invalid even if the error attribute has no contents. This is
        because the returned value is dependent on the validity of the nested forms.

        This validity also takes into account foreign keys that might be dependent on an unsaved model.

        Returns validity

        Return type bool

    media

    save (commit=True)

```

```
class tardis.tardis_portal.forms.ImportParamsForm(data=None,          files=None,
                                                  auto_id=u'id_%s', prefix=None,
                                                  initial=None, error_class=<class
                                                  'django.forms.utils.ErrorList'>,
                                                  label_suffix=None,
                                                  empty_permitted=False,
                                                  field_order=None,
                                                  use_required_attribute=None,
                                                  renderer=None)

Bases: django.forms.forms.Form

base_fields = {'params': <django.forms.fields.FileField object>, 'password': <django
declared_fields = {'params': <django.forms.fields.FileField object>, 'password': <dj
media

class tardis.tardis_portal.forms.LoginForm(*args, **kwargs)
Bases: django.contrib.auth.forms.AuthenticationForm

base_fields = {'password': <django.forms.fields.CharField object>, 'username': <djan
declared_fields = {'password': <django.forms.fields.CharField object>, 'username': <
media

class tardis.tardis_portal.forms.ManageAccountForm(data=None,          files=None,
                                                  auto_id=u'id_%s', prefix=None,
                                                  initial=None, error_class=<class
                                                  'django.forms.utils.ErrorList'>,
                                                  label_suffix=None,
                                                  empty_permitted=False,
                                                  instance=None,
                                                  use_required_attribute=None)

Bases: django.forms.models.ModelForm

Form for changing account details.

class Meta

    fields = ('first_name', 'last_name', 'email')

    model
        alias of django.contrib.auth.models.User

base_fields = {'email': <django.forms.fields.EmailField object>, 'first_name': <djan
declared_fields = {}

media
```

```

class tardis.tardis_portal.forms.ManageGroupPermissionsForm(data=None,
                                                            files=None,
                                                            auto_id=u'id_%s',
                                                            prefix=None,    ini-
                                                            tial=None,        er-
                                                            ror_class=<class
                                                            'django.forms.utils.ErrorList'>,
                                                            label_suffix=None,
                                                            empty_permitted=False,
                                                            field_order=None,
                                                            use_required_attribute=None,
                                                            renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'adduser': <django.forms.fields.CharField object>, 'admin': <django.f
    declared_fields = {'adduser': <django.forms.fields.CharField object>, 'admin': <djan
    media

class tardis.tardis_portal.forms.NoInput(attrs=None)
    Bases: django.forms.widgets.Widget

    media

    render(name, value, attrs=None)

class tardis.tardis_portal.forms.RawSearchForm(*args, **kwargs)
    Bases: haystack.forms.SearchForm

    base_fields = {'q': <django.forms.fields.CharField object>}

    declared_fields = {'q': <django.forms.fields.CharField object>}

    media

    search()

class tardis.tardis_portal.forms.RegisterExperimentForm(data=None,    files=None,
                                                         auto_id=u'id_%s',    pre-
                                                         fix=None,    initial=None,
                                                         error_class=<class
                                                         'django.forms.utils.ErrorList'>,
                                                         label_suffix=None,
                                                         empty_permitted=False,
                                                         field_order=None,
                                                         use_required_attribute=None,
                                                         renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'experiment_owner': <django.forms.fields.CharField object>, 'from_url'
    declared_fields = {'experiment_owner': <django.forms.fields.CharField object>, 'from_
    media

```

```
class tardis.tardis_portal.forms.RegistrationForm(data=None, files=None,  
                                                auto_id=u'id_%s', prefix=None,  
                                                initial=None, error_class=<class  
                                                'django.forms.utils.ErrorList'>,  
                                                label_suffix=None,  
                                                empty_permitted=False,  
                                                field_order=None,  
                                                use_required_attribute=None,  
                                                renderer=None)
```

Bases: `django.forms.forms.Form`

Form for registering a new user account.

Validates that the requested username is not already in use, and requires the password to be entered twice to catch typos.

Subclasses should feel free to add any additional validation they need, but should avoid defining a `save()` method – the actual saving of collected user data is delegated to the active registration backend.

```
base_fields = {'email': <django.forms.fields.EmailField object>, 'password1': <django
```

```
clean()
```

Verify that the values entered into the two password fields match. Note that an error here will end up in `non_field_errors()` because it doesn't apply to a single field.

```
clean_username()
```

Validate that the username is alphanumeric and is not already in use.

```
declared_fields = {'email': <django.forms.fields.EmailField object>, 'password1': <d
```

```
media
```

```
save(*kwargs)
```

```
class tardis.tardis_portal.forms.RightsForm(data=None, files=None,  
                                           auto_id=u'id_%s', prefix=None,  
                                           initial=None, error_class=<class  
                                           'django.forms.utils.ErrorList'>,  
                                           label_suffix=None,  
                                           empty_permitted=False, instance=None,  
                                           use_required_attribute=None)
```

Bases: `django.forms.models.ModelForm`

Form for changing public access and licence.

```
class Meta
```

```
    fields = ('public_access', 'license')
```

```
    model
```

```
        alias of tardis.tardis_portal.models.experiment.Experiment
```

```
    widgets = {'license': <django.forms.widgets.HiddenInput object>}
```

```
base_fields = {'license': <django.forms.models.ModelChoiceField object>, 'public_acce
```

```
clean()
```

```
declared_fields = {}
```

```
media
```

```

class tardis.tardis_portal.forms.StaticField(required=True, widget=None,
                                             label=None, initial=None,
                                             help_text=u'', error_messages=None,
                                             show_hidden_initial=False, valida-
                                             tors=(), localize=False, disabled=False,
                                             label_suffix=None)

Bases: django.forms.fields.Field

clean(value)

widget
    alias of NoInput

tardis.tardis_portal.forms.createLinkedUserAuthenticationForm(authMethods)
    Create a LinkedUserAuthenticationForm and use the contents of authMethods to the list of options in the drop-
    down menu for authenticationMethod.

tardis.tardis_portal.forms.createSearchExperimentForm()

tardis.tardis_portal.forms.create_datafile_add_form(schema, parentObject, re-
                                                    quest=None)

tardis.tardis_portal.forms.create_parameterset_edit_form(parameterset, re-
                                                         quest=None)

tardis.tardis_portal.forms.getAuthMethodChoices()

tardis.tardis_portal.forms.save_datafile_add_form(schema, parentObject, request)

tardis.tardis_portal.forms.save_datafile_edit_form(parameterset, request)

```

tardis.tardis_portal.hacks module

hacks.py For hacks which should be removed at a later stage

```

tardis.tardis_portal.hacks.oracle_dbops_hack(f)
    affects only oracle - safe for other database engines

```

tardis.tardis_portal.iiif module

```

tardis.tardis_portal.iiif.compliance_header(f)

tardis.tardis_portal.iiif.compute_etag(request, datafile_id, *args, **kwargs)

tardis.tardis_portal.iiif.download_image(request, *args, **kwargs)

tardis.tardis_portal.iiif.download_info(request, *args, **kwargs)

```

tardis.tardis_portal.logging_middleware module

```

class tardis.tardis_portal.logging_middleware.LoggingMiddleware(get_response)
    Bases: object

    process_exception(request, exception)

    process_response(request, response)

tardis.tardis_portal.logging_middleware.get_client_ip(request)

```

tardis.tardis_portal.managers module

managers.py

class tardis.tardis_portal.managers.**ExperimentManager**

Bases: *tardis.tardis_portal.managers.OracleSafeManager*

Implements a custom manager for the Experiment model which checks the authorisation rules for the requesting user first

To make this work, the request must be passed to all class functions. The username and the group memberships are then resolved via the user.userprofile.ext_groups and user objects.

The `tardis.tardis_portal.auth.AuthService` is responsible for filling the request.groups object.

all (*user*)

Returns all experiments a user - either authenticated or anonymous - is allowed to see and search

Parameters **user** (*User*) – a User instance

Returns QuerySet of Experiments

Return type QuerySet

external_users (*experiment_id*)

returns a list of groups which have external ACL rules

Parameters **experiment_id** (*int*) – the ID of the experiment to be edited

Returns list of groups with external ACLs

Return type list

get (*user*, *experiment_id*)

Returns an experiment under the consideration of the ACL rules Raises PermissionDenied if the user does not have access.

Parameters

- **user** (*User*) – a User instance
- **experiment_id** (*int*) – the ID of the experiment to be edited

Returns Experiment

Return type *Experiment*

Raises **PermissionDenied** –

group_acls_system_owned (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters **experiment_id** (*int*) – the ID of the experiment

Returns QuerySet of system-owned ACLs for experiment

Return type QuerySet

group_acls_user_owned (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters **experiment_id** (*int*) – the ID of the experiment

Returns QuerySet of ACLs

Return type QuerySet

owned (*user*)

Return all experiments which are owned by a particular user, including those shared with a group of which the user is a member.

Parameters **user** (*User*) – a User instance

Returns QuerySet of Experiments owned by user

Return type QuerySet

owned_and_shared (*user*)**owned_by_group** (*group*)

Return all experiments that are owned by a particular group

owned_by_user (*user*)

Return all experiments which are owned by a particular user id

Parameters **user** (*User*) – a User Object

Returns QuerySet of Experiments owned by user

Return type QuerySet

owned_by_user_id (*userId*)

Return all experiments which are owned by a particular user id

Parameters **userId** (*int*) – a User ID

Returns QuerySet of Experiments owned by user id

Return type QuerySet

public ()**shared** (*user*)**system_owned_groups** (*experiment_id*)

returns a list of sytem-owned groups which have ACL rules associated with this experiment

Parameters **experiment_id** (*string*) – the ID of the experiment to be edited

Returns system owned groups for experiment

Return type QuerySet

user_acls (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters **experiment_id** (*string*) – the ID of the experiment

Returns QuerySet of ACLs

Return type QuerySet

user_owned_groups (*experiment_id*)

returns a list of user owned-groups which have ACL rules associated with this experiment

Parameters **experiment_id** (*int*) – the ID of the experiment to be edited

Returns QuerySet of non system Groups

Return type QuerySet

users (*experiment_id*)

Returns a list of users who have ACL rules associated with this experiment.

Parameters **experiment_id** (*int*) – the ID of the experiment

Returns QuerySet of Users with experiment access

Return type QuerySet

class tardis.tardis_portal.managers.**OracleSafeManager**

Bases: django.db.models.manager.Manager

Implements a custom manager which automatically defers the retrieval of any TextField fields on calls to `get_queryset`. This is to avoid the known issue that ‘distinct’ calls on query_sets containing TextFields fail when Oracle is being used as the backend.

get_queryset ()

Returns a new QuerySet object. Subclasses can override this method to easily customize the behavior of the Manager.

class tardis.tardis_portal.managers.**ParameterNameManager**

Bases: django.db.models.manager.Manager

get_by_natural_key (namespace, name)

class tardis.tardis_portal.managers.**SchemaManager**

Bases: django.db.models.manager.Manager

get_by_natural_key (namespace)

tardis.tardis_portal.rfc3339 module

The function `rfc3339` formats dates according to the [RFC 3339](#). `rfc3339` tries to have as much as possible sensible defaults.

`tardis.tardis_portal.rfc3339.rfc3339` (date, utc=False, use_system_timezone=True)

Return a string formatted according to the [RFC 3339](#). If called with `utc=True`, it normalizes `date` to the UTC date. If `date` does not have any timezone information, uses the local timezone:

```
>>> date = datetime.datetime(2008, 4, 2, 20)
>>> rfc3339(date, utc=True, use_system_timezone=False)
'2008-04-02T20:00:00Z'
>>> rfc3339(date)
'2008-04-02T20:00:00...'
```

If called with `use_system_timezone=False` don’t use the local timezone and consider the offset to UTC to be zero:

```
>>> rfc3339(date, use_system_timezone=False)
'2008-04-02T20:00:00+00:00'
```

`date` must be a `datetime.datetime`, `datetime.date` or a timestamp as returned by `time.time()`:

```
>>> rfc3339(0, utc=True, use_system_timezone=False)
'1970-01-01T00:00:00Z'
>>> rfc3339(datetime.date(2008, 9, 6), use_system_timezone=False)
'2008-09-06T00:00:00+00:00'
>>> rfc3339('foo bar')
Traceback (most recent call last):
...
TypeError: expected datetime, got str instead
```

tardis.tardis_portal.search_backend module

```
class tardis.tardis_portal.search_backend.HighlightSearchBackend(connection_alias,
                                                                **connection_options)
    Bases: haystack.backends.elasticsearch_backend.ElasticsearchSearchBackend
    search(query_string, sort_by=None, start_offset=0, end_offset=None, fields="", highlight=False, facets=None, date_facets=None, query_facets=None, narrow_queries=None, spelling_query=None, limit_to_registered_models=None, result_class=None, **kwargs)
```

tardis.tardis_portal.search_query module

search_backend.py

```
class tardis.tardis_portal.search_query.FacetFixedSearchQuery(using=u'default')
    Bases: haystack.backends.elasticsearch_backend.ElasticsearchSearchQuery
    get_facet_counts()
```

tardis.tardis_portal.shortcuts module

```
class tardis.tardis_portal.shortcuts.RestfulExperimentParameterSet(schema_func,
                                                                    form_cls)
```

Bases: `object`

Helper class which enables a Backbone.sync-compatible interface to be created for a ExperimentParameterSet just by specifying a function which provides the schema and a form.

(A function for the schema is required rather than the actual schema, as to run unit tests effectively the object needs to be able to create the schema after instantiation.)

For UI consistency, it's best to make sure the schema has `hidden == true`.

schema

Use schema function to get the schema.

view_functions

```
tardis.tardis_portal.shortcuts.get_experiment_referer(request, dataset_id)
```

```
tardis.tardis_portal.shortcuts.redirect_back_with_error(request, message)
```

```
tardis.tardis_portal.shortcuts.render_error_message(request, message, status=400)
    Render a simple text error message in a generic error page. Any newlines are turned into <br>.
```

```
tardis.tardis_portal.shortcuts.render_response_index(request, *args, **kwargs)
```

```
tardis.tardis_portal.shortcuts.render_response_search(request, url, c)
```

```
tardis.tardis_portal.shortcuts.render_to_file(template, filename, context)
```

```
tardis.tardis_portal.shortcuts.return_response_error(request)
```

```
tardis.tardis_portal.shortcuts.return_response_error_message(request, redirect_path, context)
```

```
tardis.tardis_portal.shortcuts.return_response_not_found(request)
```

tardis.tardis_portal.signals module

tardis.tardis_portal.tasks module

tardis.tardis_portal.tasks.get_response(_)

tardis.tardis_portal.tasks.init_filters()
load filters and avoid circular import

tardis.tardis_portal.util module

tardis.tardis_portal.util.generate_file_checksums(sourceFile, tempFile=None,
leave_open=False)

DEPRECATED Generate checksums, etcetera for a file read from 'sourceFile'. If 'tempFile' is provided, the bytes are written to it as they are read. The result is a tuple comprising the MD5 checksum, the SHA512 checksum, the file length, and chunk containing the start of the file (for doing mimetype guessing if necessary).

tardis.tardis_portal.util.get_filesystem_safe_dataset_name(dataset)

Given a Dataset, return a filesystem safe string representing the dataset. Useful for filenames for dataset downloads, maybe URLs.

Parameters dataset (tardis.tardis_portal.models.dataset.Dataset) – A Dataset object.

Returns A filesystem safe string as a Dataset name.

Return type basestring

tardis.tardis_portal.util.get_filesystem_safe_experiment_name(experiment)

Given an Experiment, return a filesystem safe string representing the experiment. Useful for filenames for experiment downloads, maybe URLs.

Parameters experiment (tardis.tardis_portal.models.experiment.Experiment) – A Experiment object.

Returns A filesystem safe string as a Experiment name.

Return type basestring

tardis.tardis_portal.util.get_free_space(fs_dir)

Return free space on the file system holding the given directory (in bytes). This should work on Linux, BSD, Mac OSX and Windows.

tardis.tardis_portal.util.get_local_time(dt)

Ensure datetime is timezone-aware and in local time.

If the USE_TZ setting in the current dev version of Django comes in, this *should* keep providing correct behaviour.

tardis.tardis_portal.util.get_utc_time(dt)

Ensure datetime is timezone-aware and in UTC time.

If the USE_TZ setting in the current dev version of Django comes in, this *should* keep providing correct behaviour.

tardis.tardis_portal.util.render_mustache(template_name, data)

tardis.tardis_portal.util.render_public_access_badge(experiment)

tardis.tardis_portal.util.split_path(p)

tardis.tardis_portal.widgets module

```

class tardis.tardis_portal.widgets.CommaSeparatedInput (attrs=None)
    Bases: django.forms.widgets.TextInput
    media
    render (name, value, attrs=None, renderer=None)
    value_from_datadict (data, files, name)

class tardis.tardis_portal.widgets.Label (attrs=None)
    Bases: django.forms.widgets.Widget
    media
    render (name, value, attrs=None)
    tag = 'label'

class tardis.tardis_portal.widgets.Span (attrs=None)
    Bases: tardis.tardis_portal.widgets.Label
    media
    tag = 'span'

```

tardis.tardis_portal.xmlwriter module

```

class tardis.tardis_portal.xmlwriter.XMLWriter

    static write_template_to_dir (dest_dir, dest_filename, template_path, context)
        Parameters
            • dest_dir (string) – The directory to store the resulting document in
            • dest_filename (string) – The name of the file to be output
            • template_path (string) – The relative path to the Django template to be rendered
            • context (django.template.context.Context) – The Context object (dictionary of variables for template output)
        Returns The full path to the created file
        Return type string

    static write_template_to_file (prefix_dir, objectprefix, uniqueid, templatepath, context)
        Parameters
            • prefix_dir (string) – The subdirectory off of the OAI_DOCS_PATH to store the resulting document in
            • objectprefix (string) – The name prefix of the resulting file. Files are output in the format prefix-uniqueid.xml
            • uniqueid (string) – The unique ID of the file to be output
            • templatepath (string) – The relative path to the Django template to be rendered
            • context (django.template.context.Context) – The Context object (dictionary of variables for template output)

```

Returns The full path to the created file

Return type string

static write_xml_to_file (*prefix_dir*, *objectprefix*, *uniqueid*, *xmlstring*)

Parameters

- **prefix_dir** (*string*) – The subdirectory off of the OAI_DOCS_PATH to store the resulting document in
- **objectprefix** (*string*) – The name prefix of the resulting file. Files are output in the format prefix-uniqueid.xml
- **uniqueid** (*string*) – The unique ID of the file to be output
- **xmlstring** (*string*) – The relative path to the Django template to be rendered

Returns The full path to the created file

Return type string

`tardis.tardis_portal.xmlwriter.logger = <celery.utils.log.ProcessAwareLogger object>`
XML Writer

A set of static methods for writing xml files.

Module contents

importing all views files here, so that any old code will work as expected, when importing from
`tardis.tardis_portal.views`

`models/__init__.py`

tardis.urls package

Submodules

tardis.urls.accounts module

tardis.urls.ajax module

tardis.urls.api module

tardis.urls.core module

tardis.urls.datafile module

tardis.urls.dataset module

tardis.urls.display module

tardis.urls.download module

tardis.urls.experiment module

tardis.urls.facility module

tardis.urls.group module

tardis.urls.token module

Module contents

Submodules

tardis.app_config module

class `tardis.app_config.AbstractTardisAppConfig` (*app_name*, *app_module*)

Bases: `django.apps.config AppConfig`

All MyTardis app configuration classes should extend this abstract class to have their APIs and URLs automatically added to URL routing.

app_dependencies = []

`tardis.app_config.check_app_dependencies` (*app_configs*, ***kwargs*)

Checks currently installed apps for dependencies required by installed apps as defined by the `app_dependencies` attribute of the `AppConfig` object, if present.

Parameters

- **app_configs** (*AppConfig*) – a list of `app_configs` to check, or `None` for all apps to be checked
- **kwargs** (*list of args*) – unknown list of args

Returns a list of unsatisfied dependencies

Return type list of strings

`tardis.app_config.format_app_name_for_url` (*name*)

`tardis.app_config.get_tardis_apps` ()

Gets a list of tuples where the first element is the app name, and the second is the module path

Returns a list of tardis apps

Return type list of apps

`tardis.app_config.is_tardis_app` (*app_config*)

Determines whether the installed app is a MyTardis app

Parameters **app_config** (*AppConfig*) – the `AppConfig` object of an installed app

Returns True if the app is a MyTardis app, False otherwise

Return type `bool`

tardis.celery module

tardis.search_sites module

tardis.test_on_mysql_settings module

tardis.test_on_postgresql_settings module

tardis.test_settings module

`tardis.test_settings.get_all_tardis_apps()`

tardis.views module

`tardis.views.error_handler(request, **kwargs)`

Module contents

importing all views files here, so that any old code will work as expected, when importing from `tardis.tardis_portal.views`

`models/__init__.py`

11.4 Documentation for included Apps

11.4.1 Apps and Contextual Views

Introduction

In order to better represent specific data types and facilities, MyTardis allows apps to override the default views for Experiments, Datasets, DataFile metadata, and the main index and login pages. The following sections detail settings and requirements of apps to make this happen.

Datafile Views

Rationale

By default there exists an option to show the metadata of individual `DataFile`s in the default `Dataset` view. Some kinds of files allow for rich and useful visualisation and/or processing. For this purpose there exist contextual views, views that are available depending on the type of file they refer to.

User Guide

A default installation has no contextual views. To enable them a few steps are needed:

- an app needs to be installed either in `tardis/apps/`, or the app's configuration must subclass `AbstractTardisAppConfig` thereby enabling autodetection. `AbstractTardisAppConfig` replaces `AppConfig` as described in these [django docs](#).

- `DataFile`s need to be manually or automatically tagged with a schema that identifies them as viewable with a particular view. Filters are a convenient way to do this. See below for an example.
- settings need to be added to `settings.py`. A list called `DATAFILE_VIEWS` holds a tuple for each available view. The first entry of the tuple is a schema namespace and is matched against all schemas attached to the `DataFile`. If a match occurs, a link to the url given as second entry of the tuple is added to the Datafile Detail section of the default Dataset view and loaded via AJAX on demand. Example:

```
DATAFILE_VIEWS = [ ("http://example.org/schemas/datafile/my_awesome_schema",
                    "/apps/my-awesome-app/view"), ]
```

Currently, the default view is always `DataFile` metadata. This can be changed, for example, by developing a custom `Dataset` view, which is explained in the following section.

Dataset and Experiment Views

Rationale

For some specific uses the data available can be presented and/or processed in useful ways. MyTardis allows views for Experiments and Datasets to be overridden by apps on a per-schema basis, allowing custom views for specific data types. The example that this feature was built for are single-image and many-image datasets from the Australian Synchrotron. Single images can be displayed large and for a many-image dataset it is more useful to show a couple of example images taken at regular intervals not from the beginning of the set of files. These different datasets can be detected via their schema namespace and displayed differently.

User Guide

Akin to `DataFile` contextual views, `Dataset` and `Experiment` contextual views rely on matching a specific schema namespace in an attached `ParameterSet`.

Existing schemas can be used, or a special schema intended only for tagging an `Experiment` or `Dataset` for contextual view override can be attached (via an otherwise empty `ParameterSet`).

Dataset and Experiment contextual views are configured in settings by associating a schema namespace with a class-based view (or view function).

Unlike `DataFile` contextual views which inject content into the DOM via an AJAX call, these contextual views override the entire page.

Example:

```
DATASET_VIEWS = [
    ('http://example.org/schemas/dataset/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomDatasetViewSubclass'),
]

EXPERIMENT_VIEWS = [
    ('http://example.org/schemas/expt/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomExptViewSubclass'),
]
```

Custom Index View

Rationale

Specific sites or facilities often want to display a custom index page that presents recently ingested experiments in a way which is more meaningful for their particular domain or application. MyTardis support overriding the index page (/) on a per-domain or per-Site basis.

User Guide

Example:

```
INDEX_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomIndexSubclass',
    'facility.example.org': 'tardis.apps.myapp.AnotherCustomIndexSubclass'
}
```

A custom view override is defined in settings as dictionary mapping a class-based view (or view function) to a Django Site. A Site is specified by SITE_ID (an integer) or the domain name of the incoming request.

Developers creating custom contextual index views are encouraged to subclass `tardis.tardis_portal.views.pages.IndexView`.

Custom Login View

Rationale

Specific sites or facilities may want to display a custom login page that which is more meaningful to their particular domain or application. MyTardis supports overriding the login page (/login) on a per-domain or per-Site basis.

User Guide

Example:

```
LOGIN_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomLoginViewClass',
    'facility.example.org': 'tardis.apps.myapp.AnotherCustomLoginViewClass'
}
```

A custom view override is defined in settings as dictionary mapping a class-based view (or view function) to a Django Site. A Site is specified by SITE_ID (an integer) or the domain name of the incoming request.

Good practice for app developers

In order to benefit from future bug and security fixes in core MyTardis, app developers are strongly encouraged to override `IndexView`, `DatasetView` and `ExperimentView` (from `tardis.tardis_portal.pages`) when creating custom contextual views.

The default and well-tested `index.html`, `login.html`, `view_dataset.html` and `view_experiment.html` templates can be used as a basis for these custom contextual views.

New versions may change the default templates and view functions. If you copy and paste parts for your application, please check with each upgrade that you are still using up to date code.

11.4.2 OAI-PMH Producer

Using to provide RIF-CS

Minimal providers for Dublin Core and RIF-CS are included in the app.

To enable the app, include `tardis.apps.oaipmh` in `settings.INSTALLED_APPS`.

Your OAI-PMH query endpoint will be on: <http://mytardis-example.com/apps/oaipmh/>

Implementing your own providers

To allow multiple metadata formats (and types within them) the `tardis.apps.oaipmh.server.ProxyingServer` handles all requests and proxies them to the providers specified in `settings.OAIPMH_PROVIDERS`.

You should extend `tardis.apps.oaipmh.provider.base.BaseProvider` or one of the existing providers if you wish to extend the functionality in a site-specific way.

class `tardis.apps.oaipmh.provider.base.BaseProvider` (*site*)

A base provider which roughly implements the PyOAI interface for OAI-PMH servers.

Extend this if you're writing your own provider for a new type or a different metadata format.

getRecord (*metadataPrefix, identifier*)

Get a record for a metadataPrefix and identifier.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **identifier** (*string*) –
– repository-unique identifier of record

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is unknown or not supported by identifier.
- **oaipmh.error.IdDoesNotExistError** – if identifier is unknown or illegal.

Returns a header, metadata, about tuple describing the record.

identify ()

Retrieve information about the repository.

Returns an Identify object describing the repository.

listIdentifiers (*metadataPrefix, set=None, from_=None, until=None*)

Get a list of header information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return headers in set
- **from** (*datetime*) – only retrieve headers from **from_** date forward (in naive UTC)
- **until** (*datetime*) – only retrieve headers with dates up to and including until date (in naive UTC)

Raises

- **error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of headers.

listMetadataFormats (*identifier=None*)

List metadata formats supported by repository or record.

Parameters **identifier** (*string*) – identify record for which we want to know all supported metadata formats. If absent, list all metadata formats supported by repository.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record.

Returns an iterable of metadataPrefix, schema, metadataNamespace tuples (each entry in the tuple is a string).

listRecords (*metadataPrefix, set=None, from_=None, until=None*)

Get a list of header, metadata and about information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return records in set
- **from** (*datetime*) – only retrieve records from *from_* date forward (in naive UTC)
- **until** (*datetime*) – only retrieve records with dates up to and including until date (in naive UTC)

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **oaipmh.error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of header, metadata, about tuples.

listSets ()

Get a list of sets in the repository.

Raises **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of setSpec, setName tuples (strings).

writeMetadata (*element, metadata*)

Create XML elements under the given element, using the provided metadata.

Should avoid doing any model-lookups, as they should be done when creating the metadata.

Parameters

- **element** (*lxml.etree.Element*) – element to put all content under (as SubElements)
- **metadata** (*oaipmh.common.Metadata*) – metadata to turn into XML

Raises **NotImplementedError** – not implemented

class tardis.apps.oaipmh.server.**ProxyingServer** (*providers*)

getRecord (*metadataPrefix, identifier*)

Get a record for a metadataPrefix and identifier.

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if no provider returns a result, but at least one provider responds with `oaipmh.error.CannotDisseminateFormatError` (meaning the identifier exists)
- **oaipmh.error.IdDoesNotExistError** – if all providers fail with `oaipmh.error.IdDoesNotExistError`

Returns first successful provider response

Return type response

identify ()

Retrieve information about the repository.

Returns an `oaipmh.common.Identify` object describing the repository.

Return type `oaipmh.common.Identify`

listIdentifiers (*metadataPrefix, **kwargs*)

Lists identifiers from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set.Set` of headers.

Return type `set`

listMetadataFormats (***kwargs*)

List metadata formats from all providers in a single set.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record, but it does exist.

Returns a *frozenset* of `metadataPrefix, schema, metadataNamespace` tuples (each entry in the tuple is a string).

Return type `frozenset`

listRecords (*metadataPrefix, **kwargs*)

Lists records from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set.Set` of header, metadata, about tuples.

Return type `set`

listSets()

List sets.

Raises `oaipmh.error.NoSetHierarchyError` – because set hierarchies are currently not implemented

11.4.3 MyTardis Social Authentication

Usage

To enable the app, include `tardis.apps.social_auth` in `settings.INSTALLED_APPS`.

Adding backends

You will need to add authentication backends that you want to enable. To enable Google authentication add following `AUTHENTICATION_BACKENDS` to `settings.py`

```
AUTHENTICATION_BACKENDS += (
    'social_core.backends.open_id.OpenIdAuth',
    'social_core.backends.google.GoogleOpenId',
    'social_core.backends.google.GoogleOAuth2',
)
```

To enable Australian Access federation(AAF) OpenID connect Provider(OIDC) authentication add following `AUTHENTICATION_BACKENDS` to `settings.py`

```
AUTHENTICATION_BACKENDS += (
    'tardis.apps.social_auth.auth.authorisation.AAFOpenId',
)
```

Adding authentication providers

You will need add authentication providers that you want to enable.

```
AUTH_PROVIDERS += (
    ('Google', 'Google',
     'social_core.backends.google.GoogleOAuth2'),
    ('AAF', 'AAF',
     'tardis.apps.social_auth.auth.authorisation.AAFOpenId'),
)
```

Adding Exception Middleware

You may want to add exception middleware provided by `python-social-auth`. To do this add following to `settings.py`

```
MIDDLEWARE += (
    'social_django.middleware.SocialAuthExceptionMiddleware',
)
```

Adding Context Processor

You will need to add following context processor to *settings.py*

```
TEMPLATES[0]['OPTIONS']['context_processors'].extend([
'social_django.context_processors.backends',
'social_django.context_processors.login_redirect'])
```

Application setup

Once the application is enabled and installed define the following settings to enable authentication behaviour.

```
SOCIAL_AUTH_AAF_PIPELINE = (
'social_core.pipeline.social_auth.social_details',
'social_core.pipeline.social_auth.social_uid',
'social_core.pipeline.social_auth.social_user',
'social_core.pipeline.user.get_username',
'social_core.pipeline.user.create_user',
'tardis.apps.social_auth.auth.social_auth.add_authentication_method',
'tardis.apps.social_auth.auth.social_auth.approve_user_auth',
'tardis.apps.social_auth.auth.social_auth.add_user_permissions',
'social_core.pipeline.social_auth.associate_user',
'social_core.pipeline.social_auth.load_extra_data',
'social_core.pipeline.user.user_details',
)
```

```
SOCIAL_AUTH_GOOGLE_OAUTH2_PIPELINE = (
'social_core.pipeline.social_auth.social_details',
'social_core.pipeline.social_auth.social_uid',
'social_core.pipeline.social_auth.social_user',
'social_core.pipeline.user.get_username',
'social_core.pipeline.user.create_user',
'tardis.apps.social_auth.auth.social_auth.add_authentication_method',
'social_core.pipeline.social_auth.associate_user',
'social_core.pipeline.social_auth.load_extra_data',
'social_core.pipeline.user.user_details',
'tardis.apps.social_auth.auth.social_auth.send_admin_email',
)
```

Get key and secrets from the OIDC provider that you want to enable and add following settings.

```
SOCIAL_AUTH_URL_NAMESPACE_BEGIN = 'social:begin',
SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = 'Get this from Google'
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = 'Get this from Google'
SOCIAL_AUTH_AAF_KEY = 'Get this from AAF'
SOCIAL_AUTH_AAF_SECRET = 'Get this from AAF'
SOCIAL_AUTH_AAF_AUTH_URL = 'Get this from AAF'
SOCIAL_AUTH_AAF_TOKEN_URL = 'Get this from AAF'
SOCIAL_AUTH_AAF_USER_INFO_URL = 'Get this from AAF'
```

11.5 Releases

11.5.1 4.0.2

- Upgraded Django to 1.11.23
- Upgraded vulnerable dependencies of JS dev dependencies
- Fixed #1844 (remove a hard-coded LDAP attribute)

11.5.2 4.0.1

- Removed ansrc_codes tardis app which contained a potentially insecure dependency (rdflib)
- Added created_time and modified_time fields in the Instrument and Facility models
- Updated Python and Javascript dependencies which had vulnerabilities reported since the v4.0 release.
- Fixed token authentication (#1531, 615d9df)
- Fixed some Font Awesome icons (1ac549d)
- Fixed an incomplete database migration for the Dataset created_time field. This fix is included in the tardis/tardis_portal/migrations/0016_add_timestamps.py migration which also adds the created_time and modified_time fields to the Instrument and Facility models (ec238b4)
- Removed hard-coded LDAP attributes (#1664, 96a0fbf)
- Fixed issue with get_accessible_datafiles_for_user potentially returning an empty list instead of an empty QuerySet (a13cefc)
- Fixed issue with Add/Save Experiment Metadata - added a form attribute to the Save button. (fd2393a)
- In S3 storage documentation, removed reference to old fork of django-storages. (f0c62d5)
- Fixed issue where MyTardis could try to verify SHA512 sums even when COMPUTE_SHA512 was set to False (#1419, 1da1b3b)
- In S3 storage documentation, removed reference to old fork of django-storages. (f0c62d5)
- Fixed issue where MyTardis could try to verify SHA512 sums even when COMPUTE_SHA512 was set to False (#1419, 1da1b3b)
- Fixed issue where downloading a TAR of a dataset including unverified files could result in a “Truncated tar archive” error (#1425, b4fa17c)
- Fixed issue where MyTardis tried to retrieve thumbnail images for non-image files, resulting in 404 errors (e261065)
- Fixed issue where failing to set ADMINS in tardis/settings.py could cause MyTardis to attempt to send emails to bob@bobmail.com (#1613, f8ed6dd)
- Fixed issue where Facility Overview’s “Load more” button was enabled while content was still loading. (a28a253)

11.5.3 4.0

- Django 1.11
- jQuery 3.3.1

- Improved test coverage
- Continuous Integration tests run against Ubuntu 18.04 (MyTardis v3.x used 14.04)
- ChromeDriver is used for BDD (Behaviour Driven Development) tests
- Social Auth, including AAF and Google Auth via OpenID Connect
- Migrating user accounts from LDAP or localdb to OpenID Connect
- Customizable user menu
- Using `message.level_tag` instead of `message.tags` in `portal_template`, so that extra tags can be added to Django messages without interfering with the Bootstrap alert class.
- My Data page (which previously contained Owned and Shared experiments) has been split into two pages - “My Data” and “Shared” - Each page loads thumbnails asynchronously for faster initial page load time - An improved pagination widget allows for a very large number of pages.
- Index page’s thumbnails are loaded asynchronously for faster initial page load time.
- Login page can be replaced with a site-specific page
- SFTP can now be used with keys instead of passwords
- Upgraded Bootstrap from 2.0.4 to 2.3.2 (further upgrades coming soon)
- Fixed some bugs in single search
- jQuery code is being moved out of HTML templates and into JS files which can be linted (with ESLint) and tested (with QUnit).
- **Removed old broken code and unnecessary code which is duplicated in other repositories.**
 - Import via staging with jsTree
 - Uploadify
- **Updated or removed (as appropriate) some out-of-date JS dependencies bundled within the MyTardis repository**
 - Most JS dependences are installed by npm now, so we can run security checks with npm audit
- `manage.py` can now be used instead of `mytardis.py` and `mytardis.py` will soon be deprecated
- New support email setting can be used in email templates or HTML templates.
- Updating loadschemas management command for Django 1.11 and adding test for it
- Updated the dumpschemas management command for Django 1.11 and added a test for it
- **Bug fixes (GitHub Issue numbers below)** Fixed #243. Bug in `tardis_acls.change_experiment` permissions check Fixed #516 - only show “Add files” button if user has permission to upload files Fixed #636 Fixed #637 - “()” is added to “Author” line every time an experiment is edited Fixed #779 Fixed #868 Fixed #893 Fixed #988 Fixed #1083 Fixed #1185
- Added docs on X-Forwarded-Proto HTTP header for HTTPS deployments
- Added docs on configuring services in systemd or supervisor
- Removed password length restriction in linked user authentication form
- Removed `settings_changeme` - use `default_settings` instead
- Removed backslash from set of characters used to generate secret key.
- Removed `django-celery` - it is no longer necessary to run Celery via Django
- Improved forwards compatibility with Python 3, but we’re not fully Python 3 compatible yet.

- Switched to PEP 328 relative imports
- Tests no longer require the unmaintained “compare” module
- Added a default value for DATA_UPLOAD_MAX_MEMORY_SIZE (required by Django 1.10+) to default settings
- Removed some unused dependencies, e.g. PyYAML
- Removed the createmysuperuser which is no longer needed
- Removed the checkhashes management command
- Removed the diffraction image filter
- Removed the backupdb management command
- Removed the old publication form - a new publication workflow is coming soon.

11.5.4 3.9

- Added deprecation warnings for functionality which will be removed in 4.0
- Added INTERNAL_IPS to default settings for template debugging on localhost
- Disabled the old publication forms app in default settings, and ensured that MyTardis didn’t attempt to access its static content when disabled
- Removed apps code from ExperimentView’s get_context_data which assumed that each app would provide a views module with an index
- Fixed a bug where creating a group which already existed gave a 500 error
- Fixed a bug where non-ASCII characters in experiment names could break SFTP
- Made dataset thumbnails optional - disabling them can improve page load times
- Fixed a bug which had made it difficult to delete a DataFileObject without a URI from the Django shell
- Fixed a bug which made search indexing fail when there were users with non-ASCII characters in their first or last name

11.5.5 3.8.1

- Fix regression in Push To app

11.5.6 3.8

- Refactored settings
- Added pagination to My Data view
- BDD tests using behave and phantomjs
- Added download MD5 checksum buttons to Dataset View
- Add *autocaching* task that allows data from a StorageBox to be cached to another StorageBox
- Re-wrote user documentation and switched to hosting docs on RTD
- Switched to using NPM to manage JS deps.
- Facility and instrument are now visible on Experiment and dataset views - thanks @avrljk

- Added setting that allows datasets ordered by id on the Experiment page.
- Added setting to make sha512 checksums optional.

11.5.7 3.7 - 17 March 2016

- DataFile size is now a BigInteger field
- New settings for customisations, contextual view overrides (eg INDEX_VIEWS).
- A new AbstractTardisAppConfig class that all new tardis apps should subclass
- Third-party tardis app dependency checking
- Removed database index from Parameter.string_value to allow longer strings in Postgres. Migrations add a Postgres partial index for string_values shorter than 256 characters.
- Changed constraints on the instrument model; facility and instrument name are now unique together
- changed method tasks to task functions, pre-empting the removal of methods tasks in new celery versions
- RESTful API now supports ordering, e.g. &order_by=-title, for Experiments, Datasets and DataFiles.
- Allowed groups to be 'owners' of an Experiment. Enforce rule in views for web UI requiring every Experiment to have at least one user owner.
- Registration support updated for latest django-registration-redux package
- Speed-ups for dataset view page loading for datasets with large numbers of images. The carousel is now limited to a maximum of 100 preview images.
- Reorganised and updated documentation

11.5.8 3.6 - 16 March 2015

- removed legacy operations files (foreman, apache, uwsgi, etc)
- moved CI from Travis CI to Semaphore app
- removed buildout build system and setup.py dependency management
- build instructions in build.sh, using requirements.txt for dependencies now
- gunicorn instead of uwsgi
- updated Django to version 1.6.10
- removed migrations app
- renamed Dataset_File to DataFile
- DataFile have a deleted and a version flag, for upcoming support of these features.
- verifying files does not have side-effects anymore
- renamed Author_Experiment to ExperimentAuthor
- an ExperimentAuthor can now have an email and or a URL
- recoded Replica and Location as DataFileObject with associated StorageBox, based on the Django File API
- API v1 got some additions, largely or fully backwards-compatible
- a publication workflow app, guided publication of data

- download data via SFTP using a built-in SFTP server
- removed most traces of METS
- AAF authentication support
- parameters that can store a generic foreign key (link to any database object)
- new models `Instrument` and `Facility`
- basic support for SquashFS archives as `StorageBox`. Probably requires installation-specific code such as what is used at the [Australian Synchrotron](#).
- error pages are no normal-sized
- new view “Facility Overview”, for facility administrators to have overview over data.
- “MyData” includes owned and shared data
- safely allowing HTML in descriptions now. Achieved by “bleaching” of tags
- stats page faster through DB-server-side aggregation
- layout improvements
- pep8 and pylint improvements
- bug fixes

11.5.9 3.5 - 26 August 2013

- REST API
- REST API keys
- Authorisation now supports object-level permissions
- Front page overview
- Contextual views for Datafiles, Datasets and Experiments
- Backwards incompatible database changes
- Replica multi file location support
- Migration of replicas
- Streaming downloads
- Django 1.5
- REDIS option for celery queue
- auto-verify files
- provisional directory support
- Pylint testing on Travis CI
- Some error pages are now functional
- optionally upload comfortably with Filepicker.io
- Experiment view page load speedup
- Removed ancient XML ingest format.

11.5.10 3.0 - unreleased

- Twitter Bootstrap
- javascript templates
- backbone.js rendering of datasets
- UI for transferring datasets
- bpython shell
- celery queue

11.5.11 2.0 - Unreleased

- Auth/Auth redesign [Gerson, Uli, Russel]
 - Authorisation. Support for several pluggable authorisation plugins (Django internal, LDAP, VBL). The added AuthService middleware provides a mechanism to query all available auth modules to determine what group memberships a users has.
 - Alternative authorisation. Rule based experiment access control engine was implemented with the following access attributes for individual users and groups: canRead, canWrite, canDelete, isOwner. Additionally, a time stamp can be specified for each access rule.

Further information can be found at the wiki: [Authorisation Engine design](#)

- Metadata Editing [Steve, Grischa]
- New METS parser & METS exporter [Gerson]
- Dist/Buildout infrastructure [Russell]
- Through the web creation and editing of experiments [Steve, Russell]
- Through the web upload of files [Steve]
- Download protocol handler [Russel, Uli]
- Logging framework [Uli]
- Django 1.3

11.5.12 1.07 - 01/06/2010

- Publish to tardis.edu.au interface created, though not implemented, pending legal text

11.5.13 1.06 - 15/03/2010

- Parameter import interface for creation of new parameter/schema definitions
- iPhone Interface

11.5.14 1.05 - 01/03/2010

- Images as parameters supported
- Data / metadata transfer from synchrotron is now 'threaded' using asynchronous web service transfers.

11.5.15 1.0 - 01/02/2010

- MyTardis created from existin MyTardis python / django codebase
- Allows private data to be stored
- Open key/value parameter model, replacing current crystallography one
- Internal data store for data
- LDAP Login
- Pagination of files
- Creation of synchrotron-tardis from MyTardis codebase including specific code for the VBL login service and data transfer to MyTardis deployments.
- Web server changed to apache and mod_wsgi

11.5.16 0.5 - 2009

- Re-wrote federated index (python / django)
- Federated stores are now simple web server based with optional FTP access
- Runs on Jython / Tomcat

11.5.17 0.1 - 2007

- Federated index (php) running on Apache HTTP Server
- Crystallography data deposition and packaging tools for Fedora Commons (java swing desktop)
- Search Interface via web

CHAPTER 12

Indices and tables

- `genindex`
- `modindex`
- `search`

t

tardis, 238

tardis.analytics, 74

tardis.analytics.apps, 73

tardis.analytics.ga, 73

tardis.analytics.tracker, 73

tardis.app_config, 237

tardis.apps, 112

tardis.apps.deep_storage_download_mapper, 74

tardis.apps.deep_storage_download_mapper.mapper, 74

tardis.apps.deep_storage_download_mapper.urls, 74

tardis.apps.dl_mapper_df_dir_only, 75

tardis.apps.dl_mapper_df_dir_only.mapper, 74

tardis.apps.dl_mapper_df_dir_only.urls, 75

tardis.apps.equipment, 77

tardis.apps.equipment.admin, 75

tardis.apps.equipment.forms, 75

tardis.apps.equipment.migrations, 75

tardis.apps.equipment.migrations.0001_initial, 75

tardis.apps.equipment.models, 76

tardis.apps.equipment.south_migrations, 75

tardis.apps.equipment.tests, 77

tardis.apps.equipment.urls, 77

tardis.apps.equipment.views, 77

tardis.apps.filepicker, 78

tardis.apps.filepicker.filepicker_settings, 77

tardis.apps.filepicker.urls, 77

tardis.apps.filepicker.utils, 78

tardis.apps.filepicker.views, 78

tardis.apps.oaipmh, 84

tardis.apps.oaipmh.models, 83

tardis.apps.oaipmh.provider, 81

tardis.apps.oaipmh.provider.base, 78

tardis.apps.oaipmh.provider.experiment, 80

tardis.apps.oaipmh.server, 83

tardis.apps.oaipmh.tests, 82

tardis.apps.oaipmh.tests.provider, 82

tardis.apps.oaipmh.tests.provider.test_base, 81

tardis.apps.oaipmh.tests.provider.test_experiment, 81

tardis.apps.oaipmh.tests.test_oai, 82

tardis.apps.oaipmh.urls, 84

tardis.apps.oaipmh.views, 84

tardis.apps.openid_migration, 90

tardis.apps.openid_migration.apps, 86

tardis.apps.openid_migration.context_processors, 86

tardis.apps.openid_migration.default_settings, 86

tardis.apps.openid_migration.email_text, 86

tardis.apps.openid_migration.forms, 86

tardis.apps.openid_migration.migration, 86

tardis.apps.openid_migration.migrations, 85

tardis.apps.openid_migration.migrations.0001_initial, 85

tardis.apps.openid_migration.models, 87

tardis.apps.openid_migration.tasks, 89

tardis.apps.openid_migration.tests, 86

tardis.apps.openid_migration.tests.test_forms, 85

tardis.apps.openid_migration.tests.test_migration, 85

tardis.apps.openid_migration.tests.test_models, 85

tardis.apps.openid_migration.tests.test_views, 86

tardis.apps.openid_migration.urls, [89](#)
tardis.apps.openid_migration.user_menu_modifiers, [89](#)
tardis.apps.openid_migration.utils, [90](#)
tardis.apps.openid_migration.views, [90](#)
tardis.apps.push_to, [99](#)
tardis.apps.push_to.apps, [91](#)
tardis.apps.push_to.exceptions, [91](#)
tardis.apps.push_to.migrations, [91](#)
tardis.apps.push_to.migrations.0001_initial, [90](#)
tardis.apps.push_to.migrations.0002_auto_20150510_1158, [90](#)
tardis.apps.push_to.models, [91](#)
tardis.apps.push_to.oauth_tokens, [97](#)
tardis.apps.push_to.ssh_authz, [97](#)
tardis.apps.push_to.tasks, [97](#)
tardis.apps.push_to.tests, [91](#)
tardis.apps.push_to.tests.test_models, [91](#)
tardis.apps.push_to.urls, [98](#)
tardis.apps.push_to.utils, [98](#)
tardis.apps.push_to.views, [98](#)
tardis.apps.related_info, [101](#)
tardis.apps.related_info.forms, [101](#)
tardis.apps.related_info.models, [101](#)
tardis.apps.related_info.settings, [101](#)
tardis.apps.related_info.tests, [100](#)
tardis.apps.related_info.tests.test_oaipmh, [99](#)
tardis.apps.related_info.tests.tests, [99](#)
tardis.apps.related_info.urls, [101](#)
tardis.apps.related_info.views, [101](#)
tardis.apps.sftp, [111](#)
tardis.apps.sftp.admin, [103](#)
tardis.apps.sftp.api, [103](#)
tardis.apps.sftp.apps, [103](#)
tardis.apps.sftp.default_settings, [104](#)
tardis.apps.sftp.forms, [104](#)
tardis.apps.sftp.management, [102](#)
tardis.apps.sftp.management.commands, [102](#)
tardis.apps.sftp.management.commands.sftpadmin, [101](#)
tardis.apps.sftp.migrations, [102](#)
tardis.apps.sftp.migrations.0001_initial, [102](#)
tardis.apps.sftp.models, [104](#)
tardis.apps.sftp.sftp, [105](#)
tardis.apps.sftp.tests, [102](#)
tardis.apps.sftp.tests.test_sftp, [102](#)
tardis.apps.sftp.urls, [110](#)
tardis.apps.sftp.user_menu_modifiers, [110](#)
tardis.apps.sftp.views, [111](#)
tardis.apps.social_auth, [112](#)
tardis.apps.social_auth.apps, [112](#)
tardis.apps.social_auth.auth, [112](#)
tardis.apps.social_auth.auth.social_auth, [111](#)
tardis.apps.social_auth.default_settings, [112](#)
tardis.celery, [237](#)
tardis.default_settings, [116](#)
tardis.default_settings.admins, [112](#)
tardis.default_settings.analytics, [112](#)
tardis.default_settings.apps, [112](#)
tardis.default_settings.auth, [113](#)
tardis.default_settings.caches, [113](#)
tardis.default_settings.celery_settings, [113](#)
tardis.default_settings.custom_views, [113](#)
tardis.default_settings.database, [114](#)
tardis.default_settings.debug, [114](#)
tardis.default_settings.downloads, [114](#)
tardis.default_settings.email, [114](#)
tardis.default_settings.filters, [115](#)
tardis.default_settings.frontend, [115](#)
tardis.default_settings.i18n, [115](#)
tardis.default_settings.localisation, [115](#)
tardis.default_settings.logging, [115](#)
tardis.default_settings.middlewares, [115](#)
tardis.default_settings.publication, [115](#)
tardis.default_settings.search, [115](#)
tardis.default_settings.sharing, [115](#)
tardis.default_settings.site_customisations, [115](#)
tardis.default_settings.static_files, [115](#)
tardis.default_settings.storage, [115](#)
tardis.default_settings.templates, [116](#)
tardis.default_settings.uploads, [116](#)
tardis.default_settings.urls, [116](#)
tardis.search, [118](#)
tardis.search.datafile_index, [116](#)
tardis.search.forms, [116](#)
tardis.search.search_indexes, [117](#)
tardis.search.urls, [118](#)
tardis.search.utils, [118](#)
tardis.search.views, [118](#)
tardis.search_sites, [238](#)
tardis.tardis_portal, [236](#)
tardis.tardis_portal.admin, [204](#)
tardis.tardis_portal.api, [209](#)

tardis.tardis_portal.auth, 125	128
tardis.tardis_portal.auth.authentication, 119	tardis.tardis_portal.migrations.0002_auto_20150528_128
tardis.tardis_portal.auth.authorisation, 119	tardis.tardis_portal.migrations.0003_auto_20150907_128
tardis.tardis_portal.auth.authservice, 120	tardis.tardis_portal.migrations.0004_storageboxopt_129
tardis.tardis_portal.auth.decorators, 121	tardis.tardis_portal.migrations.0005_datafile_add_129
tardis.tardis_portal.auth.fix_circular, 122	tardis.tardis_portal.migrations.0006_datafile_remove_129
tardis.tardis_portal.auth.interfaces, 123	tardis.tardis_portal.migrations.0007_remove_paramet_129
tardis.tardis_portal.auth.localdb_auth, 124	tardis.tardis_portal.migrations.0008_string_value_p_129
tardis.tardis_portal.auth.token_auth, 124	tardis.tardis_portal.migrations.0009_auto_20160128_130
tardis.tardis_portal.auth.utils, 125	tardis.tardis_portal.migrations.0010_auto_20160503_130
tardis.tardis_portal.constants, 217	tardis.tardis_portal.migrations.0011_auto_20160505_130
tardis.tardis_portal.context_processors, 217	tardis.tardis_portal.migrations.0012_userauthenticat_130
tardis.tardis_portal.creativecommonshandling, 218	tardis.tardis_portal.migrations.0013_auto_20181002_130
tardis.tardis_portal.deprecations, 218	tardis.tardis_portal.migrations.0014_auto_20181002_130
tardis.tardis_portal.download, 219	tardis.tardis_portal.migrations.0015_dataset_create_131
tardis.tardis_portal.email, 219	tardis.tardis_portal.migrations.0016_add_timestamps_131
tardis.tardis_portal.errors, 220	tardis.tardis_portal.models, 176
tardis.tardis_portal.fields, 220	tardis.tardis_portal.models.access_control, 131
tardis.tardis_portal.filters, 126	tardis.tardis_portal.models.datafile, 136
tardis.tardis_portal.filters.jeolsem, 125	tardis.tardis_portal.models.dataset, 141
tardis.tardis_portal.forms, 220	tardis.tardis_portal.models.experiment, 144
tardis.tardis_portal.hacks, 229	tardis.tardis_portal.models.facility, 149
tardis.tardis_portal.iiif, 229	tardis.tardis_portal.models.hooks, 150
tardis.tardis_portal.logging_middleware, 229	tardis.tardis_portal.models.instrument, 150
tardis.tardis_portal.management, 128	tardis.tardis_portal.models.jti, 151
tardis.tardis_portal.management.commands, 128	tardis.tardis_portal.models.license, 152
tardis.tardis_portal.management.commands.add_experiment, 126	tardis.tardis_portal.models.parameters, 153
tardis.tardis_portal.management.commands.add_facility, 126	tardis.tardis_portal.models.storage, 169
tardis.tardis_portal.management.commands.add_instrument, 126	tardis.tardis_portal.models.token, 175
tardis.tardis_portal.management.commands.add_license, 127	tardis.tardis_portal.ParameterSetManager, 163
tardis.tardis_portal.management.commands.add_parameters, 127	tardis.tardis_portal.publish, 177
tardis.tardis_portal.management.commands.add_provider, 127	
tardis.tardis_portal.management.commands.run_filters, 127	
tardis.tardis_portal.managers, 230	
tardis.tardis_portal.migrations, 131	
tardis.tardis_portal.migrations.0001_initial, 128	
tardis.tardis_portal.migrations.0001_schema, 128	

176	181
tardis.tardis_portal.publish.provider.rifasprovider	tardis.tardis_portal.tests.api.test_experiment_met
176	181
tardis.tardis_portal.publish.publishservic	tardis.tardis_portal.tests.api.test_experiment_res
176	182
tardis.tardis_portal.rfc3339, 232	tardis.tardis_portal.tests.api.test_facility_resou
tardis.tardis_portal.search_backend, 233	182
tardis.tardis_portal.search_query, 233	tardis.tardis_portal.tests.api.test_group_resource,
tardis.tardis_portal.shortcuts, 233	182
tardis.tardis_portal.signals, 234	tardis.tardis_portal.tests.api.test_instrument_res
tardis.tardis_portal.storage, 177	182
tardis.tardis_portal.storage.file_system	tardis.tardis_portal.tests.api.test_location_resou
177	183
tardis.tardis_portal.tasks, 234	tardis.tardis_portal.tests.api.test_replica_resourc
tardis.tardis_portal.templatetags, 180	183
tardis.tardis_portal.templatetags.approve	tardis.tardis_portal.tests.api.test_schema_resource
177	183
tardis.tardis_portal.templatetags.basiccomp	tardis.tardis_portal.tests.api.test_serializer,
177	183
tardis.tardis_portal.templatetags.bleacht	tardis.tardis_portal.tests.auth, 184
178	tardis.tardis_portal.tests.filters, 185
tardis.tardis_portal.templatetags.capture	tardis.tardis_portal.tests.filters.test_jeolsem,
178	184
tardis.tardis_portal.templatetags.dataset	tardis.tardis_portal.tests.filters.test_middleware,
178	184
tardis.tardis_portal.templatetags.dynurl	tardis.tardis_portal.tests.ldap_ldif,
178	185
tardis.tardis_portal.templatetags.experiment	tardis.tardis_portal.tests.mock_vbl_auth,
179	185
tardis.tardis_portal.templatetags.experiment	tardis.tardis_portal.tests.mock_vbl_download,
179	185
tardis.tardis_portal.templatetags.facility	tardis.tardis_portal.tests.slapped, 185
179	tardis.tardis_portal.tests.test_authentication,
tardis.tardis_portal.templatetags.feed,	187
179	tardis.tardis_portal.tests.test_authorisation,
tardis.tardis_portal.templatetags.formfield	187,
179	tardis.tardis_portal.tests.test_authservice,
tardis.tardis_portal.templatetags.lookup	187
179	tardis.tardis_portal.tests.test_collectstatic,
tardis.tardis_portal.templatetags.pagination,	188
180	tardis.tardis_portal.tests.test_createuser,
tardis.tardis_portal.templatetags.xmldate,	188
180	tardis.tardis_portal.tests.test_download,
tardis.tardis_portal.tests, 197	188
tardis.tardis_portal.tests.api, 183	tardis.tardis_portal.tests.test_download_apikey,
tardis.tardis_portal.tests.api.test_auth,	189
180	tardis.tardis_portal.tests.test_dumpschemas,
tardis.tardis_portal.tests.api.test_datafile	189
180	tardis.tardis_portal.tests.test_data_resources,
tardis.tardis_portal.tests.api.test_datafile	189
181	tardis.tardis_portal.tests.test_facility_overview,
tardis.tardis_portal.tests.api.test_dataset	190
181	tardis.tardis_portal.tests.test_forms,
tardis.tardis_portal.tests.api.test_dataset	190
190	tardis.tardis_portal.tests.test_iiif,
tardis.tardis_portal.tests.api.test_dataset	190
190	tardis.tardis_portal.tests.test_iiif,

tardis.tardis_portal.tests.test_ldap,
191
tardis.tardis_portal.tests.test_loadschemas,
191
tardis.tardis_portal.tests.test_models,
191
tardis.tardis_portal.tests.test_parametersets,
192
tardis.tardis_portal.tests.test_publishservice,
193
tardis.tardis_portal.tests.test_rmexperiment,
193
tardis.tardis_portal.tests.test_storage,
193
tardis.tardis_portal.tests.test_tar_download,
194
tardis.tardis_portal.tests.test_tasks,
194
tardis.tardis_portal.tests.test_tokens,
194
tardis.tardis_portal.tests.test_views,
195
tardis.tardis_portal.tests.tests, 196
tardis.tardis_portal.util, 234
tardis.tardis_portal.views, 203
tardis.tardis_portal.views.ajax_actions,
197
tardis.tardis_portal.views.ajax_json,
197
tardis.tardis_portal.views.ajax_pages,
197
tardis.tardis_portal.views.authentication,
197
tardis.tardis_portal.views.authorisation,
198
tardis.tardis_portal.views.facilities,
198
tardis.tardis_portal.views.images, 199
tardis.tardis_portal.views.machine, 199
tardis.tardis_portal.views.pages, 199
tardis.tardis_portal.views.parameters,
202
tardis.tardis_portal.views.upload, 203
tardis.tardis_portal.views.utils, 203
tardis.tardis_portal.widgets, 235
tardis.tardis_portal.xmlwriter, 235
tardis.test_on_mysql_settings, 238
tardis.test_on_postgresql_settings, 238
tardis.test_settings, 238
tardis.views, 238

A

`about()` (in module `tardis.tardis_portal.views.pages`), 201
`abstract` (`tardis.apps.push_to.models.KeyPair.Meta` attribute), 93
`abstract` (`tardis.tardis_portal.models.parameters.ParameterMeta` attribute), 162
`abstract` (`tardis.tardis_portal.models.parameters.ParameterSer.Meta` attribute), 167
`AbstractExperimentProvider` (class in `tardis.apps.oaipmh.provider.experiment`), 80
`AbstractExperimentProviderTC` (class in `tardis.apps.oaipmh.tests.provider.test_experiment`), 81
`AbstractTardisAppConfig` (class in `tardis.app_config`), 237
`accessible_keys` (`tardis.tardis_portal.api.StorageBoxOptionResource` attribute), 216
`acl_id` (`tardis.apps.openid_migration.models.OpenidACLMigration` attribute), 87
`acl_id_id` (`tardis.apps.openid_migration.models.OpenidACLMigration` attribute), 87
`acl_migration()` (in module `tardis.apps.openid_migration.migration`), 86
`ACLAuthorization` (class in `tardis.tardis_portal.api`), 209
`ACLAuthorizationTest` (class in `tardis.tardis_portal.tests.api.test_auth`), 180
`ACLAwareBackend` (class in `tardis.tardis_portal.auth.authorisation`), 119
`aclOwnershipType` (`tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.ObjectACL` attribute), 222
`aclOwnershipType` (`tardis.tardis_portal.models.access_control.ObjectACL` attribute), 132
`add_arguments()` (`tardis.apps.sftp.management.commands.sftpd.Command` method), 101
`add_arguments()` (`tardis.tardis_portal.management.commands.createuser.Command` method), 126
`add_arguments()` (`tardis.tardis_portal.management.commands.dumps.Command` method), 126
`add_arguments()` (`tardis.tardis_portal.management.commands.loadsch.Command` method), 127
`add_arguments()` (`tardis.tardis_portal.management.commands.rmexpe.Command` method), 127
`add_arguments()` (`tardis.tardis_portal.management.commands.runfilt.Command` method), 127
`add_auth_method()` (in module `tardis.tardis_portal.auth.authentication`), 119
`add_authentication_method()` (in module `tardis.apps.social_auth.auth.social_auth`), 111
`add_child()` (`tardis.apps.sftp.sftp.DynamicTree` method), 105
`add_datafile_par()` (in module `tardis.tardis_portal.views.parameters`), 202
`add_dataset()` (in module `tardis.tardis_portal.views.pages`), 201
`add_dataset_par()` (in module `tardis.tardis_portal.views.parameters`), 202
`add_experiment_par()` (in module `tardis.tardis_portal.views.parameters`), 202
`add_migrate_account_menu_item()` (in module `tardis.apps.openid_migration.user_menu_modifiers`), 89
`add_migration_permission()` (in module `tardis.apps.social_auth.auth.social_auth`), 111
`add_par()` (in module `tardis.tardis_portal.views.parameters`), 202
`add_path()` (`tardis.apps.sftp.sftp.DynamicTree` method), 105
`add_path_elems()` (`tardis.apps.sftp.sftp.DynamicTree` method), 105
`add_ssh_keys_menu_item()` (in module `tardis.apps.sftp.user_menu_modifiers`), 110
`add_user_permissions()` (in module `tardis.apps.social_auth.auth.social_auth`), 111

added (*tardis.apps.sftp.models.SFTPPublicKey* attribute), 105

AddGroupPermissionsForm (class in *tardis.tardis_portal.forms*), 220

AddUserPermissionsForm (class in *tardis.tardis_portal.forms*), 220

administrator (*tardis.apps.push_to.models.RemoteHost* attribute), 95

administrator_id (*tardis.apps.push_to.models.RemoteHost* attribute), 96

ADMINS (in module *tardis.default_settings.admins*), 112

all() (*tardis.tardis_portal.managers.ExperimentManager* method), 230

allow_for_all (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94

allow_reuse_address (*tardis.apps.sftp.sftp.MyTSFTPTCPServer* attribute), 107

allowed_groups (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94

ALLOWED_HOSTS, 45

ALLOWED_HOSTS (in module *tardis.default_settings.debug*), 114

allowed_methods (*tardis.tardis_portal.api.UserResource.Meta* attribute), 216

allowed_remote_hosts (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94

allowed_users (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94

allows_distribution (*tardis.tardis_portal.models.license.License* attribute), 152

always_return_data (*tardis.tardis_portal.api.DatasetResource.Meta* attribute), 211

always_return_data (*tardis.tardis_portal.api.ExperimentResource.Meta* attribute), 212

always_return_data (*tardis.tardis_portal.api.FacilityResource.Meta* attribute), 213

always_return_data (*tardis.tardis_portal.api.InstrumentResource.Meta* attribute), 213

AnalyticsConfig (class in *tardis.analytics.apps*), 73

ApiKeyDownloadTestCase (class in *tardis.tardis_portal.tests.test_download_apikey*), 189

app_dependencies (*tardis.app_config.AbstractTardisAppConfig* attribute), 237

app_label (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend* attribute), 119

app_label (*tardis.tardis_portal.models.parameters.Parameter.Meta* attribute), 148

app_label (*tardis.tardis_portal.models.parameters.ParameterSet.Meta* attribute), 167

approve_user_auth() (in module *tardis.apps.social_auth.auth.social_auth*), 111

approved (*tardis.tardis_portal.models.access_control.UserAuthentication* attribute), 134

approved (*tardis.tardis_portal.models.experiment.Experiment* attribute), 145

args (*tardis.tardis_portal.management.commands.dumpschemas.Command* attribute), 126

args (*tardis.tardis_portal.management.commands.loadschemas.Command* attribute), 127

args (*tardis.tardis_portal.management.commands.rmexperiment.Command* attribute), 127

args (*tardis.tardis_portal.management.commands.runfilters.Command* attribute), 127

args (*tardis.tardis_portal.management.commands.runfilters.Command* attribute), 127

attributes (*tardis.tardis_portal.models.storage.StorageBox* attribute), 170

auth_timeout (*tardis.apps.sftp.sftp.MyTSFTPRequestHandler* attribute), 106

authenticate() (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend* method), 120

authenticate() (*tardis.tardis_portal.auth.authservice.AuthService* method), 120

authenticate() (*tardis.tardis_portal.auth.interfaces.AuthProvider* method), 123

authenticate() (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend* method), 124

authenticate() (*tardis.tardis_portal.tests.mock_ybl_auth.MockBackend* method), 185

authenticate() (*tardis.tardis_portal.tests.test_authservice.MockAuthService* method), 188

authentication (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta* attribute), 103

authentication (*tardis.tardis_portal.api.GroupResource.Meta* attribute), 213

authentication (*tardis.tardis_portal.api.MyTardisModelResource.Meta* attribute), 214

authentication (*tardis.tardis_portal.api.ObjectACLResource.Meta* attribute), 214

authentication (*tardis.tardis_portal.api.UserResource.Meta* attribute), 216

authenticationMethod (*tardis.tardis_portal.models.access_control.UserAuthentication* attribute), 134

AuthenticationTestCase (class in *tardis.tardis_portal.tests.test_authentication*), 187

author (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 148

[authorization \(tardis.apps.sftp.api.SFTPPublicKeyAppResourceMeta attribute\), 103](#)
[authorization \(tardis.tardis_portal.api.GroupResourceMeta attribute\), 213](#)
[authorization \(tardis.tardis_portal.api.MyTardisModelResourceMeta attribute\), 214](#)
[authorization \(tardis.tardis_portal.api.ObjectACLResourceMeta attribute\), 214](#)
[authorization \(tardis.tardis_portal.api.UserResourceMeta attribute\), 216](#)
[authorize_remote_access\(\) \(in module base_fields \(tardis.tardis_portal.api.ExperimentParameterResource attribute\), 212\)](#)
[AuthProvider \(class in base_fields \(tardis.tardis_portal.api.ExperimentParameterSetResource attribute\), 212\)](#)
[AuthService \(class in base_fields \(tardis.tardis_portal.api.ExperimentResource attribute\), 212\)](#)
[AuthServiceTestCase \(class in base_fields \(tardis.tardis_portal.api.FacilityResource attribute\), 213\)](#)
[autocache \(tardis.tardis_portal.models.storage.StorageBox attribute\), 170](#)
[AUTOGENERATE_API_KEY \(in module base_fields \(tardis.tardis_portal.api.LocationResource attribute\), 213\)](#)
[tardis.default_settings.auth\), 113](#)

B

[BackgroundTaskTestCase \(class in base_fields \(tardis.tardis_portal.api.ObjectACLResource attribute\), 214\)](#)
[base_fields \(tardis.apps.equipment.forms.EquipmentSearchForm attribute\), 75](#)
[base_fields \(tardis.apps.push_to.models.CredentialForm attribute\), 93](#)
[base_fields \(tardis.apps.related_info.forms.RelatedInfoForm attribute\), 101](#)
[base_fields \(tardis.apps.sftp.api.SFTPPublicKeyAppResource attribute\), 103](#)
[base_fields \(tardis.apps.sftp.forms.KeyAddForm attribute\), 104](#)
[base_fields \(tardis.apps.sftp.forms.KeyGenerateForm attribute\), 104](#)
[base_fields \(tardis.search.forms.GroupedSearchForm attribute\), 116](#)
[base_fields \(tardis.tardis_portal.admin.DatafileAdminForm attribute\), 205](#)
[base_fields \(tardis.tardis_portal.admin.DataFileObjectInlineForm attribute\), 204](#)
[base_fields \(tardis.tardis_portal.admin.StorageBoxAttributeInlineForm attribute\), 208](#)
[base_fields \(tardis.tardis_portal.admin.StorageBoxForm attribute\), 208](#)
[base_fields \(tardis.tardis_portal.admin.StorageBoxOptionInlineForm attribute\), 209](#)
[base_fields \(tardis.tardis_portal.api.DatafileParameterResource attribute\), 221](#)
[base_fields \(tardis.tardis_portal.api.DataFileResource attribute\), 210](#)
[base_fields \(tardis.tardis_portal.api.DatasetParameterResource attribute\), 211](#)
[base_fields \(tardis.tardis_portal.api.DatasetParameterSetResource attribute\), 211](#)
[base_fields \(tardis.tardis_portal.api.DatasetResource attribute\), 211](#)
[base_fields \(tardis.tardis_portal.api.ExperimentParameterResource attribute\), 212](#)
[base_fields \(tardis.tardis_portal.api.ExperimentParameterSetResource attribute\), 212](#)
[base_fields \(tardis.tardis_portal.api.ExperimentResource attribute\), 212](#)
[base_fields \(tardis.tardis_portal.api.FacilityResource attribute\), 213](#)
[base_fields \(tardis.tardis_portal.api.GroupResource attribute\), 213](#)
[base_fields \(tardis.tardis_portal.api.InstrumentResource attribute\), 213](#)
[base_fields \(tardis.tardis_portal.api.LocationResource attribute\), 213](#)
[base_fields \(tardis.tardis_portal.api.MyTardisModelResource attribute\), 214](#)
[base_fields \(tardis.tardis_portal.api.ObjectACLResource attribute\), 214](#)
[base_fields \(tardis.tardis_portal.api.ParameterNameResource attribute\), 215](#)
[base_fields \(tardis.tardis_portal.api.ParameterResource attribute\), 215](#)
[base_fields \(tardis.tardis_portal.api.ParameterSetResource attribute\), 215](#)
[base_fields \(tardis.tardis_portal.api.ReplicaResource attribute\), 215](#)
[base_fields \(tardis.tardis_portal.api.SchemaResource attribute\), 216](#)
[base_fields \(tardis.tardis_portal.api.StorageBoxAttributeResource attribute\), 216](#)
[base_fields \(tardis.tardis_portal.api.StorageBoxOptionResource attribute\), 216](#)
[base_fields \(tardis.tardis_portal.api.StorageBoxResource attribute\), 216](#)
[base_fields \(tardis.tardis_portal.api.UserResource attribute\), 217](#)
[base_fields \(tardis.tardis_portal.forms.AddGroupPermissionsForm attribute\), 220](#)
[base_fields \(tardis.tardis_portal.forms.AddUserPermissionsForm attribute\), 220](#)
[base_fields \(tardis.tardis_portal.forms.ChangeGroupPermissionsForm attribute\), 221](#)
[base_fields \(tardis.tardis_portal.forms.ChangeUserPermissionsForm attribute\), 223](#)

base_fields (tardis.tardis_portal.forms.CreateGroupPermissionsForm (attribute), 223	canDelete (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.CreateUserPermissionsForm (attribute), 224	canDelete (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.DatasetForm (attribute), 224	cache_files (tardis.tardis_portal.models.storage.StorageBox (attribute), 170
base_fields (tardis.tardis_portal.forms.ExperimentAuthForm (attribute), 225	CACHES (in module tardis.default_settings.caches), 113
base_fields (tardis.tardis_portal.forms.ExperimentForm (attribute), 225	can_copy (in module tardis.apps.push_to.utils), 98
base_fields (tardis.tardis_portal.forms.ImportParamsForm (attribute), 226	can_publish (tardis.tardis_portal.publish.provider.rifcsprovider.RifC (method), 176
base_fields (tardis.tardis_portal.forms.LoginForm (attribute), 226	canDelete (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.ManageAccountForm (attribute), 226	canonicalize (tardis.apps.sftp.sftp.MyTSFTPServerInterface (method), 106
base_fields (tardis.tardis_portal.forms.ManageGroupPermissionsForm (attribute), 227	canDelete (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.RawSearchForm (attribute), 227	canRead (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.RegisterExperimentForm (attribute), 227	canWrite (tardis.tardis_portal.models.access_control.ObjectACL (attribute), 133
base_fields (tardis.tardis_portal.forms.RegistrationForm (attribute), 228	capture (in module tardis.tardis_portal.templatetags.capture), 178
base_fields (tardis.tardis_portal.forms.RightsForm (attribute), 228	CaptureNode (class in module tardis.tardis_portal.templatetags.capture), 178
BaseProvider (class in module tardis.apps.oaipmh.provider.base), 78, 241	cast_string_to_integer (in module tardis.tardis_portal.migrations.0001_squashed_0011_auto_201601281258), 128
BaseProviderTestCase (class in module tardis.apps.oaipmh.tests.provider.test_base), 81	cast_string_to_integer (in module tardis.tardis_portal.migrations.0005_datafile_add_size_int_column), 129
blank_param (tardis.tardis_portal.ParameterSetManager.ParameterSetManager (attribute), 203	cert_signing_url (tardis.apps.push_to.models.OAuthSSHCertSigning (attribute), 95
BLEACH_ALLOWED_ATTRIBUTES (in module tardis.default_settings.frontend), 115	ChangeGroupPermissionsForm (class in module tardis.tardis_portal.forms), 221
BLEACH_ALLOWED_TAGS (in module tardis.default_settings.frontend), 115	ChangeUserPermissionsForm (class in module tardis.tardis_portal.forms), 221
bleach_value (in module tardis.tardis_portal.templatetags.bleach_tag), 178	ChangeUserPermissionsForm.Meta (class in module tardis.tardis_portal.forms), 221
build_template_html (in module tardis.tardis_portal.email), 219	ChangeUserPermissionsForm.Meta.ObjectACL (class in module tardis.tardis_portal.forms), 221
build_template_text (in module tardis.tardis_portal.email), 219	ChangeUserPermissionsForm.Meta.ObjectACL.DoesNotExist (class in module tardis.tardis_portal.forms), 221
BUNDLE (tardis.tardis_portal.models.storage.StorageBox (attribute), 170	ChangeUserPermissionsForm.Meta.ObjectACL.MultipleObjectsDoesNotExist (class in module tardis.tardis_portal.forms), 222
bytes_available (in module tardis.apps.push_to.utils), 98	check_app_dependencies (in module tardis.app_config), 237
C	check_auth_interactive (tardis.apps.sftp.sftp.MyTServerInterface (method), 106
CACHE (tardis.tardis_portal.models.storage.StorageBox (attribute), 170	
cache_box (tardis.tardis_portal.models.storage.StorageBox (attribute), 170	

- method*), 108
- `check_auth_interactive_response()`
(*tardis.apps.sftp.sftp.MyTServerInterface*
method), 108
- `check_auth_password()`
(*tardis.apps.sftp.sftp.MyTServerInterface*
method), 108
- `check_auth_publickey()`
(*tardis.apps.sftp.sftp.MyTServerInterface*
method), 109
- `check_channel_request()`
(*tardis.apps.sftp.sftp.MyTServerInterface*
method), 109
- `check_if_facility_manager()` (in module
tardis.tardis_portal.templatetags.facility_tags),
179
- `check_if_user_not_approved()` (in module
tardis.tardis_portal.templatetags.approved_user_tags),
177
- `check_paths()` (*tardis.tardis_portal.tests.slapd.Slapd*
class method), 186
- `child_boxes` (*tardis.tardis_portal.models.storage.StorageBox*
attribute), 170
- `CHOICES` (*tardis.tardis_portal.models.access_control.UserAuthenticati*
attribute), 134
- `choices` (*tardis.tardis_portal.models.parameters.ParameterName*
attribute), 164
- `classic_mapper()` (in module
tardis.tardis_portal.download), 219
- `clean()` (*tardis.apps.sftp.forms.KeyAddForm* *method*),
104
- `clean()` (*tardis.tardis_portal.forms.RegistrationForm*
method), 228
- `clean()` (*tardis.tardis_portal.forms.RightsForm*
method), 228
- `clean()` (*tardis.tardis_portal.forms.StaticField*
method), 229
- `clean_username()` (*tardis.tardis_portal.forms.RegistrationForm*
method), 228
- `cleanup()` (*tardis.apps.filepicker.utils.FilepickerFile*
method), 78
- `clear_children()` (*tardis.apps.sftp.sftp.DynamicTree*
method), 105
- `close()` (*tardis.analytics.tracker.IteratorTracker*
method), 73
- `close_gzip()` (*tardis.tardis_portal.download.UncachedTarStream*
method), 219
- `close_request()` (*tardis.apps.sftp.sftp.MyTSFTPTCPServer*
method), 108
- `CollectstaticTest` (class in
tardis.tardis_portal.tests.test_collectstatic),
188
- `comm` (*tardis.apps.equipment.models.Equipment* *at-*
tribute), 76
- `Command` (class in *tardis.apps.sftp.management.commands.sftpd*),
101
- `Command` (class in *tardis.tardis_portal.management.commands.createuser*),
126
- `Command` (class in *tardis.tardis_portal.management.commands.dumpschem*),
126
- `Command` (class in *tardis.tardis_portal.management.commands.loadschem*),
127
- `Command` (class in *tardis.tardis_portal.management.commands.rmexperim*),
127
- `Command` (class in *tardis.tardis_portal.management.commands.runfilters*),
127
- `CommaSeparatedInput` (class in
tardis.tardis_portal.widgets), 235
- `comparison_type` (*tardis.tardis_portal.models.parameters.ParameterN*
attribute), 164
- `compliance_header()` (in module
tardis.tardis_portal.iiif), 229
- `compress()` (*tardis.tardis_portal.download.UncachedTarStream*
method), 219
- `compress()` (*tardis.tardis_portal.fields.MultiValueCommaSeparatedField*
method), 220
- `compute_checksums()` (in module
tardis.tardis_portal.models.datafile), 141
- `compute_etag()` (in module *tardis.tardis_portal.iiif*),
229
- `compute_size()` (*tardis.tardis_portal.download.UncachedTarStream*
method), 219
- `configure()` (*tardis.tardis_portal.tests.slapd.Slapd*
method), 186
- `configure_user()` (in module
tardis.tardis_portal.auth.utils), 125
- `confirm_migration()` (in module
tardis.apps.openid_migration.migration),
87
- `CONTAINS_COMPARISON`
(*tardis.tardis_portal.models.parameters.ParameterName*
attribute), 164
- `content_object` (*tardis.tardis_portal.forms.ChangeUserPermissionsFo*
attribute), 222
- `content_object` (*tardis.tardis_portal.models.access_control.ObjectAC*
attribute), 133
- `content_type` (*tardis.tardis_portal.forms.ChangeUserPermissionsForm*
attribute), 222
- `content_type` (*tardis.tardis_portal.models.access_control.ObjectACL*
attribute), 133
- `content_type_id` (*tardis.tardis_portal.forms.ChangeUserPermissionsS*
attribute), 222
- `content_type_id` (*tardis.tardis_portal.models.access_control.ObjectA*
attribute), 133
- `ContextualViewTest` (class in
tardis.tardis_portal.tests.test_views), 195
- `control_panel()` (in module
tardis.tardis_portal.views.pages), 201

`copy_file()` (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 145
 method), 139
`copy_files()` (*tardis.tardis_portal.models.storage.StorageBox* attribute), 149
 method), 170
`copy_to_master()` (*tardis.tardis_portal.models.storage.StorageBox* attribute), 150
 method), 171
`create_datafile_add_form()` (in module *tardis.tardis_portal.forms*), 229
`create_detail()` (*tardis.apps.sftp.api.SFTPAuthorization* *tardis.tardis_portal.forms*), 223
 method), 103
`create_detail()` (*tardis.tardis_portal.api.ACLAuthorization* *module tardis.tardis_portal.forms*), 229
 method), 209
`create_experiment()` (in module *tardis.tardis_portal.views.pages*), 201
`create_group()` (in module *tardis.tardis_portal.views.authorisation*), 198
`create_list()` (*tardis.tardis_portal.api.ACLAuthorization* *method*), 209
`create_local_box()` (*tardis.tardis_portal.models.storage.StorageBox* *class method*), 171
`create_OpenidUserMigration()` (*tardis.apps.openid_migration.tests.test_models.ModelTestCase* *method*), 85
`create_parameterset_edit_form()` (in module *tardis.tardis_portal.forms*), 229
`create_response()` (*tardis.search.views.ExperimentSearchView* *method*), 118
`create_set_uri()` (*tardis.tardis_portal.models.datafile.DataFileObject* *method*), 140
`create_user()` (in module *tardis.tardis_portal.auth.utils*), 125
`create_user()` (in module *tardis.tardis_portal.views.authentication*), 197
`create_user_api_key()` (in module *tardis.tardis_portal.models.access_control*), 136
`create_user_profile()` (in module *tardis.tardis_portal.models.access_control*), 136
`created_by` (*tardis.tardis_portal.models.experiment.Experiment* attribute), 145
`created_by_id` (*tardis.tardis_portal.models.experiment.Experiment* attribute), 145
`created_time` (*tardis.tardis_portal.models.datafile.DataFile* attribute), 137
`created_time` (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 140
`created_time` (*tardis.tardis_portal.models.dataset.Dataset* attribute), 142
`created_time` (*tardis.tardis_portal.models.experiment.Experiment* attribute), 154
`created_time` (*tardis.tardis_portal.models.facility.Facility* attribute), 145
`created_time` (*tardis.tardis_portal.models.instrument.Instrument* attribute), 145
`created_time` (*tardis.tardis_portal.models.jti.JTI* attribute), 151
`CreateGroupPermissionsForm` (*class* in *tardis.tardis_portal.forms*), 223
`createLinkedUserAuthenticationForm()` (in module *tardis.tardis_portal.forms*), 229
`createSearchExperimentForm()` (in module *tardis.tardis_portal.forms*), 229
`CreateTestCase` (*class* in *tardis.apps.related_info.tests.tests*), 99
`CreateUserPermissionsForm` (*class* in *tardis.tardis_portal.forms*), 224
`CreateUserTestCase` (*class* in *tardis.tardis_portal.tests.test_createuser*), 188
`CreativeCommonsHandler` (*class* in *tardis.tardis_portal.creativecommonshandler*), 218
`ModelTestCase` (*class* in *tardis.apps.push_to.models*), 91
`Credential.DoesNotExist`, 91
`Credential.MultipleObjectsReturned`, 91
`credential_set` (*tardis.apps.push_to.models.RemoteHost* attribute), 96
`CredentialAdmin` (*class* in *tardis.apps.push_to.models*), 92
`CredentialForm` (*class* in *tardis.apps.push_to.models*), 93
`CredentialForm.Meta` (*class* in *tardis.apps.push_to.models*), 93
`cyberduck_connection_window()` (in module *tardis.apps.sftp.views*), 111

D

`data_type` (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164
`DATABASE_ENGINE` (*tardis.default_settings* attribute), 45
`DATABASE_HOST` (*tardis.default_settings* attribute), 45
`DATABASE_NAME` (*tardis.default_settings* attribute), 45
`DATABASE_PASSWORD` (*tardis.default_settings* attribute), 45
`DATABASE_PORT` (*tardis.default_settings* attribute), 45
`DATABASE_USER` (*tardis.default_settings* attribute), 45
`DataFile` (*class* in *tardis.tardis_portal.models.datafile*), 136
`datafile` (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 140
`datafile` (*tardis.tardis_portal.models.parameters.DatafileParameterSet* attribute), 154

- DATAFILE (*tardis.tardis_portal.models.parameters.Schema attribute*), 167
- DataFile.DoesNotExist, 136
- DataFile.MultipleObjectsReturned, 136
- datafile_access_required() (in module *tardis.tardis_portal.auth.decorators*), 121
- datafile_filename (*tardis.search.datafile_index.DataFileIndex attribute*), 116
- datafile_id (*tardis.tardis_portal.models.datafile.DataFileObject attribute*), 140
- datafile_id (*tardis.tardis_portal.models.parameters.DatafileParameterSet attribute*), 154
- datafile_set (*tardis.tardis_portal.models.dataset.Dataset attribute*), 142
- DatafileAdmin (class in *tardis.tardis_portal.admin*), 204
- DatafileAdminForm (class in *tardis.tardis_portal.admin*), 205
- DatafileAdminForm.Meta (class in *tardis.tardis_portal.admin*), 205
- DataFileIndex (class in *tardis.search.datafile_index*), 116
- DataFileObject (class in *tardis.tardis_portal.models.datafile*), 139
- DataFileObject.DoesNotExist, 139
- DataFileObject.MultipleObjectsReturned, 139
- DataFileObjectInline (class in *tardis.tardis_portal.admin*), 204
- DataFileObjectInlineForm (class in *tardis.tardis_portal.admin*), 204
- DataFileObjectInlineForm.Meta (class in *tardis.tardis_portal.admin*), 204
- DatafileParameter (class in *tardis.tardis_portal.models.parameters*), 153
- DatafileParameter.DoesNotExist, 153
- DatafileParameter.MultipleObjectsReturned, 153
- datafileparameter_set (*tardis.tardis_portal.models.parameters.DatafileParameterSet attribute*), 154
- datafileparameter_set (*tardis.tardis_portal.models.parameters.ParameterSet attribute*), 164
- DatafileParameterResource (class in *tardis.tardis_portal.api*), 210
- DatafileParameterResource.Meta (class in *tardis.tardis_portal.api*), 210
- DatafileParameterResourceTest (class in *tardis.tardis_portal.tests.api.test_datafile_metadata_resources*), 180
- DatafileParameterSet (class in *tardis.tardis_portal.models.parameters*), 154
- DatafileParameterSet.DoesNotExist, 154
- DatafileParameterSet.MultipleObjectsReturned, 154
- datafileparameterset_set (*tardis.tardis_portal.models.datafile.DataFile attribute*), 137
- datafileparameterset_set (*tardis.tardis_portal.models.parameters.Schema attribute*), 168
- DatafileParameterSetResource (class in *tardis.tardis_portal.api*), 210
- DatafileParameterSetResource.Meta (class in *tardis.tardis_portal.api*), 210
- DatafileParameterSetResourceTest (class in *tardis.tardis_portal.tests.api.test_datafile_metadata_resources*), 180
- datafileparametersets (class in *tardis.tardis_portal.models.storage.StorageBox attribute*), 171
- DataFileResource (class in *tardis.tardis_portal.api*), 209
- DataFileResource.Meta (class in *tardis.tardis_portal.api*), 210
- DataFileResourceTest (class in *tardis.tardis_portal.tests.api.test_datafile_resource*), 181
- Dataset (class in *tardis.tardis_portal.models.dataset*), 141
- dataset (*tardis.apps.equipment.models.Equipment attribute*), 76
- dataset (*tardis.tardis_portal.models.datafile.DataFile attribute*), 137
- dataset (*tardis.tardis_portal.models.parameters.DatasetParameterSet attribute*), 156
- DATASET (*tardis.tardis_portal.models.parameters.Schema attribute*), 167
- Dataset.DoesNotExist, 142
- Dataset.MultipleObjectsReturned, 142
- dataset_access_required() (in module *tardis.tardis_portal.auth.decorators*), 121
- dataset_aggregate_info() (in module *tardis.tardis_portal.views.facilities*), 198
- dataset_datafiles_badge() (in module *tardis.tardis_portal.templatetags.dataset_tags*), 178
- dataset_description (*tardis.search.search_indexes.DatasetIndex attribute*), 117
- dataset_download_required() (in module *tardis.tardis_portal.auth.decorators*), 121
- dataset_experiments_badge() (in module *tardis.tardis_portal.templatetags.dataset_tags*), 178

- 178
- `dataset_id` (*tardis.tardis_portal.models.datafile.DataFile* attribute), 137
- `dataset_id` (*tardis.tardis_portal.models.parameters.DatasetParameterSet* attribute), 156
- `dataset_id_stored` (*tardis.search.datafile_index.DataFileIndex* attribute), 116
- `dataset_id_stored` (*tardis.search.search_indexes.DatasetIndex* attribute), 117
- `dataset_set` (*tardis.tardis_portal.models.instrument.Instrument* attribute), 150
- `dataset_size_badge()` (in module *tardis.tardis_portal.templatetags.dataset_tags*), 178
- `dataset_tiles()` (in module *tardis.tardis_portal.templatetags.dataset_tags*), 178
- `DATASET_VIEWS` (in module *tardis.default_settings.custom_views*), 113
- `dataset_write_permissions_required()` (in module *tardis.tardis_portal.auth.decorators*), 121
- `DatasetAdmin` (class in *tardis.tardis_portal.admin*), 205
- `DatasetForm` (class in *tardis.tardis_portal.forms*), 224
- `DatasetForm.Meta` (class in *tardis.tardis_portal.forms*), 224
- `DatasetIndex` (class in *tardis.search.search_indexes*), 117
- `DatasetParameter` (class in *tardis.tardis_portal.models.parameters*), 155
- `DatasetParameter.DoesNotExist`, 155
- `DatasetParameter.MultipleObjectsReturned`, 155
- `datasetparameter_set` (*tardis.tardis_portal.models.parameters.DatasetParameterSet* attribute), 156
- `datasetparameter_set` (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164
- `DatasetParameterResource` (class in *tardis.tardis_portal.api*), 211
- `DatasetParameterResource.Meta` (class in *tardis.tardis_portal.api*), 211
- `DatasetParameterResourceTest` (class in *tardis.tardis_portal.tests.api.test_dataset_metadata_resources*), 181
- `DatasetParameterSet` (class in *tardis.tardis_portal.models.parameters*), 156
- `DatasetParameterSet.DoesNotExist`, 156
- `DatasetParameterSet.MultipleObjectsReturned`, 156
- `datasetparameterset_set` (*tardis.tardis_portal.models.parameters.Schema* attribute), 168
- `DatasetParameterSetResource` (class in *tardis.tardis_portal.api*), 211
- `DatasetParameterSetResource.Meta` (class in *tardis.tardis_portal.api*), 211
- `DatasetParameterSetResourceTest` (class in *tardis.tardis_portal.tests.api.test_dataset_metadata_resources*), 181
- `datasetparametersets` (*tardis.tardis_portal.models.storage.StorageBox* attribute), 171
- `DatasetResource` (class in *tardis.tardis_portal.api*), 211
- `DatasetResource.Meta` (class in *tardis.tardis_portal.api*), 211
- `DatasetResourceTest` (class in *tardis.tardis_portal.tests.api.test_dataset_resource*), 181
- `datasets` (*tardis.tardis_portal.models.experiment.Experiment* attribute), 145
- `DatasetView` (class in *tardis.tardis_portal.views.pages*), 199
- `DATETIME` (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164
- `datetime_to_us()` (in module *tardis.tardis_portal.views.facilities*), 198
- `datetime_value` (*tardis.tardis_portal.models.parameters.Parameter* attribute), 162
- `DBHostKeyPolicy` (class in *tardis.apps.push_to.models*), 93
- `DcExperimentProvider` (class in *tardis.apps.oaipmh.provider.experiment*), 80
- `DcExperimentProviderTestCase` (class in *tardis.apps.oaipmh.tests.provider.test_experiment*), 82
- `DEBUG`, 45
- `DEBUG` (in module *tardis.default_settings.debug*), 114
- `declared_fields` (*tardis.apps.equipment.forms.EquipmentSearchForm* attribute), 75
- `declared_fields` (*tardis.apps.push_to.models.CredentialForm* attribute), 93
- `declared_fields` (*tardis.apps.related_info.forms.RelatedInfoForm* attribute), 101
- `declared_fields` (*tardis.apps.sftp.api.SFTPPublicKeyAppResource* attribute), 103
- `declared_fields` (*tardis.apps.sftp.forms.KeyAddForm*

Index 269

dehydrate() (tardis.apps.sftp.api.SFTPPublicKeyAppResource attribute), 129
 method), 103
 dehydrate() (tardis.tardis_portal.api.ExperimentResource attribute), 129
 method), 212
 dehydrate() (tardis.tardis_portal.api.ReplicaResource attribute), 129
 method), 215
 dehydrate() (tardis.tardis_portal.api.UserResource attribute), 129
 method), 217
 delete_all_params() (tardis.tardis_portal.ParameterSetManager.ParameterSetManager attribute), 130
 method), 204
 delete_data() (tardis.tardis_portal.models.datafile.DataFileObject attribute), 130
 method), 140
 delete_detail() (tardis.apps.sftp.api.SFTPAuthorization attribute), 130
 method), 103
 delete_detail() (tardis.tardis_portal.api.ACLAuthorization attribute), 130
 method), 209
 delete_dfo() (in module tardis.tardis_portal.models.datafile), 141
 dependencies (tardis.tardis_portal.migrations.0010_auto_20160503_1411), 130
 delete_directory_content() (in module tardis.tardis_portal.tests.slapped), 186
 dependencies (tardis.tardis_portal.migrations.0011_auto_20160505_1411), 130
 delete_list() (tardis.tardis_portal.api.ACLAuthorization attribute), 130
 method), 209
 delete_params() (tardis.tardis_portal.ParameterSetManager.ParameterSetManager attribute), 130
 method), 204
 delete_permissions_required() (in module tardis.tardis_portal.auth.decorators), 121
 dependencies (tardis.tardis_portal.migrations.0012_userauthentication_20160505_1411), 130
 deleted (tardis.tardis_portal.models.datafile.DataFile attribute), 137
 dependencies (tardis.tardis_portal.migrations.0013_auto_20181002_1411), 130
 deleted_time (tardis.tardis_portal.models.datafile.DataFile attribute), 137
 dependencies (tardis.tardis_portal.migrations.0014_auto_20181002_1411), 130
 DeleteTestCase (class in tardis.apps.related_info.tests.tests), 99
 description (tardis.tardis_portal.models.dataset.Dataset attribute), 142
 dependencies (tardis.apps.equipment.migrations.0001_initial.Migration attribute), 75
 description (tardis.tardis_portal.models.experiment.Experiment attribute), 145
 dependencies (tardis.apps.openid_migration.migrations.0001_initial.Migration attribute), 85
 description (tardis.tardis_portal.models.storage.StorageBox attribute), 171
 dependencies (tardis.apps.push_to.migrations.0001_initial.Migration attribute), 90
 deserialize() (tardis.tardis_portal.api.DataFileResource method), 210
 dependencies (tardis.apps.push_to.migrations.0002_auto_20160518_1053.Migration attribute), 90
 initial.Migration attribute), 103
 dependencies (tardis.apps.sftp.migrations.0001_initial.Migration attribute), 102
 df_dir_only() (in module tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta attribute), 103
 dependencies (tardis.tardis_portal.migrations.0001_initial.Migration attribute), 128
 df_dir_only() (in module tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta attribute), 103
 dependencies (tardis.tardis_portal.migrations.0001_squashed_0014.Migration attribute), 128
 dependencies (tardis.tardis_portal.migrations.0001_initial.Migration attribute), 102
 dependencies (tardis.tardis_portal.migrations.0002_auto_20150528_1128.Migration attribute), 128
 dependencies (tardis.tardis_portal.migrations.0001_initial.Migration attribute), 102
 dependencies (tardis.tardis_portal.migrations.0003_auto_20150907_1315.Migration attribute), 128
 DjangoAuthBackend (class in tardis.tardis_portal.auth.localdb_auth), 124
 dependencies (tardis.tardis_portal.migrations.0004_storageboxoptimal.Migration attribute), 129
 DjangoGroupProvider (class in tardis.tardis_portal.auth.localdb_auth), 124
 dependencies (tardis.tardis_portal.migrations.0005_datafile_add_size_in_tardis_portal.Migration attribute), 124
 DjangoUserProvider (class in tardis.tardis_portal.auth.localdb_auth), 124

[do_file_copy\(\)](#) (in module [tardis.apps.push_to.tasks](#)), 97
[do_migration\(\)](#) (in module [tardis.apps.openid_migration.migration](#)), 87
[download_api_key\(\)](#) (in module [tardis.tardis_portal.download](#)), 219
[download_datafile\(\)](#) (in module [tardis.tardis_portal.download](#)), 219
[download_datafile\(\)](#) (in module [tardis.tardis_portal.tests.mock_vbl_download](#)), 185
[download_file\(\)](#) ([tardis.tardis_portal.api.DataFileResource](#) method), 210
[download_image\(\)](#) (in module [tardis.tardis_portal.iiif](#)), 229
[download_info\(\)](#) (in module [tardis.tardis_portal.iiif](#)), 229
[DownloadTestCase](#) (class in [tardis.tardis_portal.tests.test_download](#)), 188
[DummyStorage](#) (class in [tardis.tardis_portal.storage](#)), 177
[DumpSchemasTestCase](#) (class in [tardis.tardis_portal.tests.test_dumpschemas](#)), 189
[DynamicTree](#) (class in [tardis.apps.sftp.sftp](#)), 105
[dynurl\(\)](#) (in module [tardis.tardis_portal.templatetags.dynurl](#)), 178
[DynUrlNode](#) (class in [tardis.tardis_portal.templatetags.dynurl](#)), 178

E

[edit_auth_method\(\)](#) (in module [tardis.tardis_portal.auth.authentication](#)), 119
[edit_datafile_par\(\)](#) (in module [tardis.tardis_portal.views.parameters](#)), 202
[edit_dataset\(\)](#) (in module [tardis.tardis_portal.views.pages](#)), 201
[edit_dataset_par\(\)](#) (in module [tardis.tardis_portal.views.parameters](#)), 202
[edit_experiment_par\(\)](#) (in module [tardis.tardis_portal.views.parameters](#)), 202
[edit_parameters\(\)](#) (in module [tardis.tardis_portal.views.parameters](#)), 202
[EditParameterSetTestCase](#) (class in [tardis.tardis_portal.tests.test_parametersets](#)), 192
[effectiveDate](#) ([tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta](#) attribute), 222
[effectiveDate](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) attribute), 133
[email](#) ([tardis.tardis_portal.models.experiment.ExperimentAuthor](#) attribute), 148
[EMAIL_HOST](#) (in module [tardis.default_settings.email](#)), 114
[EMAIL_HOST_PASSWORD](#) (in module [tardis.default_settings.email](#)), 114
[EMAIL_HOST_USER](#) (in module [tardis.default_settings.email](#)), 115
[email_migration_success\(\)](#) (in module [tardis.apps.openid_migration.email_text](#)), 86
[EMAIL_PORT](#) (in module [tardis.default_settings.email](#)), 115
[EMAIL_USE_TLS](#) (in module [tardis.default_settings.email](#)), 115
[email_user\(\)](#) (in module [tardis.tardis_portal.email](#)), 219
[end_time](#) ([tardis.tardis_portal.models.experiment.Experiment](#) attribute), 145
[endpoint\(\)](#) (in module [tardis.apps.oaipmh.views](#)), 84
[EndpointTestCase](#) (class in [tardis.apps.oaipmh.tests.test_oai](#)), 82
[entityId](#) ([tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta](#) attribute), 222
[entityId](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) attribute), 133
[Equipment](#) (class in [tardis.apps.equipment.models](#)), 76
[Equipment.DoesNotExist](#), 76
[Equipment.MultipleObjectsReturned](#), 76
[equipment_set](#) ([tardis.tardis_portal.models.dataset.Dataset](#) attribute), 142
[EquipmentSearchForm](#) (class in [tardis.apps.equipment.forms](#)), 75
[EquipmentTestCase](#) (class in [tardis.apps.equipment.tests](#)), 77
[error_handler\(\)](#) (in module [tardis.views](#)), 238
[EXACT_VALUE_COMPARISON](#) ([tardis.tardis_portal.models.parameters.ParameterName](#) attribute), 164
[Experiment](#) (class in [tardis.tardis_portal.models.experiment](#)), 144
[experiment](#) ([tardis.tardis_portal.models.experiment.ExperimentAuthor](#) attribute), 148
[experiment](#) ([tardis.tardis_portal.models.parameters.ExperimentParameter](#) attribute), 158
[EXPERIMENT](#) ([tardis.tardis_portal.models.parameters.Schema](#) attribute), 167
[experiment](#) ([tardis.tardis_portal.models.token.Token](#) attribute), 175
[Experiment.DoesNotExist](#), 144
[Experiment.MultipleObjectsReturned](#), 144

`experiment_access_required()` (in module `tardis.tardis_portal.auth.decorators`), 121
`experiment_author` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_browse_item()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_created_time` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_creator` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_datafiles_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_datasets_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_description` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_download_required()` (in module `tardis.tardis_portal.auth.decorators`), 121
`experiment_end_time` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_file_count()` (in module `tardis.tardis_portal.templatetags.experimentstats`), 179
`experiment_id` (`tardis.tardis_portal.creativecommons_handler.CreativeCommonsHandler` attribute), 218
`experiment_id` (`tardis.tardis_portal.models.experiment.Experiment` attribute), 148
`experiment_id` (`tardis.tardis_portal.models.parameters.ExperimentParameter` attribute), 159
`experiment_id` (`tardis.tardis_portal.models.token.Token` attribute), 175
`experiment_id_stored` (`tardis.search.datafile_index.DataFileIndex` attribute), 116
`experiment_id_stored` (`tardis.search.search_indexes.DatasetIndex` attribute), 117
`experiment_id_stored` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_institution_name` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_last_updated_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_ownership_required()` (in module `tardis.tardis_portal.auth.decorators`), 121
`experiment_public_access_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_public_access_badge()` (in module `tardis.tardis_portal.views.ajax_pages`), 197
`experiment_set` (`tardis.tardis_portal.models.license.License` attribute), 152
`experiment_size_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 179
`experiment_start_time` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_title` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`experiment_update_time` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
`EXPERIMENT_VIEWS` (in module `tardis.default_settings.custom_views`), 113
`ExperimentAdmin` (class in `tardis.tardis_portal.admin`), 205
`ExperimentAuthor` (class in `tardis.tardis_portal.forms`), 224
`ExperimentAuthor` (class in `tardis.tardis_portal.models.experiment`), 148
`ExperimentAuthor.DoesNotExist`, 148
`ExperimentAuthor.Meta` (class in `tardis.tardis_portal.models.experiment`), 224
`ExperimentAuthor.MultipleObjectsReturned`, 148
`experimentauthor_set` (`tardis.tardis_portal.models.experiment.Experiment` attribute), 145
`ExperimentForm` (class in `tardis.tardis_portal.forms`), 225
`ExperimentForm.FullExperiment` (class in `tardis.tardis_portal.forms`), 225
`ExperimentForm.Meta` (class in `tardis.tardis_portal.forms`), 225
`ExperimentIndex` (class in `tardis.search.search_indexes`), 117
`ExperimentListsTest` (class in `tardis.tardis_portal.tests.test_views`), 195
`ExperimentManager` (class in `tardis.tardis_portal.managers`), 230
`ExperimentParameter` (class in `tardis.tardis_portal.models.parameters`), 157
`ExperimentParameter.DoesNotExist`, 157
`ExperimentParameter.MultipleObjectsReturned`, 157

157

experimentparameter_set (tardis.tardis_portal.models.parameters.ExperimentParameterSet attribute), 159

experimentparameter_set (tardis.tardis_portal.models.parameters.ParameterSetName attribute), 165

ExperimentParameterInline (class in tardis.tardis_portal.admin), 205

ExperimentParameterResource (class in tardis.tardis_portal.api), 211

ExperimentParameterResource.Meta (class in tardis.tardis_portal.api), 211

ExperimentParameterResourceTest (class in tardis.tardis_portal.tests.api.test_experiment_metadata_resources), 181

ExperimentParameterSet (class in tardis.tardis_portal.models.parameters), 158

ExperimentParameterSet.DoesNotExist, 158

ExperimentParameterSet.MultipleObjectsReturned, 158

experimentparameterset_set (tardis.tardis_portal.models.experiment.ExperimentParameterSet attribute), 145

experimentparameterset_set (tardis.tardis_portal.models.parameters.Schema attribute), 168

ExperimentParameterSetAdmin (class in tardis.tardis_portal.admin), 205

ExperimentParameterSetResource (class in tardis.tardis_portal.api), 212

ExperimentParameterSetResource.Meta (class in tardis.tardis_portal.api), 212

ExperimentParameterSetResourceTest (class in tardis.tardis_portal.tests.api.test_experiment_metadata_resources), 181

experimentparametersets (tardis.tardis_portal.models.storage.StorageBox attribute), 171

ExperimentResource (class in tardis.tardis_portal.api), 212

ExperimentResource.Meta (class in tardis.tardis_portal.api), 212

ExperimentResourceTest (class in tardis.tardis_portal.tests.api.test_experiment_resource), 182

experiments (tardis.apps.sftp.sftp.MyTSFTPServerInterface attribute), 106

experiments (tardis.tardis_portal.models.dataset.Dataset attribute), 143

ExperimentSearchView (class in tardis.search.views), 118

ExperimentTestCase (class in tardis.tardis_portal.tests.test_views), 195

ExperimentView (class in tardis.tardis_portal.views.pages), 200

expiry_date (tardis.tardis_portal.models.token.Token attribute), 175

expiryDate (tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta attribute), 222

expiryDate (tardis.tardis_portal.models.access_control.ObjectACL attribute), 133

ext_groups (tardis.tardis_portal.models.access_control.UserProfile attribute), 135

external_users () (tardis.tardis_portal.managers.ExperimentManager method), 230

extra (tardis.tardis_portal.admin.DataFileObjectInline attribute), 204

extra (tardis.tardis_portal.admin.ExperimentParameterInline attribute), 205

extra (tardis.tardis_portal.admin.InstrumentParameterInline attribute), 206

extra (tardis.tardis_portal.admin.ObjectACLInline attribute), 206

extra (tardis.tardis_portal.admin.ParameterNameInline attribute), 207

extra (tardis.tardis_portal.admin.StorageBoxAttributeInline attribute), 207

extra (tardis.tardis_portal.admin.StorageBoxOptionInline attribute), 208

extra_context () (tardis.search.views.ExperimentSearchView method), 118

ExtraTestCases (class in tardis.tardis_portal.tests.test_iif), 190

F

FacetFixedSearchQuery (class in tardis.tardis_portal.search_query), 233

facilities_managed_by () (in module tardis.tardis_portal.models.facility), 150

Facility (class in tardis.tardis_portal.models.facility), 149

facility (tardis.tardis_portal.models.instrument.Instrument attribute), 150

Facility.DoesNotExist, 149

Facility.MultipleObjectsReturned, 149

facility_id (tardis.tardis_portal.models.instrument.Instrument attribute), 151

facility_overview () (in module tardis.tardis_portal.views.pages), 201

facility_overview_data_count () (in module tardis.tardis_portal.views.facilities), 198

facility_overview_datafile_list () (in module tardis.tardis_portal.views.facilities), 199

facility_overview_dataset_detail () (in module tardis.tardis_portal.views.facilities),

- 199
- `facility_overview_experiments()` (in module `tardis.tardis_portal.views.facilities`), 199
- `facility_overview_facilities_list()` (in module `tardis.tardis_portal.views.facilities`), 199
- `FacilityAdmin` (class in `tardis.tardis_portal.admin`), 206
- `FacilityOverviewTestCase` (class in `tardis.tardis_portal.tests.test_facility_overview`), 189
- `FacilityResource` (class in `tardis.tardis_portal.api`), 212
- `FacilityResource.Meta` (class in `tardis.tardis_portal.api`), 212
- `FacilityResourceTest` (class in `tardis.tardis_portal.tests.api.test_facility_resource`), 182
- `feedback()` (in module `tardis.tardis_portal.views.utils`), 203
- `fields` (`tardis.apps.push_to.models.CredentialForm.Meta` attribute), 93
- `fields` (`tardis.apps.push_to.models.RemoteHostAdmin` attribute), 96
- `fields` (`tardis.search.datafile_index.DataFileIndex` attribute), 116
- `fields` (`tardis.search.search_indexes.DatasetIndex` attribute), 117
- `fields` (`tardis.search.search_indexes.ExperimentIndex` attribute), 117
- `fields` (`tardis.tardis_portal.admin.DatafileAdminForm.Meta` attribute), 205
- `fields` (`tardis.tardis_portal.admin.DataFileObjectInlineForm.Meta` attribute), 204
- `fields` (`tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta` attribute), 208
- `fields` (`tardis.tardis_portal.admin.StorageBoxForm.Meta` attribute), 208
- `fields` (`tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta` attribute), 209
- `fields` (`tardis.tardis_portal.api.UserResource.Meta` attribute), 217
- `fields` (`tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta` attribute), 223
- `fields` (`tardis.tardis_portal.forms.DatasetForm.Meta` attribute), 224
- `fields` (`tardis.tardis_portal.forms.ExperimentAuthor.Meta` attribute), 224
- `fields` (`tardis.tardis_portal.forms.ExperimentForm.Meta` attribute), 225
- `fields` (`tardis.tardis_portal.forms.ManageAccountForm.Meta` attribute), 226
- `fields` (`tardis.tardis_portal.forms.RightsForm.Meta` attribute), 228
- `file_object` (`tardis.tardis_portal.models.datafile.DataFile` attribute), 137
- `file_object` (`tardis.tardis_portal.models.datafile.DataFileObject` attribute), 140
- `file_objects` (`tardis.tardis_portal.models.datafile.DataFile` attribute), 137
- `file_objects` (`tardis.tardis_portal.models.storage.StorageBox` attribute), 171
- `filename` (`tardis.tardis_portal.models.datafile.DataFile` attribute), 138
- `FILENAME` (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 164
- `filepicker_url_regex` (`tardis.apps.filepicker.utils.FilepickerFile` attribute), 78
- `FilepickerFile` (class in `tardis.apps.filepicker.utils`), 78
- `Filter1` (class in `tardis.tardis_portal.tests.filters.test_middleware`), 184
- `Filter2` (class in `tardis.tardis_portal.tests.filters.test_middleware`), 184
- `filtering` (`tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta` attribute), 103
- `filtering` (`tardis.tardis_portal.api.DataFileResource.Meta` attribute), 210
- `filtering` (`tardis.tardis_portal.api.DatasetResource.Meta` attribute), 211
- `filtering` (`tardis.tardis_portal.api.ExperimentResource.Meta` attribute), 212
- `filtering` (`tardis.tardis_portal.api.FacilityResource.Meta` attribute), 213
- `filtering` (`tardis.tardis_portal.api.GroupResource.Meta` attribute), 213
- `filtering` (`tardis.tardis_portal.api.InstrumentResource.Meta` attribute), 213
- `filtering` (`tardis.tardis_portal.api.ObjectACLResource.Meta` attribute), 214
- `filtering` (`tardis.tardis_portal.api.ParameterNameResource.Meta` attribute), 214
- `filtering` (`tardis.tardis_portal.api.ReplicaResource.Meta` attribute), 215
- `filtering` (`tardis.tardis_portal.api.SchemaResource.Meta` attribute), 215
- `filtering` (`tardis.tardis_portal.api.UserResource.Meta` attribute), 217
- `FilterInitMiddleware` (class in `tardis.tardis_portal.filters`), 126
- `FilterInitTestCase` (class in `tardis.tardis_portal.tests.filters.test_middleware`), 184
- `find_available_tcp_port()` (in module `tardis.tardis_portal.tests.slapped`), 186
- `find_custom_view_override()` (`tardis.tardis_portal.views.pages.DatasetView` attribute), 186

method), 199
 find_custom_view_override() (tardis.tardis_portal.views.pages.ExperimentView method), 200
 fixtures (tardis.apps.equipment.tests.EquipmentTestCase attribute), 77
 form (tardis.apps.push_to.models.CredentialAdmin attribute), 93
 form (tardis.tardis_portal.admin.DatafileAdmin attribute), 205
 form (tardis.tardis_portal.admin.DataFileObjectInline attribute), 204
 form (tardis.tardis_portal.admin.StorageBoxAdmin attribute), 207
 form (tardis.tardis_portal.admin.StorageBoxAttributeInline attribute), 207
 form (tardis.tardis_portal.admin.StorageBoxOptionInline attribute), 208
 form_class (tardis.search.views.SingleSearchView attribute), 118
 form_valid() (tardis.search.views.SingleSearchView method), 118
 format_app_name_for_url() (in module tardis.app_config), 237
 formfield_overrides (tardis.tardis_portal.admin.ExperimentParameterInline attribute), 205
 FreeTextSearchField (class in tardis.tardis_portal.models.parameters), 159
 FreeTextSearchField.DoesNotExist, 159
 FreeTextSearchField.MultipleObjectsReturned, 160
 freetextsearchfield_set (tardis.tardis_portal.models.parameters.ParameterName attribute), 165
 FreeTextSearchFieldAdmin (class in tardis.tardis_portal.admin), 206
 freeze_time() (tardis.tardis_portal.tests.test_tokens.FrozenTime class method), 194
 FrozenTime (class in tardis.tardis_portal.tests.test_tokens), 194
 full_name (tardis.tardis_portal.models.parameters.ParameterName attribute), 165
 get() (tardis.tardis_portal.models.parameters.Parameter method), 162
 get() (tardis.tardis_portal.views.pages.DatasetView method), 200
 get() (tardis.tardis_portal.views.pages.ExperimentView method), 200
 get() (tardis.tardis_portal.views.pages.IndexView method), 201
 get_absolute_filepath() (tardis.tardis_portal.models.datafile.DataFile method), 138
 get_absolute_url() (tardis.tardis_portal.models.dataset.Dataset method), 143
 get_absolute_url() (tardis.tardis_portal.models.experiment.Experiment method), 146
 get_accessible_datafiles_for_user() (in module tardis.tardis_portal.auth.decorators), 121
 get_accessible_experiments() (in module tardis.tardis_portal.auth.decorators), 121
 get_accessible_experiments_for_dataset() (in module tardis.tardis_portal.auth.decorators), 121
 get_accessible_hosts() (in module tardis.apps.push_to.views), 98
 get_aclOwnershipType_display() (tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.O method), 222
 get_aclOwnershipType_display() (tardis.tardis_portal.models.access_control.ObjectACL method), 133
 get_address() (tardis.tardis_portal.tests.slapped.Slapped method), 186
 get_all_storage_boxes_used() (tardis.tardis_portal.models.dataset.Dataset method), 143
 get_installed_tardis_apps() (in module tardis.test_settings), 238
 get_allowed_auths() (tardis.apps.sftp.sftp.MyTServerInterface method), 110
 get_api_key() (in module tardis.apps.openid_migration.migration), 87
 get_apikey_credentials() (tardis.tardis_portal.tests.api.MyTardisResourceTestCase method), 183
 get_as_temporary_file() (tardis.tardis_portal.models.datafile.DataFile method), 138
 get_auth_method() (in module tardis.apps.social_auth.auth.social_auth),

G

generate_file_checksums() (in module tardis.tardis_portal.util), 234
 generate_keypair_credential() (tardis.apps.push_to.models.Credential static method), 92
 get() (tardis.tardis_portal.managers.ExperimentManager method), 230

111

get_available_signing_services() (tardis.apps.push_to.models.OAuthSSHCertSigningService static method), 95

get_beamline() (tardis.tardis_portal.tests.test_publishservice.MockRiftCsProvider method), 193

get_by_natural_key() (tardis.tardis_portal.managers.ParameterNameManager method), 232

get_by_natural_key() (tardis.tardis_portal.managers.SchemaManager method), 232

get_client_for_host() (tardis.apps.push_to.models.Credential method), 92

get_client_ip() (in module tardis.tardis_portal.logging_middleware), 229

get_comparison_type_display() (tardis.tardis_portal.models.parameters.ParameterName method), 165

get_context() (tardis.tardis_portal.publish.publishservice.PublishService method), 176

get_context_data() (tardis.tardis_portal.views.pages.DatasetView method), 200

get_context_data() (tardis.tardis_portal.views.pages.ExperimentView method), 200

get_context_data() (tardis.tardis_portal.views.pages.IndexView method), 201

get_create_token_url() (tardis.tardis_portal.models.experiment.Experiment method), 146

get_credential() (in module tardis.apps.push_to.views), 98

get_credentials() (tardis.tardis_portal.tests.api.MyTardisResourceTestCase method), 183

get_ct() (tardis.tardis_portal.models.experiment.Experiment method), 146

get_data_type_display() (tardis.tardis_portal.models.parameters.ParameterName method), 165

get_datafiles() (tardis.tardis_portal.api.DatasetResource method), 211

get_datafiles() (tardis.tardis_portal.models.dataset.Dataset method), 143

get_datafiles() (tardis.tardis_portal.models.experiment.Experiment method), 146

get_dataset_info() (in module tardis.tardis_portal.views.utils), 203

get_default_push_location() (in module tardis.apps.push_to.utils), 98

get_default_storage() (tardis.tardis_portal.models.storage.StorageBox class method), 171

get_experiment_box() (tardis.tardis_portal.models.datafile.DataFile method), 138

get_experiment_suffix() (tardis.tardis_portal.tests.slapped.Slapped method), 186

get_download_organizations() (in module tardis.tardis_portal.download), 219

get_download_url() (tardis.tardis_portal.models.datafile.DataFile method), 138

get_download_urls() (tardis.tardis_portal.models.dataset.Dataset method), 143

get_download_urls() (tardis.tardis_portal.models.experiment.Experiment method), 146

get_edit_url() (tardis.tardis_portal.models.dataset.Dataset method), 143

get_edit_url() (tardis.tardis_portal.models.experiment.Experiment method), 146

get_effective_query() (tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.O class method), 222

get_effective_query() (tardis.tardis_portal.models.access_control.ObjectACL class method), 133

get_experiment_referer() (in module tardis.tardis_portal.shortcuts), 233

get_facet_counts() (tardis.tardis_portal.search_query.FacetFixedSearchQuery method), 233

get_file() (tardis.apps.filepicker.utils.FilepickerFile method), 78

get_file() (tardis.tardis_portal.models.datafile.DataFile method), 138

get_file_contents() (tardis.tardis_portal.filters.jeolsem.JEOLSEMFiler method), 125

get_filesystem_safe_dataset_name() (in module tardis.tardis_portal.util), 234

get_filesystem_safe_experiment_name() (in module tardis.tardis_portal.util), 234

get_first_experiment() (tardis.tardis_portal.models.dataset.Dataset method), 143

get_experiment_namespace() (in module tardis.tardis_portal.util), 234

get_full_path() (tardis.tardis_portal.models.datafile.DataFileObject method), 140

get_git_version() (in module

tardis.default_settings), 116
 get_groups() (*tardis.tardis_portal.models.experiment.Experiment* method), 175
 get_id() (*tardis.apps.oaipmh.provider.experiment.AbstractExperiment* static method), 80
 get_identifier() (*tardis.tardis_portal.api.MyTardisAuthentication* method), 214
 get_image_data() (*tardis.tardis_portal.models.datafile.DataFile* method), 146
 get_images() (*tardis.tardis_portal.models.dataset.Dataset* method), 143
 get_images() (*tardis.tardis_portal.models.experiment.Experiment* method), 146
 get_initialised_storage_instance() (*tardis.tardis_portal.models.storage.StorageBox* method), 172
 get_item() (in module *tardis.tardis_portal.templatetags.lookupfilters*), 179
 get_leaf() (*tardis.apps.sftp.sftp.DynamicTree* method), 105
 get_license_uri() (*tardis.tardis_portal.tests.test_publishservice.MockRefCsProvider* method), 193
 get_local_time() (in module *tardis.tardis_portal.util*), 234
 get_matching_auth_provider() (in module *tardis.apps.openid_migration.migration*), 87
 get_matching_authmethod() (in module *tardis.tardis_portal.templatetags.approved_user_tags*), 177
 get_metadata() (*tardis.tardis_portal.filters.jeolsem.JEOLSEMFilters* method), 125
 get_mimetype() (*tardis.tardis_portal.models.datafile.DataFile* method), 138
 get_model() (*tardis.search.datafile_index.DataFileIndex* method), 116
 get_model() (*tardis.search.search_indexes.DatasetIndex* method), 117
 get_model() (*tardis.search.search_indexes.ExperimentIndex* method), 117
 get_next_by_added() (*tardis.apps.sftp.models.SFTPPublicKey* method), 105
 get_next_by_created_time() (*tardis.tardis_portal.models.datafile.DataFileObject* method), 140
 get_next_by_created_time() (*tardis.tardis_portal.models.experiment.Experiment* method), 146
 get_next_by_created_time() (*tardis.tardis_portal.models.jti.JTI* method), 151
 get_next_by_expiry_date() (*tardis.tardis_portal.models.token.Token* method), 175
 get_next_by_migration_timestamp() (*tardis.apps.openid_migration.models.OpenidUserMigration* method), 88
 get_next_by_update_time() (*tardis.tardis_portal.models.experiment.Experiment* method), 146
 get_none_option_license() (*tardis.tardis_portal.models.license.License* class method), 152
 get_auth_service() (*tardis.apps.push_to.models.OAuthSSHCertSigningService* static method), 95
 get_object_size() (in module *tardis.apps.push_to.utils*), 98
 get_options_as_dict() (*tardis.tardis_portal.models.storage.StorageBox* method), 172
 get_or_create_cc_parameterset() (*tardis.tardis_portal.creativecommonshandler.CreativeCommonshandler* method), 218
 get_or_create_directory() (*tardis.tardis_portal.models.experiment.Experiment* method), 146
 get_or_create_user() (in module *tardis.tardis_portal.auth.utils*), 125
 get_or_create_user() (*tardis.tardis_portal.auth.authservice.AuthService* method), 121
 get_owned_experiments() (in module *tardis.tardis_portal.auth.decorators*), 121
 get_owners() (*tardis.tardis_portal.models.experiment.Experiment* method), 146
 get_param() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 204
 get_params() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 204
 get_path() (*tardis.tardis_portal.models.dataset.Dataset* method), 143
 get_perm_bool() (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend* method), 120
 get_preferred_dfo() (*tardis.tardis_portal.models.datafile.DataFile* method), 138
 get_previous_by_added() (*tardis.apps.sftp.models.SFTPPublicKey* method), 105
 get_previous_by_created_time() (*tardis.tardis_portal.models.datafile.DataFileObject* method), 140
 get_previous_by_created_time() (*tardis.tardis_portal.models.experiment.Experiment* method), 146

[get_previous_by_created_time\(\)](#) ([tardis.tardis_portal.models.jti.JTI](#) method), 152
[get_previous_by_expiry_date\(\)](#) ([tardis.tardis_portal.models.token.Token](#) method), 175
[get_previous_by_migration_timestamp\(\)](#) ([tardis.apps.openid_migration.models.OpenidUserMigration](#) method), 88
[get_previous_by_update_time\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 146
[get_public_access_display\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 146
[get_push_url_for_host\(\)](#) (in module [tardis.apps.push_to.views](#)), 98
[get_queryset\(\)](#) ([tardis.tardis_portal.managers.OracleSchemaManager](#) method), 232
[get_receiving_storage_box\(\)](#) ([tardis.tardis_portal.models.datafile.DataFile](#) method), 138
[get_related_object\(\)](#) ([tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.ObjectACL](#) method), 222
[get_related_object\(\)](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) method), 133
[get_related_object_group\(\)](#) ([tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.ObjectACL](#) method), 223
[get_related_object_group\(\)](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) method), 133
[get_response\(\)](#) (in module [tardis.tardis_portal.tasks](#)), 234
[get_response\(\)](#) ([tardis.tardis_portal.download.UncachedTarStream](#) method), 219
[get_rifcs_context\(\)](#) ([tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider](#) method), 176
[get_rifcs_context\(\)](#) ([tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider](#) method), 193
[get_rifcs_id\(\)](#) ([tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider](#) static method), 80
[get_root_dn\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapped](#) method), 186
[get_root_password\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapped](#) method), 186
[get_schema\(\)](#) ([tardis.tardis_portal.ParameterSetManager.ParameterSetManager](#) method), 204
[get_schema_type_name\(\)](#) ([tardis.tardis_portal.models.parameters.Schema](#) class method), 168
[get_server\(\)](#) (in module [tardis.apps.oaipmh.server](#)), 84
[get_session_expiry\(\)](#) ([tardis.tardis_portal.models.token.Token](#) method), 175
[get_signed_experiments\(\)](#) (in module [tardis.tardis_portal.auth.decorators](#)), 121
[get_signing_services\(\)](#) (in module [tardis.apps.push_to.views](#)), 98
[get_size\(\)](#) ([tardis.tardis_portal.models.datafile.DataFile](#) method), 138
[get_size\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 143
[get_size\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 146
[get_sha1_and_sha512sum\(\)](#) (in module [tardis.tardis_portal.tests.test_download](#)), 189
[get_suitable_credential\(\)](#) ([tardis.apps.push_to.models.Credential](#) static method), 92
[get_user_permissions\(\)](#) ([tardis.tardis_portal.models.license.License](#) class method), 152
[get_tardis_apps\(\)](#) (in module [tardis.app_config](#)), 237
[get_template\(\)](#) ([tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider](#) method), 176
[get_template\(\)](#) ([tardis.tardis_portal.publish.publishservice.PublishService](#) method), 176
[get_template\(\)](#) ([tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider](#) method), 193
[get_thumbnail_url\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 143
[get_tmpdir\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapped](#) method), 186
[get_tokens\(\)](#) (in module [tardis.apps.push_to.oauth_tokens](#)), 97
[get_token_data\(\)](#) (in module [tardis.apps.push_to.oauth_tokens](#)), 97
[get_type_display\(\)](#) ([tardis.tardis_portal.models.parameters.Schema](#) method), 168
[get_url\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapped](#) method), 186
[get_user\(\)](#) ([tardis.tardis_portal.auth.interfaces.AuthProvider](#) method), 123
[get_user\(\)](#) ([tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend](#) method), 185
[get_user\(\)](#) ([tardis.tardis_portal.tests.mock_vbl_auth.MockBackend](#) method), 185

[get_utc_time\(\)](#) (in module `tardis.tardis_portal.util`), [234](#)
[get_value_type_display\(\)](#) (`tardis.tardis_portal.models.storage.StorageBoxOptions` method), [174](#)
[get_view_url\(\)](#) (`tardis.tardis_portal.models.datafile.DataFile` method), [138](#)
[getAuthMethodChoices\(\)](#) (in module `tardis.tardis_portal.forms`), [229](#)
[getAuthMethodDescription\(\)](#) (`tardis.tardis_portal.models.access_control.UserAuthentication` method), [134](#)
[getGroupId\(\)](#) (`tardis.tardis_portal.auth.interfaces.GroupProvider` method), [123](#)
[getGroupId\(\)](#) (`tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider` method), [124](#)
[getGroupId\(\)](#) (`tardis.tardis_portal.tests.test_authservice.MockGroupProvider` method), [188](#)
[getGroups\(\)](#) (in module `tardis.tardis_portal.auth.fix_circular`), [122](#)
[getGroups\(\)](#) (`tardis.tardis_portal.auth.authservice.AuthService` method), [120](#)
[getGroups\(\)](#) (`tardis.tardis_portal.auth.interfaces.GroupProvider` method), [123](#)
[getGroups\(\)](#) (`tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider` method), [124](#)
[getGroups\(\)](#) (`tardis.tardis_portal.auth.token_auth.TokenGroupProvider` method), [125](#)
[getGroups\(\)](#) (`tardis.tardis_portal.tests.test_authservice.MockGroupProvider` method), [188](#)
[getGroupsForEntity\(\)](#) (`tardis.tardis_portal.auth.authservice.AuthService` method), [120](#)
[getGroupsForEntity\(\)](#) (`tardis.tardis_portal.auth.interfaces.GroupProvider` method), [123](#)
[getGroupsForEntity\(\)](#) (`tardis.tardis_portal.tests.test_authservice.MockGroupProvider` method), [188](#)
[getNamespaces\(\)](#) (`tardis.tardis_portal.models.parameters.Schema` class method), [168](#)
[getParameterSets\(\)](#) (`tardis.tardis_portal.models.datafile.DataFile` method), [138](#)
[getParameterSets\(\)](#) (`tardis.tardis_portal.models.dataset.Dataset` method), [143](#)
[getParameterSets\(\)](#) (`tardis.tardis_portal.models.experiment.Experiment` method), [146](#)
[getParameterSets\(\)](#) (`tardis.tardis_portal.models.instrument.Instrument` method), [151](#)
[getRecord\(\)](#) (`tardis.apps.oaipmh.provider.base.BaseProvider` method), [78](#), [241](#)
[getRecord\(\)](#) (`tardis.apps.oaipmh.provider.experiment.AbstractExperiment` method), [80](#)
[getRecord\(\)](#) (`tardis.apps.oaipmh.server.ProxyingServer` method), [83](#), [243](#)
[getSchemaTypes\(\)](#) (`tardis.tardis_portal.models.parameters.Schema` class method), [168](#)
[getSupportedAuthMethods\(\)](#) (in module `tardis.apps.openid_migration.migration`), [87](#)
[getTestAuthUser\(\)](#) (class in `tardis.apps.related_info.tests.tests`), [100](#)
[getTestFilter1\(\)](#) (`tardis.tardis_portal.tests.filters.test_middleware.Filter1` class method), [184](#)
[getTestFilter2\(\)](#) (`tardis.tardis_portal.tests.filters.test_middleware.Filter2` class method), [184](#)
[getTestMockGroupProvider\(\)](#) (`tardis.tardis_portal.models.parameters.ParameterName` method), [165](#)
[getUser\(\)](#) (`tardis.tardis_portal.auth.authservice.AuthService` method), [120](#)
[getUserAuthentications\(\)](#) (`tardis.tardis_portal.models.access_control.UserProfile` method), [135](#)
[getUserGroupProvider\(\)](#) (`tardis.tardis_portal.auth.interfaces.UserProvider` method), [123](#)
[getUserProvider\(\)](#) (`tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider` method), [124](#)
[getUserProfileByEmail\(\)](#) (`tardis.tardis_portal.auth.authservice.AuthService` method), [121](#)
[getUsernameByEmail\(\)](#) (`tardis.tardis_portal.auth.interfaces.AuthProvider` method), [123](#)
[getUsernameByEmail\(\)](#) (`tardis.tardis_portal.auth.interfaces.UserProvider` method), [123](#)
[getContexts\(\)](#) (in module `tardis.tardis_portal.context_processors`), [217](#)
[google_analytics\(\)](#) (in module `tardis.tardis_portal.context_processors`), [217](#)
[GREATER_THAN_COMPARISON](#) (`tardis.tardis_portal.models.parameters.ParameterName` attribute), [164](#)
[GREATER_THAN_EQUAL_COMPARISON](#) (`tardis.tardis_portal.models.parameters.ParameterName` attribute), [164](#)
[group](#) (`tardis.tardis_portal.models.access_control.GroupAdmin` attribute), [131](#)
[group_acls_system_owned\(\)](#) (`tardis.tardis_portal.managers.ExperimentManager` method), [230](#)

`group_acls_user_owned()` (in module `tardis.tardis_portal.managers.ExperimentManager` method), 230
`group_id()` (in module `tardis.tardis_portal.models.access_control.GroupAdmin` attribute), 131
`group_ownership_required()` (in module `tardis.tardis_portal.auth.decorators`), 121
`GroupAdmin` (class in `tardis.tardis_portal.models.access_control`), 131
`GroupAdmin.DoesNotExist`, 131
`GroupAdmin.MultipleObjectsReturned`, 131
`GroupedSearchForm` (class in `tardis.search.forms`), 116
`GroupProvider` (class in `tardis.tardis_portal.auth.interfaces`), 123
`GroupResource` (class in `tardis.tardis_portal.api`), 213
`GroupResource.Meta` (class in `tardis.tardis_portal.api`), 213
`GroupResourceTest` (class in `tardis.tardis_portal.tests.api.test_group_resource`), 182
`gt()` (in module `tardis.tardis_portal.templatetags.basiccomparisonfilters`), 177
`gte()` (in module `tardis.tardis_portal.templatetags.basiccomparisonfilters`), 177
H
`handle()` (in module `tardis.tardis_portal.models.experiment.Experiment` attribute), 146
`handle()` (in module `tardis.apps.sftp.management.commands.sftpd.Command` attribute), 101
`handle()` (in module `tardis.apps.sftp.sftp.MyTSFTPRequestHandler` method), 106
`handle()` (in module `tardis.tardis_portal.management.commands.createuser.Command` attribute), 127
`handle()` (in module `tardis.tardis_portal.management.commands.createuser.Command` method), 126
`handle()` (in module `tardis.tardis_portal.management.commands.dumpschemas.Command` attribute), 127
`handle()` (in module `tardis.tardis_portal.management.commands.dumpschemas.Command` method), 126
`handle()` (in module `tardis.tardis_portal.management.commands.loadschemas.Command` attribute), 127
`handle()` (in module `tardis.tardis_portal.management.commands.loadschemas.Command` method), 127
`handle()` (in module `tardis.tardis_portal.management.commands.rmexperiment.Command` attribute), 127
`handle()` (in module `tardis.tardis_portal.management.commands.rmexperiment.Command` method), 127
`handle()` (in module `tardis.tardis_portal.management.commands.runfilters.Command` attribute), 127
`handle()` (in module `tardis.tardis_portal.management.commands.runfilters.Command` method), 127
`handle_timeout()` (in module `tardis.apps.sftp.sftp.MyTSFTPRequestHandler` method), 106
`has_cc_license()` (in module `tardis.tardis_portal.creativecommons.handle.creativecommonsutils` method), 218
`has_datafile_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_datafile_download_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_dataset_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_dataset_download_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_dataset_ownership()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_dataset_write()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_delete_permissions()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_experiment_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_experiment_download_access()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_experiment_ownership()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_experiment_write()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_image()` (in module `tardis.tardis_portal.models.datafile.DataFile` method), 138
`has_perm()` (in module `tardis.tardis_portal.auth.authorisation.ACLAwareBackend` method), 120
`has_read_or_owner_ACL()` (in module `tardis.tardis_portal.auth.decorators`), 122
`has_write_permissions()` (in module `tardis.tardis_portal.auth.decorators`), 122
`hasReader()` (in module `tardis.apps.oaipmh.server.ProxyingMetadataRegistry` method), 83
`hasWriter()` (in module `tardis.apps.oaipmh.server.ProxyingMetadataRegistry` method), 83
`help()` (in module `tardis.tardis_portal.management.commands.createuser.Command` attribute), 126
`help()` (in module `tardis.tardis_portal.management.commands.dumpschemas.Command` attribute), 126
`help()` (in module `tardis.tardis_portal.management.commands.loadschemas.Command` attribute), 127
`help()` (in module `tardis.tardis_portal.management.commands.rmexperiment.Command` attribute), 127
`help()` (in module `tardis.tardis_portal.management.commands.runfilters.Command` attribute), 127
`hidden()` (in module `tardis.tardis_portal.models.parameters.Schema` attribute), 188
`HighlightSearchBackend` (class in `tardis.tardis_portal.search_backend`), 233
`host_name` (in module `tardis.apps.push_to.models.RemoteHost` attribute), 96
`HttpResponseMethodNotAllowed` (class in `tardis.tardis_portal.views.utils`), 203
`HttpResponseSeeAlso` (class in `tardis.tardis_portal.views.utils`), 203
`hydrate()` (in module `tardis.apps.sftp.api.SFTPPublicKeyAppResource` method), 103
`hydrate()` (in module `tardis.tardis_portal.api.DataFileResource` method), 210

hydrate() (tardis.tardis_portal.api.ObjectACLResource id (tardis.tardis_portal.models.parameters.DatafileParameterSet method), 214 attribute), 154

hydrate() (tardis.tardis_portal.api.ParameterResource id (tardis.tardis_portal.models.parameters.DatasetParameter method), 215 attribute), 155

hydrate() (tardis.tardis_portal.api.ReplicaResource id (tardis.tardis_portal.models.parameters.DatasetParameterSet method), 215 attribute), 157

hydrate_m2m() (tardis.tardis_portal.api.ExperimentResource id (tardis.tardis_portal.models.parameters.ExperimentParameter method), 212 attribute), 157

hydrate_schema() (tardis.tardis_portal.api.ParameterSetResource id (tardis.tardis_portal.models.parameters.ExperimentParameterSet method), 215 attribute), 159

I id (tardis.tardis_portal.models.parameters.FreeTextSearchField attribute), 160

id (tardis.apps.equipment.models.Equipment attribute), id (tardis.tardis_portal.models.parameters.InstrumentParameter attribute), 160

76 id (tardis.tardis_portal.models.parameters.InstrumentParameterSet attribute), 161

id (tardis.apps.openid_migration.models.OpenidACLMigration attribute), 87 id (tardis.tardis_portal.models.parameters.ParameterName attribute), 165

id (tardis.apps.openid_migration.models.OpenidUserMigration attribute), 88 id (tardis.tardis_portal.models.parameters.Schema attribute), 168

id (tardis.apps.push_to.models.Credential attribute), 92 id (tardis.tardis_portal.models.parameters.Schema attribute), 168

id (tardis.apps.push_to.models.OAuthSSHCertSigningService attribute), 95 id (tardis.tardis_portal.models.storage.StorageBox attribute), 172

id (tardis.apps.push_to.models.RemoteHost attribute), id (tardis.tardis_portal.models.storage.StorageBoxAttribute attribute), 173

96 id (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 174

id (tardis.apps.sftp.models.SFTPPublicKey attribute), id (tardis.tardis_portal.models.token.Token attribute), 175

105 id (tardis.tardis_portal.models.token.Token attribute), 175

id (tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.ObjectACL attribute), 223 identify() (tardis.apps.oaipmh.provider.base.BaseProvider method), 78, 241

id (tardis.tardis_portal.models.access_control.GroupAdmin attribute), 132 identify() (tardis.apps.oaipmh.server.ProxyingServer method), 83, 243

id (tardis.tardis_portal.models.access_control.ObjectACL attribute), 133 image (tardis.tardis_portal.models.dataset.Dataset attribute), 143

id (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 134 image_url (tardis.tardis_portal.models.license.License attribute), 152

id (tardis.tardis_portal.models.access_control.UserProfile attribute), 135 immutable (tardis.tardis_portal.models.dataset.Dataset attribute), 143

id (tardis.tardis_portal.models.datafile.DataFile attribute), 138 immutable (tardis.tardis_portal.models.parameters.ParameterName attribute), 165

id (tardis.tardis_portal.models.datafile.DataFileObject attribute), 140 immutable (tardis.tardis_portal.models.parameters.Schema attribute), 169

id (tardis.tardis_portal.models.dataset.Dataset attribute), 143 ImportParamsForm (class in tardis.tardis_portal.forms), 225

id (tardis.tardis_portal.models.experiment.Experiment attribute), 146 index() (in module tardis.apps.equipment.views), 77

id (tardis.tardis_portal.models.experiment.ExperimentAuthor attribute), 148 index_queryset() (tardis.search.search_indexes.ExperimentIndex method), 117

id (tardis.tardis_portal.models.facility.Facility attribute), 149 INDEX_VIEWS (in module tardis.default_settings.custom_views), 113

id (tardis.tardis_portal.models.instrument.Instrument attribute), 151 IndexView (class in tardis.tardis_portal.views.pages), 201

id (tardis.tardis_portal.models.jti.JTI attribute), 152 init_filters() (in module tardis.tardis_portal.tasks), 234

id (tardis.tardis_portal.models.license.License attribute), 152 initial (tardis.apps.openid_migration.migrations.0001_initial.Migration attribute), 153

[attribute](#)), 85
[initial](#) ([tardis.apps.sftp.migrations.0001_initial.Migration](#)
[attribute](#)), 102
[inlines](#) ([tardis.tardis_portal.admin.DatafileAdmin](#) [at-](#)
[tribute](#)), 205
[inlines](#) ([tardis.tardis_portal.admin.ExperimentAdmin](#)
[attribute](#)), 205
[inlines](#) ([tardis.tardis_portal.admin.ExperimentParameterSetAdmin](#)
[attribute](#)), 206
[inlines](#) ([tardis.tardis_portal.admin.InstrumentParameterSetAdmin](#)
[attribute](#)), 206
[inlines](#) ([tardis.tardis_portal.admin.SchemaAdmin](#) [at-](#)
[tribute](#)), 207
[inlines](#) ([tardis.tardis_portal.admin.StorageBoxAdmin](#)
[attribute](#)), 207
[instantiateFilters](#) ()
([tardis.tardis_portal.management.commands.runfilters.Comman-](#)
[d](#) [attribute](#)), 172
[method](#)), 127
[institution](#) ([tardis.tardis_portal.models.experiment.ExperimentAdmin](#)
[attribute](#)), 148
[institution_name](#) ([tardis.tardis_portal.models.experiment.ExperimentAdmin](#)
[attribute](#)), 146
[Instrument](#) (class in [tardis.tardis_portal.models.instrument](#)), 150
[instrument](#) ([tardis.tardis_portal.models.dataset.Dataset](#)
[attribute](#)), 143
[instrument](#) ([tardis.tardis_portal.models.parameters.InstrumentParameterSet](#)
[attribute](#)), 161
[INSTRUMENT](#) ([tardis.tardis_portal.models.parameters.Schema](#)
[attribute](#)), 167
[Instrument.DoesNotExist](#), 150
[Instrument.MultipleObjectsReturned](#), 150
[instrument_id](#) ([tardis.tardis_portal.models.dataset.Dataset](#)
[attribute](#)), 144
[instrument_id](#) ([tardis.tardis_portal.models.parameters.InstrumentParameterSet](#)
[attribute](#)), 161
[instrument_set](#) ([tardis.tardis_portal.models.facility.Facility](#)
[attribute](#)), 149
[InstrumentAdmin](#) (class in [tardis.tardis_portal.admin](#)), 206
[InstrumentParameter](#) (class in [tardis.tardis_portal.models.parameters](#)),
160
[InstrumentParameter.DoesNotExist](#), 160
[InstrumentParameter.MultipleObjectsReturned](#), 160
[instrumentparameter_set](#)
([tardis.tardis_portal.models.parameters.InstrumentParameterSet](#)
[attribute](#)), 161
[instrumentparameter_set](#)
([tardis.tardis_portal.models.parameters.ParameterName](#)
[attribute](#)), 165
[InstrumentParameterInline](#) (class in [tardis.tardis_portal.admin](#)), 206

[InstrumentParameterSet](#) (class in [tardis.tardis_portal.models.parameters](#)),
161
[InstrumentParameterSet.DoesNotExist](#), 161
[InstrumentParameterSet.MultipleObjectsReturned](#),
161
[instrumentparameterset_set](#)
([tardis.tardis_portal.models.instrument.Instrument](#)
[attribute](#)), 151
[instrumentparameterset_set](#)
([tardis.tardis_portal.models.parameters.Schema](#)
[attribute](#)), 169
[InstrumentParameterSetAdmin](#) (class in
[tardis.tardis_portal.admin](#)), 206
[instrumentparametersets](#)
([tardis.tardis_portal.models.storage.StorageBox](#)
[attribute](#)), 172
[InstrumentResource](#) (class in
[tardis.tardis_portal.api](#)), 213
[InstrumentResource.Meta](#) (class in
[tardis.tardis_portal.api](#)), 213
[InstrumentResourceTest](#) (class in
[tardis.tardis_portal.tests.api.test_instrument_resource](#)),
182
[internal_description](#)
([tardis.tardis_portal.models.license.License](#)
[attribute](#)), 152
[INTERNAL_IPS](#) (in module
[tardis.default_settings.debug](#)), 114
[interpolate_template](#) () (in module
[tardis.apps.openid_migration.email_text](#)),
86
[is_active](#) ([tardis.tardis_portal.models.license.License](#)
[attribute](#)), 153
[InstrumentParameterSet.is_authenticated](#) ()
([tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter](#)
[method](#)), 125
[is_authenticated](#) ()
([tardis.tardis_portal.api.MyTardisAuthentication](#)
[method](#)), 214
[is_directory](#) () (in module
[tardis.apps.push_to.utils](#)), 98
[is_expired](#) () ([tardis.tardis_portal.models.token.Token](#)
[method](#)), 175
[is_facility_manager](#) () (in module
[tardis.tardis_portal.models.facility](#)), 150
[is_group_admin](#) () (in module
[tardis.tardis_portal.auth.decorators](#)), 122
[is_image](#) () ([tardis.tardis_portal.models.datafile.DataFile](#)
[method](#)), 138
[is_jeol_sem_metadata](#) ()
([tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter](#)
[method](#)), 125
[is_json](#) () ([tardis.tardis_portal.models.parameters.ParameterName](#)

- method), 166
- is_local() (tardis.tardis_portal.models.datafile.DataFile attribute), 138
- is_online (tardis.tardis_portal.models.datafile.DataFile attribute), 138
- is_online (tardis.tardis_portal.models.dataset.Dataset attribute), 144
- is_openid_migration_enabled() (in module tardis.apps.social_auth.auth.social_auth), 111
- is_public() (tardis.tardis_portal.models.datafile.DataFile attribute), 138
- is_publication() (tardis.tardis_portal.models.experiment.Experiment attribute), 146
- is_publication_draft() (tardis.tardis_portal.models.experiment.Experiment attribute), 146
- is_schema_valid() (tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider attribute), 176
- is_schema_valid() (tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider attribute), 193
- is_searchable (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- is_tardis_app() (in module tardis.app_config), 237
- is_text_file() (tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter attribute), 125
- is_valid() (tardis.tardis_portal.forms.ExperimentForm attribute), 225
- is_valid_email() (in module tardis.tardis_portal.management.commands.createuser), 126
- isDateTime() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isDjangoAccount (tardis.tardis_portal.models.access_control.UserProfile attribute), 135
- isFilename() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isLink() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isLongString() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isNumeric() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isOwner (tardis.tardis_portal.forms.ChangeUserPermissionsForm attribute), 223
- isOwner (tardis.tardis_portal.models.access_control.ObjectACL attribute), 133
- isString() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isURL() (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- isValidPublicContact() (tardis.tardis_portal.models.access_control.UserProfile attribute), 135
- method), 135
- IteratorTracker (class in tardis.analytics.tracker), 73
- J**
- JEOLSEMFilter (class in tardis.tardis_portal.filters.jeolsem), 125
- JEOLSEMFilterTestCase (class in tardis.tardis_portal.tests.filters.test_jeolsem), 184
- JSON (tardis.tardis_portal.models.parameters.ParameterName attribute), 164
- json_indent (tardis.tardis_portal.api.PrettyJSONSerializer attribute), 215
- JTI (class in tardis.tardis_portal.models.jti), 151
- jti (tardis.tardis_portal.models.jti.JTI attribute), 152
- JTI.DoesNotExist, 151
- JSONObjectObjectsReturned, 151
- K**
- key (tardis.apps.equipment.models.Equipment attribute), 76
- key (tardis.tardis_portal.models.push_to.models.KeyPair attribute), 93
- key (tardis.tardis_portal.models.storage.StorageBoxAttribute attribute), 173
- key (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 174
- key_type (tardis.apps.push_to.models.KeyPair attribute), 93
- key_type (tardis.apps.sftp.models.SFTPPublicKey attribute), 105
- KeyAddForm (class in tardis.apps.sftp.forms), 104
- KeyCreateForm (class in tardis.apps.sftp.forms), 104
- KeyPair (class in tardis.apps.push_to.models), 93
- KeyPair.Meta (class in tardis.apps.push_to.models), 93
- key_type (tardis.tardis_portal.models.parameters.ParameterName attribute), 166
- L**
- Label (class in tardis.tardis_portal.widgets), 235
- last_verified_time (tardis.tardis_portal.models.datafile.DataFileObject attribute), 140
- LDAP_BASE (tardis.default_settings attribute), 54
- LDAP_GROUP_ATTR_MAP (tardis.default_settings attribute), 54
- LDAP_GROUP_BASE (tardis.default_settings attribute), 54
- LDAP_GROUP_ID_ATTR (tardis.default_settings attribute), 54
- LDAP_TLS (tardis.default_settings attribute), 54
- LDAP_URL (tardis.default_settings attribute), 54
- LDAP_USER_ATTR_MAP (tardis.default_settings attribute), 54

LDAP_USER_BASE (*tardis.default_settings* attribute), 54

LDAP_USER_LOGIN_ATTR (*tardis.default_settings* attribute), 54

ldapadd() (*tardis.tardis_portal.tests.slapi.Slapd* method), 186

LDAPErrorTest (class in *tardis.tardis_portal.tests.test_ldap*), 191

ldapsearch() (*tardis.tardis_portal.tests.slapi.Slapd* method), 186

LDAPTest (class in *tardis.tardis_portal.tests.test_ldap*), 191

length_gt() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 177

length_gte() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 177

length_lt() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 177

length_lte() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 178

LESS_THAN_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164

LESS_THAN_EQUAL_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164

Level0TestCase (class in *tardis.tardis_portal.tests.test_iiif*), 190

Level1TestCase (class in *tardis.tardis_portal.tests.test_iiif*), 190

Level2TestCase (class in *tardis.tardis_portal.tests.test_iiif*), 190

License (class in *tardis.tardis_portal.models.license*), 152

license (*tardis.tardis_portal.models.experiment.Experiment* attribute), 146

License.DoesNotExist, 152

License.MultipleObjectsReturned, 152

license_id (*tardis.tardis_portal.models.experiment.Experiment* attribute), 147

LINK (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164

link_ct (*tardis.tardis_portal.models.parameters.DatafileParameter* attribute), 153

link_ct (*tardis.tardis_portal.models.parameters.DatasetParameter* attribute), 155

link_ct (*tardis.tardis_portal.models.parameters.ExperimentParameter* attribute), 157

link_ct (*tardis.tardis_portal.models.parameters.InstrumentParameter* attribute), 160

link_ct (*tardis.tardis_portal.models.parameters.Parameter* attribute), 162

link_ct_id (*tardis.tardis_portal.models.parameters.Parameter* attribute), 163

link_gfk (*tardis.tardis_portal.models.parameters.DatafileParameter* attribute), 153

link_gfk (*tardis.tardis_portal.models.parameters.DatasetParameter* attribute), 155

link_gfk (*tardis.tardis_portal.models.parameters.ExperimentParameter* attribute), 158

link_gfk (*tardis.tardis_portal.models.parameters.InstrumentParameter* attribute), 160

link_gfk (*tardis.tardis_portal.models.parameters.Parameter* attribute), 163

link_id (*tardis.tardis_portal.models.parameters.Parameter* attribute), 163

link_url (*tardis.tardis_portal.models.parameters.Parameter* attribute), 163

list_allowed_methods (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta* attribute), 103

list_auth_methods() (in module *tardis.tardis_portal.auth.authentication*), 119

list_display (*tardis.apps.openid_migration.models.OpenidACLMigration* attribute), 88

list_display (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 89

list_display (*tardis.tardis_portal.admin.ObjectACLAdmin* attribute), 206

list_folder() (*tardis.apps.sftp.sftp.MyTSFTPServerInterface* method), 106

list_subdirectories() (in module *tardis.apps.push_to.utils*), 98

listFilters() (*tardis.tardis_portal.management.commands.runfilters* method), 127

listIdentifiers() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 79, 241

listIdentifiers() (*tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider* method), 80

listIdentifiers() (*tardis.apps.oaipmh.server.ProxyingServer* method), 83, 243

listMetadataFormats() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 79, 242

listMetadataFormats() (*tardis.apps.oaipmh.provider.experiment.DcExperimentProvider* method), 80

listMetadataFormats() (*tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider* method), 81

listMetadataFormats() (class in *tardis.apps.oaipmh.server.ProxyingServer* method), 84, 243

listRecords() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 79, 242

listRecords() (*tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider* method), 80

listRecords() (*tardis.apps.oaipmh.server.ProxyingServer* method), 84, 243

listSets() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 79, 242

listSets() (*tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider* method), 80

listSets() (*tardis.apps.oaipmh.server.ProxyingServer* method), 84, 244

ListTestCase (class in *tardis.apps.related_info.tests.tests*), 100

listTestCase (class in *tardis.tardis_portal.tests.test_views*), 196

load_datafile_image() (in module *tardis.tardis_portal.views.images*), 199

load_dataset_image() (in module *tardis.tardis_portal.views.images*), 199

load_experiment_image() (in module *tardis.tardis_portal.views.images*), 199

load_image() (in module *tardis.tardis_portal.views.images*), 199

LoadSchemasTestCase (class in *tardis.tardis_portal.tests.test_loadschemas*), 191

LocationResource (class in *tardis.tardis_portal.api*), 213

LocationResource.Meta (class in *tardis.tardis_portal.api*), 213

LocationResourceTest (class in *tardis.tardis_portal.tests.api.test_location_resource*), 183

locked (*tardis.tardis_portal.models.experiment.Experiment* attribute), 147

logger (in module *tardis.tardis_portal.xmlwriter*), 236

LoggingMiddleware (class in *tardis.tardis_portal.logging_middleware*), 229

login() (in module *tardis.tardis_portal.views.authentication*), 197

LOGIN_VIEWS (in module *tardis.default_settings.custom_views*), 114

LoginForm (class in *tardis.tardis_portal.forms*), 226

logo_img (*tardis.apps.push_to.models.RemoteHost* attribute), 96

logout() (in module *tardis.tardis_portal.views.authentication*), 198

LONGSTRING (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164

lookup_by_unique_id_only() (in module *tardis.tardis_portal.api*), 217

lookup_kwargs_with_identifiers() (*tardis.tardis_portal.api.MyTardisModelResource* method), 214

lookup_kwargs_with_identifiers() (*tardis.tardis_portal.api.SchemaResource* method), 216

lstat() (*tardis.apps.sftp.sftp.MyTSFTPServerInterface* method), 178

lt() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 178

lte() (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 178

M

make (*tardis.apps.equipment.models.Equipment* attribute), 76

make_dirs() (in module *tardis.apps.push_to.tasks*), 97

make_mapper() (in module *tardis.tardis_portal.download*), 219

make_tar() (*tardis.tardis_portal.download.UncachedTarStream* method), 219

manage_auth_methods() (in module *tardis.tardis_portal.views.authentication*), 198

manage_groups() (in module *tardis.tardis_portal.views.authorisation*), 198

manage_rifcs() (*tardis.tardis_portal.publish.publishservice.PublishService* method), 176

manage_user_account() (in module *tardis.tardis_portal.views.authentication*), 198

ManageAccountForm (class in *tardis.tardis_portal.forms*), 226

ManageAccountForm.Meta (class in *tardis.tardis_portal.forms*), 226

ManageAccountTestCase (class in *tardis.tardis_portal.tests.test_views*), 195

ManageGroupPermissionsForm (class in *tardis.tardis_portal.forms*), 226

manager_group (*tardis.tardis_portal.models.facility.Facility* attribute), 149

manager_group_id (*tardis.tardis_portal.models.facility.Facility* attribute), 149

master_box (*tardis.tardis_portal.models.storage.StorageBox* attribute), 172

master_box_id (*tardis.tardis_portal.models.storage.StorageBox* attribute), 172

<code>max_size</code> (<code>tardis.tardis_portal.models.storage.StorageBox</code> attribute), 172	<code>media</code> (<code>tardis.tardis_portal.admin.ParameterNameAdmin</code> attribute), 206
<code>md5sum</code> (<code>tardis.tardis_portal.models.datafile.DataFile</code> attribute), 138	<code>media</code> (<code>tardis.tardis_portal.admin.ParameterNameInline</code> attribute), 207
<code>media</code> (<code>tardis.apps.equipment.forms.EquipmentSearchForm</code> attribute), 76	<code>media</code> (<code>tardis.tardis_portal.admin.SchemaAdmin</code> attribute), 207
<code>media</code> (<code>tardis.apps.openid_migration.models.OpenidACLMigrationAdmin</code> attribute), 88	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxAdmin</code> attribute), 207
<code>media</code> (<code>tardis.apps.openid_migration.models.OpenidUserMigrationAdmin</code> attribute), 89	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxAttributeInline</code> attribute), 207
<code>media</code> (<code>tardis.apps.push_to.models.CredentialAdmin</code> attribute), 93	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxAttributeInlineForm</code> attribute), 208
<code>media</code> (<code>tardis.apps.push_to.models.CredentialForm</code> attribute), 93	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxForm</code> attribute), 208
<code>media</code> (<code>tardis.apps.push_to.models.RemoteHostAdmin</code> attribute), 97	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxOptionInline</code> attribute), 208
<code>media</code> (<code>tardis.apps.related_info.forms.RelatedInfoForm</code> attribute), 101	<code>media</code> (<code>tardis.tardis_portal.admin.StorageBoxOptionInlineForm</code> attribute), 209
<code>media</code> (<code>tardis.apps.sftp.forms.KeyAddForm</code> attribute), 104	<code>media</code> (<code>tardis.tardis_portal.admin.UserAuthenticationAdmin</code> attribute), 209
<code>media</code> (<code>tardis.apps.sftp.forms.KeyGenerateForm</code> attribute), 104	<code>media</code> (<code>tardis.tardis_portal.forms.AddGroupPermissionsForm</code> attribute), 220
<code>media</code> (<code>tardis.search.forms.GroupedSearchForm</code> attribute), 116	<code>media</code> (<code>tardis.tardis_portal.forms.AddUserPermissionsForm</code> attribute), 221
<code>media</code> (<code>tardis.tardis_portal.admin.DatafileAdmin</code> attribute), 205	<code>media</code> (<code>tardis.tardis_portal.forms.ChangeGroupPermissionsForm</code> attribute), 221
<code>media</code> (<code>tardis.tardis_portal.admin.DatafileAdminForm</code> attribute), 205	<code>media</code> (<code>tardis.tardis_portal.forms.ChangeUserPermissionsForm</code> attribute), 223
<code>media</code> (<code>tardis.tardis_portal.admin.DataFileObjectInline</code> attribute), 204	<code>media</code> (<code>tardis.tardis_portal.forms.CreateGroupPermissionsForm</code> attribute), 224
<code>media</code> (<code>tardis.tardis_portal.admin.DataFileObjectInlineForm</code> attribute), 204	<code>media</code> (<code>tardis.tardis_portal.forms.CreateUserPermissionsForm</code> attribute), 224
<code>media</code> (<code>tardis.tardis_portal.admin.DatasetAdmin</code> attribute), 205	<code>media</code> (<code>tardis.tardis_portal.forms.DatasetForm</code> attribute), 224
<code>media</code> (<code>tardis.tardis_portal.admin.ExperimentAdmin</code> attribute), 205	<code>media</code> (<code>tardis.tardis_portal.forms.ExperimentAuthor</code> attribute), 225
<code>media</code> (<code>tardis.tardis_portal.admin.ExperimentParameterInline</code> attribute), 205	<code>media</code> (<code>tardis.tardis_portal.forms.ExperimentForm</code> attribute), 225
<code>media</code> (<code>tardis.tardis_portal.admin.ExperimentParameterSetAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.ImportParamsForm</code> attribute), 226
<code>media</code> (<code>tardis.tardis_portal.admin.FacilityAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.LoginForm</code> attribute), 226
<code>media</code> (<code>tardis.tardis_portal.admin.FreeTextSearchFieldAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.ManageAccountForm</code> attribute), 226
<code>media</code> (<code>tardis.tardis_portal.admin.InstrumentAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.ManageGroupPermissionsForm</code> attribute), 227
<code>media</code> (<code>tardis.tardis_portal.admin.InstrumentParameterInline</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.NoInput</code> attribute), 227
<code>media</code> (<code>tardis.tardis_portal.admin.InstrumentParameterSetAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.RawSearchForm</code> attribute), 227
<code>media</code> (<code>tardis.tardis_portal.admin.ObjectACLAdmin</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.RegisterExperimentForm</code> attribute), 227
<code>media</code> (<code>tardis.tardis_portal.admin.ObjectACLInline</code> attribute), 206	<code>media</code> (<code>tardis.tardis_portal.forms.RegistrationForm</code> attribute), 228

media (*tardis.tardis_portal.forms.RightsForm* attribute), 129
 228 Migration (class in
 media (*tardis.tardis_portal.widgets.CommaSeparatedInput* *tardis.tardis_portal.migrations.0006_datafile_remove_size_string*
 attribute), 235 129
 media (*tardis.tardis_portal.widgets.Label* attribute), Migration (class in
 235 *tardis.tardis_portal.migrations.0007_remove_parameter_string_*
 media (*tardis.tardis_portal.widgets.Span* attribute), 235 129
 merge_auth_method() (in module Migration (class in
tardis.tardis_portal.auth.authentication), *tardis.tardis_portal.migrations.0008_string_value_partial_index*,
 119 129
 METADATA_STORE_PATH (in module Migration (class in
tardis.default_settings.storage), 115 *tardis.tardis_portal.migrations.0009_auto_20160128_1119*),
 migrate_accounts() (in module 130
tardis.apps.openid_migration.views), 90 Migration (class in
 migrate_api_key() (in module *tardis.tardis_portal.migrations.0010_auto_20160503_1443*),
tardis.apps.openid_migration.migration), 130
 87 Migration (class in
 migrate_user_message() (in module *tardis.tardis_portal.migrations.0011_auto_20160505_1643*),
tardis.apps.social_auth.auth.social_auth), 130
 111 Migration (class in
 migrate_user_permissions() (in module *tardis.tardis_portal.migrations.0012_userauthentication_approve*
tardis.apps.openid_migration.migration), 87 130
 Migration (class in Migration (class in
tardis.apps.equipment.migrations.0001_initial), *tardis.tardis_portal.migrations.0013_auto_20181002_1136*),
 75 130
 Migration (class in Migration (class in
tardis.apps.openid_migration.migrations.0001_initial), *tardis.tardis_portal.migrations.0014_auto_20181002_1154*),
 85 130
 Migration (class in Migration (class in
tardis.apps.push_to.migrations.0001_initial), *tardis.tardis_portal.migrations.0015_dataset_created_time*),
 90 131
 Migration (class in Migration (class in
tardis.apps.push_to.migrations.0002_auto_20160518_1953), *tardis.tardis_portal.migrations.0016_add_timestamps*),
 90 131
 Migration (class in migration_status (*tardis.apps.openid_migration.models.OpenidUser*
tardis.apps.sftp.migrations.0001_initial), attribute), 88
 102 migration_timestamp
 Migration (class in (*tardis.apps.openid_migration.models.OpenidUserMigration*
tardis.tardis_portal.migrations.0001_initial), attribute), 88
 128 mimetype (*tardis.tardis_portal.models.datafile.DataFile*
 Migration (class in attribute), 139
tardis.tardis_portal.migrations.0001_squashed_0015_auto_20160505_1643), 177
 128 *FileNotFoundError*, 177
 missing_host_key() (in module *tardis.tardis_portal.migrations.0002_auto_20150528_1128*), 93
 Migration (class in (*tardis.apps.push_to.models.DBHostKeyPolicy*
tardis.tardis_portal.migrations.0002_auto_20150528_1128), method), 93
 128
 Migration (class in mkdirs() (in module *tardis.tardis_portal.tests.slappd*),
tardis.tardis_portal.migrations.0003_auto_20150907_1315), 186
 128 OpenIDProvider (class in
 Migration (class in *tardis.tardis_portal.tests.test_authservice*),
tardis.tardis_portal.migrations.0004_storageboxopinion_base_type), (class in
 129 *tardis.tardis_portal.tests.mock_vbl_auth*),
 Migration (class in 185
tardis.tardis_portal.migrations.0005_datafile_add_music_group_id), (class in
 185 *MusicGroupProvider*)

<code>tardis.tardis_portal.tests.test_authservice</code>), 188	<code>tardis.apps.openid_migration.tests.test_models</code>), 85
<code>MockRequest</code> (class in <code>tardis.tardis_portal.tests.test_authservice</code>), 188	<code>ModelTestCase</code> (class in <code>tardis.tardis_portal.tests.test_models</code>), 191
<code>MockRifCsProvider</code> (class in <code>tardis.tardis_portal.tests.test_publishservice</code>), 193	<code>ModelTestCase</code> (class in <code>tardis.tardis_portal.tests.test_storage</code>), 193
<code>MockSettings</code> (class in <code>tardis.tardis_portal.tests.test_authservice</code>), 188	<code>modification_time</code> (<code>tardis.tardis_portal.models.datafile.DataFile</code> attribute), 139
<code>model</code> (<code>tardis.apps.equipment.models.Equipment</code> attribute), 76	<code>modified_time</code> (<code>tardis.tardis_portal.models.datafile.DataFileObject</code> attribute), 140
<code>model</code> (<code>tardis.apps.push_to.models.CredentialForm.Meta</code> attribute), 93	<code>modified_time</code> (<code>tardis.tardis_portal.models.dataset.Dataset</code> attribute), 144
<code>model</code> (<code>tardis.tardis_portal.admin.DatafileAdminForm.Meta</code> attribute), 205	<code>modified_time</code> (<code>tardis.tardis_portal.models.facility.Facility</code> attribute), 149
<code>model</code> (<code>tardis.tardis_portal.admin.DataFileObjectInline</code> attribute), 204	<code>modified_time</code> (<code>tardis.tardis_portal.models.instrument.Instrument</code> attribute), 151
<code>model</code> (<code>tardis.tardis_portal.admin.DataFileObjectInlineForm.Meta</code> attribute), 204	<code>move_file()</code> (<code>tardis.tardis_portal.models.datafile.DataFileObject</code> method), 140
<code>model</code> (<code>tardis.tardis_portal.admin.ExperimentParameterInline</code> attribute), 205	<code>move_files()</code> (<code>tardis.tardis_portal.models.storage.StorageBox</code> method), 172
<code>model</code> (<code>tardis.tardis_portal.admin.ExperimentParameterInlineForm.Meta</code> attribute), 205	<code>move_to_master()</code> (<code>tardis.tardis_portal.models.storage.StorageBox</code> method), 172
<code>model</code> (<code>tardis.tardis_portal.admin.InstrumentParameterInline</code> attribute), 206	<code>MultiValueCommaSeparatedField</code> (class in <code>tardis.tardis_portal.fields</code>), 220
<code>model</code> (<code>tardis.tardis_portal.admin.ObjectACLInline</code> attribute), 206	<code>my_data()</code> (in module <code>tardis.tardis_portal.views.pages</code>), 201
<code>model</code> (<code>tardis.tardis_portal.admin.ParameterNameInline</code> attribute), 207	<code>myt_auth()</code> (<code>tardis.apps.sftp.sftp.MyTServerInterface</code> method), 110
<code>model</code> (<code>tardis.tardis_portal.admin.StorageBoxAttributeInline</code> attribute), 207	<code>MyTardisAuthentication</code> (class in <code>tardis.tardis_portal.api</code>), 214
<code>model</code> (<code>tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta</code> attribute), 208	<code>MyTardisAuthenticationTest</code> (class in <code>tardis.tardis_portal.tests.api.test_auth</code>), 180
<code>model</code> (<code>tardis.tardis_portal.admin.StorageBoxForm.Meta</code> attribute), 208	<code>MyTardisLocalFileSystemStorage</code> (class in <code>tardis.tardis_portal.storage.file_system</code>), 177
<code>model</code> (<code>tardis.tardis_portal.admin.StorageBoxOptionInline</code> attribute), 208	<code>MyTardisModelResource</code> (class in <code>tardis.tardis_portal.api</code>), 214
<code>model</code> (<code>tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta</code> attribute), 209	<code>MyTardisModelResource.Meta</code> (class in <code>tardis.tardis_portal.api</code>), 214
<code>model</code> (<code>tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta</code> attribute), 223	<code>MyTardisModelResourceTestCase</code> (class in <code>tardis.tardis_portal.tests.api</code>), 183
<code>model</code> (<code>tardis.tardis_portal.forms.DatasetForm.Meta</code> attribute), 224	<code>MyTServerInterface</code> (class in <code>tardis.apps.sftp.sftp</code>), 108
<code>model</code> (<code>tardis.tardis_portal.forms.ExperimentAuthor.Meta</code> attribute), 225	<code>MyTSFTPHandle</code> (class in <code>tardis.apps.sftp.sftp</code>), 106
<code>model</code> (<code>tardis.tardis_portal.forms.ExperimentForm.Meta</code> attribute), 225	<code>MyTSFTPRequestHandler</code> (class in <code>tardis.apps.sftp.sftp</code>), 106
<code>model</code> (<code>tardis.tardis_portal.forms.ManageAccountForm.Meta</code> attribute), 226	<code>MyTSFTPServer</code> (class in <code>tardis.apps.sftp.sftp</code>), 106
<code>model</code> (<code>tardis.tardis_portal.forms.RightsForm.Meta</code> attribute), 228	<code>MyTSFTPServerInterface</code> (class in <code>tardis.apps.sftp.sftp</code>), 106
<code>ModelsTestCase</code> (class in <code>tardis.apps.push_to.tests.test_models</code>), 91	<code>MyTSFTPTCPServer</code> (class in <code>tardis.apps.sftp.sftp</code>), 107
<code>ModelTestCase</code> (class in <code>tardis.tardis_portal.tests.test_authservice</code>), 188	N
<code>ModelTestCase</code> (class in <code>tardis.tardis_portal.tests.test_publishservice</code>), 193	<code>name</code> (<code>tardis.analytics.apps.AnalyticsConfig</code> attribute),

73

name (`tardis.apps.openid_migration.apps.OpenidMigrationConfig`) (`tardis.analytics.tracker.IteratorTracker` attribute), 86

name (`tardis.apps.push_to.apps.PushToConfig` attribute), 91

name (`tardis.apps.sftp.apps.SFTPConfig` attribute), 103

name (`tardis.apps.sftp.models.SFTPPublicKey` attribute), 105

name (`tardis.apps.social_auth.apps.SocialAuthConfig` attribute), 112

name (`tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider` attribute), 124

name (`tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider` attribute), 124

name (`tardis.tardis_portal.auth.token_auth.TokenGroupProvider` attribute), 125

name (`tardis.tardis_portal.models.facility.Facility` attribute), 150

name (`tardis.tardis_portal.models.instrument.Instrument` attribute), 151

name (`tardis.tardis_portal.models.license.License` attribute), 153

name (`tardis.tardis_portal.models.parameters.DatafileParameter` attribute), 153

name (`tardis.tardis_portal.models.parameters.DatasetParameter` attribute), 156

name (`tardis.tardis_portal.models.parameters.ExperimentParameter` attribute), 158

name (`tardis.tardis_portal.models.parameters.InstrumentParameter` attribute), 160

name (`tardis.tardis_portal.models.parameters.Parameter` attribute), 163

name (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 166

name (`tardis.tardis_portal.models.parameters.Schema` attribute), 169

name (`tardis.tardis_portal.models.storage.StorageBox` attribute), 172

name_id (`tardis.tardis_portal.models.parameters.Parameter` attribute), 163

namespace (`tardis.tardis_portal.models.parameters.Schema` attribute), 169

natural_key () (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 166

natural_key () (`tardis.tardis_portal.models.parameters.Schema` attribute), 169

new_param () (`tardis.tardis_portal.ParameterSetManager.ParameterSetManager` attribute), 204

new_user (`tardis.apps.openid_migration.models.OpenidUserMigration` attribute), 88

new_user_auth_method (`tardis.apps.openid_migration.models.OpenidUserMigration` attribute), 88

new_user_id (`tardis.apps.openid_migration.models.OpenidUserMigration` attribute), 88

attribute), 89

method), 73

nickname (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

nickname (`tardis.apps.push_to.models.RemoteHost` attribute), 96

NoInput (class in `tardis.tardis_portal.forms`), 227

NONE (`tardis.tardis_portal.models.parameters.Schema` attribute), 168

Provider (class in `tardis.tardis_portal.models.parameters.Schema` attribute), 168

NOT_EQUAL_COMPARISON

(`tardis.tardis_portal.models.parameters.ParameterName` attribute), 164

verify_user () (in module `tardis.apps.push_to.tasks`), 97

now () (`tardis.tardis_portal.tests.test_tokens.FrozenTime` class method), 194

NS_CC (`tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider` attribute), 80

NUMERIC (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 164

numerical_value (`tardis.tardis_portal.models.parameters.Parameter` attribute), 163

O

oauth_authorize_url (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

oauth_callback () (in module `tardis.apps.push_to.views`), 99

oauth_callback_url () (in module `tardis.apps.push_to.views`), 99

oauth_check_token_url (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

oauth_client_id (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

oauth_client_secret (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

oauth_token_url (`tardis.apps.push_to.models.OAuthSSHCertSigningService` attribute), 95

OAuthSSHCertSigningService (class in `tardis.apps.push_to.models`), 94

OAuthSSHCertSigningService.DoesNotExist,

OAuthSSHCertSigningService.MultipleObjectsReturned,

oauthsshcertsigningservice_set (`tardis.apps.push_to.models.RemoteHost` attribute), 96

obj_create () (`tardis.tardis_portal.api.DataFileResource` attribute), 210

`obj_create()` (`tardis.tardis_portal.api.ExperimentResource` [132](#)
`method`), [212](#) `ObjectACL.DoesNotExist`, [132](#)
`object_class` (`tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta`, `MultipleObjectsReturned`, [132](#)
`attribute`), [103](#) `ObjectACLAdmin` (class in
`object_class` (`tardis.tardis_portal.api.DatafileParameterResource.Meta`, `tardis.tardis_portal.admin`), [206](#)
`attribute`), [210](#) `ObjectACLInline` (class in
`object_class` (`tardis.tardis_portal.api.DatafileParameterSetResource.Meta`, `tardis.tardis_portal.admin`), [206](#)
`attribute`), [210](#) `ObjectACLResource` (class in
`object_class` (`tardis.tardis_portal.api.DataFileResource.Meta`, `tardis.tardis_portal.api`), [214](#)
`attribute`), [210](#) `ObjectACLResource.Meta` (class in
`object_class` (`tardis.tardis_portal.api.DatasetParameterResource.Meta`, `tardis.tardis_portal.api`), [214](#)
`attribute`), [211](#) `objectacIs` (`tardis.tardis_portal.models.experiment.Experiment`
`object_class` (`tardis.tardis_portal.api.DatasetParameterSetResource.Meta`, `tardis.tardis_portal.admin`), [147](#)
`attribute`), [211](#) `ObjectACLTestCase` (class in
`object_class` (`tardis.tardis_portal.api.DatasetResource.Meta`, `tardis.tardis_portal.tests.test_authorisation`),
`attribute`), [211](#) [187](#)
`object_class` (`tardis.tardis_portal.api.ExperimentParameterResource.Meta`, `tardis.apps.equipment.models.Equipment` `attribute`), [212](#)
`attribute`), [76](#) `object_class` (`tardis.tardis_portal.api.ExperimentParameterSetResource.Meta`, `tardis.apps.openid_migration.models.OpenidACLMigration`
`attribute`), [212](#) `attribute`), [87](#)
`object_class` (`tardis.tardis_portal.api.ExperimentResource.Meta`, `tardis.apps.openid_migration.models.OpenidUserMigration`
`attribute`), [212](#) `attribute`), [89](#)
`object_class` (`tardis.tardis_portal.api.FacilityResource.Meta`, `Objects` (`tardis.apps.push_to.models.Credential`
`attribute`), [213](#) `attribute`), [92](#)
`object_class` (`tardis.tardis_portal.api.GroupResource.Meta`, `Objects` (`tardis.apps.push_to.models.OAuthSSHCertSigningService`
`attribute`), [213](#) `attribute`), [95](#)
`object_class` (`tardis.tardis_portal.api.InstrumentResource.Meta`, `Objects` (`tardis.apps.push_to.models.RemoteHost` `attribute`), [213](#)
`attribute`), [213](#) `attribute`), [96](#)
`object_class` (`tardis.tardis_portal.api.LocationResource.Meta`, `Objects` (`tardis.apps.sftp.models.SFTPPublicKey` `attribute`), [213](#)
`attribute`), [213](#) `attribute`), [105](#)
`object_class` (`tardis.tardis_portal.api.MyTardisModelResource.Meta`, `Objects` (`tardis.search.datafile_index.DataFileIndex`
`attribute`), [214](#) `attribute`), [116](#)
`object_class` (`tardis.tardis_portal.api.ObjectACLResource.Meta`, `Objects` (`tardis.search.search_indexes.DatasetIndex`
`attribute`), [214](#) `attribute`), [117](#)
`object_class` (`tardis.tardis_portal.api.ParameterNameResource.Meta`, `Objects` (`tardis.search.search_indexes.ExperimentIndex`
`attribute`), [215](#) `attribute`), [117](#)
`object_class` (`tardis.tardis_portal.api.ReplicaResource.Meta`, `Objects` (`tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta`, `Objects`
`attribute`), [215](#) `attribute`), [223](#)
`object_class` (`tardis.tardis_portal.api.SchemaResource.Meta`, `Objects` (`tardis.tardis_portal.models.access_control.GroupAdmin`
`attribute`), [216](#) `attribute`), [132](#)
`object_class` (`tardis.tardis_portal.api.StorageBoxAttributeResource.Meta`, `Objects` (`tardis.tardis_portal.models.access_control.ObjectACL`
`attribute`), [216](#) `attribute`), [134](#)
`object_class` (`tardis.tardis_portal.api.StorageBoxOptionResource.Meta`, `Objects` (`tardis.tardis_portal.models.access_control.UserAuthentication`
`attribute`), [216](#) `attribute`), [134](#)
`object_class` (`tardis.tardis_portal.api.StorageBoxResource.Meta`, `Objects` (`tardis.tardis_portal.models.access_control.UserProfile`
`attribute`), [216](#) `attribute`), [135](#)
`object_class` (`tardis.tardis_portal.api.UserResource.Meta`, `Objects` (`tardis.tardis_portal.models.datafile.DataFile`
`attribute`), [217](#) `attribute`), [139](#)
`object_id` (`tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta`, `Objects` (`tardis.tardis_portal.models.datafile.DataFileObject`
`attribute`), [223](#) `attribute`), [140](#)
`object_id` (`tardis.tardis_portal.models.access_control.ObjectACL`, `Objects` (`tardis.tardis_portal.models.dataset.Dataset`
`attribute`), [134](#) `attribute`), [144](#)
`ObjectACL` (class in `objects` (`tardis.tardis_portal.models.experiment.Experiment`
`tardis.tardis_portal.models.access_control`), `attribute`), [147](#)

objects (*tardis.tardis_portal.models.experiment.Experiment* attribute), 148

objects (*tardis.tardis_portal.models.facility.Facility* attribute), 150

objects (*tardis.tardis_portal.models.instrument.Instrument* attribute), 151

objects (*tardis.tardis_portal.models.jti.JTI* attribute), 152

objects (*tardis.tardis_portal.models.license.License* attribute), 153

objects (*tardis.tardis_portal.models.parameters.DatafileParameter* attribute), 155

objects (*tardis.tardis_portal.models.parameters.DatasetParameter* attribute), 157

objects (*tardis.tardis_portal.models.parameters.ExperimentParameter* attribute), 159

objects (*tardis.tardis_portal.models.parameters.FreeTextSearchField* attribute), 160

objects (*tardis.tardis_portal.models.parameters.InstrumentParameter* attribute), 162

objects (*tardis.tardis_portal.models.parameters.Parameter* attribute), 163

objects (*tardis.tardis_portal.models.parameters.ParameterOption* attribute), 166

objects (*tardis.tardis_portal.models.parameters.Schema* attribute), 169

objects (*tardis.tardis_portal.models.storage.StorageBox* attribute), 172

objects (*tardis.tardis_portal.models.storage.StorageBoxAttribute* attribute), 173

objects (*tardis.tardis_portal.models.storage.StorageBoxOption* attribute), 174

objects (*tardis.tardis_portal.models.token.Token* attribute), 175

offline_types (*tardis.tardis_portal.models.storage.StorageBox* attribute), 172

old_user (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 89

old_user_auth_method (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 89

old_user_id (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 89

online_types (*tardis.tardis_portal.models.storage.StorageBox* attribute), 172

open() (*tardis.apps.sftp.sftp.MyTSFTPServerInterface* method), 107

openid_migration_method() (in module *tardis.apps.openid_migration.migration*), 87

openid_migration_processor() (in module *tardis.apps.openid_migration.context_processors*), 86

openid_user_migration_form() (in module *tardis.apps.openid_migration.forms*), 86

OpenidACLMigration (class in *tardis.apps.openid_migration.models*), 87

OpenidACLMigration.DoesNotExist, 87

OpenidACLMigration.MultipleObjectsReturned, 87

openidaclmigration_set (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 89

openidaclmigration_set (*tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta* attribute), 223

OpenidUserMigration (class in *tardis.tardis_portal.models.access_control.ObjectACL* attribute), 134

OpenidACLMigrationAdmin (class in *tardis.apps.openid_migration.models*), 88

OpenidMigrationConfig (class in *tardis.apps.openid_migration.apps*), 86

OpenIDMigrationFormTestCase (class in *tardis.apps.openid_migration.tests.test_forms*), 85

OpenIDMigrationTestCase (class in *tardis.apps.openid_migration.tests.test_migration*), 85

OpenIDMigrationViewTestCase (class in *tardis.apps.openid_migration.tests.test_views*), 86

OpenidUserMigration (class in *tardis.apps.openid_migration.models*), 88

OpenidUserMigration.DoesNotExist, 88

OpenidUserMigration.MultipleObjectsReturned, 88

OpenidUserMigrationAdmin (class in *tardis.apps.openid_migration.models*), 89

operations (*tardis.apps.equipment.migrations.0001_initial.Migration* attribute), 75

operations (*tardis.apps.openid_migration.migrations.0001_initial.Migration* attribute), 85

operations (*tardis.apps.push_to.migrations.0001_initial.Migration* attribute), 90

operations (*tardis.apps.push_to.migrations.0002_auto_20160518_1951.Migration* attribute), 90

operations (*tardis.apps.sftp.migrations.0001_initial.Migration* attribute), 102

operations (*tardis.tardis_portal.migrations.0001_initial.Migration* attribute), 128

operations (*tardis.tardis_portal.migrations.0001_squashed_0011_auto_20150907_1315.Migration* attribute), 128

operations (*tardis.tardis_portal.migrations.0002_auto_20150528_1128.Migration* attribute), 128

operations (*tardis.tardis_portal.migrations.0003_auto_20150907_1315.Migration* attribute), 128

operations (*tardis.tardis_portal.migrations.0004_storageboxoption_val.Migration* attribute), 128

[attribute](#)), 129
[operations \(tardis.tardis_portal.migrations.0005_datafile_add_size\)](#) ([tardis.tardis_portal.migrations.0005_datafile_add_size](#)), 231
[attribute](#)), 129
[operations \(tardis.tardis_portal.migrations.0006_datafile_remove_owner\)](#) ([tardis.tardis_portal.migrations.0006_datafile_remove_owner](#)), 222
[attribute](#)), 129
[operations \(tardis.tardis_portal.migrations.0007_remove_parameter_name\)](#) ([tardis.tardis_portal.migrations.0007_remove_parameter_name](#)), 132
[attribute](#)), 129
[operations \(tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres\)](#) ([tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres](#)), 119
[attribute](#)), 129
[operations \(tardis.tardis_portal.migrations.0009_auto_pagination\)](#) ([tardis.tardis_portal.migrations.0009_auto_pagination](#)), 130
[attribute](#)), 130
[operations \(tardis.tardis_portal.migrations.0010_auto_20160503_1643\)](#) ([tardis.tardis_portal.migrations.0010_auto_20160503_1643](#)), 144
[attribute](#)), 130
[operations \(tardis.tardis_portal.migrations.0011_auto_20160505_1643\)](#) ([tardis.tardis_portal.migrations.0011_auto_20160505_1643](#)), 180
[attribute](#)), 130
[operations \(tardis.tardis_portal.migrations.0012_user_authentication_approved\)](#) ([tardis.tardis_portal.migrations.0012_user_authentication_approved](#)), 136
[attribute](#)), 130
[operations \(tardis.tardis_portal.migrations.0013_auto_20181002_162\)](#) ([tardis.tardis_portal.migrations.0013_auto_20181002_162](#)), 136
[attribute](#)), 130
[operations \(tardis.tardis_portal.migrations.0014_auto_20181002_162\)](#) ([tardis.tardis_portal.migrations.0014_auto_20181002_162](#)), 131
[attribute](#)), 131
[operations \(tardis.tardis_portal.migrations.0015_dataset_created_time\)](#) ([tardis.tardis_portal.migrations.0015_dataset_created_time](#)), 155
[attribute](#)), 131
[operations \(tardis.tardis_portal.migrations.0016_add_timestamps\)](#) ([tardis.tardis_portal.migrations.0016_add_timestamps](#)), 157
[attribute](#)), 131
[options \(tardis.tardis_portal.models.storage.StorageBox\)](#) ([tardis.tardis_portal.models.storage.StorageBox](#)), 172
[attribute](#)), 172
[oracle_dbops_hack \(\)](#) ([tardis.tardis_portal.hacks](#)), 229
[OracleSafeManager](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 232
[order \(tardis.tardis_portal.models.experiment.ExperimentAuthor\)](#) ([tardis.tardis_portal.models.experiment.ExperimentAuthor](#)), 148
[attribute](#)), 148
[order \(tardis.tardis_portal.models.parameters.ParameterName\)](#) ([tardis.tardis_portal.models.parameters.ParameterName](#)), 166
[attribute](#)), 166
[ordering \(tardis.tardis_portal.api.DataFileResource.Meta\)](#) ([tardis.tardis_portal.models.parameters.DatafileParameterClass](#)), 210
[attribute](#)), 210
[ordering \(tardis.tardis_portal.api.DatasetResource.Meta\)](#) ([tardis.tardis_portal.models.parameters.DatasetParameterClass](#)), 211
[attribute](#)), 211
[ordering \(tardis.tardis_portal.api.ExperimentResource.Meta\)](#) ([tardis.tardis_portal.models.parameters.ExperimentParameterClass](#)), 212
[attribute](#)), 212
[ordering \(tardis.tardis_portal.models.parameters.Parameter.Meta\)](#) ([tardis.tardis_portal.models.parameters.ParameterClass](#)), 162
[attribute](#)), 162
[ordering \(tardis.tardis_portal.models.parameters.ParameterSet.Meta\)](#) ([tardis.tardis_portal.models.parameters.ParameterSetClass](#)), 167
[attribute](#)), 167
[owned \(\)](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 230
[method](#)), 230
[owned_and_shared \(\)](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 231
[method](#)), 231
[owned_by_group \(\)](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 231
[method](#)), 231
[owned_by_user \(\)](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 231
[method](#)), 231
[owned_by_user_id \(\)](#) ([tardis.tardis_portal.managers.ExperimentManager](#)), 231
[method](#)), 231
[parameter_choices_format_error](#), 220
[parameter_name](#) ([tardis.tardis_portal.models.parameters.FreeTextSearchField](#)), 160
[attribute](#)), 160
[parameter_name_id](#) ([tardis.tardis_portal.models.parameters.FreeTextSearchField](#)), 160
[attribute](#)), 160
[parameter_type \(tardis.tardis_portal.models.parameters.DatafileParameterClass\)](#) ([tardis.tardis_portal.models.parameters.DatafileParameterClass](#)), 154
[attribute](#)), 154
[parameter_type \(tardis.tardis_portal.models.parameters.DatasetParameterClass\)](#) ([tardis.tardis_portal.models.parameters.DatasetParameterClass](#)), 156
[attribute](#)), 156
[parameter_type \(tardis.tardis_portal.models.parameters.ExperimentParameterClass\)](#) ([tardis.tardis_portal.models.parameters.ExperimentParameterClass](#)), 158
[attribute](#)), 158
[parameter_type \(tardis.tardis_portal.models.parameters.InstrumentParameterClass\)](#) ([tardis.tardis_portal.models.parameters.InstrumentParameterClass](#)), 161
[attribute](#)), 161
[parameter_type \(tardis.tardis_portal.models.parameters.ParameterClass\)](#) ([tardis.tardis_portal.models.parameters.ParameterClass](#)), 163
[attribute](#)), 163
[parameter_name_does_not_exist](#), 164
[parameter_name_multiple_objects_returned](#), 164
[parameter_name_form \(\)](#) ([tardis.tardis_portal.models.parameters.ParameterName](#)), 184
[in module](#)

<code>tardis.tardis_portal.templatetags.formfieldfilters</code>),	<code>password</code> (<code>tardis.apps.push_to.models.Credential</code> attribute), 92
<code>parametername_set</code> (<code>tardis.tardis_portal.models.parameters.Schema</code> attribute), 169	<code>PATH_LDAPADD</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterNameAdmin</code> (class in <code>tardis.tardis_portal.admin</code>), 206	<code>PATH_LDAPSEARCH</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterNameInline</code> (class in <code>tardis.tardis_portal.admin</code>), 207	<code>PATH_SCHEMA_DIR</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterNameManager</code> (class in <code>tardis.tardis_portal.managers</code>), 232	<code>PATH_SLAPD</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterNameResource</code> (class in <code>tardis.tardis_portal.api</code>), 214	<code>PATH_SLAPTEST</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterNameResource.Meta</code> (class in <code>tardis.tardis_portal.api</code>), 214	<code>PATH_TMPDIR</code> (<code>tardis.tardis_portal.tests.slapped.Slapd</code> attribute), 185
<code>ParameterResource</code> (class in <code>tardis.tardis_portal.api</code>), 215	<code>PICKLE</code> (<code>tardis.tardis_portal.models.storage.StorageBoxOption</code> attribute), 174
<code>parameters</code> (<code>tardis.tardis_portal.ParameterSetManager.ParameterSetManager</code> attribute), 204	<code>pluginId</code> (<code>tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta</code> attribute), 223
<code>ParameterSet</code> (class in <code>tardis.tardis_portal.models.parameters</code>), 166	<code>pluginId</code> (<code>tardis.tardis_portal.models.access_control.ObjectACL</code> attribute), 134
<code>parameterset</code> (<code>tardis.tardis_portal.models.parameters.DataFileParameter</code> attribute), 154	<code>port</code> (<code>tardis.apps.push_to.models.RemoteHost</code> attribute), 96
<code>parameterset</code> (<code>tardis.tardis_portal.models.parameters.DataFileParameter</code> attribute), 156	<code>prepare_experiment_creator()</code> (<code>tardis.tardis_portal.api.DataFileResource</code> method), 210
<code>parameterset</code> (<code>tardis.tardis_portal.models.parameters.ExperimentParameter</code> attribute), 158	<code>prepare_experiment()</code> (in module <code>tardis.tardis_portal.models.hooks</code>), 150
<code>parameterset</code> (<code>tardis.tardis_portal.models.parameters.ExperimentParameter</code> attribute), 161	<code>prepare_experiment_parameter()</code> (in module <code>tardis.tardis_portal.models.hooks</code>), 150
<code>parameterset</code> (<code>tardis.tardis_portal.models.parameters.InstrumentParameter</code> attribute), 161	<code>prepare_experimentauthor()</code> (in module <code>tardis.tardis_portal.models.hooks</code>), 150
<code>parameterset</code> (<code>tardis.tardis_portal.ParameterSetManager.ParameterSetManager</code> attribute), 204	<code>PREPARE_OUTPUT</code> (<code>tardis.default_settings</code> attribute), 46
<code>ParameterSet.Meta</code> (class in <code>tardis.tardis_portal.models.parameters</code>), 166	<code>prepare_experiment_creator()</code> (<code>tardis.search.search_indexes.ExperimentIndex</code> method), 117
<code>parameterset_id</code> (<code>tardis.tardis_portal.models.parameters.DataFileParameter</code> attribute), 154	<code>prepare_experiment_id_stored()</code> (<code>tardis.search.datafile_index.DataFileIndex</code> method), 116
<code>parameterset_id</code> (<code>tardis.tardis_portal.models.parameters.DataFileParameter</code> attribute), 156	<code>prepare_experiment_id_stored()</code> (<code>tardis.search.datafile_index.DataFileIndex</code> method), 116
<code>parameterset_id</code> (<code>tardis.tardis_portal.models.parameters.ExperimentParameter</code> attribute), 158	<code>prepare_experiment_id_stored()</code> (<code>tardis.search.search_indexes.DatasetIndex</code> method), 117
<code>parameterset_id</code> (<code>tardis.tardis_portal.models.parameters.ExperimentParameter</code> attribute), 161	<code>prepare_experimentauthor()</code> (<code>tardis.search.search_indexes.ExperimentIndex</code> method), 117
<code>ParameterSetManager</code> (class in <code>tardis.tardis_portal.ParameterSetManager</code>), 203	<code>prepare_output()</code> (<code>tardis.tardis_portal.download.UncachedTarStream</code> method), 219
<code>ParameterSetManagerMixin</code> (class in <code>tardis.tardis_portal.models.parameters</code>), 167	<code>prepare_text()</code> (<code>tardis.search.datafile_index.DataFileIndex</code> method), 116
<code>ParameterSetManagerTestCase</code> (class in <code>tardis.tardis_portal.tests.test_parametersets</code>), 192	<code>prepare_text()</code> (<code>tardis.search.search_indexes.DatasetIndex</code> method), 117
<code>ParameterSetResource</code> (class in <code>tardis.tardis_portal.api</code>), 215	<code>prepare_text()</code> (<code>tardis.search.search_indexes.ExperimentIndex</code> method), 117
	<code>prepend_urls()</code> (<code>tardis.tardis_portal.api.DataFileResource</code> method), 210

```

prepend_urls() (tardis.tardis_portal.api.DatasetResource attribute), 144
method), 211
PrettyJSONSerializer (class in (tardis.tardis_portal.models.experiment.Experiment
tardis.tardis_portal.api), 215 attribute), 144
private_key (tardis.apps.push_to.models.KeyPair at- PUBLICATION_SCHEMA_ROOT
tribute), 93 (tardis.tardis_portal.models.experiment.Experiment
attribute), 144
process_exception()
(tardis.tardis_portal.logging_middleware.LoggingMiddleware public_expt_rifcs() (in module
method), 229 tardis.tardis_portal.models.hooks), 150
process_request() PublishService (class in
(tardis.tardis_portal.auth.token_auth.TokenAuthMiddleware tardis.tardis_portal.publish.publishservice),
method), 124 176
process_response() PublishServiceTestCase (class in
(tardis.tardis_portal.logging_middleware.LoggingMiddleware tardis.tardis_portal.tests.test_publishservice),
method), 229 193
ProxyingMetadataRegistry (class in PushToConfig (class in tardis.apps.push_to.apps), 91
tardis.apps.oaipmh.server), 83 put_detail() (tardis.tardis_portal.api.DataFileResource
method), 210
ProxyingServer (class in tardis.apps.oaipmh.server), 83, 242
psm (tardis.tardis_portal.creativecommonshandler.Creative CommonsHandler
attribute), 218 query_string() (tardis.search.utils.SearchQueryString
method), 118
public() (tardis.tardis_portal.managers.ExperimentManager method), 118
queryset (tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta
attribute), 103
public_access (tardis.tardis_portal.models.experiment.Experiment attribute), 103
queryset (tardis.tardis_portal.api.DatafileParameterResource.Meta
attribute), 147 attribute), 210
PUBLIC_ACCESS_CHOICES queryset (tardis.tardis_portal.api.DatafileParameterSetResource.Meta
attribute), 144 attribute), 211
PUBLIC_ACCESS_EMBARGO queryset (tardis.tardis_portal.api.DataFileResource.Meta
attribute), 144 attribute), 210
PUBLIC_ACCESS_FULL queryset (tardis.tardis_portal.api.DatasetParameterResource.Meta
attribute), 144 attribute), 211
queryset (tardis.tardis_portal.api.DatasetParameterSetResource.Meta
attribute), 211
public_access_implies_distribution() queryset (tardis.tardis_portal.api.DatasetResource.Meta
attribute), 147 attribute), 211
queryset (tardis.tardis_portal.api.ExperimentParameterResource.Meta
attribute), 212
PUBLIC_ACCESS_METADATA queryset (tardis.tardis_portal.api.ExperimentParameterSetResource.Meta
attribute), 144 attribute), 212
PUBLIC_ACCESS_NONE queryset (tardis.tardis_portal.api.ExperimentResource.Meta
attribute), 145 attribute), 212
queryset (tardis.tardis_portal.api.FacilityResource.Meta
attribute), 213
public_data() (in module tardis.tardis_portal.views.pages), 201
queryset (tardis.tardis_portal.api.GroupResource.Meta
attribute), 213
public_download_allowed() queryset (tardis.tardis_portal.api.InstrumentResource.Meta
attribute), 147 attribute), 213
queryset (tardis.tardis_portal.api.LocationResource.Meta
attribute), 213
public_key (tardis.apps.push_to.models.KeyPair at- queryset (tardis.tardis_portal.api.ObjectACLResource.Meta
tribute), 94 attribute), 214
public_key (tardis.apps.sftp.models.SFTPPublicKey queryset (tardis.tardis_portal.api.ParameterNameResource.Meta
tribute), 105 attribute), 215
PUBLICATION_DETAILS_SCHEMA
(tardis.tardis_portal.models.experiment.Experiment

```

`queryset (tardis.tardis_portal.api.ReplicaResource.Meta.remote_hosts (tardis.apps.push_to.models.Credential attribute), 215`
`attribute), 92`
`queryset (tardis.tardis_portal.api.SchemaResource.Meta.remote_user (tardis.apps.push_to.models.Credential attribute), 216`
`attribute), 92`
`queryset (tardis.tardis_portal.api.StorageBoxAttributeResource.Meta (class in tardis.apps.push_to.models), 95`
`attribute), 216`
`RemoteHost.DoesNotExist, 95`
`queryset (tardis.tardis_portal.api.StorageBoxOptionResource.Meta.RemoteHost.MultipleObjectsReturned, 95`
`attribute), 216`
`RemoteHostAdmin (class in`
`queryset (tardis.tardis_portal.api.StorageBoxResource.Meta tardis.apps.push_to.models), 96`
`attribute), 216`
`remove_auth_method () (in module`
`queryset (tardis.tardis_portal.api.UserResource.Meta tardis.tardis_portal.auth.authentication),`
`attribute), 217`
`119`
`quote () (in module tardis.tardis_portal.tests.slappd), remove_csrf_token () (in module`
`186`
`tardis.tardis_portal.views.utils), 203`

R
`RANGE_COMPARISON (tardis.tardis_portal.models.parameters.Param (tardis.tardis_portal.forms.NoInput method),`
`attribute), 164`
`227`
`rapidConnectEduPersonTargetedID render () (tardis.tardis_portal.template.tags.capture.CaptureNode`
`(tardis.tardis_portal.models.access_control.UserProfile method), 178`
`attribute), 135`
`render () (tardis.tardis_portal.template.tags.dynurl.DynUrlNode`
`RawSearchForm (class in tardis.tardis_portal.forms), method), 178`
`227`
`render () (tardis.tardis_portal.widgets.CommaSeparatedInput`
`rcauth () (in module method), 235`
`tardis.tardis_portal.views.authentication), render () (tardis.tardis_portal.widgets.Label method),`
`198`
`235`
`read_detail () (tardis.apps.sftp.api.SFTPACLAuthorization render_error_message () (in module`
`method), 103`
`tardis.apps.push_to.views), 99`
`read_detail () (tardis.tardis_portal.api.ACLAuthorization render_error_message () (in module`
`method), 209`
`tardis.tardis_portal.shortcuts), 233`
`read_list () (tardis.apps.sftp.api.SFTPACLAuthorization render_mustache () (in module`
`method), 103`
`tardis.tardis_portal.util), 234`
`read_list () (tardis.tardis_portal.api.ACLAuthorization render_public_access_badge () (in module`
`method), 209`
`tardis.tardis_portal.util), 234`
`readMetadata () (tardis.apps.oaipmh.server.ProxyingMetadataRegistry.render_response_index () (in module`
`method), 83`
`tardis.tardis_portal.shortcuts), 233`
`redirect_back_with_error () (in module render_response_search () (in module`
`tardis.tardis_portal.shortcuts), 233`
`tardis.tardis_portal.shortcuts), 233`
`RegisterExperimentForm (class in render_success_message () (in module`
`tardis.tardis_portal.forms), 227`
`tardis.apps.push_to.views), 99`
`registerReader () (tardis.apps.oaipmh.server.ProxyingMetadataRegistry.render_style () (in module`
`method), 83`
`tardis.tardis_portal.shortcuts), 233`
`registerWriter () (tardis.apps.oaipmh.server.ProxyingMetadataRegistry.render_style () (in module`
`method), 83`
`tardis.tardis_portal.shortcuts), 233`
`REGISTRATION_OPEN (in module ReplicaResource (class in tardis.tardis_portal.api),`
`tardis.default_settings.auth), 113`
`215`
`registration_processor () (in module ReplicaResource.Meta (class in`
`tardis.tardis_portal.context_processors), tardis.tardis_portal.api), 215`
`217`
`ReplicaResourceTest (class in`
`RegistrationForm (class in tardis.tardis_portal.tests.api.test_replica_resource),`
`tardis.tardis_portal.forms), 227`
`183`
`RelatedInfoForm (class in REQUIRE_DATAFILE_CHECKSUMS`
`tardis.apps.related_info.forms), 101`
`(tardis.default_settings attribute), 46`
`REQUIRE_DATAFILE_SIZES (tardis.default_settings`

- attribute*), 46
- REQUIRE_SSL_TO_GENERATE_KEY (in module *tardis.apps.sftp.default_settings*), 104
- REQUIRE_VALIDATION_ON_INGESTION (*tardis.default_settings* attribute), 46
- requires_admin_approval() (in module *tardis.apps.social_auth.auth.social_auth*), 111
- resource_name (*tardis.apps.sftp.api.SFTPPublicKeyAppResource* attribute), 103
- resource_name (*tardis.tardis_portal.api.DataFileResource* attribute), 210
- restart() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
- RestfulExperimentParameterSet (class in *tardis.tardis_portal.shortcuts*), 233
- retrieve_access_list_group_readonly() (in module *tardis.tardis_portal.views.authorisation*), 198
- retrieve_access_list_user_readonly() (in module *tardis.tardis_portal.views.authorisation*), 198
- retrieve_group_list() (in module *tardis.tardis_portal.views.authorisation*), 198
- retrieve_group_list_by_user() (in module *tardis.tardis_portal.views.authorisation*), 198
- retrieve_group_userlist_readonly() (in module *tardis.tardis_portal.views.authorisation*), 198
- retrieve_licenses() (in module *tardis.tardis_portal.views.ajax_json*), 197
- retrieve_owned_exps_list() (in module *tardis.tardis_portal.views.ajax_pages*), 197
- retrieve_shared_exps_list() (in module *tardis.tardis_portal.views.ajax_pages*), 197
- retrieve_user_list() (in module *tardis.tardis_portal.views.authorisation*), 198
- return_response_error() (in module *tardis.tardis_portal.shortcuts*), 233
- return_response_error_message() (in module *tardis.tardis_portal.shortcuts*), 233
- return_response_not_found() (in module *tardis.tardis_portal.shortcuts*), 233
- RFC
- RFC 3339, 232
- rfc3339() (in module *tardis.tardis_portal.rfc3339*), 232
- RifCsExperimentProvider (class in *tardis.apps.oaipmh.provider.experiment*), 80
- RifCsExperimentProvider.ExperimentWriter (class in *tardis.apps.oaipmh.provider.experiment*), 80
- RifCsExperimentProviderTestCase (class in *tardis.apps.oaipmh.tests.provider.test_experiment*), 82
- RifCsProvider (class in *tardis.tardis_portal.publish.provider.rifcsprovider*), 176
- RifCSTestCase (class in *tardis.apps.related_info.tests.test_oaipmh*), 99
- RegistrationForm (class in *tardis.tardis_portal.forms*), 228
- RightsForm.Meta (class in *tardis.tardis_portal.forms*), 228
- RightsFormTestCase (class in *tardis.tardis_portal.tests.test_forms*), 190
- RightsTestCase (class in *tardis.tardis_portal.tests.test_views*), 195
- RmExperimentTestCase (class in *tardis.tardis_portal.tests.test_rmexperiment*), 193
- rollback_migration() (in module *tardis.apps.openid_migration.utils*), 90
- runFilters() (*tardis.tardis_portal.management.commands.runfilters* method), 127
- RunFiltersTestCase (class in *tardis.tardis_portal.tests.filters.test_middleware*), 184
- ## S
- safe (*tardis.tardis_portal.models.experiment.Experiment* attribute), 147
- sanitize_html() (in module *tardis.tardis_portal.templatetags.formfieldfilters*), 179
- save() (*tardis.apps.push_to.models.KeyPair* method), 94
- save() (*tardis.tardis_portal.forms.ExperimentForm* method), 225
- save() (*tardis.tardis_portal.forms.RegistrationForm* method), 228
- save() (*tardis.tardis_portal.models.access_control.UserAuthentication* method), 134
- save() (*tardis.tardis_portal.models.datafile.DataFile* method), 139
- save() (*tardis.tardis_portal.models.datafile.DataFileObject* method), 140
- save() (*tardis.tardis_portal.models.dataset.Dataset* method), 144
- save() (*tardis.tardis_portal.models.experiment.Experiment* method), 147
- save() (*tardis.tardis_portal.models.experiment.ExperimentAuthor* method), 148
- save() (*tardis.tardis_portal.models.facility.Facility* method), 150

`save()` (`tardis.tardis_portal.models.instrument.InstrumentSchemaResourceTest` (class in `tardis.tardis_portal.tests.api.test_schema_resource`), method), 151
`save()` (`tardis.tardis_portal.models.parameters.ExperimentParameterSet` (class in `tardis.tardis_portal.models.parameters`), method), 158
`save()` (`tardis.tardis_portal.models.parameters.ParametersSearch` (class in `tardis.tardis_portal.models.parameters`), method), 167
`save_datafile_add_form()` (in module `tardis.tardis_portal.forms`), 229
`save_datafile_edit_form()` (in module `tardis.tardis_portal.forms`), 229
`save_license()` (`tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler` (class in `tardis.tardis_portal.creativecommonshandler`), method), 218
`save_m2m()` (`tardis.tardis_portal.forms.ExperimentForm.FullExperimentForm` (class in `tardis.tardis_portal.forms`), method), 225
`save_metadata()` (`tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter` (class in `tardis.tardis_portal.filters.jeolsem`), method), 125
`save_with_random_token()` (`tardis.tardis_portal.models.token.Token` (class in `tardis.tardis_portal.models.token`), method), 175
`Schema` (class in `tardis.tardis_portal.models.parameters`), 167
`schema` (`tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler` (class in `tardis.tardis_portal.creativecommonshandler`), attribute), 218
`SCHEMA` (`tardis.tardis_portal.filters.jeolsem.JEOLSEMFilter` (class in `tardis.tardis_portal.filters.jeolsem`), attribute), 125
`schema` (`tardis.tardis_portal.models.parameters.DatafileParameterSet` (class in `tardis.tardis_portal.models.parameters`), attribute), 155
`schema` (`tardis.tardis_portal.models.parameters.DatasetParameterSet` (class in `tardis.tardis_portal.models.parameters`), attribute), 157
`schema` (`tardis.tardis_portal.models.parameters.ExperimentParameterSet` (class in `tardis.tardis_portal.models.parameters`), attribute), 159
`schema` (`tardis.tardis_portal.models.parameters.InstrumentParameterSet` (class in `tardis.tardis_portal.models.parameters`), attribute), 162
`schema` (`tardis.tardis_portal.models.parameters.ParametersNameSearchEntities` (class in `tardis.tardis_portal.models.parameters`), attribute), 166
`schema` (`tardis.tardis_portal.models.parameters.ParametersSearchGroups` (class in `tardis.tardis_portal.models.parameters`), attribute), 167
`schema` (`tardis.tardis_portal.shortcuts.RestfulExperimentParameterSet` (class in `tardis.tardis_portal.shortcuts`), attribute), 233
`Schema.DoesNotExist`, 167
`Schema.MultipleObjectsReturned`, 168
`Schema.UnsupportedType`, 168
`schema_id` (`tardis.tardis_portal.models.parameters.ParameterName` (class in `tardis.tardis_portal.models.parameters`), attribute), 166
`schema_id` (`tardis.tardis_portal.models.parameters.ParameterSet` (class in `tardis.tardis_portal.models.parameters`), attribute), 167
`SchemaAdmin` (class in `tardis.tardis_portal.admin`), 207
`SchemaManager` (class in `tardis.tardis_portal.managers`), 232
`SchemaResource` (class in `tardis.tardis_portal.api`), 215
`SchemaResource.Meta` (class in `tardis.tardis_portal.api`), 215

`search()` (in module `tardis.apps.equipment.views`), 77
`search()` (`tardis.tardis_portal.forms.RawSearchForm` (class in `tardis.tardis_portal.forms`), method), 227
`search()` (`tardis.tardis_portal.search_backend.HighlightSearchBackend` (class in `tardis.tardis_portal.search_backend`), method), 233
`search()` (`tardis.tardis_portal.admin.DatafileAdmin` (class in `tardis.tardis_portal.admin`), attribute), 205
`search()` (`tardis.tardis_portal.admin.DatasetAdmin` (class in `tardis.tardis_portal.admin`), attribute), 205
`search()` (`tardis.tardis_portal.admin.ExperimentAdmin` (class in `tardis.tardis_portal.admin`), attribute), 205
`search()` (`tardis.tardis_portal.admin.FacilityAdmin` (class in `tardis.tardis_portal.admin`), attribute), 206
`search()` (`tardis.tardis_portal.admin.InstrumentAdmin` (class in `tardis.tardis_portal.admin`), attribute), 206
`search()` (`tardis.tardis_portal.admin.ObjectACLAdmin` (class in `tardis.tardis_portal.admin`), attribute), 206
`search()` (`tardis.tardis_portal.admin.ParameterNameAdmin` (class in `tardis.tardis_portal.admin`), attribute), 207
`search()` (`tardis.tardis_portal.admin.SchemaAdmin` (class in `tardis.tardis_portal.admin`), attribute), 207
`search()` (`tardis.tardis_portal.admin.StorageBoxAdmin` (class in `tardis.tardis_portal.admin`), attribute), 207
`search()` (`tardis.tardis_portal.admin.UserAuthenticationAdmin` (class in `tardis.tardis_portal.admin`), attribute), 209
`search_quick()` (in module `tardis.search.views`), 118
`search_entities()` (`tardis.tardis_portal.auth.authservice.AuthService` (class in `tardis.tardis_portal.auth.authservice`), method), 121
`search_groups()` (`tardis.tardis_portal.auth.authservice.AuthService` (class in `tardis.tardis_portal.auth.authservice`), method), 121
`search_groups()` (`tardis.tardis_portal.auth.interfaces.GroupProvider` (class in `tardis.tardis_portal.auth.interfaces`), method), 123
`search_groups()` (`tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider` (class in `tardis.tardis_portal.auth.localdb_auth`), method), 124
`search_groups()` (`tardis.tardis_portal.auth.token_auth.TokenGroupProvider` (class in `tardis.tardis_portal.auth.token_auth`), method), 125
`search_groups()` (`tardis.tardis_portal.tests.test_authservice.MockGroupProvider` (class in `tardis.tardis_portal.tests.test_authservice`), method), 188
`SearchQueryString` (class in `tardis.search.utils`), 118
`SearchQueryTypeUnprovidedError`, 220
`SearchTestCase` (class in `tardis.tardis_portal.tests.tests`), 196
`search_users()` (`tardis.tardis_portal.auth.authservice.AuthService` (class in `tardis.tardis_portal.auth.authservice`), method), 121
`search_users()` (`tardis.tardis_portal.auth.interfaces.UserProvider` (class in `tardis.tardis_portal.auth.interfaces`), method), 123

SECRET_KEY, 45
 send_admin_email() (in module *tardis.apps.social_auth.auth.social_auth*), 111
 serial (*tardis.apps.equipment.models.Equipment* attribute), 76
 serializer (*tardis.tardis_portal.api.MyTardisResourceMeta* attribute), 214
 serializer (*tardis.tardis_portal.api.UserResource.Meta* attribute), 217
 SerializerTest (class in *tardis.tardis_portal.tests.api.test_serializer*), 183
 service (in module *tardis.analytics.tracker*), 73
 session_ended() (*tardis.apps.sftp.sftp.MyTSFTPServiceInterface* method), 107
 session_started() (*tardis.apps.sftp.sftp.MyTSFTPServiceInterface* method), 107
 set_debug() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_dn_suffix() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_param() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 204
 set_param_list() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 204
 set_params_from_dict() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 204
 set_port() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_root_cn() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_root_password() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_slapd_debug_level() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_tmpdir() (*tardis.tardis_portal.tests.slapd.Slapd* method), 186
 set_token() (in module *tardis.apps.push_to.oauth_tokens*), 97
 set_value() (*tardis.tardis_portal.models.parameters.Parameter* method), 163
 setPost() (*tardis.tardis_portal.tests.test_authservice.MockRequest* method), 188
 setUp() (*tardis.apps.equipment.tests.EquipmentTestCase* method), 77
 setUp() (*tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestSuite* method), 81
 setUp() (*tardis.apps.oaipmh.tests.provider.test_experiment_base.ExperimentBaseProviderTestSuite* method), 81
 setUp() (*tardis.apps.oaipmh.tests.test_oai.EndpointTestCase* method), 82
 setUp() (*tardis.apps.openid_migration.tests.test_forms.OpenIDMigrationTestCase* method), 85
 setUp() (*tardis.apps.openid_migration.tests.test_migration.OpenIDMigrationTestCase* method), 85
 setUp() (*tardis.apps.openid_migration.tests.test_models.ModelTestCase* method), 85
 setUp() (*tardis.apps.openid_migration.tests.test_views.OpenIDMigrationTestCase* method), 86
 setUp() (*tardis.apps.push_to.tests.test_models.ModelsTestCase* method), 91
 setUp() (*tardis.apps.related_info.tests.test_oaipmh.RifCTestCase* method), 99
 setUp() (*tardis.apps.related_info.tests.tests.CreateTestCase* method), 99
 setUp() (*tardis.apps.related_info.tests.tests.DeleteTestCase* method), 99
 setUp() (*tardis.apps.related_info.tests.tests.GetTestCase* method), 100
 setUp() (*tardis.apps.related_info.tests.tests.ListTestCase* method), 100
 setUp() (*tardis.apps.related_info.tests.tests.TabTestCase* method), 100
 setUp() (*tardis.apps.related_info.tests.tests.UpdateTestCase* method), 100
 setUp() (*tardis.apps.sftp.sftp.MyTSFTPRequestHandler* method), 106
 setUp() (*tardis.apps.sftp.tests.test_sftp.SFTPTestSuite* method), 102
 setUp() (*tardis.tardis_portal.tests.api.MyTardisResourceTestCase* method), 183
 setUp() (*tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTestCase* method), 181
 setUp() (*tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTestCase* method), 181
 setUp() (*tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTestCase* method), 182
 setUp() (*tardis.tardis_portal.tests.filters.test_jeolsem.JEOLSEMFilterTestCase* method), 184
 setUp() (*tardis.tardis_portal.tests.filters.test_middleware.FilterInitTestCase* method), 184
 setUp() (*tardis.tardis_portal.tests.filters.test_middleware.RunFiltersTestCase* method), 184
 setUp() (*tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase* method), 187
 setUp() (*tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase* method), 187
 setUp() (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase* method), 187
 setUp() (*tardis.tardis_portal.tests.test_collectstatic.CollectstaticTestCase* method), 188
 setUp() (*tardis.tardis_portal.tests.test_download.DownloadTestCase* method), 188

[setUp \(\) \(tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTest.setUp \(method\), 189](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_dumpschemas.DumpSchemaTestCase.setUp \(method\), 189](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase.setUp \(method\), 189](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_forms.RightsFormTestCase.setUp \(method\), 190](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_iiif.ExtraTestCases.setUp \(method\), 190](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_iiif.Level0TestCase.setUp \(method\), 190](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_iiif.Level1TestCase.setUp \(method\), 190](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_iiif.Level2TestCase.setUp \(method\), 190](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_ldap.LDAPTest.setUp \(method\), 191](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_models.ModelTestCase.setUp \(method\), 191](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_parametersets.EditableParametersetTestCase.setUp \(method\), 192](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_parametersets.ParametersetModelTestCase.setUp \(method\), 192](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase.setUp \(method\), 193](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_storage.ModelTestCase.setUp \(method\), 193](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_tar_download.TarDownloadTestCase.setUp \(method\), 194](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase.setUp \(method\), 194](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_tokens.TokenTestCase.setUp \(method\), 194](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.ContextualViewTestCase.setUp \(method\), 195](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.ExperimentListViewTestCase.setUp \(method\), 195](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.ExperimentTestCase.setUp \(method\), 195](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.listTestCase.setUp \(method\), 196](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.UploadTestCase.setUp \(method\), 195](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.UserListTestCase.setUp \(method\), 196](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.ViewTemplateContextsTestCase.setUp \(method\), 196](#)
[setUp \(\) \(tardis.tardis_portal.tests.test_views.SearchTestCase.setUp \(method\), 196](#)
[sftp_access \(\) \(in module tardis.apps.sftp.views\), 111](#)
[sftp_keys \(\) \(in module tardis.apps.sftp.views\), 111](#)
[SFTP_USERNAME_ATTRIBUTE \(in module](#)

[Slapd \(class in tardis.tardis_portal.tests.slapped\), 185](#)
[SocialAuthConfig \(class in tardis.apps.social_auth.apps\), 112](#)
[Span \(class in tardis.tardis_portal.widgets\), 235](#)
[split_path \(\) \(in module tardis.tardis_portal.util\), 234](#)
[SPONSORED_TEXT \(in module](#)

[tardis.default_settings.site_customisations](#)),
[115](#)
[start\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#)
[method](#)), [186](#)
[start_server\(\)](#) (in module [tardis.apps.sftp.sftp](#)),
[110](#)
[start_time](#) ([tardis.tardis_portal.models.experiment.Experiment](#)
[attribute](#)), [147](#)
[started\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#)
[method](#)), [186](#)
[stat\(\)](#) ([tardis.apps.sftp.sftp.MyTSFTPHandle](#)
[method](#)), [106](#)
[stat\(\)](#) ([tardis.apps.sftp.sftp.MyTSFTPServerInterface](#)
[method](#)), [107](#)
[STATIC_ROOT](#) ([tardis.default_settings](#) attribute), [48](#)
[STATIC_URL](#) ([tardis.default_settings](#) attribute), [48](#)
[StaticField](#) (class in [tardis.tardis_portal.forms](#)), [228](#)
[stats\(\)](#) (in module [tardis.tardis_portal.views.pages](#)),
[202](#)
[status](#) ([tardis.tardis_portal.models.datafile.DataFile](#)
[attribute](#)), [139](#)
[status](#) ([tardis.tardis_portal.models.storage.StorageBox](#)
[attribute](#)), [173](#)
[status_code](#) ([tardis.tardis_portal.views.utils.HttpResponseMethodNotAllowed](#)
[attribute](#)), [203](#)
[status_code](#) ([tardis.tardis_portal.views.utils.HttpResponseSeeAlso](#)
[attribute](#)), [203](#)
[stop\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#) method),
[186](#)
[storage_box](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#)
[attribute](#)), [140](#)
[storage_box](#) ([tardis.tardis_portal.models.parameters.DatafileParameterSet](#)
[attribute](#)), [155](#)
[storage_box](#) ([tardis.tardis_portal.models.parameters.DatafileParameterSet](#)
[attribute](#)), [157](#)
[storage_box](#) ([tardis.tardis_portal.models.parameters.ExperimentParameterSet](#)
[attribute](#)), [159](#)
[storage_box](#) ([tardis.tardis_portal.models.parameters.InstallationParameterSet](#)
[attribute](#)), [162](#)
[storage_box](#) ([tardis.tardis_portal.models.parameters.ParameterSet](#)
[attribute](#)), [167](#)
[storage_box](#) ([tardis.tardis_portal.models.storage.StorageBoxAttribute](#)
[attribute](#)), [173](#)
[storage_box](#) ([tardis.tardis_portal.models.storage.StorageBoxOption](#)
[attribute](#)), [174](#)
[storage_box_id](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#)
[attribute](#)), [141](#)
[storage_box_id](#) ([tardis.tardis_portal.models.storage.StorageBoxAttribute](#)
[attribute](#)), [174](#)
[storage_box_id](#) ([tardis.tardis_portal.models.storage.StorageBoxOption](#)
[attribute](#)), [174](#)
[storage_type](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#)
[attribute](#)), [141](#)
[storage_type](#) ([tardis.tardis_portal.models.storage.StorageBox](#)
[attribute](#)), [173](#)
[StorageBox](#) (class in
[tardis.tardis_portal.models.storage](#)), [169](#)
[StorageBox.DoesNotExist](#), [170](#)
[StorageBox.MultipleObjectsReturned](#), [170](#)
[StorageBoxAdmin](#) (class in
[tardis.tardis_portal.admin](#)), [207](#)
[StorageBoxAttribute](#) (class in
[tardis.tardis_portal.models.storage](#)), [173](#)
[StorageBoxAttribute.DoesNotExist](#), [173](#)
[StorageBoxAttribute.MultipleObjectsReturned](#),
[173](#)
[StorageBoxAttributeInline](#) (class in
[tardis.tardis_portal.admin](#)), [207](#)
[StorageBoxAttributeInlineForm](#) (class in
[tardis.tardis_portal.admin](#)), [207](#)
[StorageBoxAttributeInlineForm.Meta](#) (class
in [tardis.tardis_portal.admin](#)), [207](#)
[StorageBoxAttributeResource](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[StorageBoxAttributeResource.Meta](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[StorageBoxForm](#) (class in
[tardis.tardis_portal.admin](#)), [208](#)
[StorageBoxForm.Meta](#) (class in
[tardis.tardis_portal.admin](#)), [208](#)
[StorageBoxOption](#) (class in
[tardis.tardis_portal.models.storage](#)), [174](#)
[StorageBoxOption.DoesNotExist](#), [174](#)
[StorageBoxOption.MultipleObjectsReturned](#),
[174](#)
[StorageBoxOptionInline](#) (class in
[tardis.tardis_portal.admin](#)), [208](#)
[StorageBoxOptionInlineForm](#) (class in
[tardis.tardis_portal.admin](#)), [208](#)
[StorageBoxOptionInlineForm.Meta](#) (class in
[tardis.tardis_portal.admin](#)), [209](#)
[StorageBoxOptionResource](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[StorageBoxOptionResource.Meta](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[StorageBoxResource](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[StorageBoxResource.Meta](#) (class in
[tardis.tardis_portal.api](#)), [216](#)
[storage_download_datafiles\(\)](#) (in module
[tardis.tardis_portal.download](#)), [219](#)
[StorageBoxAdmin](#) ([tardis.tardis_portal.models.parameters.ParameterName](#)
[attribute](#)), [164](#)
[StorageBoxOption](#) ([tardis.tardis_portal.models.storage.StorageBoxOption](#)
[attribute](#)), [174](#)
[StorageBoxOption.value](#) ([tardis.tardis_portal.models.parameters.Parameter](#)
[attribute](#)), [163](#)
[StorageBoxType](#) ([tardis.tardis_portal.models.parameters.Schema](#)

attribute), 169
 suite() (in module tardis.apps.equipment.tests), 77
 suite() (in module tardis.tardis_portal.tests.tests), 197
 sum_sizes() (tardis.tardis_portal.models.datafile.DataFile
 class method), 139
 supports_anonymous_user
 (tardis.tardis_portal.auth.authorisation.ACLAwareBackend
 attribute), 120
 supports_object_permissions
 (tardis.tardis_portal.auth.authorisation.ACLAwareBackend
 attribute), 120
 SYSTEM_OWNED (tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta.OwnedACL
 attribute), 222
 SYSTEM_OWNED (tardis.tardis_portal.models.access_control.ObjectACL
 attribute), 132
 system_owned_groups()
 (tardis.tardis_portal.managers.ExperimentManager
 method), 231

T

TabTestCase (class in
 tardis.apps.related_info.tests.tests), 100
 tag (tardis.tardis_portal.widgets.Label attribute), 235
 tag (tardis.tardis_portal.widgets.Span attribute), 235
 TAPE (tardis.tardis_portal.models.storage.StorageBox
 attribute), 170
 tardis (module), 238
 tardis.analytics (module), 74
 tardis.analytics.apps (module), 73
 tardis.analytics.ga (module), 73
 tardis.analytics.tracker (module), 73
 tardis.app_config (module), 237
 tardis.apps (module), 112
 tardis.apps.deep_storage_download_mapper (module), 74
 tardis.apps.deep_storage_download_mapper.mapper (module), 74
 tardis.apps.deep_storage_download_mapper.tape (module), 74
 tardis.apps.dl_mapper_df_dir_only (module), 75
 tardis.apps.dl_mapper_df_dir_only.mapper (module), 74
 tardis.apps.dl_mapper_df_dir_only.urls (module), 75
 tardis.apps.equipment (module), 77
 tardis.apps.equipment.admin (module), 75
 tardis.apps.equipment.forms (module), 75
 tardis.apps.equipment.migrations (module), 75
 tardis.apps.equipment.migrations.0001_initial (module), 75
 tardis.apps.equipment.models (module), 76
 tardis.apps.equipment.south_migrations (module), 75
 tardis.apps.equipment.tests (module), 77
 tardis.apps.equipment.urls (module), 77
 tardis.apps.equipment.views (module), 77
 tardis.apps.filepicker (module), 78
 tardis.apps.filepicker.filepicker_settings (module), 77
 tardis.apps.filepicker.urls (module), 77
 tardis.apps.filepicker.utils (module), 78
 tardis.apps.filepicker.views (module), 78
 tardis.apps.forms_metadata (module), 84
 tardis.apps.oaipmh.models (module), 83
 tardis.apps.oaipmh.provider (module), 81
 tardis.apps.oaipmh.provider.base (module), 78
 tardis.apps.oaipmh.provider.experiment (module), 80
 tardis.apps.oaipmh.server (module), 83
 tardis.apps.oaipmh.tests (module), 82
 tardis.apps.oaipmh.tests.provider (module), 82
 tardis.apps.oaipmh.tests.provider.test_base (module), 81
 tardis.apps.oaipmh.tests.provider.test_experiment (module), 81
 tardis.apps.oaipmh.tests.test_oai (module), 82
 tardis.apps.oaipmh.urls (module), 84
 tardis.apps.oaipmh.views (module), 84
 tardis.apps.openid_migration (module), 90
 tardis.apps.openid_migration.apps (module), 86
 tardis.apps.openid_migration.context_processors (module), 86
 tardis.apps.openid_migration.default_settings (module), 86
 tardis.apps.openid_migration.email_text (module), 86
 tardis.apps.openid_migration.forms (module), 86
 tardis.apps.openid_migration.migration (module), 86
 tardis.apps.openid_migration.migrations (module), 85
 tardis.apps.openid_migration.migrations.0001_initial (module), 85
 tardis.apps.openid_migration.models (module), 87
 tardis.apps.openid_migration.tasks (module), 89
 tardis.apps.openid_migration.tests (module), 86
 tardis.apps.openid_migration.tests.test_forms

(*module*), 85

tardis.apps.openid_migration.tests.test_migration(*module*), 85

tardis.apps.openid_migration.tests.test_models(*module*), 85

tardis.apps.openid_migration.tests.test_views(*module*), 86

tardis.apps.openid_migration.urls (*module*), 89

tardis.apps.openid_migration.user_menu_modifiers(*module*), 89

tardis.apps.openid_migration.utils (*module*), 90

tardis.apps.openid_migration.views (*module*), 90

tardis.apps.push_to (*module*), 99

tardis.apps.push_to.apps (*module*), 91

tardis.apps.push_to.exceptions (*module*), 91

tardis.apps.push_to.migrations (*module*), 91

tardis.apps.push_to.migrations.0001_initial (*module*), 90

tardis.apps.push_to.migrations.0002_auto201605181953(*module*), 90

tardis.apps.push_to.models (*module*), 91

tardis.apps.push_to.oauth_tokens (*module*), 97

tardis.apps.push_to.ssh_authz (*module*), 97

tardis.apps.push_to.tasks (*module*), 97

tardis.apps.push_to.tests (*module*), 91

tardis.apps.push_to.tests.test_models (*module*), 91

tardis.apps.push_to.urls (*module*), 98

tardis.apps.push_to.utils (*module*), 98

tardis.apps.push_to.views (*module*), 98

tardis.apps.related_info (*module*), 101

tardis.apps.related_info.forms (*module*), 101

tardis.apps.related_info.models (*module*), 101

tardis.apps.related_info.settings (*module*), 101

tardis.apps.related_info.tests (*module*), 100

tardis.apps.related_info.tests.test_oaipmh (*module*), 99

tardis.apps.related_info.tests.tests (*module*), 99

tardis.apps.related_info.urls (*module*), 101

tardis.apps.related_info.views (*module*), 101

tardis.apps.sftp (*module*), 111

tardis.apps.sftp.admin (*module*), 103

tardis.apps.sftp.api (*module*), 103

tardis.apps.sftp.apps (*module*), 103

tardis.apps.sftp.default_settings (*module*), 104

tardis.apps.sftp.forms (*module*), 104

tardis.apps.sftp.management (*module*), 102

tardis.apps.sftp.management.commands (*module*), 102

tardis.apps.sftp.management.commands.sftpd (*module*), 101

tardis.apps.sftp.migrations (*module*), 102

tardis.apps.sftp.migrations.0001_initial (*module*), 102

tardis.apps.sftp.models (*module*), 104

tardis.apps.sftp.sftp (*module*), 105

tardis.apps.sftp.tests (*module*), 102

tardis.apps.sftp.tests.test_sftp (*module*), 102

tardis.apps.sftp.urls (*module*), 110

tardis.apps.sftp.user_menu_modifiers (*module*), 110

tardis.apps.sftp.views (*module*), 111

tardis.apps.social_auth (*module*), 112

tardis.apps.social_auth.apps (*module*), 112

tardis.apps.social_auth.auth (*module*), 112

tardis.apps.social_auth.auth.social_auth (*module*), 111

tardis.apps.social_auth.default_settings (*module*), 112

tardis.celery (*module*), 237

tardis.default_settings (*module*), 116

tardis.default_settings.admins (*module*), 112

tardis.default_settings.analytics (*module*), 112

tardis.default_settings.apps (*module*), 112

tardis.default_settings.auth (*module*), 113

tardis.default_settings.caches (*module*), 113

tardis.default_settings.celery_settings (*module*), 113

tardis.default_settings.custom_views (*module*), 113

tardis.default_settings.database (*module*), 114

tardis.default_settings.debug (*module*), 114

tardis.default_settings.downloads (*module*), 114

tardis.default_settings.email (*module*), 114

tardis.default_settings.filters (*module*), 115

[tardis.default_settings.frontend \(module\), 115](#)
[tardis.default_settings.i18n \(module\), 115](#)
[tardis.default_settings.localisation \(module\), 115](#)
[tardis.default_settings.logging \(module\), 115](#)
[tardis.default_settings.middlewares \(module\), 115](#)
[tardis.default_settings.publication \(module\), 115](#)
[tardis.default_settings.search \(module\), 115](#)
[tardis.default_settings.sharing \(module\), 115](#)
[tardis.default_settings.site_customisation \(module\), 115](#)
[tardis.default_settings.static_files \(module\), 115](#)
[tardis.default_settings.storage \(module\), 115](#)
[tardis.default_settings.templates \(module\), 116](#)
[tardis.default_settings.uploads \(module\), 116](#)
[tardis.default_settings.urls \(module\), 116](#)
[tardis.search \(module\), 118](#)
[tardis.search.datafile_index \(module\), 116](#)
[tardis.search.forms \(module\), 116](#)
[tardis.search.search_indexes \(module\), 117](#)
[tardis.search.urls \(module\), 118](#)
[tardis.search.utils \(module\), 118](#)
[tardis.search.views \(module\), 118](#)
[tardis.search_sites \(module\), 238](#)
[tardis.tardis_portal \(module\), 236, 238](#)
[tardis.tardis_portal.admin \(module\), 204](#)
[tardis.tardis_portal.api \(module\), 209](#)
[tardis.tardis_portal.auth \(module\), 125](#)
[tardis.tardis_portal.auth.authentication \(module\), 119](#)
[tardis.tardis_portal.auth.authorisation \(module\), 119](#)
[tardis.tardis_portal.auth.authservice \(module\), 120](#)
[tardis.tardis_portal.auth.decorators \(module\), 121](#)
[tardis.tardis_portal.auth.fix_circular \(module\), 122](#)
[tardis.tardis_portal.auth.interfaces \(module\), 123](#)
[tardis.tardis_portal.auth.localdb_auth \(module\), 124](#)
[tardis.tardis_portal.auth.token_auth \(module\), 124](#)
[tardis.tardis_portal.auth.utils \(module\), 125](#)
[tardis.tardis_portal.constants \(module\), 217](#)
[tardis.tardis_portal.context_processors \(module\), 217](#)
[tardis.tardis_portal.creativecommons_handler \(module\), 218](#)
[tardis.tardis_portal.deprecations \(module\), 218](#)
[tardis.tardis_portal.download \(module\), 219](#)
[tardis.tardis_portal.email \(module\), 219](#)
[tardis.tardis_portal.errors \(module\), 220](#)
[tardis.tardis_portal.fields \(module\), 220](#)
[tardis.tardis_portal.filters \(module\), 126](#)
[tardis.tardis_portal.filters.jeolsem \(module\), 125](#)
[tardis.tardis_portal.forms \(module\), 220](#)
[tardis.tardis_portal.hacks \(module\), 229](#)
[tardis.tardis_portal.iiif \(module\), 229](#)
[tardis.tardis_portal.logging_middleware \(module\), 229](#)
[tardis.tardis_portal.management \(module\), 128](#)
[tardis.tardis_portal.management.commands \(module\), 128](#)
[tardis.tardis_portal.management.commands.createuser \(module\), 126](#)
[tardis.tardis_portal.management.commands.dumpschema \(module\), 126](#)
[tardis.tardis_portal.management.commands.loadschema \(module\), 127](#)
[tardis.tardis_portal.management.commands.rmexperiment \(module\), 127](#)
[tardis.tardis_portal.management.commands.runfilters \(module\), 127](#)
[tardis.tardis_portal.managers \(module\), 230](#)
[tardis.tardis_portal.migrations \(module\), 131](#)
[tardis.tardis_portal.migrations.0001_initial \(module\), 128](#)
[tardis.tardis_portal.migrations.0001_squashed_0011 \(module\), 128](#)
[tardis.tardis_portal.migrations.0002_auto_20150528 \(module\), 128](#)
[tardis.tardis_portal.migrations.0003_auto_20150907 \(module\), 128](#)
[tardis.tardis_portal.migrations.0004_storageboxopt \(module\), 129](#)
[tardis.tardis_portal.migrations.0005_datafile_add \(module\), 129](#)
[tardis.tardis_portal.migrations.0006_datafile_remove \(module\), 129](#)

(*module*), 129

tardis.tardis_portal.migrations.0007_remove_parameter_value_index (*module*), 176

(*module*), 129

tardis.tardis_portal.migrations.0008_string_value_tardis_portal_index_apostrophe (*module*), 233

(*module*), 129

tardis.tardis_portal.migrations.0009_authenticate_tardis_portal.search_query (*module*), 233

(*module*), 130

tardis.tardis_portal.migrations.0010_authenticate_tardis_portal.shortcuts (*module*), 233

(*module*), 130

tardis.tardis_portal.migrations.0011_authenticate_tardis_portal.signals (*module*), 234

(*module*), 130

tardis.tardis_portal.migrations.0012_user_authentication_approvedrage.file_system (*module*), 177

(*module*), 130

tardis.tardis_portal.migrations.0013_authenticate_tardis_portal.tasks (*module*), 234

(*module*), 130

tardis.tardis_portal.migrations.0014_auto_20181102_180154 (*module*), 180

(*module*), 130

tardis.tardis_portal.migrations.0015_dataset_create_time (*module*), 177

(*module*), 131

tardis.tardis_portal.migrations.0016_add_timestamp (*module*), 177

(*module*), 131

tardis.tardis_portal.models (*module*), 176, 236, 238

tardis.tardis_portal.models.access_control (*module*), 178

(*module*), 131

tardis.tardis_portal.models.datafile (*module*), 178

(*module*), 136

tardis.tardis_portal.models.dataset (*module*), 178

(*module*), 141

tardis.tardis_portal.models.experiment (*module*), 179

(*module*), 144

tardis.tardis_portal.models.facility (*module*), 179

(*module*), 149

tardis.tardis_portal.models.hooks (*module*), 179

(*module*), 150

tardis.tardis_portal.models.instrument (*module*), 179

(*module*), 150

tardis.tardis_portal.models.jti (*module*), 179

(*module*), 151

tardis.tardis_portal.models.license (*module*), 179

(*module*), 152

tardis.tardis_portal.models.parameters (*module*), 180

(*module*), 153

tardis.tardis_portal.models.storage (*module*), 180

(*module*), 169

tardis.tardis_portal.models.token (*module*), 180

(*module*), 175

tardis.tardis_portal.ParameterSetManagertardis.tardis_portal.tests.api.test_auth (*module*), 180

(*module*), 203

tardis.tardis_portal.publish (*module*), 177

tardis.tardis_portal.publish.provider (*module*), 180

(*module*), 176

tardis.tardis_portal.publish.provider.rifcsprovider (*module*), 181

(*module*), 176

tardis.tardis_portal.publish.publishservice (*module*), 176

tardis.tardis_portal.rfc3339 (*module*), 232

tardis.tardis_portal.search_query (*module*), 233

tardis.tardis_portal.shortcuts (*module*), 233

tardis.tardis_portal.signals (*module*), 234

tardis.tardis_portal.storage (*module*), 177

tardis.tardis_portal.tasks (*module*), 234

tardis.tardis_portal.templatetags (*module*), 177

tardis.tardis_portal.templatetags.approved_user_tag (*module*), 177

tardis.tardis_portal.templatetags.basiccomparisonfilter (*module*), 178

tardis.tardis_portal.templatetags.bleach_tag (*module*), 178

tardis.tardis_portal.templatetags.capture (*module*), 178

tardis.tardis_portal.templatetags.dataset_tags (*module*), 178

tardis.tardis_portal.templatetags.dynurl (*module*), 178

tardis.tardis_portal.templatetags.experiment_tags (*module*), 179

tardis.tardis_portal.templatetags.experimentstats (*module*), 179

tardis.tardis_portal.templatetags.facility_tags (*module*), 179

tardis.tardis_portal.templatetags.feed (*module*), 179

tardis.tardis_portal.templatetags.formfieldfilters (*module*), 179

tardis.tardis_portal.templatetags.lookupfilters (*module*), 179

tardis.tardis_portal.templatetags.pagination (*module*), 180

tardis.tardis_portal.templatetags.xmldate (*module*), 180

tardis.tardis_portal.tests (*module*), 197

tardis.tardis_portal.tests.api (*module*), 183

tardis.tardis_portal.tests.api.test_auth (*module*), 180

tardis.tardis_portal.tests.api.test_datafile_metadata (*module*), 180

tardis.tardis_portal.tests.api.test_datafile_resources (*module*), 181

tardis.tardis_portal.tests.api.test_dataset_metadata (*module*), 181

(module), 181
 tardis.tardis_portal.tests.api.test_databases (module), 181
 tardis.tardis_portal.tests.api.test_experimentals (module), 181
 tardis.tardis_portal.tests.api.test_experimentals.tardis_portal.tests.test_ldap (module), 182
 tardis.tardis_portal.tests.api.test_facilities (module), 182
 tardis.tardis_portal.tests.api.test_group_permissions (module), 182
 tardis.tardis_portal.tests.api.test_instruments (module), 182
 tardis.tardis_portal.tests.api.test_location_permissions (module), 183
 tardis.tardis_portal.tests.api.test_replicas (module), 183
 tardis.tardis_portal.tests.api.test_schemas (module), 183
 tardis.tardis_portal.tests.api.test_serializers (module), 183
 tardis.tardis_portal.tests.auth (module), 184
 tardis.tardis_portal.tests.filters (module), 185
 tardis.tardis_portal.tests.filters.test_javascript (module), 184
 tardis.tardis_portal.tests.filters.test_middleware (module), 184
 tardis.tardis_portal.tests.ldap_ldif (module), 185
 tardis.tardis_portal.tests.mock_vbl_auth (module), 185
 tardis.tardis_portal.tests.mock_vbl_download (module), 185
 tardis.tardis_portal.tests.slapd (module), 185
 tardis.tardis_portal.tests.test_authentication (module), 187
 tardis.tardis_portal.tests.test_authorisation (module), 187
 tardis.tardis_portal.tests.test_authservice (module), 187
 tardis.tardis_portal.tests.test_collectstatic (module), 188
 tardis.tardis_portal.tests.test_createuser (module), 188
 tardis.tardis_portal.tests.test_download (module), 188
 tardis.tardis_portal.tests.test_download_apikey (module), 189
 tardis.tardis_portal.tests.test_dumpschemas (module), 189
 tardis.tardis_portal.tests.test_facility_overview (module), 189
 tardis.tardis_portal.tests.test_forms (module), 190
 tardis.tardis_portal.tests.test_iiif (module), 190
 tardis.tardis_portal.tests.test_ldap (module), 191
 tardis.tardis_portal.tests.test_loadschemas (module), 191
 tardis.tardis_portal.tests.test_models (module), 191
 tardis.tardis_portal.tests.test_parametersets (module), 192
 tardis.tardis_portal.tests.test_publishservice (module), 193
 tardis.tardis_portal.tests.test_rmexperiment (module), 193
 tardis.tardis_portal.tests.test_storage (module), 193
 tardis.tardis_portal.tests.test_tar_download (module), 194
 tardis.tardis_portal.tests.test_tasks (module), 194
 tardis.tardis_portal.tests.test_tokens (module), 194
 tardis.tardis_portal.tests.test_views (module), 195
 tardis.tardis_portal.tests.tests (module), 196
 tardis.tardis_portal.util (module), 234
 tardis.tardis_portal.views (module), 203, 236, 238
 tardis.tardis_portal.views.ajax_actions (module), 197
 tardis.tardis_portal.views.ajax_json (module), 197
 tardis.tardis_portal.views.ajax_pages (module), 197
 tardis.tardis_portal.views.authentication (module), 197
 tardis.tardis_portal.views.authorisation (module), 198
 tardis.tardis_portal.views.facilities (module), 198
 tardis.tardis_portal.views.images (module), 199
 tardis.tardis_portal.views.machine (module), 199
 tardis.tardis_portal.views.pages (module), 199
 tardis.tardis_portal.views.parameters (module), 202
 tardis.tardis_portal.views.upload (module), 203

tardis.tardis_portal.views.utils (module), 203	tearDown() (tardis.tardis_portal.tests.test_views.listTestCase method), 196
tardis.tardis_portal.widgets (module), 235	tearDown() (tardis.tardis_portal.tests.test_views.UploadTestCase method), 195
tardis.tardis_portal.xmlwriter (module), 235	tearDown() (tardis.tardis_portal.tests.test_views.UserListTestCase method), 196
tardis.test_on_mysql_settings (module), 238	tearDown() (tardis.tardis_portal.tests.test_views.ViewTemplateContextsTestCase method), 196
tardis.test_on_postgresql_settings (module), 238	tearDown() (tardis.tardis_portal.tests.test_views.SearchTestCase method), 196
tardis.test_settings (module), 238	temp_url (tardis.tardis_portal.api.DataFileResource attribute), 210
tardis.views (module), 238	template_name (tardis.search.views.SingleSearchView attribute), 118
TarDownDownloadTestCase (class in tardis.tardis_portal.tests.test_tar_download), 194	tearDown() (tardis.tardis_portal.views.pages.DatasetView attribute), 200
tarinfo_for_df() (tardis.tardis_portal.download.UncachedTarStream method), 219	tearDown() (tardis.tardis_portal.views.pages.ExperimentView attribute), 201
tearDown() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase method), 81	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentTestCase method), 81	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.apps.oaipmh.tests.provider.test_experiment.BaseExperimentTestCase method), 82	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.apps.oaipmh.tests.provider.test_experiment.BaseExperimentTestCase method), 82	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase method), 82	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.filters.test_middleware.RunFilterTestCase method), 184	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_authorisation.ObjectAccessTestCase method), 187	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase method), 187	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_collectstatic.CollectstaticTest method), 188	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_download.DownloadTestCase method), 188	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTest method), 189	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_dumpschemas.DumpSchemasTest method), 189	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_ldap.LDAPTest method), 191	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest method), 192	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTest method), 192	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_storage.ModelTestCase method), 193	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_tar_download.TarDownDownloadTest method), 194	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_tokens.TokenTestCase method), 194	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_views.ContextualViewTest method), 195	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201
tearDown() (tardis.tardis_portal.tests.test_views.ExperimentListsTest method), 195	tearDown() (tardis.tardis_portal.views.pages.IndexView attribute), 201

<code>test_cyberduck_connection_window()</code>	<code>method</code>), 91
<code>(tardis.apps.sftp.tests.test_sftp.SFTPTest</code>	<code>test_get_dataset_filter_instrument()</code>
<code>method</code>), 102	<code>(tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResou</code>
<code>test_datafile()</code> (<code>tardis.tardis_portal.tests.test_models.ModelTestCase</code>)	<code>method</code>), 181
<code>method</code>), 191	<code>test_get_dataset_no_instrument()</code>
<code>test_dataset()</code> (<code>tardis.tardis_portal.tests.test_models.ModelTestCase</code>)	<code>(tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResou</code>
<code>method</code>), 191	<code>method</code>), 181
<code>test_debug_serializer()</code>	<code>test_get_dataset_with_instrument()</code>
<code>(tardis.tardis_portal.tests.api.test_serializer.SerializerTest</code>	<code>(tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResou</code>
<code>method</code>), 183	<code>method</code>), 181
<code>test_default_expiry()</code>	<code>test_get_experiment()</code>
<code>(tardis.tardis_portal.tests.test_tokens.TokenTestCase</code>	<code>(tardis.tardis_portal.tests.api.test_experiment_resource.Experime</code>
<code>method</code>), 194	<code>method</code>), 182
<code>test_deleting_dfo_without_uri()</code>	<code>test_get_facility_by_id()</code>
<code>(tardis.tardis_portal.tests.test_models.ModelTestCase</code>	<code>(tardis.tardis_portal.tests.api.test_facility_resource.FacilityResou</code>
<code>method</code>), 192	<code>method</code>), 182
<code>test_djangoauth()</code>	<code>test_get_facility_by_manager_group_id()</code>
<code>(tardis.tardis_portal.tests.test_authentication.AuthenticationTest</code>	<code>(tardis.tardis_portal.tests.api.test_facility_resource.FacilityResou</code>
<code>method</code>), 187	<code>method</code>), 182
<code>test_do_migration()</code>	<code>test_get_facility_by_name()</code>
<code>(tardis.apps.openid_migration.tests.test_migration.OpenIDMigrationTest</code>	<code>(tardis.tardis_portal.tests.api.test_facility_resource.FacilityResou</code>
<code>method</code>), 85	<code>method</code>), 182
<code>test_download_apikey()</code>	<code>test_get_group_by_id()</code>
<code>(tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTest</code>	<code>(tardis.tardis_portal.tests.api.test_group_resource.GroupResource</code>
<code>method</code>), 189	<code>method</code>), 182
<code>test_download_file()</code>	<code>test_get_group_by_name()</code>
<code>(tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest</code>	<code>(tardis.tardis_portal.tests.api.test_group_resource.GroupResource</code>
<code>method</code>), 181	<code>method</code>), 182
<code>test_edit_datafile_params()</code>	<code>test_get_instrument_by_id()</code>
<code>(tardis.tardis_portal.tests.test_parametersets.EditParametersetTest</code>	<code>(tardis.tardis_portal.tests.api.test_instrument_resource.Instrumen</code>
<code>method</code>), 192	<code>method</code>), 182
<code>test_edit_dataset_params()</code>	<code>test_get_instrument_by_name()</code>
<code>(tardis.tardis_portal.tests.test_parametersets.EditParametersetTest</code>	<code>(tardis.tardis_portal.tests.api.test_instrument_resource.Instrumen</code>
<code>method</code>), 192	<code>method</code>), 182
<code>test_edit_experiment_params()</code>	<code>test_get_receiving_box()</code>
<code>(tardis.tardis_portal.tests.test_parametersets.EditParametersetTest</code>	<code>(tardis.tardis_portal.tests.test_storage.ModelTestCase</code>
<code>method</code>), 192	<code>method</code>), 193
<code>test_ensures_suitable_license()</code>	<code>test_get_session_expiry()</code>
<code>(tardis.tardis_portal.tests.test_forms.RightsFormTestCase</code>	<code>(tardis.tardis_portal.tests.test_tokens.TokenTestCase</code>
<code>method</code>), 190	<code>method</code>), 194
<code>test_existing_parameterset()</code>	<code>test_get_session_expiry_expired_token()</code>
<code>(tardis.tardis_portal.tests.test_parametersets.ParameterSetTestCase</code>	<code>(tardis.tardis_portal.tests.test_tokens.TokenTestCase</code>
<code>method</code>), 192	<code>method</code>), 194
<code>test_experiment()</code>	<code>test_get_session_expiry_near_expiry()</code>
<code>(tardis.tardis_portal.tests.test_models.ModelTestCase</code>	<code>(tardis.tardis_portal.tests.test_tokens.TokenTestCase</code>
<code>method</code>), 192	<code>method</code>), 194
<code>test_facility_overview_datafile_list()</code>	<code>test_getgroupbyid()</code>
<code>(tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTest</code>	<code>(tardis.tardis_portal.tests.test_ldap.LDAPTest</code>
<code>method</code>), 189	<code>method</code>), 191
<code>test_facility_overview_experiments()</code>	<code>test_getgroups()</code> (<code>tardis.tardis_portal.tests.test_ldap.LDAPTest</code>
<code>(tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTest</code>	<code>method</code>), 191
<code>method</code>), 189	<code>test_getgroupsforentity()</code>
<code>test_get_allowed_signing_services()</code>	<code>(tardis.tardis_portal.tests.test_ldap.LDAPTest</code>
<code>(tardis.apps.push_to.tests.test_models.ModelsTestCase</code>	<code>method</code>), 191

<code>test_getuserbyid()</code> (<code>tardis.tardis_portal.tests.test_ldap.LDAPTest</code> method), 191	<code>test_pretty_serializer()</code> (<code>tardis.tardis_portal.tests.api.test_serializer.SerializerTest</code> method), 183
<code>test_init()</code> (<code>tardis.apps.openid_migration.tests.test_forms.OpenIDMigrationFormTestCase</code> method), 85	<code>test_retrieve_access_list_tokens()</code> (<code>tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTest</code> method), 182
<code>test_instrument()</code> (<code>tardis.tardis_portal.tests.test_models.ModelTestCase</code> method), 192	<code>test_root()</code> (<code>tardis.tardis_portal.tests.tests.UserInterfaceTestCase</code> method), 197
<code>test_is_expired()</code> (<code>tardis.tardis_portal.tests.test_tokens.TokenTestCase</code> method), 194	<code>test_save_with_random_token()</code> (<code>tardis.tardis_portal.tests.test_tokens.TokenTestCase</code> method), 194
<code>test_keys_from_private_key_only()</code> (<code>tardis.apps.push_to.tests.test_models.ModelsTestCase</code> method), 91	<code>test_save_with_random_token_failures()</code> (<code>tardis.tardis_portal.tests.test_tokens.TokenTestCase</code> method), 194
<code>test_link_parameter_type()</code> (<code>tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase</code> method), 192	<code>test_save_with_random_token_gives_up()</code> (<code>tardis.tardis_portal.tests.test_tokens.TokenTestCase</code> method), 195
<code>test_link_parameter_type_extra()</code> (<code>tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase</code> method), 192	<code>test_search()</code> (<code>tardis.tardis_portal.tests.test_ldap.LDAPErrorTest</code> method), 191
<code>test_login()</code> (<code>tardis.tardis_portal.tests.tests.UserInterfaceTestCase</code> method), 197	<code>test_search_urls()</code> (<code>tardis.tardis_portal.tests.tests.UserInterfaceTestCase</code> method), 197
<code>test_migrate_accounts()</code> (<code>tardis.apps.openid_migration.tests.test_views.OpenIDMigrationViewTestCase</code> method), 86	<code>test_searchgroups()</code> (<code>tardis.tardis_portal.tests.test_ldap.LDAPTest</code> method), 191
<code>test_mydata_view()</code> (<code>tardis.tardis_portal.tests.test_views.ExperimentListsTest</code> method), 195	<code>test_sftp()</code> (<code>tardis.apps.sftp.tests.test_sftp.SFTPTTest</code> method), 102
<code>test_needs_confirmation()</code> (<code>tardis.tardis_portal.tests.test_forms.RightsFormTestCase</code> method), 190	<code>test_static_docs_dataset()</code> (<code>tardis.apps.sftp.tests.test_sftp.SFTPTTest</code> method), 102
<code>test_new_parameterset()</code> (<code>tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase</code> method), 192	<code>test_dynamic_docs_experiment()</code> (<code>tardis.apps.sftp.tests.test_sftp.SFTPTTest</code> method), 102
<code>test_OpenidUserMigration_creation()</code> (<code>tardis.apps.openid_migration.tests.test_models.ModelTestCase</code> method), 85	<code>test_sftp_key_connect()</code> (<code>tardis.apps.sftp.tests.test_sftp.SFTPTTest</code> method), 102
<code>test_parameter()</code> (<code>tardis.tardis_portal.tests.test_models.ModelTestCase</code> method), 192	<code>test_shared_fs_many_files()</code> (<code>tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest</code> method), 181
<code>test_pkey_to_credential()</code> (<code>tardis.apps.push_to.tests.test_models.ModelsTestCase</code> method), 91	<code>test_shared_fs_single_file()</code> (<code>tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest</code> method), 182
<code>test_post_dataset()</code> (<code>tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTest</code> method), 181	<code>test_shared_view()</code> (<code>tardis.tardis_portal.tests.test_views.ExperimentListsTest</code> method), 195
<code>test_post_experiment()</code> (<code>tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTest</code> method), 182	<code>test_storageboxoption()</code> (<code>tardis.tardis_portal.tests.test_storage.ModelTestCase</code> method), 192
<code>test_post_instrument()</code> (<code>tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTest</code> method), 182	<code>test_tar_experiment_download()</code>
<code>test_post_single_file()</code> (<code>tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest</code> method), 181	

(tardis.tardis_portal.tests.test_tar_download.TarDownloadTestCaseRequiredFormats()
 method), 194
 test_token_delete() (tardis.tardis_portal.tests.test_tokens.TokenTestCaseTestCanEditLockedExperiment()
 method), 195
 test_tz_aware_date_handling() (tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase
 method), 187
 test_tz_naive_date_handling() (tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCasePermissions()
 method), 192
 test_unauthorized_instrument_access_attempt() (tardis.tardis_portal.tests.test_authentication.ObjectACLTestCase
 method), 187
 test_unresolvable_link_parameter() (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCaseTestCreateAndEdit()
 method), 193
 test_urls() (tardis.tardis_portal.tests.test_views.ExperimentTestCaseTestCreateNewAccount()
 method), 195
 test_urls_with_some_content() (tardis.tardis_portal.tests.test_authentication.AuthenticationTestCaseMungeTestCaseportal.tests.test_authentication.AuthenticationTestC
 method), 192
 TEST_UTILS_DIR (tardis.tardis_portal.tests.slupd.SlapdTestCaseDatasetFile()
 attribute), 185
 test_wrong_size_verification() (tardis.tardis_portal.tests.test_download.DownloadTestCaseTestDatasetJson()
 method), 194
 testAccessWithoutReadPerms() (tardis.tardis_portal.tests.test_views.ExperimentTestCaseTestDatasetView()
 method), 195
 testAccessWithReadPerms() (tardis.tardis_portal.tests.test_views.ViewTemplateContextsTest
 method), 196
 testAll() (tardis.tardis_portal.tests.filters.test_middlewares.RunFilterTestCaseContextualViewTest
 method), 184
 testAuthenticate() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 187
 testCanCreate() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 184
 testCanDelete() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 99
 testCanGetInfoAsJSON() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 190
 testCanGetInfoAsXML() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 190
 testCanGetJpegFormat() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 190
 testCanGetOriginalImage() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 190
 testCreateNewAccount() (tardis.tardis_portal.tests.test_authentication.AuthenticationTestCaseMungeTestCaseportal.tests.test_authentication.AuthenticationTestC
 method), 187
 testDatasetFile() (tardis.tardis_portal.tests.test_download.DownloadTestCaseTestDatasetJson()
 method), 189
 testDatasetJson() (tardis.tardis_portal.tests.test_views.ExperimentTestCaseTestDatasetView()
 method), 195
 testDetailsDisplay() (tardis.tardis_portal.tests.test_views.ViewTemplateContextsTest
 method), 196
 testDetectsBadInput() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 195
 testDetectsBadInput() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 99
 testDetectsBadInput() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 100
 testDownload() (tardis.tardis_portal.tests.test_download.DownloadTestCaseTestDatasetView()
 method), 189
 testDryRun() (tardis.tardis_portal.tests.filters.test_middlewares.RunFilterTestCaseContextualViewTest
 method), 184
 testDumpSchemas() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 189
 testEquipmentDetail() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 77
 testEquipmentList() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 77
 testExistsInOaipmh() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 99
 testExperimentView() (tardis.tardis_portal.tests.test_views.ContextualViewTest
 method), 196

testFileUpload() (tardis.tardis_portal.tests.test_views.UploadTestCases method), 196	testUploadTestCases() (tardis.apps.related_info.tests.tests.GetTestCase method), 100
testFiltering() (tardis.tardis_portal.tests.filters.test_middleware.middleware.FilterTestCases method), 184	testHandlesSingleEntry() (tardis.apps.related_info.tests.tests.ListTestCase method), 100
testGetGroupList() (tardis.tardis_portal.tests.test_views.listTestCase method), 196	testIdentify() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase method), 81
testGetGroupsForEntity() (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCases method), 187	testIdentify() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase method), 82
testGetRecord() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase method), 81	testIdentify() (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase method), 82
testGetRecord() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase method), 82	testIdentify() (tardis.tardis_portal.tests.test_iiif.ExtraTestCases method), 190
testGetRecord() (tardis.apps.oaipmh.tests.provider.test_experiment.RijkExperimentProviderTestCase method), 82	testImageHasEtags() (tardis.tardis_portal.tests.test_iiif.ExtraTestCases method), 190
testGetRecord() (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase method), 82	testInfoHasEtags() (tardis.tardis_portal.tests.test_iiif.ExtraTestCases method), 190
testGetRecordHandlesInvalidIdentifiers() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase method), 81	testInitialisation() (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCases method), 187
testGetUserList() (tardis.tardis_portal.tests.test_views.listTestCase method), 196	testInitialisation() (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCases method), 193
testGetUserList() (tardis.tardis_portal.tests.test_views.UserListTestCase method), 196	testInitialisationNoProvider() (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCases method), 193
testGroupProvider() (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCases method), 187	testInteractive() (tardis.tardis_portal.tests.test_createuser.CreateUserTestCase method), 188
testGroupSearch() (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCases method), 187	testJEOLComplex() (tardis.tardis_portal.tests.filters.test_jeolsem.JEOLSEMFilterTestCases method), 184
testHandleRegions() (tardis.tardis_portal.tests.test_iiif.Level1TestCase method), 190	testJEOLSimple() (tardis.tardis_portal.tests.filters.test_jeolsem.JEOLSEMFilterTestCases method), 184
testHandleRotation() (tardis.tardis_portal.tests.test_iiif.Level1TestCase method), 190	testList() (tardis.tardis_portal.tests.filters.test_middleware.RunFiltersTestCases method), 184
testHandlesEmptySet() (tardis.apps.related_info.tests.tests.ListTestCase method), 100	testList() (tardis.tardis_portal.tests.test_rmexperiment.RmExperimentTestCases method), 193
testHandlesFound() (tardis.apps.related_info.tests.tests.GetTestCase method), 100	testListIdentifiers() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase method), 81
testHandleSizing() (tardis.tardis_portal.tests.test_iiif.Level1TestCase method), 190	testListIdentifiers() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase method), 82
testHandleSizing() (tardis.tardis_portal.tests.test_iiif.Level2TestCase method), 191	testListIdentifiers() (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase method), 82
testHandlesMultipleEntries() (tardis.apps.related_info.tests.tests.ListTestCase method), 100	testListIdentifiersDoesNotHandleSets() (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase method), 82

- tribute), 175
- Token.DoesNotExist, 175
- Token.MultipleObjectsReturned, 175
- token_delete() (in module *tardis.tardis_portal.views.authorisation*), 198
- token_set(*tardis.tardis_portal.models.experiment.Experiment* attribute), 147
- TokenAuthMiddleware (class in *tardis.tardis_portal.auth.token_auth*), 124
- TokenGroupProvider (class in *tardis.tardis_portal.auth.token_auth*), 124
- TokenTestCase (class in *tardis.tardis_portal.tests.test_tokens*), 194
- toxmldatetime() (in module *tardis.tardis_portal.templatetags.xmldate*), 180
- track_download() (in module *tardis.analytics.ga*), 73
- track_login() (in module *tardis.analytics.ga*), 73
- track_logout() (in module *tardis.analytics.ga*), 73
- tuples(*tardis.tardis_portal.tests.filters.test_middleware.Filter* attribute), 184
- tuples(*tardis.tardis_portal.tests.filters.test_middleware.Filter2* attribute), 184
- type(*tardis.apps.equipment.models.Equipment* attribute), 77
- type(*tardis.tardis_portal.models.parameters.Schema* attribute), 169
- TYPE_CHOICES(*tardis.tardis_portal.models.storage.StorageBoxOption* attribute), 174
- type_order(*tardis.tardis_portal.models.storage.StorageBox* attribute), 173
- TYPE_UNKNOWN(*tardis.tardis_portal.models.storage.StorageBox* attribute), 170
- TYPES(*tardis.tardis_portal.models.storage.StorageBox* attribute), 170
- ## U
- UncachedTarStream (class in *tardis.tardis_portal.download*), 219
- units(*tardis.tardis_portal.models.parameters.ParameterName* attribute), 166
- unpickled_value(*tardis.tardis_portal.models.storage.StorageBoxOption* attribute), 174
- UnsupportedSearchQueryTypeError, 220
- update_all_files() (in module *tardis.apps.sftp.sftp.DynamicTree* method), 106
- update_dataset_files() (in module *tardis.apps.sftp.sftp.DynamicTree* method), 106
- update_datasets() (in module *tardis.apps.sftp.sftp.DynamicTree* method), 106
- update_detail() (*tardis.tardis_portal.api.ACLAuthorization* method), 209
- update_experiments() (in module *tardis.apps.sftp.sftp.DynamicTree* method), 106
- update_list() (*tardis.tardis_portal.api.ACLAuthorization* method), 209
- update_mimetype() (in module *tardis.tardis_portal.models.datafile.DataFile* method), 139
- update_nothing() (*tardis.apps.sftp.sftp.DynamicTree* method), 106
- update_time(*tardis.tardis_portal.models.experiment.Experiment* attribute), 148
- UpdateTestCase (class in *tardis.apps.related_info.tests.tests*), 100
- upload_auth() (in module *tardis.tardis_portal.auth.decorators*), 122
- upload_complete() (in module *tardis.tardis_portal.views.upload*), 203
- UPLOAD_METHOD (in module *tardis.default_settings.uploads*), 116
- UploadTestCase (class in *tardis.tardis_portal.tests.test_views*), 195
- uri(*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 141
- url(*tardis.apps.equipment.models.Equipment* attribute), 77
- URL(*tardis.tardis_portal.models.parameters.ParameterName* attribute), 164
- url_safe_query() (*tardis.search.utils.SearchQueryString* method), 118
- urls(*tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase* attribute), 187
- urls(*tardis.tardis_portal.tests.test_tokens.TokenTestCase* attribute), 195
- use_orbiconnect() (in module *tardis.tardis_portal.views.pages*), 202
- user(*tardis.apps.push_to.models.Credential* attribute), 92
- user(*tardis.apps.sftp.models.SFTPPublicKey* attribute), 105
- user(*tardis.tardis_portal.models.access_control.GroupAdmin* attribute), 132
- user(*tardis.tardis_portal.models.access_control.UserProfile* attribute), 135
- user(*tardis.tardis_portal.models.token.Token* attribute), 106

tribute), 175

user_acls() (tardis.tardis_portal.managers.ExperimentManager attribute), 135

method), 231

user_details_processor() (in module tardis.tardis_portal.context_processors), 217

user_guide() (in module tardis.tardis_portal.views.pages), 202

user_id (tardis.apps.push_to.models.Credential attribute), 92

user_id (tardis.apps.sftp.models.SFTPPublicKey attribute), 105

user_id (tardis.tardis_portal.models.access_control.GroupAdmin attribute), 132

user_id (tardis.tardis_portal.models.access_control.UserProfile attribute), 136

user_id (tardis.tardis_portal.models.token.Token attribute), 176

USER_MENU_MODIFIERS (in module tardis.default_settings.apps), 112

user_menu_processor() (in module tardis.tardis_portal.context_processors), 217

user_migration (tardis.apps.openid_migration.models.OpenidACLMigration attribute), 87

user_migration_id (tardis.apps.openid_migration.models.OpenidACLMigration attribute), 88

user_migration_obj() (tardis.apps.openid_migration.models.OpenidACLMigrationAdmin attribute), 88

method), 88

user_owned_groups() (tardis.tardis_portal.managers.ExperimentManager attribute), 231

method), 231

UserAuthentication (class in tardis.tardis_portal.models.access_control), 134

UserAuthentication.DoesNotExist, 134

UserAuthentication.MultipleObjectsReturned, 134

userauthentication_set (tardis.tardis_portal.models.access_control.UserProfile attribute), 136

UserAuthenticationAdmin (class in tardis.tardis_portal.admin), 209

UserInterfaceTestCase (class in tardis.tardis_portal.tests.tests), 197

UserListTestCase (class in tardis.tardis_portal.tests.test_views), 196

username (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 135

UserProfile (class in tardis.tardis_portal.models.access_control), 135

userProfile (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 135

UserProfile.DoesNotExist, 135

UserProfile.MultipleObjectsReturned, 135

userProfile_id (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 135

UserProvider (class in tardis.tardis_portal.auth.interfaces), 123

UserResource (class in tardis.tardis_portal.api), 216

UserResource.Meta (class in tardis.tardis_portal.api), 216

users() (tardis.tardis_portal.managers.ExperimentManager attribute), 231

V

validate_remote_path() (in module tardis.apps.push_to.views), 99

validation (tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta attribute), 103

value (tardis.tardis_portal.models.storage.StorageBoxAttribute attribute), 174

value (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 174

value_from_url() (tardis.tardis_portal.widgets.CommaSeparatedInput attribute), 235

value_type (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 174

verbose_name (tardis.analytics.apps.AnalyticsConfig attribute), 73

verbose_name (tardis.apps.openid_migration.apps.OpenidMigrationConfig attribute), 86

verbose_name (tardis.apps.push_to.apps.PushToConfig attribute), 91

verbose_name (tardis.apps.sftp.apps.SFTPConfig attribute), 103

verbose_name (tardis.apps.social_auth.apps.SocialAuthConfig attribute), 112

verified (tardis.tardis_portal.models.datafile.DataFile attribute), 139

verified (tardis.tardis_portal.models.datafile.DataFileObject attribute), 141

verify() (tardis.tardis_portal.models.datafile.DataFile attribute), 139

verify() (tardis.tardis_portal.models.datafile.DataFileObject attribute), 141

verify_file() (tardis.tardis_portal.api.DataFileResource attribute), 210

verify_remote_access() (tardis.apps.push_to.models.Credential attribute), 92

version (tardis.tardis_portal.models.datafile.DataFile attribute), 139

`view_datafile()` (in module `tardis.tardis_portal.download`), 219

`view_functions` (`tardis.tardis_portal.shortcuts.RestfulExperimentMetadataSet` attribute), 233

`view_id()` (in module `tardis.apps.equipment.views`), 77

`view_key()` (in module `tardis.apps.equipment.views`), 77

`ViewTemplateContextsTest` (class in `tardis.tardis_portal.tests.test_views`), 196

W

`wait()` (`tardis.tardis_portal.tests.slapped.Slapped` method), 186

`which()` (in module `tardis.tardis_portal.tests.slapped`), 186

`widget` (`tardis.tardis_portal.forms.StaticField` attribute), 229

`widgets` (`tardis.apps.push_to.models.CredentialForm.Meta` attribute), 93

`widgets` (`tardis.tardis_portal.admin.DatafileAdminForm.Meta` attribute), 205

`widgets` (`tardis.tardis_portal.admin.DataFileObjectInlineForm.Meta` attribute), 204

`widgets` (`tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta` attribute), 208

`widgets` (`tardis.tardis_portal.admin.StorageBoxForm.Meta` attribute), 208

`widgets` (`tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta` attribute), 209

`widgets` (`tardis.tardis_portal.forms.ChangeUserPermissionsForm.Meta` attribute), 223

`widgets` (`tardis.tardis_portal.forms.RightsForm.Meta` attribute), 228

`write()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter` method), 80

`write_permissions_required()` (in module `tardis.tardis_portal.auth.decorators`), 122

`write_template_to_dir()` (`tardis.tardis_portal.xmlwriter.XMLWriter` static method), 235

`write_template_to_file()` (`tardis.tardis_portal.xmlwriter.XMLWriter` static method), 235

`write_xml_to_file()` (`tardis.tardis_portal.xmlwriter.XMLWriter` static method), 236

`writeExperimentMetadata()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` static method), 81

`writeMetadata()` (`tardis.apps.oaipmh.provider.base.BaseProvider` method), 80, 242

`writeMetadata()` (`tardis.apps.oaipmh.server.ProxyingMetadataRegistry` method), 83

`writeRegistryObjectsWrapper()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` method), 80

`writeRelatedAuthor()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` method), 80

`writeRelatedInfo()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` method), 80

`writeRelatedUser()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` method), 80

`writeSubject()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` method), 80

`writeUserMetadata()` (`tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider` static method), 81

X

`XMLWriter` (class in `tardis.tardis_portal.xmlwriter`), 235