
MyTardis Documentation

Release 4.1

Oct 15, 2019

Contents

1	Overview	3
2	Key features for users	5
3	Key features for instrument facilities	7
4	Developing for MyTardis	9
5	Find out more	11
6	Known deployments	13
7	Related projects and repositories	15
8	Releases	17
9	Reporting Bugs	19
10	Contributing	21
11	Documentation	23
11.1	User Guide	23
11.2	Configuration and Administration	42
11.3	Development	64
11.4	Documentation for included Apps	238
11.5	Releases	246
12	Indices and tables	255
	Python Module Index	257
	Index	263

CHAPTER 1

Overview

MyTardis began at Monash University to solve the problem of users needing to store large datasets and share them with collaborators online. Its particular focus is on integration with scientific instruments, instrument facilities and research storage and computing infrastructure; to address the challenges of data storage, data access, collaboration and data publication.

[Read more...](#)

CHAPTER 2

Key features for users

The MyTardis data management platform is a software solution that manages research data and the associated meta-data. MyTardis handles the underlying storage to ensure that data is securely archived and provides access to the data through a web portal. Data hosted in MyTardis can also be accessed via SFTP.

[Read more...](#)

CHAPTER 3

Key features for instrument facilities

MyTardis takes care of distributing data to your users. Its instrument integration technology takes care of securely and automatically shifting data from instrument to repository and makes it accessible by the right users.

[Read more...](#)

CHAPTER 4

Developing for MyTardis

MyTardis is mostly written in the [Python programming language](#) and is built on top of the [Django web framework](#). A complete installation of the service also includes an [Elasticsearch](#) index, a [RabbitMQ](#)-based task queue, an [Nginx](#) server, and a [PostgreSQL](#) database.

To set up and manage these services we employ the [SaltStack](#) orchestration software and cloud technologies.

[Read more...](#)

CHAPTER 5

Find out more

Project homepage <http://mytardis.org>

The source code is hosted at <https://github.com/mytardis/mytardis>

Documentation at <http://mytardis.readthedocs.org> includes

- User documentation
- Administrator documentation
- Developer documentation

The wiki at <https://github.com/mytardis/mytardis/wiki> includes

- Links to MyTardis add-ons, including apps and post-save filters
- Information about MyTardis community events

CHAPTER 6

Known deployments

- **Store.Synchrotron:** <https://store.synchrotron.org.au/>
- **Store.Monash:** <https://store.erc.monash.edu>
- **NIF ImageTrove:** <https://imagetrove.cai.uq.edu.au/>
- **MHTP Medical Genomics:** <https://mhtp-seq.erc.monash.edu/>
- **ANSTO:** <https://tardis.nbi.ansto.gov.au/>
- **Monash MyTardis Demo:** <https://mytardisdemo.erc.monash.edu/>

Related projects and repositories

- **MyData:** <https://github.com/mytardis/mydata>
 - A desktop application for managing uploads to MyTardis
- **NIF ImageTrove:** <https://github.com/NIF-au/imagetrove>
 - A tool for ingesting and archiving NIF datasets, including
 - * Web front end: [MyTardis](#)
 - * A DICOM server: [DICOM ToolKit](#)
 - * A dataset uploader: [imagetrove-uploader](#)
 - * Federated authentication with the Australian Access Federation’s [Rapid Connect](#) service
- **NIF ImageTrove Docker deployment:** <https://github.com/UWA-FoS/docker-mytardis>
 - For ease of deployment, all of ImageTrove’s components are packaged into a Docker container.
- **NIF Trusted Data Repositories:** <https://github.com/NIF-au/TDR>
 - Delivering durable, reliable, high-quality image data

CHAPTER 8

Releases

The default branch on GitHub is `develop`. This is the cutting edge development version. Please DO NOT use this in production, as it may have bugs that eat your data.

The `master` branch is the current stable release with all the latest bugfixes included. It will move to newer versions automatically. Follow this branch if you want to stay up to date in a production environment.

Each version has its own branch named by version number. At the time of writing, the latest release is `4.0.2`, tagged from the `series-4.0` branch. Follow this branch for your production installation and perform version upgrades manually.

Each bugfix or set of fixes bumps the minor version and each new release is tagged, eg. `4.0.3`. Use tagged releases if you are paranoid about changes to the code you have not tested yourself.

To follow development, please see the contributing section below.

CHAPTER 9

Reporting Bugs

Bug reports and feature requests can be made via our [public issue tracker](#).

CHAPTER 10

Contributing

New contributors are always welcome, however all developers should review the [pull-request checklist](#) before making pull requests.

For any wishes, comments, praise etc. either open a GitHub issue or contact us.

Active developers are also welcome to join our Slack team.

Contact details can be found on mytardis.org.

11.1 User Guide

11.1.1 Basics

Organising Data

Data Structure Overview

Data in MyTardis is organised into a uniform hierarchy, which includes Experiments, Datasets and Data Files. Experiments are at the top of the hierarchy and can contain multiple Datasets. Similarly, Datasets can contain multiple Data Files. The hierarchy can be thought of like a directory structure on a typical PC (Fig. 1) in which a the Experiment directory contains multiple Dataset directories, which in turn contain multiple Data Files.

Creating Experiments

1. Navigate to the **My Data** page.
2. Click on the **Create** button to the right of the page.

MyTardis Home About **My Data** Public Data Stats Help

Experiments

1 Experiment You Own

[+ Create](#)

[Collapse all](#) [Expand all](#)

Test Experiment	yesterday	1	0	Private
Download data as .tar				
Peter Capaldi				
Microscopy experiment				
Latest dataset in this experiment				
Dataset 1				

3. Fill in the 'Create Experiment' form. Requires at least a Title and one author.




Fig. 1: Fig. 1. Data hierarchy in MyTardis

MyTardis

HomeAboutMy DataPublic DataStatsHelp

thedoctor

Create Experiment

Title

Test Experiment

Authors

Peter Capaldi

Comma-separated authors and optional emails/URLs

Institution name

Monash University

Description

Microscopy experiment

Save

Cancel

Powered by MyTardis

4. Click **Save**.

Adding Datasets

Datasets always have at least one parent Experiment. To add a dataset to an Experiment:

1. Navigate to the Experiment page into which you would like to add a dataset.
2. Click the **+ Add New** button to the right of the page.

MyTardis Home About My Data Public Data Stats Help thedoctor

Experiment
Test Experiment
Peter Capaldi

Create publication Edit Experiment

1 0 0 bytes yesterday Private

Microscopy experiment

Description Metadata Sharing Transfer Datasets

Institution Monash University

Licensing Unspecified

Administrators thedoctor

Download All TAR SFTP

1 Dataset
Download Selected

Just start typing to filter datasets based on descriptions

Dataset 1

0 0 bytes

+ Add New

Powered by MyTardis

3. Fill in the 'Add new dataset' form. Note: The 'Description' field is actually the name of the dataset.

MyTardis Home About My Data Public Data Stats Help thedoctor

Add new dataset

Description Dataset 1

Directory

Instrument

Save

Powered by MyTardis

4. Click **Save**.

Adding Data Files

Data Files can be added to a particular Dataset from the Dataset page.

1. Navigate to the Dataset into which you want to add new files.
2. Click the green **Add files...** button to the right of the page.

The screenshot shows the MyTardis interface for 'Dataset 1'. The top navigation bar includes 'MyTardis', 'Home', 'About', 'My Data', 'Public Data', 'Stats', and 'Help'. The user 'thedoctor' is logged in. The dataset page has a title 'Dataset 1' and a link to 'Test Experiment'. On the right, there's an 'Edit Dataset Description' button and a status bar showing '0 Files', '0 bytes', and a red box around the 'Add files...' button. The 'Datafile Information' section contains a message: 'Click the [icon] button next to any file to view details and actions.' The 'Dataset Metadata' section has an 'Add Dataset Metadata' button and a message: 'There is no metadata for this dataset.' The 'Other Experiments' section has a message: 'This dataset doesn't appear in any other experiments.' The '0 Files' section shows download options (TAR, SFTP, MD5) and a search bar. The 'Select' dropdown is set to 'All'.

3. Select the files you want to add from the file selector dialog and Click **Open**. You can add multiple files by holding the “Shift” or “Ctrl” keys to select multiple files in the dialog.

Accessing Data

Download a Data File

Individual Data Files can be downloaded as follows:

1. Navigate to the Dataset containing the Data File you want to download.
2. Click the **Download** button on the Data File you want to download.

The screenshot shows the MyTardis interface for 'Dataset 1' with 4 files. The top navigation bar is the same. The dataset page shows '4 Files' and '3.1 GB'. The 'Preview Images' section shows a thumbnail of a file named 'cell5_deskewed_C2_T0.ome.tif'. The 'Datafile Information' section contains the same message as before. The 'Dataset Metadata' section has the same message. The '4 Files' section shows a list of files with checkboxes and download buttons. The file 'cell5_deskewed_C2_T0.ome.tif' (1.0 GB) has its download button highlighted in a red box. The 'Select' dropdown is set to 'All'.

Download a Dataset

Entire Datasets can be downloaded as a tar archive.

1. Navigate to the Dataset you want to download.
2. Click the **tar** button to the right of the page.

The screenshot shows the MyTardis interface for 'Dataset 1'. The top navigation bar includes links for Home, About, My Data, Public Data, Stats, and Help, along with a user profile 'thedoctor'. The dataset page header shows 'Dataset 1' from the experiment 'Test Experiment' and an 'Edit Dataset Description' button. A summary bar indicates 4 files totaling 3.1 GB. The 'Preview Images' section shows a thumbnail of a file named 'cell5_deskewed_C2_T0.ome.tif'. The 'Datafile Information' section has a note to click the file icon for details. The 'Dataset Metadata' section states there is no metadata. On the right, the '4 Files' section shows download options (TAR, SFTP, MDS) and a list of files: 'cell5_deskewed.companion.ome' (292.2 KB), 'cell5_deskewed_C0_T0.ome.tif' (1.0 GB), 'cell5_deskewed_C1_T0.ome.tif' (1.0 GB), and 'cell5_deskewed_C2_T0.ome.tif' (1.0 GB). Each file has a download icon, a plus icon, and a list icon.

Note: *tar* is an archive format like *zip* that may not be familiar to Windows users and a default Windows installation may not have the appropriate software to expand *tar* archives. We suggest that users install [7-zip](#) to expand *tar* archives from MyTardis.

Download an Experiment

Entire Experiments can be downloaded as a tar archive.

1. Navigate to the Experiment you want to download.
2. Click the **tar** button under the 'Description' section of the page.

MyTardis Home About My Data Public Data Stats Help thedoctor

Experiment
Test Experiment
Peter Capaldi

Create publication Edit Experiment

1 4 3.1 GB 5th December 2017 Private

Microscopy experiment

Description Metadata Sharing Transfer Datasets

Institution Monash University
Licensing Unspecified
Administrators thedoctor

Download All **TAR** SFTP

1 Dataset **Dataset 1** 3.1 GB

Powered by MyTardis

Note: *tar* is an archive format like *zip* that may not be familiar to Windows users and a default Windows installation may not have the appropriate software to expand *tar* archives. We suggest that users install [7-zip](#) to expand *tar* archives from MyTardis.

Sharing and Publishing Data

MyTardis provides 3 primary mechanisms for sharing your data:

- Sharing with another MyTardis user.
- Sharing via a temporary (obfuscated) link.
- Making data public.

Data sharing is done at the Experiment level and you can find the options to share an Experiment under the **Sharing** tab on the left side of an Experiment page.

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#)[Metadata](#)[Sharing](#)[Transfer Datasets](#)

Public Access

Current Public Access Settings

Private

Current License

Unspecified

[⚙️ Change Public Access](#)

Sharing

Users

Users who have a share in this experiment:

Username	Name
thedoctor	none

[↗️ Change User Sharing](#)

Groups

Groups who have a share in this experiment:

There are currently no groups with access to this experiment.[↗️ Change Group Sharing](#)

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined

[Create New Temporary Link](#)

Sharing Data with Another MyTardis User

To share an Experiment with another MyTardis user:

1. Navigate to the Experiment you want to share.
2. Click on the **Sharing** tab on the left side of the page.
3. Click the **Change User Sharing** button.

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#)[Metadata](#)[Sharing](#)[Transfer Datasets](#)

Public Access

Current Public Access Settings

[Private](#)

Current License

[Unspecified](#)[⚙️ Change Public Access](#)

Sharing

Users

Users who have a share in this experiment:

Username	Name
thedoctor	none

[↪️ Change User Sharing](#)

Groups

Groups who have a share in this experiment:

There are currently no groups with access to this experiment.[↪️ Change Group Sharing](#)

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined

[Create New Temporary Link](#)

4. Enter the **Username** of the user with which you want to share the data.

User Sharing

Current User Permissions

[thedoctor] (doctor@tardis.org) Read Edit Owner Edit Delete

Add new user

Username:

Permissions:

Owners have the ability to change access controls and share experiments with others.

+ Add User

Note: Entering the users name or email address with activate autocomplete, which helps to find the username of the user.

5. Select the permissions you'd like to give the user from the **Permissions** dropdown.
6. Click the **+Add User** button.
7. You should now see a new entry under the **Current User Permissions** section showing the user you've shared the Experiment with and the permissions you've given them.

User Sharing

Current User Permissions

[thedoctor] (doctor@tardis.org)	Read	Edit	Owner	Edit	Delete
[rosetyler] (rosetyler@tardis.org)	Read	Edit		Edit	Delete

Add new user

Username:

Permissions:

Owners have the ability to change access controls and share experiments with others.

[+ Add User](#)

Sharing Data via a Temporary Link

You can also share Data in an Experiment via a temporary (obfuscated) link. Temporary links expire after 1 month or can be deleted manually. Note: temporary links are not protected (i.e., anybody with the link can access the data); however, they are obfuscated and are thus difficult to find without prior knowledge of the link.

To share an Experiment via a temporary link:

1. Navigate to the Experiment you want to share.
2. Click on the **Sharing** tab on the left of the page.
3. Click the **Create New Temporary Link** button in the links section.

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared for direct access.

Temporary access links provide full access to recipients regardless of an experiment's public status.

No tokens defined


[Create New Temporary Link](#)

4. You should now see a new entry in the **Links** section. The new entry will provide links to both the Experiment page and a direct download link. These can be copied to the clipboard using the relevant buttons. These can then be shared with collaborators using email etc.

Links

This experiment is private. A temporary link can be created by its owner(s) and privately shared for direct access.

Temporary access links provide full access to recipients regardless of an experiment's public status.

Temporary Link	Archive direct download	Expiry	Granted By
Page link  Copy to clipboard	Archive link  Copy to clipboard	10th January 2018	thedoctor  Delete
			

Publishing Data

Access to an Experiment in MyTardis is set to “private” by default and no license is attached to the data; however, MyTardis allows data from an Experiment to be made publicly available with an appropriate license. To make an Experiment publicly available:

1. Navigate to the Experiment you wish to publish and activate the **Sharing** tab to the left of the page.
2. Click the **Change Public Access** button. This will activate the Public Access dialog and display the current status of the data.
3. Select **Public** in the “Public access” dropdown menu.
4. Select an appropriate license from the list of licenses presented. In the following screenshot, a “Creative Commons Attribution” license is selected; however, your choices may be different as licenses are configured by your service provider.

Public Access ×

Step 1: Change Public Access:

Public access

Public

Step 2: Select a license:

Creative Commons Attribution 3.0 Australia (CC BY 3.0)

This licence lets others distribute, remix, tweak, and build upon your work, even commercially, as long as they credit you for the original creation. This is the most accommodating of licences offered under Creative Commons.



[Reselect License](#)

Step 3: Accept The Legal Agreement:

Monash University (ABN 12 377 614 012) ("University") maintains a digital repository ("Repository") in which it stores and makes available various works via the Internet or other electronic means.

By submitting material for the Repository ("Work") the person(s) submitting the Work ("Depositor") agree to the following terms and conditions:

5. Agree to the "Terms of Publishing" of your service provider.
6. Click **Confirm**

11.1.2 SFTP Access

SFTP is a secure and convenient way to access, browse and download large Experiments, Datasets and Files in MyTardis. Importantly, the SFTP interface to MyTardis is read only i.e., it is a mechanism to access data in MyTardis but does **not** allow adding data to MyTardis.

Prerequisites for accessing data via SFTP

In order to access data on MyTardis via SFTP, you will first need to install an SFTP client. There are many free and commercial SFTP clients for you to choose from; however, we recommend [Cyberduck \(Win & Mac\)](#), [FileZilla \(All platforms\)](#) or [WinSCP \(Win only\)](#) for the majority of users. The instructions here will focus on [Cyberduck \(Win & Mac\)](#).

Registering and managing SSH keys in MyTardis

MyTardis uses SSH key pairs to authenticate you when connecting via SFTP. Using SSH keys to authenticate is more secure and private than password-based authentication. SSH keys generally come in a pair: (1) a private part and (2) a public part. Key-based authentication typically requires you to share your public key with the service, again which you use your private key to authenticate. Never share your private key!

MyTardis provide to mechanism for registering a public key:


1. *Adding an existing public SSH key to MyTardis*
2. *Have MyTardis to generate an SSH key pair*

Adding an existing public SSH key to MyTardis


If you have an existing SSH keypair, you can register the public key in MyTardis. For instructions on how to create an SSH key pair, Gitlab provide some nice documentation on how to do so [here](#).

To register a public key in MyTardis:

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the + *Add Key* button:



3. Fill in the *Add SSH Keys* form by entering a name for the key and the public key text. The public key text should be in OpenSSH format e.g., `ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQADYznXpTP6e/BsQw+...`

Add SSH Keys ✕

Add your own public SSH Key using the form below. **Important:** Don't add your private key.

Device Name:

Public Key:

```
ssh-rsa
AAAAB3NzaC1vc2EAAAADAQABAAQBAQDYZYnXpTP6e/BsQw+QEVdtpvdKJV2pxc9Q
DlSipqsV464bxerFs7+deNSHlpJiHy7zBO4zbzGd2vE2wuxXa02tGRwKqhQm3/fFRH6ZL4
pfJ/tkasYd7i5sAIKlkh0tPVVU+6HYbNbNjN+riIYh16ECrp7+YmtwPwVieeiTn69cSTkG+way
TFXwO6M3dolb/SMY8zE5JMotVnqxBJTwNwpQZHmQW4eh87eIHbv7QrtRF7ws/Ph6ME
Bpy1A9V118ysBKMG4YxybxGuwOOMDAOI/2RhqMGV1MPXlulshIOAy9vrYCeS40AukYjE
```

Close Add Key

4. Click the *Add Key* button.

If successful you should get a new entry in the SSH keys table.

MyTardis [Home](#) [About](#) [My Data](#) [Public Data](#) [Stats](#) [Help](#)

SSH Keys

Add and manage your public SSH keys for accessing MyTardis via SFTP.

+ Add key + Generate key

Key
massive Delete Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-07


Have MyTardis to generate an SSH key pair

Creating SSH key pairs can be a bit of a challenge, particularly on Windows systems. For this reason, MyTardis provides another you another option for registering a public keys. In this case, MyTardis will generate the key pair for


you, store the public part of the key and provide you with a one time opportunity to download the private part of the key.

It is important to note that MyTardis never stores your private key. If you lose/delete it, MyTardis cannot recover it for you. This isn't really a problem, since MyTardis can always generate another key pair for you; however, you should revoke the public key associated to the lost private key in your account to ensure that no one who gains access to your private key can access your data. See [Deleting previously registered public keys in MyTardis](#).

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the + *Generate key* button:



3. Give the key a name and click the *Generate & Download* button. The server will generate an SSH key pair, register the public key and trigger your browser to download the private key.

SFTP:

Generate an SSH key pair ×

MyTardis can generate an SSH key pair for you. Only the public part of the key pair will be stored by MyTardis and you will be provided with a one time opportunity to download the private part of the key pair.

Name:

Important: Keep your private key in a safe place. Anyone with access to the private key will be able to access your data on MyTardis.

- The SSH keys table will be updated with your newly registered public key.

MyTardis
Home
About
My Data
Public Data
Stats
Help

SSH Keys


Add and manage your public SSH keys for accessing MyTardis via SFTP.

Key
massive Delete Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-07
TestKey Delete Type: SSH-RSA Fingerprint: 3c4c3c3eb293d274fbeb687cc46aff76 Date added: 2018-08-07

Deleting previously registered public keys in MyTardis

Removing a previously registered public SSH key from MyTardis is straightforward.

1. Navigate to the SSH key management page using the *Manage SSH Keys* link in the user menu.



2. Click the *Delete* button on the key you wish to remove.

MyTardis Home About My Data Public Data Stats Help

SSH Keys

Add and manage your public SSH keys for accessing MyTardis via SFTP.

+ Add key + Generate key

Key
massive Delete Type: SSH-RSA Fingerprint: f68edca12548c068f8836d412230bdd4 Date added: 2018-08-08
TestKey Delete Type: SSH-RSA Fingerprint: e27936d5ccac5b7e5af83cefb29f01f0 Date added: 2018-08-09


Attempting to connect to MyTardis via SFTP using the private sister key to the deleted key will no longer work.

Connecting to MyTardis via SFTP

1. Open your SFTP client and create a new connection with the following configuration:

Parameter	Value
Server:	<i>URL for your MyTardis deployment e.g. https://store.erc.monash.edu</i>
Port:	<i>Port on which SFTP server is running</i>
Username:	<i>Your MyTardis username</i>
Password:	<i>Leave this blank</i>
SSH Private Key	<i>Path to a private SSH key¹</i>

Note: substitute your credentials and details for your MyTardis deployment for the *italicised* values. If you are unsure about any of these value, please contact your system admin should be able to provide these to you.



2. Click **Connect**

3. Upon successful connection you will be presented with a file browser showing all your data on MyTardis.

Data is organised according to the Experiment/Dataset/Data File hierarchy/structure described in the [Organising Data](#) section.

Browse and/or Download a Specific Experiment or Dataset

MyTardis also provides a convenient way to access/browse a particular Experiment or Dataset via SFTP.

1. Navigate to the Experiment or Dataset page that you want to access via SFTP using your web browser.
2. There is an **SFTP** button in the *Download* section on both the Experiment and Dataset views.

¹ You must register the public key in MyTardis first, see [Registering and managing SSH keys in MyTardis](#)

Experiment View

Experiment

Test Experiment

Peter Capaldi

Microscopy experiment

[Description](#) [Metadata](#) [Sharing](#) [Transfer Datasets](#)

Institution Monash University

Licensing Unspecified

Administrators Peter Capaldi

Download All [TAR](#) [SFTP](#)

Dataset View

4 Files

Download Dataset: [TAR](#) [SFTP](#) [MD5](#)[Add files...](#)

Search: Enter part or all of a filename, then press enter.

Select: [All](#) / [None](#)[Download Selected Files](#)

☐	cell5_deskewed.companion.ome (292.2 KB)	Download + List
☐	cell5_deskewed_C0_T0.ome.tif (1.0 GB)	Download + List
☐	cell5_deskewed_C1_T0.ome.tif (1.0 GB)	Download + List
☐	cell5_deskewed_C2_T0.ome.tif (1.0 GB)	Download + List

- Clicking the **SFTP** button at either of these two locations will redirect you to a page with instructions and links for starting an SFTP session for a specific experiment or dataset.

11.2 Configuration and Administration

11.2.1 Installation

The sections through to Extended Configuration below provide a Quick Start guide for getting a basic MyTardis installation up and running. The following section provides additional information on advanced configuration and add-on capabilities of MyTardis.

Prerequisites

Ubuntu (18.04 LTS is recommended)

Run this script for Python 3:

```
sudo bash install-ubuntu-py3-requirements.sh
```

It will install required packages with these commands:

```
# for Ubuntu 16.04 or 18.04
# sudo bash install-ubuntu-py3-requirements.sh

apt-get update
apt-get install \
    git libldap2-dev libmagickwand-dev libsasl2-dev \
    libssl-dev libxml2-dev libxslt1-dev libmagic-dev curl gnupg \
    python3-dev python3-pip python3-venv zlib1g-dev libfreetype6-dev libjpeg-dev

curl -sL https://deb.nodesource.com/setup_10.x | sudo -E bash -
sudo apt-get install -y nodejs
```

Or run this script for Python 2.7:

```
sudo bash install-ubuntu-py2-requirements.sh
```

It will install required packages with these commands:

```
# for Ubuntu 16.04 or 18.04
# sudo bash install-ubuntu-py2-requirements.sh

apt-get update
apt-get install git libldap2-dev libmagickwand-dev libsasl2-dev \
  libssl-dev libxml2-dev libxslt1-dev libmagic-dev curl gnupg \
  python-dev python-pip python-virtualenv virtualenvwrapper \
  zlib1g-dev libfreetype6-dev libjpeg-dev

curl -sL https://deb.nodesource.com/setup_10.x | sudo -E bash -
sudo apt-get install -y nodejs
```

Download

To get the most recent stable release:

```
git clone -b master https://github.com/mytardis/mytardis.git
cd mytardis
```

This clones the repository as read-only.

Or, to get the current development branch:

```
git clone -b develop git://github.com/mytardis/mytardis.git
cd mytardis
```

Quick configuration

It is recommended that you use a virtualenv. The list of packages above for Python 2.7 includes the virtualenvwrapper toolkit.

If using Python 3, you can, install virtualenvwrapper with `sudo pip3 install virtualenvwrapper` and set the export `VIRTUALENV_PYTHON=/usr/bin/python3` in your `~/.bashrc` or `~/.profile` to ensure that `mkvirtualenv` will make a Python 3 virtual environment. For more information on configuring virtualenvwrapper, see <https://virtualenvwrapper.readthedocs.io/en/latest/install.html#shell-startup-file>

To activate virtualenvwrapper:

For Ubuntu 18.04 with Python 3 (using pip3 installed virtualenvwrapper):

```
source /usr/local/bin/virtualenvwrapper.sh
```

For Ubuntu 18.04 with Python 2.7 (using apt-get installed virtualenvwrapper):

```
source /etc/bash_completion.d/virtualenvwrapper
```

For Ubuntu 16.04 with Python 2.7 (using apt-get installed virtualenvwrapper):

```
source /usr/share/virtualenvwrapper/virtualenvwrapper.sh
```

Then create the mytardis virtual environment

```
mkvirtualenv mytardis
pip install -U pip
```

Note: the next time you want to work with this virtualenv, run the appropriate `source` command and then use the command: `workon mytardis`

MyTardis dependencies are then installed with `pip`:

```
pip install -U -r requirements.txt
```

To install minimal Javascript dependencies for production:

```
npm install --production
```

To install Javascript dependencies for production and for testing:

```
npm install && npm test
```

Configuring MyTardis is done through a standard Django `settings.py` file. MyTardis comes with a set of default settings in its `tardis/default_settings/` package. You can import this as the basis of your own config file - options defined here will override the relevant options in `default_settings/*.py`.

Create a new file `tardis/settings.py` containing the following:

```
from .default_settings import *

# Add site specific changes here.

# Turn on django debug mode.
DEBUG = True

# Use the built-in SQLite database for testing.
# The database needs to be named something other than "tardis" to avoid
# a conflict with a directory of the same name.
DATABASES['default']['ENGINE'] = 'django.db.backends.sqlite3'
DATABASES['default']['NAME'] = 'tardis_db'
```

In addition you will need to create a new `SECRET_KEY` for your installation. This is important for security reasons.

A convenient method is to run the following command in your mytardis installation location:

```
python -c "import os; from random import choice; key_line = '%sSECRET_KEY=\"%s\"' % (choice('abcdefghijklmnopqrstuvwxyz0123456789@#%^&*()-_+='), choice('abcdefghijklmnopqrstuvwxyz0123456789@#%^&*()-_+=')) for i in range(50)); f=open('tardis/settings.py', 'a+'); f.write(key_line); f.close()"
```

This is the minimum set of changes required to successfully run the server in development mode. You can make any other site-specific changes as necessary.

Initialisation

Create and configure the database:

```
python manage.py migrate
python manage.py createcachetable default_cache
python manage.py createcachetable celery_lock_cache
```

This avoids creating a superuser before the MyTardis specific `UserProfile` table has been created. More information about the migrate commands can be found at [Configuration and Administration](#).

Next, create a superuser:

```
python manage.py createsuperuser
```

MyTardis can now be executed in its simplest form using:

```
python manage.py runserver
```

This will start the Django web server at <http://localhost:8000/>.

Extended configuration

See below for some extra configuration options that are specific to MyTardis.

An automatically generated documentation of the settings can be found in [tardis package](#).

Essential Production Settings

These settings are essential if you want to run MyTardis in production mode (`DEBUG = False`).

SECRET_KEY

This key needs to be unique per installation and, as the name implies, be kept secret.

A new one can be conveniently generated with the command:

```
echo "SECRET_KEY=`python manage.py generate_secret_key`" >> tardis/settings.py
```

However, the more complex command shown above needs to be used at installation time.

ALLOWED_HOSTS

`ALLOWED_HOSTS` is a list of hostnames and/or IP addresses under which the server is accessible. If this is not set you will get a 500 Error for any request.

Database

tardis.default_settings.DATABASE_ENGINE

The database server engine that will be used to store the MyTardis metadata, possible values are *postgresql-psycopg2*, *postgresql*, *mysql*, *sqlite3* or *oracle*.

tardis.default_settings.DATABASE_NAME

The name of the database to used to store the data, this is the path to the database if you are using the SQLite storage engine.

tardis.default_settings.DATABASE_USER

The user name used to authenticate to the database. If you are using SQLite this field is not used.

tardis.default_settings.DATABASE_PASSWORD

The password used to authenticate to the database. If you are using SQLite this field is not used.

tardis.default_settings.DATABASE_HOST

The host name of the machine hosting the database service. If this is empty then localhost will be used. If you are using SQLite then this field is ignored.

`tardis.default_settings.DATABASE_PORT`

The port the database is running on. If this is empty then the default port for the database engine will be used. If you are using SQLite then this field is ignored.

LDAP

For further information see [LDAP authentication](#)

Repository

`tardis.default_settings.DEFAULT_STORAGE_BASE_DIR`

The path to the default MyTardis storage location. This is where files will be stored to if you do not provide any other location explicitly through “StorageBox”es.

`tardis.default_settings.REQUIRE_DATAFILE_CHECKSUMS`

If True, a Datafile requires an MD5 or SHA-512 checksum from the time it is first recorded in the MyTardis database. This enables a model-level constraint check each time a Datafile record is saved. Defaults to True. Datafile record is saved.

`tardis.default_settings.REQUIRE_DATAFILE_SIZES`

If True, a Datafile require a size from the time it is first recorded in the MyTardis database. This enables a model-level constraint check each time a Datafile record is saved. Defaults to True.

`tardis.default_settings.REQUIRE_VALIDATION_ON_INGESTION`

If True, ingestion of a Datafile is only permitted if the Datafile matches its supplied size and/or checksums. Defaults to True.

Access Rights & Licensing

Licences

By default, the Creative Commons Attribution 4.0 International licences are loaded.

You can use the admin interface to add other licences. Please ensure `allows_distribution` is set to the correct value to ensure the licence appears in conjunction with suitable public access types.

Legal Notice

When changing the public access rights or licence for an experiment, a legal notice is displayed. You can override it by specifying following settings in `settings.py`:

```
LEGAL_TEXT = "A sample legal Text"
```

Filters

`tardis.default_settings.POST_SAVE_FILTERS`

This contains a list of post save filters that are execute when a new data file is created.

The `POST_SAVE_FILTERS` variable is specified like:

```
POST_SAVE_FILTERS = [
    ("tardis.tardis_portal.filters.exif.EXIFFilter", ["EXIF", "http://exif.schema
↪"]),
]
```

For further details please see the *Filter Setup* section.

Archive Organizations

tardis.default_settings.DEFAULT_ARCHIVE_FORMATS.

This is a prioritized list of download archive formats to be used in contexts where only one choice is offered to the user; e.g. the “download selected” buttons. (The list allows for using different archive formats depending on the user’s platform.)

tardis.default_settings.DEFAULT_PATH_MAPPER.

This gives the default archive “organization” to be used. Organizations are defined via the next attribute.

tardis.default_settings.DOWNLOAD_PATH_MAPPERS.

This is a hash that maps archive organization names to Datafile filename mapper functions. These functions are responsible for generating the archive pathnames used for files written to “tar” and “zip” archives by the downloads module.

The **DOWNLOAD_PATH_MAPPERS** variable is specified like:

```
DOWNLOAD_PATH_MAPPERS = {
    'test': ('tardis.apps.example.ExampleMapper',),
    'test2': ('tardis.apps.example.ExampleMapper', {'foo': 1})
}
```

The key for each entry is the logical name for the organization, and the value is a tuple consisting of the function’s pathname and a set of optional keyword arguments to be passed to the function. At runtime, the function is called with each Datafile as a positional argument, and an additional ‘rootdir’ keyword argument. The function should compute and return a (unique) pathname based on the Datafile and associated objects. If the function returns **None**, this tells the archive builder to leave out the file.

By default, the archive builder uses the built-in “deep-storage” mapper which gives pathnames that try to use directory information to rebuild a file tree.

Storage Locations (**StorageBox** es)

A MyTardis instance can be configured to support multiple locations (**StorageBox** es) for storing data files. Each location holds copies (**DataFileObject** s) of **DataFile** s that are recorded in the MyTardis database.

The **StorageBox** architecture is compatible with the **Django File Storage API**. This makes it relatively easy to support a number of different storage backends such as cloud storage or SFTP servers. Please refer to the *StorageBox documentation* for more detailed information.

Single Search

Instructions on installing and configuring Elasticsearch for advanced search are available from *Setting Up Search*.

Additional Tabs

Additional and custom tabs may be configured in MyTardis on a per-installation basis. The tabs are implemented as separate Django applications with a single view (index), listed in the `TARDIS_APPS` configuration item and either linked to, or installed in the `TARDIS_APP_ROOT` directory, by default `tardis/apps`.

Documentation on the additional tabs is available from *Apps and Contextual Views*.

Additional Views

Custom views may be configured in MyTardis on a per-installation basis. The tabs are implemented as separate Django applications with a single view function listed in the `*_VIEWS` configuration item and added to the `INSTALLED_APPS` list.

Refer to the *views documentation* for further information.

Site Customisations

Some settings that allow customised messages and styles.

```
PUBLICATION_INTRODUCTION = """
<p><strong>... introduction and publication agreement ...</strong></p>
"""
SITE_STYLES = '' # should be CSS

# if either GA setting is empty, GA is disabled
GOOGLE_ANALYTICS_ID = '' # whatever Google provides
GOOGLE_ANALYTICS_HOST = '' # the host registered with Google

# these refer to any template finder findable location, e.g. APPDIR/templates/...
CUSTOM_ABOUT_SECTION_TEMPLATE = 'tardis_portal/about_include.html'
CUSTOM_USER_GUIDE = 'user_guide/index.html'
```

Deployment

Collecting Static Files

For performance reasons you should avoid static files being served via the application, and instead serve them directly through the webserver.

To collect all the static files to a single directory:

```
python manage.py collectstatic
```

`tardis.default_settings.STATIC_ROOT`

This contains the location to deposit static content for serving.

`tardis.default_settings.STATIC_URL`

The path static content will be served from. (eg. `/static` or `http://mytardis-resources.example.com/`)

See also:

`collectstatic`, `STATIC_ROOT`, `STATIC_URL`

Serving with Nginx + Gunicorn

In this configuration, Nginx serves static files and proxies application requests to a Gunicorn server:



Nginx should then be configured to send requests to the server. Here is an example configuration (SSL part from Mozilla SSL configurator). Please amend for your own needs and understand the settings before deploying it:

```

upstream mytardis {
    server unix:/var/run/gunicorn/mytardis/socket;
    server 127.0.0.1:8000 backup;
}
server {
    listen 80 default_server;
    server_name demo.mytardis.org;
    return 301 https://$server_name$request_uri;
}

server {
    listen 443 default_server ssl;
    server_name demo.mytardis.org;

    # certs sent to the client in SERVER HELLO are concatenated in ssl_certificate
    ssl_certificate /path/to/signed_cert_plus_intermediates;
    ssl_certificate_key /path/to/private_key;
    ssl_session_timeout 5m;
    ssl_session_cache shared:SSL:50m;

    # Diffie-Hellman parameter for DHE ciphersuites, recommended 2048 bits
    ssl_dhparam /path/to/dhparam.pem;

    # intermediate configuration. tweak to your needs.
    ssl_protocols TLSv1.1 TLSv1.2;
    ssl_ciphers 'ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-
↪AES256-GCM-SHA384:ECDHE-ECDSA-AES256-GCM-SHA384:DHE-RSA-AES128-GCM-SHA256:DHE-DSS-
↪AES128-GCM-SHA256:kEDH+AESGCM:ECDHE-RSA-AES128-SHA256:ECDHE-ECDSA-AES128-
↪SHA256:ECDHE-RSA-AES128-SHA:ECDSA-AES128-SHA:ECDSA-AES128-SHA:ECDSA-AES256-SHA384:ECDSA-
↪ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA:ECDSA-AES256-SHA:DHE-RSA-AES128-
↪SHA256:DHE-RSA-AES128-SHA:DHE-DSS-AES128-SHA256:DHE-RSA-AES256-SHA256:DHE-DSS-
↪AES256-SHA:DHE-RSA-AES256-SHA:DES-CBC3-SHA:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!
↪PSK:!aECDH:!EDH-DSS-DES-CBC3-SHA:!EDH-RSA-DES-CBC3-SHA:!KRB5-DES-CBC3-SHA';
    ssl_prefer_server_ciphers on;

    # HSTS (ngx_http_headers_module is required) (15768000 seconds = 6 months)
    add_header Strict-Transport-Security max-age=15768000;

    # OCSP Stapling ---
    # fetch OCSP records from URL in ssl_certificate and cache them
    ssl_stapling on;
    ssl_stapling_verify on;

    ## verify chain of trust of OCSP response using Root CA and Intermediate certs
    ssl_trusted_certificate /path/to/root_CA_cert_plus_intermediates;

```

(continues on next page)

(continued from previous page)

```
resolver <IP DNS resolver>;

client_max_body_size 4G;
keepalive_timeout 5;

gzip off; # security reasons
gzip_proxied any;
# MyTardis generates uncompressed archives, so compress them in transit
gzip_types application/x-javascript text/css;
gzip_min_length 1024;
gzip_vary on;

location / {
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header X-Forwarded-Proto $scheme;
    proxy_set_header Host $http_host;
    proxy_redirect off;
    proxy_pass http://mytardis;
    client_max_body_size 4G;
    client_body_buffer_size 8192k;
    proxy_connect_timeout 2000;
    proxy_send_timeout 2000;
    proxy_read_timeout 2000;
}

location /static/ {
    expires 7d;
    alias /srv/static_files/;
}
}
```

The X-Forwarded-Proto header is explained in <http://docs.gunicorn.org/en/stable/deploy.html#id5>:

It is recommended to pass protocol information to Gunicorn. Many web frameworks use this information to generate URLs. Without this information, the application may mistakenly generate ‘http’ URLs in ‘https’ responses, leading to mixed content warnings or broken applications.

To tell MyTardis to set this header in its HTTP requests and redirects, you’ll need the following in your `settings.py`:

```
SECURE_PROXY_SSL_HEADER = ('HTTP_X_FORWARDED_PROTO', 'https')
```

For more information, including warnings on the risks of misconfiguring this setting, see: <https://docs.djangoproject.com/en/1.11/ref/settings/#secure-proxy-ssl-header>

Don’t forget to create the static files directory and give it appropriate permissions. The location is set in the `settings.py` file.

```
# Collect static files to ``settings.STATIC_ROOT``
python manage.py collectstatic
# Allow Nginx read permissions
setfacl -R -m user:nginx:rx static_dir
```

See also:

[Django with Gunicorn](#)

Serving with Apache HTTPD + mod_wsgi

We do not support the use of Apache. If you need this and want to support this use case, we welcome your contribution of any relevant documentation.

Creating Systemd Services for Gunicorn and Celery

Gunicorn is a Python WSGI HTTP Server which is suitable for production (when combined with NGINX). Gunicorn is typically run from a Systemd service (on Ubuntu 16.04 or Ubuntu 18.04), saved in */etc/systemd/system/gunicorn.service*:

```
[Unit]
Description=gunicorn daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/gunicorn \
  -c gunicorn_settings.py -b unix:/tmp/gunicorn.socket \
  -b 127.0.0.1:8000 \
  --log-syslog \
  wsgi:application

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Gunicorn service would be configured in */etc/supervisor/conf.d/gunicorn.conf*:

```
[program:gunicorn]
command=/home/mytardis/.virtualenvs/mytardis/bin/gunicorn
  -c /home/mytardis/mytardis/gunicorn_settings.py
  -b unix:/tmp/gunicorn.socket
  -b 127.0.0.1:8000
  --log-syslog
  wsgi:application
user=mytardis
stdout_logfile=/var/log/gunicorn.log
redirect_stderr=true
```

A single server MyTardis deployment requires only one Gunicorn service, but MyTardis can be installed on multiple web nodes, each running NGINX and Gunicorn to accomodate load balancing and high availability using HAProxy.

The Celery workers which run MyTardis asynchronous tasks also require a service configuration, which is typically implemented with Systemd (on Ubuntu 16.04 or Ubuntu 18.04), saved in */etc/systemd/system/celeryworker.service*:

```
[Unit]
Description=celeryworker daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
```

(continues on next page)

(continued from previous page)

```
Environment=DJANGO_SETTINGS_MODULE=tardis.settings
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/celery worker \
  -A tardis.celery.tardis_app \
  -c 2 -Q celery,default -n "allqueues.%%h"

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Celery worker service would be configured in */etc/supervisor/conf.d/celeryworker.conf*:

```
[program:celeryd]
environment=
  DJANGO_SETTINGS_MODULE=tardis.settings
command=/home/mytardis/.virtualenvs/mytardis/bin/celery worker
  -A tardis.celery.tardis_app
  -c 2 -Q celery,default -n "allqueues.%%h"
user=mytardis
directory=/home/mytardis/mytardis
stdout_logfile=/var/log/celeryd.log
redirect_stderr=true
killasgroup=true
stopwaitsecs=600
```

For tasks scheduled by Celerybeat, the Systemd service configuration (for Ubuntu 16.04 or Ubuntu 18.04), is saved in */etc/systemd/system/celerybeat.service*:

```
[Unit]
Description=celerybeat daemon
After=network.target

[Service]
User=mytardis
Group=mytardis
WorkingDirectory=/home/mytardis/mytardis
Environment=DJANGO_SETTINGS_MODULE=tardis.settings
ExecStart=/home/mytardis/.virtualenvs/mytardis/bin/celery beat \
  -A tardis.celery.tardis_app --loglevel INFO

[Install]
WantedBy=multi-user.target
```

On older systems (Ubuntu 14.04), Supervisor can be used instead of Systemd. In this case, the Celerybeat service would be configured in */etc/supervisor/conf.d/celerybeat.conf*:

```
[program:celerybeat]
environment=
  DJANGO_SETTINGS_MODULE=tardis.settings
command=/home/mytardis/.virtualenvs/mytardis/bin/celery beat
  -A tardis.celery.tardis_app --loglevel INFO
user=mytardis
directory=/home/mytardis/mytardis
stdout_logfile=/var/log/celerybeat.log
redirect_stderr=true
```

11.2.2 Authentication Methods

Users

MyTardis supports several sources of authentication and identity, referred to as user providers.

In the *settings.py* user providers are activated by specifying them within the **USER_PROVIDERS** variable:

```
USER_PROVIDERS = ('tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider',)
```

Groups

MyTardis also supports several sources for group membership information, referred to as group providers.

In the *settings.py* group providers are activated by specifying them within the **GROUP_PROVIDERS** variable:

```
GROUP_PROVIDERS = ('tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider',
                   'tardis.tardis_portal.auth.vbl_auth.VblGroupProvider',)
```

Included Auth Plugins

HTTP Basic Endpoint Authentication

`tardis.tardis_portal.auth.httpbasicendpoint_auth`

HTTP Basic Endpoint authentication uses access to a HTTP resource (or endpoint) to determine if authentication should be allowed.

To use HTTP Basic Endpoint authentication, you'll need a HTTP resource protected by HTTP Basic Auth which is accessible from the MyTardis server.

In the *settings.py* add the following to **AUTH_PROVIDERS** with an appropriate name. eg.

```
AUTH_PROVIDERS = (
    ('acls', 'acls', 'tardis.tardis_portal.auth.httpbasicendpoint_auth.
↪HttpBasicEndpointAuth'),
)
```

On each request, MyTardis will attempt to use basic authentication with the provided credentials to access the HTTP resource. If it fails, access is denied.

Endpoint to use in HTTP Basic Endpoint Auth. eg.

```
HTTP_BASIC_AUTH_ENDPOINT = 'https://test.example/endpoint'
```

LDAP Authentication

`tardis.tardis_portal.auth.ldap_auth`

To enable LDAP you'll need to specify which components of the LDAP authentication backend are enabled. In the *settings.py* add the following to either Authentication, User Provider, Group Provider slugs.:

```
'tardis.tardis_portal.auth.ldap_auth.ldap_auth'
```

This is a wrapper function that allows initialisation of the LDAP provider using *settings.py* values.

ldap_auth() Function

The following are configuration settings that are used when initialising the LDAP backend.

`tardis.default_settings.LDAP_TLS`

Enable TLS connections.

`tardis.default_settings.LDAP_URL`

Set the URL of the LDAP server, e.g. `ldap://localhost:389/`

`tardis.default_settings.LDAP_USER_LOGIN_ATTR`

Set the login attribute of the users, usually this will be either *cn* or *uid*

`tardis.default_settings.LDAP_USER_ATTR_MAP`

The LDAP user attribute map is used to map internal identifiers like *first_name*, *last_name* and *email* to their LDAP equivalents e.g. `{"givenName": "first_name", "sn": "last_name", "mail": "email"}`

`tardis.default_settings.LDAP_GROUP_ID_ATTR`

This is where you specify the group identifier from LDAP, usually it will be *cn*.

`tardis.default_settings.LDAP_GROUP_ATTR_MAP`

This map is used to map internal identifiers like *display* e.g. `{"description": "display"}`

`tardis.default_settings.LDAP_BASE`

Sets the search base of the LDAP queries *dc=example, dc=com*

`tardis.default_settings.LDAP_USER_BASE`

Sets the suffix to append to the user RDN (e.g. *uid=jsmith*) to construct the DN e.g. `"ou=People, " + LDAP_BASE`

`tardis.default_settings.LDAP_GROUP_BASE`

Sets the suffix to append to the group RDN (e.g. *cn=group1*) to construct the DN e.g. `"ou=Group, " + LDAP_BASE`

Temporary Token Authentication

`tardis.tardis_portal.auth.token_auth`

To use token authentication, you'll need to specify the following *settings.py*

`'tardis.tardis_portal.auth.token_auth.TokenGroupProvider',`

`TOKEN_EXPIRY_DAYS = 30`

`TOKEN_LENGTH = 30`

`TOKEN_USERNAME = 'tokenuser'`

and create a user with

`bin/django createtokenuser`

Cleaning up

`bin/django cleanuptokens`

It is recommended that you schedule regular purging of expired tokens. Set a cronjob to run `bin/django cleanuptokens`

Expiry

Token auth works by hijacking the group provider system.

MyTardis groups are calculated and cached when a user logs in.

This means that if a session is active, and a token becomes invalid (either through deletion or expiry) that access will still be granted. To mitigate this, when a token user logs in, an explicit expiry is set on their session - the earlier of 4am the next day, or the session expiry date (the end of the day)

This forces the user to attempt to log in again, and be denied access.

- `tardis.tardis_portal.auth.ip_auth`

The *tardis.tardis_portal.auth* package module contains the authentication specific code.

11.2.3 Filter Setup

With the `USE_FILTERS` option set to `True` in settings, filters will be called once a file object has been verified.

Filters allow post-processing of uploaded files and can be used to extract metadata from file headers and/or generate thumbnail images.

The `DataFileObject`'s `verify` method submits a task called “mytardis.apply_filters” to the message broker (RabbitMQ).

This task can be picked up by the “mytardis-filters” microservice: <https://github.com/mytardis/mytardis-filters> or by your own custom microservice.

11.2.4 Database

Initialising

When creating a new database the `migrate` command will need to be called to initialise the schema and insert the initial data fixtures.

Usage

```
python manage.py migrate
```

Migrating

Some of the upgrades to MyTardis will require that the database schema be upgraded to match the internal data model. The `migrate` command migrates data from old database schemas to the current one. It detects which version of the database you are currently running and will automatically migrate to the current version.

In certain cases it is also necessary to update the permissions table.

Usage

```
python manage.py migrate
```

If the model changes require it, run:

```
python manage.py update_permissions
```

creating superuser

After success of database initialization or migration, please use a command line utility called `createsuperuser` to create an administrator account using the admin site which is hooked to the URL `/admin/`.

Usage

```
python manage.py createsuperuser
```

Backup

Previous versions of MyTardis included a `backupdb` management command but it has been removed in 4.0. Please use the recommended backup tool for your database engine, e.g. `pg_dump` or `mysqldump`.

11.2.5 Schema and Parameter Sets

MyTardis stores metadata as *Parameters*, which are grouped in to *Parameter Sets*, which are defined by a *Schema*.

Managing Schema

Schema are managed through the Django administrative interface. The administrative interface is normally accesible from a link similar to:

```
http://domain.com:8000/admin/
```

Selecting “Schemas” in the administrative interface will display a list of the installed schemas. Clicking on a schema displays the editor for that schema.

Schema definitions are the combination of two tables, *Schema* and *ParameterName*.

The *Schema* fields are:

Namespace The namespace uniquely identifies the schema. When exporting an experiment as a METS file the namespace is used as an XML Namespace, and thus must follow the XML standard, i.e. in the form of a URL.

The MyTardis naming convention is:

```
http://domain.com/localidentifiers/schemaname/version
```

Name The display name of the schema.

Type Experiment, Dataset or Datafile.

Subtype Used to group and identify schema for forms based searching.

The *ParameterName* fields are:

Schema The namespace of the schema which this parameter belongs to.

Name The identifier used to ingest parameters.

Full Name The display name of the parameter.

Units The display name of the units for numerical values.

Data Type One of:

- Numeric
- String
- Longstring
- URL
- Filename
- Datetime
- Link

Strings use the input field widget for editing, while longstrings use a textarea widget.

Immutable If true, no user editing of the parameter is allowed, regardless of access.

Comparison Type The type of search to be performed with Forms Based Search. Not used by Advanced Search.

Is Searchable Flag whether this parameter is searchable.

Choices If defined, a drop down list of values is displayed.

Order The display order of the parameters within the schema. Sorting is by Order, then alphabetically.

11.2.6 Setting Up Search

Tardis comes with a single search option which provides users with a search field that returns a list of matching Experiments, Datasets and Datafiles.

The single search box uses Elasticsearch, and Django Elasticsearch DSL library that allows indexing of django models in elasticsearch, and accordingly requires some setup. The single search box is disabled by default.

Setting up Elasticsearch

Elasticsearch doesn't work out of the box with MyTardis. It is not currently installed with pip and requires a number of manual steps to get working.

Elasticsearch can be found here: <https://www.elastic.co/products/elasticsearch>

The following are a very simple list of steps that will get everything up and running. It is advisable to follow up with the person responsible for overseeing security policy at your home institution to see if any extra setup is necessary.

Django Configuration

Enabling Single Search

A list of default settings for Single Search are already in `default_settings.py` in the MyTardis repository. Single search is enabled by setting the `SINGLE_SEARCH_ENABLED` option to True.

MyTardis comes with a search app that allows indexing Experiments, Dataset and Datafile models and also provides view and api to perform elasticsearch query on these models. This can be enabled by adding 'tardis.apps.search' to the list of installed apps.

Other settings are shown below:

ELASTICSEARCH_DSL Settings

The default value is

```
INSTALLED_APPS += ('django_elasticsearch_dsl', 'tardis.apps.search',)
ELASTICSEARCH_DSL = {
    'default': {
        'hosts': 'http://localhost:9200'
    },
}
ELASTICSEARCH_DSL_INDEX_SETTINGS = {
    'number_of_shards': 1
}
```

Updating Indexes

Once Elasticsearch is set up, and Single Search is enabled (i.e. the `SINGLE_SEARCH_ENABLED` option in settings is set to True) Elasticsearch DSL will automatically register the addition of and changes to models and reflect these in the search index. That is, as soon as a new instance of a model is added to the database, or changes are made to an existing instance, these changes will be searchable.

If you're adding search to an existing deployment of Django then you'll need to manually trigger a rebuild of the indexes (automatic indexing only happens through signals when models are added or changed).

Elasticsearch DSL registers a number of management commands with the Django framework, these commands can be listed by running the following command

```
python manage.py search_index --help
```

the important one here being the `--rebuild` command. To rebuild, navigate to your checkout and call the following command

```
python manage.py search_index --rebuild
```

Elasticsearch DSL will then ask you to confirm your decision (Note: Rebuilding will destroy your existing indexes, and will take a while for large datasets, so be sure), and then start rebuilding.

11.2.7 Storage Options and Architecture in MyTardis

Database layout for storage

The storage for each `DataFile` is configured individually. A “way to store data” is called `StorageBox`. Each file has one or many related `DataFileObjects`, which link a `DataFile` with a `StorageBox`. A `DataFile` can have several copies stored in different `StorageBoxes` via several `DataFileObjects`.

StorageBoxes

`StorageBoxes` contain all the information needed to store a file except an id unique to the file and `storagebox`.

Each `StorageBox` points to a class that implements the Django storage API via a python module path as string.

Optional instantiation parameters for each `StorageBox` can be stored in `StorageBoxOptions`. These are used as parameters to the storage class set in the `django_storage_class` attribute of a `StorageBox`

These parameters are string types by default. However, by setting the optional parameter `value_type` to `'pickle'`, any pickleable object can be stored here and hence used for instantiation of the storage class.

Optional classification and other metadata can be stored in `StorageBoxAttributes`.

A special case is where someone registers a file and wants to put it into location themselves but needs to be given the place to put it (via the API). Such situation can only be resolved with `StorageBoxes` that implement the `“build_save_location”` function. Such `StorageBoxes` need to have a `StorageBoxAttribute` with key `“staging”` and value `“True”`.

DataFiles

`DataFiles` are the logical representation of the file. They contain information about the name, size, checksum, dates etc.

DataFileObjects

`DataFileObjects` point to the `DataFile` they belong to and the `StorageBox` they reside in. They also have an identifier that the `StorageBox` uses to find the actual file. `DataFileObjects` also have a date, and a state-flag.

Available backends

Django storage API compatible backends are available for example at <https://github.com/jschneier/django-storages>

We have tested the following backends with MyTardis:

- File on disk or any other system mounted storage
- SFTP
- SWIFT Object Storage

Documented backends

S3 compatible storage

S3 and S3 compatible storage backends are supported by the `django-storages` package.

The `django-storages` package is now included in MyTardis’s `requirements-base.txt`

It can be used to configure an S3 storage box, or it can be used to store static assets in S3, as described at <https://django-storages.readthedocs.io/en/latest/backends/amazon-S3.html>

Configuration

The following options can be set as `StorageBoxOption` on your S3 storage box or system wide in your Django settings (a default of `*` labels mandatory settings):

StorageBoxOption	Django Setting	Default
access_key	AWS_S3_ACCESS_KEY_ID AWS_ACCESS_KEY_ID	*
secret_key	AWS_S3_SECRET_ACCESS_KEY AWS_SECRET_ACCESS_KEY	*
file_overwrite	AWS_S3_FILE_OVERWRITE	True
headers	AWS_HEADERS	{}
bucket_name	AWS_STORAGE_BUCKET_NAME	
auto_create_bucket	AWS_AUTO_CREATE_BUCKET	False
default_acl	AWS_DEFAULT_ACL	public-read
bucket_acl	AWS_BUCKET_ACL	default_acl
querystring_auth	AWS_QUERYSTRING_AUTH	True
querystring_expire	AWS_QUERYSTRING_EXPIRE	600
reduced_redundancy	AWS_REDUCED_REDUNDANCY	False
location	AWS_LOCATION	' '
encryption	AWS_S3_ENCRYPTION	False
custom_domain	AWS_S3_CUSTOM_DOMAIN	None
calling_format	AWS_S3_CALLING_FORMAT	SubdomainCallingFormat()
secure_urls	AWS_S3_SECURE_URLS	True
file_name_charset	AWS_S3_FILE_NAME_CHARSET	'utf-8'
gzip	AWS_IS_GZIPPED	False
preload_metadata	AWS_PRELOAD_METADATA	False
gzip_content_types	GZIP_CONTENT_TYPES	('text/css', 'text/javascript', 'application/javascript', 'application/x-javascript', 'image/svg+xml')
url_protocol	AWS_S3_URL_PROTOCOL	http:
host	AWS_S3_HOST	S3Connection.DefaultHost
use_ssl	AWS_S3_USE_SSL	True
port	AWS_S3_PORT	None
proxy	AWS_S3_PROXY_HOST	None
proxy_port	AWS_S3_PROXY_PORT	None
The max amount of memory a returned file can take up before being rolled over into a temporary file on disk. Default is 0: Do not roll over.		
max_memory_size	AWS_S3_MAX_MEMORY_SIZE	0

Appendix: Conversion of ‘Replicas’

Replicas used to be the method of file storage abstraction in MyTardis versions 3.x. The StorageBoxes replace this. For pain-free upgrading, a conversion has been included with the database migrations that works as follows:

All ‘Locations’ that are local are converted to default (folder on disk) StorageBoxes. All ‘Locations’ that are not local are converted to dummy ‘link only’ StorageBoxes with the corresponding name. These can be upgraded manually to a StorageBox with an appropriate backend after the migration has taken place.

Max size is set to size of disk, hence for multiple locations on the same disk this number provides no protection. This also should be set to reasonable values manually after the migration.

Each ‘Replica’ of a file will be converted to a DataFileObject pointing to the relevant StorageBox.

All files are manually reverified, so that unverified entries can be checked for errors.


11.2.8 Facility Overview

Introduction

The Facility Overview included with MyTardis allows facility administrators to monitor the output of connected instruments, highlighting unverified files, dataset size, file counts and file listings.

Setup

In order for datasets to appear in the Facility Overview, each dataset must be associated with an Instrument, which is itself associated with a Facility. The Facility object will reference a facility administrator's group, members of which may view the Facility Overview.



The facility managers, facility manager groups, facilities and instruments may be configured via the django admin interface. MyData, the desktop uploader client for the MyTardis server, can be configured to assign the appropriate instrument to uploaded datasets at the point of ingestion.

It should be noted that the dataset visibility within the facility overview is limited to dataset and datafile listings only. Access to the experiment and dataset views, as well as raw data, is still controlled via the [ACL framework](#).

Usage

Members of the facility manager groups for one or more facilities will see the “Facility Overview” menu item in the MyTardis web portal. After opening the facility overview, a list of recently ingested datasets will be displayed from the facility being managed. If a user manages multiple facilities, a blue drop-down selector will also appear on the right-hand side of the page. As the facility overview is designed to give a snapshot of recently uploaded datasets, older data is not immediately accessible; MyTardis’ [search feature](#) is better suited to this.

In addition to simply listing the most recent datasets, the datasets can be grouped by instrument or by owner, and filtered by username, experiment name and instrument name. Note that while filters are active, it may appear as though no new pages are loaded by clicking “Load more”, since the additional datasets fetched from the server might not match the active filters.

11.2.9 Task Priorities

Overview

From v4.1.0, MyTardis assumes the use of RabbitMQ as its message broker, and instructs Celery to create a “celery” queue with task priorities enabled. The queue’s maximum priority is set to 10 in `tardis/default_settings/celery_settings.py` which is used when setting up the Celery app in `tardis/celery.py`:

```
tardis/default_settings/celery_settings.py
-----
...
MAX_TASK_PRIORITY = 10
DEFAULT_TASK_PRIORITY = 5
DEFAULT_EMAIL_TASK_PRIORITY = 10

CELERY_DEFAULT_QUEUE = 'celery'
# The 'x-max-priority' argument will only be respected by the RabbitMQ broker,
# which is the recommended broker for MyTardis:
CELERY_QUEUES = (
    Queue('celery', Exchange('celery'),
        routing_key='celery',
        queue_arguments={'x-max-priority': MAX_TASK_PRIORITY}),
)

tardis/celery.py
-----
...
tardis_app = Celery('tardis')
tardis_app.config_from_object('django.conf:settings')
...
```

Celery's `apply_async` method's `shadow` argument is used to annotate storage box related task names with the location (storage box name) which they are running in, e.g. `dfo_verify` becomes `dfo_verify location:default-storage`:

```
tardis/tardis_portal/tasks.py
-----
...
def verify_dfos(**kwargs):
    ...
    for dfo in dfos_to_verify:
        kwargs['priority'] = dfo.priority
        kwargs['shadow'] = 'dfo_verify location:%s' % dfo.storage_box.name
        dfo_verify.apply_async(args=[dfo.id], **kwargs)
    ...
```

Monitoring

We can confirm that the `x-max-priority` argument was supplied when creating the queue by running `rabbitmqctl report` on our RabbitMQ server:

```
$ sudo rabbitmqctl report | grep 'x-max-priority'
...
Listing queues for vhost mytardis ...
name    durable auto_delete    arguments ...
...
celery      true     false    [{"x-max-priority",10}] ...
```

We can list the tasks currently running (and observe their priorities) by running `celery inspect active` from one of our Celery nodes:

```
(mytardis) mytardis@celery0 ~/mytardis$ DJANGO_SETTINGS_MODULE=tardis.settings celery_
↪-A tardis.celery.tardis_app inspect active
↪-> celery@allqueues.celery0: OK
```

(continues on next page)

(continued from previous page)

```

    * {u'args': u'[32933203]', u'time_start': 1548368931.7151582, u'name': u'dfo_
↪verify location:default-storage',
      u'delivery_info': {u'priority': 5, u'redelivered': False, u'routing_key': u
↪'celery', u'exchange': u''},
      u'hostname': u'celery@allqueues.celery0', u'acknowledged': False, u'kwargs': u'
↪{}',
      u'type': u'tardis_portal.dfo.verify', u'id': u'50c80b84-5d64-44c7-a6d4-
↪c551b6d14e22', u'worker_pid': 3730}
-> celery@allqueues.celery2: OK
    - empty -
...
-> celery@allqueues.celery7: OK
    * {u'args': u'[30476811]', u'time_start': 1548368924.2799926, u'name': u'dfo_
↪verify location:default-storage',
      u'delivery_info': {u'priority': 5, u'redelivered': False, u'routing_key': u
↪'celery', u'exchange': u''},
      u'hostname': u'celery@allqueues.celery7', u'acknowledged': False, u'kwargs': u'
↪{}',
      u'type': u'tardis_portal.dfo.verify', u'id': u'de7d0fe1-f386-4937-af7f-
↪a693e7630fb5', u'worker_pid': 9051}
...
-> celery@allqueues.celery14: OK
    * {u'args': u'[289]', u'time_start': 1548368427.9639463, u'name': u'sbox_cache_
↪files location:big-data1',
      u'delivery_info': {u'priority': 4, u'redelivered': False, u'routing_key': u
↪'celery', u'exchange': u''},
      u'hostname': u'celery@allqueues.celery14', u'acknowledged': False, u'kwargs': u
↪'{}',
      u'type': u'tardis_portal.storage_box.cache_files', u'id': u'8767709f-ae98-4735-
↪9d29-21bb5b13e230', u'worker_pid': 15906}

```

Notice that most tasks have the default priority of 5 (defined in `tardis/default_settings/celery_settings.py` as `DEFAULT_TASK_PRIORITY` and that the task operating on a file from the `big-data1` storage boxes has a lower priority of 4.

Default priorities for storage boxes can be configured via `StorageBox` Attributes. We can check which storage boxes have priorities specified in the Django shell as follows:

```

(myrtardis) myrtardis@celery0:~/myrtardis$ ./manage.py shell_plus

>>> StorageBoxAttribute.objects.filter(key='priority')
<QuerySet [<StorageBoxAttribute: big-data1-> priority: 4>, <StorageBoxAttribute: big-
↪data2-> priority: 4>]>

```

So in the example above, explicit priorities are only set for the “big-data1” and “big-data2” storage boxes.

Common Problems and Solutions

Celery workers time out when running `celery inspect active`

When running `celery inspect active` sometimes you will see this error:

```
Error: No nodes replied within time constraint.
```

Usually, running `celery inspect active` again will resolve the problem, i.e. it will just work without error on subsequent attempts.

If desired, you can specify a timeout e.g. `timeout 10` but usually running `celery inspect active` again does the trick.

Non-priority queue already exists

If an attempt to submit a task to the queue (with `apply_async` triggers an error like this:

```
PreconditionFailed: Queue.declare: (406) PRECONDITION_FAILED - inequivalent arg 'x-
↪max-priority' for queue 'celery' in vhost '/':
received the value '10' of type 'signedint' but current is none
```

This means that the MyTardis process attempting to submit the task is expecting the queue to have the `x-max-priority` argument, but it doesn't have that argument (see `rabbitmqctl` report above).

In this case, you can delete the `celery` queue, and allow Celery to recreate it with the `x-max-priority` argument:

```
(mytardis) mytardis@celery0 ~/mytardis$ DJANGO_SETTINGS_MODULE=tardis.settings celery_
↪-A tardis.celery.tardis_app amqp queue.delete celery
```

11.3 Development

11.3.1 Architecture

This page describes the architecture of MyTardis.

MyTardis is built on the Django web framework, which itself is built on Python, thus MyTardis follows the architectural model of Django.

Component Architecture

Web Server MyTardis is typically deployed with the standard `Nginx + Gunicorn + Django + Python` stack.

RDBMS Ideally, use PostgreSQL. MySQL or MariaDB may be usable but it is not as well tested.

Data Storage Local disk, network mounted disks as well as S3 and SFTP are supported.

Ingestion Ingestion is normally site specific. A desktop application is available (MyData).

Functional Architecture

MyTardis follows the standard Django architecture.

The major functional modules in MyTardis are:

API A RESTful API provides anonymous and authenticated access to most of the stored data.

Auth Authentication and Authorisation.

Download Data download functionality.

Filters Processing of metadata as data is uploaded, e.g. extract EXIF metadata from JPEG files.

Management Additional commands for the Django CLI. The backup utility is implemented as a Django command.

Migrations Database migration code.

Publish RIF-CS metadata publication.

Search Provides a searchable and authorisation enabled index for quickly finding data.

SFTP server Provides read access to data in MyTardis via the SFTP protocol

Information on the individual modules is available from the modindex.

Scalability Model

At the component / module level, performance and Scalability within MyTardis is achieved by:

- Allowing long lived or compute intensive operations to be hosted on separate machines from the main web server.
 - E.g. by running multiple web servers and sending long lived operations, such as ingestion, to a server reserved for such operations.
- Performance and Scalability of the database is achieved by a combination of 1) optimising the SQL requests issued by MyTardis, and 2) database specific scalability, please refer to the appropriate database documentation.
- Performance and Scalability of the web server is provided through the normal mechanisms for nginx / wsgi hosted python applications, e.g.:
 - Increasing individual Server capability
 - * Individual Server performance / utilization may be managed by controlling the number of python (django) processes active at any one time.
 - Deploying multiple web servers
 - * Multiple web servers may be deployed using standard mechanisms, e.g. load balancers. State (session) information is distributed using Django's standard session model.
- The Data Archive is a normal file system, e.g. NFS, SAMBA, etc., with performance and scalability dependent on the implementation and deployment.
- Extraction and formatting of metadata for ingestion is up to the client and may be distributed across any number of machines.

SQL Scalability Notes

The datafileparameter table is expected to be the single largest table by an order of magnitude, in the hundreds of millions of records (at the Australian Synchrotron).

For Postgres, this will probably be addressed by table partitioning. In this case using a date field to partition is often recommended. Dates may be introduced as part of the support for annotations, raw data, versioned data and derived data.

Persistence and Data Architecture

Django provides an Object-Relational-Model that maps Django Models to the underlying relational database.

The Django Models are defined in `tardis.tardis_portal.models`.

Security Model

Authentication

Access to data catalogued by MyTardis may be either public, i.e. anonymous access allowed, or private, requiring authentication. The Authentication Framework is documented in `ref-authframework`.

Authorisation

MyTardis includes an extensible authorisation engine, documented in `ref-authframework` and *Authorisation Framework*.

Class Diagram

Unless the application has a very rich business model (which MyTardis does not), a class diagram doesn't convey much information in Django applications (it ends up being a flat list of classes). To understand the context in which the MyTardis classes are created, please refer to the Django documentation, <http://docs.djangoproject.com/> on the responsibilities of models, views, managers and templates.

Source Code

This section describes the top level layout of the source code in the [GitHub repository](#).

- docs
 - MyTardis User and Administrative documentation
- tardis
 - apps
 - * **Contains all the optional functionality and installation specific** functionality. Examples include the optional ANDS Register (`ands_register`) and Related Info (`related_info`) tabs, and the ANSTO (`mecat-ansto`) and Australian Synchrotron (`mecat-as`) installation specific modules.
 - * **Some applications are part of the main code base, others can be added** at installation time.
 - search
 - * Search related code
 - tardis_portal
 - * This is the main django application that contains most of the core MyTardis functionality

11.3.2 Authorisation Framework

Django Authorisation

Django has a built-in authorisation/permission mechanism that is in use by default. It is enabled in MyTardis in `default_settings.py` together with the custom object level permission framework described below.

```
AUTHENTICATION_BACKENDS = (
    'django.contrib.auth.backends.ModelBackend',
    'tardis.tardis_portal.auth.authorisation.ACLAwareBackend',
)
```

The Django default permissions are automatically available for each Model. The verbs are add, change, delete, and they can be queried on the user object as follows:

```
user.has_perm('tardis_portal.add_experiment')
user.has_perm('tardis_portal.add_dataset')
user.has_perm('tardis_portal.change_experiment')
user.has_perm('tardis_portal.delete_datasetparameterset')
```

There is a function in `tardis.tardis_portal.auth.authservice` called `_set_user_from_dict` that adds the following permissions for each new user created using custom methods:

```
'add_experiment'
'change_experiment'
'change_group'
'change_userauthentication'
'change_experimentacl'
```

These permissions apply in general and are augmented by ACLs

Object Level Permissions and Access Control Lists

The main purpose of the ACL system is to manage per experiment permissions. The architecture allows for future expansion to more fine grained permission management. However, at this stage only the Experiment level is supported by the user interface.

Permissions are applied with a few predefined roles:

read read permission allows individuals and groups access to view an experiment.

write write permissions cover addition of new datasets and datafiles and also deletion of datafile.

delete delete permission allows deletion of datasets and experiments.

Roles are applied through the web using the *Control Panel* and can be applied to either users or groups.

To make an experiment public requires an explicit publish action.

The ACL permissions can be queried on the user object just like standard permissions, however, with the addition of the object in question:

```
user.has_perm('tardis_acls.change_experiment', experiment)
```

Verbs currently available are change, view, delete, owns, share.

The translation of ACLs to `has_perm` verbs is defined in a function in `tardis.tardis_portal.auth.authorisation`.

To allow for querying on any object related to experiments, extra logic was added to some of the models. To support the logic, in addition to ACLs, `has_perm` calls model functions named `_has_VERB_perm`, which allows model-specific permission logic.

The current policy is that if those functions return True or False then that result is returned without further checking. If they return an object, permissions will be checked for this object thereby allowing delegation.

11.3.3 RESTful API for MyTardis

The data and metadata stored in MyTardis instances is made accessible through a RESTful API.

Not all functionality has been exposed via the API at this time. This documentation reflects what is available and tested.

The API version v1 is built on the Tastypie framework.

The RESTful API can also be explored via the automatically generated Swagger documentation at <http://mytardis-example.com/api/v1/swagger/>.

See swagger.io for details on the Swagger standard.

API accessible models

- Experiment
- ExperimentParameterSet
- ExperimentParameter
-
- Dataset
- DatasetParameterSet
- DatasetParameter
-
- DataFile
- DatafileParameterSet
- DatafileParameter
-
- StorageBox
- StorageBoxOption
- StorageBoxAttribute
-
- Schema
- ParameterName
-
- User
- Group
-
- Facility
- Instrument
-
- ObjectACL

Authentication

Currently implemented are Basic Auth, to be used via HTTPS only, and SessionAuth which queries Django sessions.

Due to our desire to provide information to users without any login, eg. for public data, the Basic Auth mechanism is slightly non-standard.

The standard sends an anonymous request, awaits a WWW-Authenticate header, then sends authentication credentials. Instead, this API sends public data for anonymous requests.

Using `curl` or the `requests` library this poses no problem. However, using `urllib2` or web browser without a Django session is not going to work out of the box.

Here is a snippet (found here: <http://stackoverflow.com/questions/4628610/does-urllib2-support-preemptive-authentication-authentication>) that makes `urllib2` work, should you want to use this library:

```
class PreemptiveBasicAuthHandler(urllib2.BaseHandler):

    def __init__(self, password_mgr=None):
        if password_mgr is None:
            password_mgr = urllib2.HTTPPasswordMgrWithDefaultRealm()
        self.passwd = password_mgr
        self.add_password = self.passwd.add_password

    def http_request(self, req):
        uri = req.get_full_url()
        user, pw = self.passwd.find_user_password(None, uri)
        if pw is None:
            return req

        raw = "%s:%s" % (user, pw)
        auth = 'Basic %s' % base64.b64encode(raw).strip()
        req.add_unredirected_header('Authorization', auth)
        return req

auth_handler = PreemptiveBasicAuthHandler()
auth_handler.add_password(realm=None,
                        uri=url,
                        user='mytardis',
                        passwd='mytardis')
opener = urllib2.build_opener(auth_handler)
# ...and install it globally so it can be used with urlopen.
urllib2.install_opener(opener)
```

Querying the database (GET)

All endpoints support querying lists and individual records via GET requests. Some support more complex queries via GET parameters as well.

Creating objects, adding files (POST)

The creation of Experiments, Datasets and Dataset_Files via POSTs with the option to include metadata/parametersets has been implemented and tested.

The following examples demonstrate how to go about it.

In all except the file attachment case the POST data should be a JSON string, the `Content-Type` header needs to be set to `application/json` and the `Accept` header as well. Other response formats may be made available in the future.

In all cases the URI of the created object is returned in the `Location` header of the response.

Experiments

Example JSON input

```
{
  "title": "API-created Experiment #1",
  "description": "Wow, all automatic!",
  "institution_name": "Monash University",
  "parameter_sets": [
    {
      "schema": "http://institution.com/my/schema",
      "parameters": [
        {
          "name": "important_parameter_1",
          "value": "Test16"
        },
        {
          "name": "important_parameter_3",
          "value": "57.136"
        }
      ]
    },
    {
      "schema": "http://company.com/some/other/schema",
      "parameters": [
        {
          "name": "meaningful_name",
          "value": "Test17"
        },
        {
          "name": "meaningless_name",
          "value": "1234"
        }
      ]
    }
  ]
}
```

This creates an experiment with two parametersets with two parameters each.

Alternative to Schema namespaces and Parameter names, you can also specify the URIs to each. Until the querying of Schemas and Parameters is documented this is discouraged.

Datasets

Example JSON input:

```
{
  "description": "API-created Dataset",
  "experiments": [
```

(continues on next page)

(continued from previous page)

```

    "/api/v1/experiment/1/",
    "/api/v1/experiment/2/"
  ],
  "immutable": false,
  "parameter_sets": [
    {
      "parameters": [
        {
          "name": "obscure-instrument-setting-52",
          "value": "awesome dataset api POST"
        },
        {
          "name": "temperature",
          "value": "301"
        }
      ],
      "schema": "http://datasets.com/need/schemas/too"
    },
    {
      "parameters": [
        {
          "name": "someotherparameter",
          "value": "some other value"
        }
      ],
      "schema": "http://better-datasets.com/offers/better/schemas"
    }
  ]
}

```

DataFiles

There are three ways to add a file to MyTardis via the API.

Via multipart form POST

This works for single files at the moment.

The key is to send a multipart-form instead of 'application/json'. This can be accomplished with the requests library as shown in the following example.

To use requests you need to install it first, eg. `pip install requests`.

Also, for this to work, the POST data needs to be sent with the JSON string called 'json_data' and the file called 'attached_file'.

Example JSON input:

```

{
  "dataset": "/api/v1/dataset/1/",
  "filename": "mytestfile.txt",
  "md5sum": "c858d6319609d6db3c091b09783c479c",
  "size": "12",
  "mimetype": "text/plain",
  "parameter_sets": [{

```

(continues on next page)

(continued from previous page)

```
"schema": "http://datafilesshop.com/fileinfo/v1",
"parameters": [{
    "name": "fileparameter1",
    "value": "123"
},
{
    "name": "fileparameter2",
    "value": "1234"
}]
}]
}
```

Example requests script:

```
import requests
from requests.auth import HTTPBasicAuth

url = "http://localhost:8000/api/v1/dataset_file/"
headers = {'Accept': 'application/json'}
response = requests.post(url, data={"json_data": data}, headers=headers,
                        files={'attached_file': open(filename, 'rb')},
                        auth=HTTPBasicAuth(username, password)
                        )
```

Via staging location

Another way to add a file is to create the database entry first without providing a storage location. This will return back a location on the server that you are assumed to have access to. Once the file appears there, for example when you copy it there, it will be moved to its permanent storage location managed by MyTardis.

The full file path that you should copy/move the file to is returned as the content of the response.

Example JSON input:

```
{
  "dataset": "/api/v1/dataset/1/",
  "filename": "mytestfile.txt",
  "md5sum": "c858d6319609d6db3c091b09783c479c",
  "size": "12",
  "mimetype": "text/plain",
  "parameter_sets": [{
    "schema": "http://datafilesshop.com/fileinfo/v1",
    "parameters": [{
      "name": "fileparameter1",
      "value": "123"
    },
    {
      "name": "fileparameter2",
      "value": "1234"
    }
  ]
}]
}
```

Via shared permanent storage location

This method assumes that there exists a storage that is shared between MyTardis and you. The registered file will remain in this location.

For this to work you need to get a `Location` (internal MyTardis settings) name to submit with your metadata.

Examples JSON:

```
{
  "dataset": "/api/v1/dataset/1/",
  "filename": "mytestfile.txt",
  "md5sum": "c858d6319609d6db3c091b09783c479c",
  "size": "12",
  "mimetype": "text/plain",
  "replicas": [{
    "url": "mytestfile.txt",
    "location": "local",
    "protocol": "file"
  }],
  "parameter_sets": [{
    "schema": "http://datafiles.shop.com/fileinfo/2",
    "parameters": [{
      "name": "fileparameter1",
      "value": "123"
    },
    {
      "name": "fileparameter2",
      "value": "123"
    }
  ]
}]
}
```

urllib2 POST example script

Replace `MODEL` with one of the available model names in lower case. `data` is the JSON as a string.

```
import urllib2
url = "http://localhost:8000/api/v1/MODEL/"
headers = {'Accept': 'application/json',
           'Content-Type': 'application/json'}
auth_handler = urllib2.HTTPBasicAuthHandler()
auth_handler.add_password(realm="django-tastypie",
                          uri=url,
                          user=username,
                          passwd=password)
opener = urllib2.build_opener(auth_handler)
urllib2.install_opener(opener)
myrequest = urllib2.Request(url=url, data=data,
                             headers=headers)
myrequest.get_method = lambda: 'POST'
output = "error"
output = urllib2.urlopen(myrequest)
print output.headers["Location"]
```

11.3.4 Tests

Running the Test Suite

Run this command to run the unit tests:

```
./test.py
```

If you want to specify any options or specific tests to run, the test argument is required first:

```
./test.py test --some-argument
```

You can choose to run the test suite with different options (e.g. with coverage, with different verbosity, etc.). To see the full list of options, run the same command with the `--help` flag.

Running Individual Unit Tests

The unit tests reside in the `tardis/tardis_portal/tests` directory. To run the unit tests individually, you can use this command:

```
./test.py test <test_module_name_here>
```

Note that the test module name argument should be the relative file path with “.” as folder separator. For example, if you want to run the test “`test_authentication.py`”, then your command to execute this test would be:

```
./test.py test tardis.tardis_portal.tests.test_authentication
```

Other options

You can choose to include different options when running the unit tests (e.g. run in verbose mode, print out a traceback, etc.). Run the test or django test command with `--help` flag to see the the full list of options:

```
./test.py test --help
```

Running BDD tests

To run BDD (Behaviour Driven Development) tests with the default settings and headless Chrome, download ChromeDriver from <http://chromedriver.chromium.org/downloads> and make it available in your PATH (e.g. in `/usr/local/bin/`) and run:

```
./test.py behave
```

Running QUnit tests

The QUnit tests reside in the `js_tests/` directory.

`package.json` contains `devDependencies` required for running these tests.

Running `npm install` will install everything you need, whereas `npm install --production` will skip the `devDependencies`.

You can run the QUnit tests with:

```
npm test
```

Or by running a web server:

```
python -m SimpleHTTPServer
```

and opening http://127.0.0.1:8000/js_tests/tests.html in your browser.

11.3.5 tardis

tardis package

Subpackages

tardis.analytics package

Submodules

tardis.analytics.apps module

```
class tardis.analytics.apps.AnalyticsConfig (app_name, app_module)
    Bases: django.apps.config.AppConfig
    name = 'tardis.analytics'
    verbose_name = 'Analytics framework'
```

tardis.analytics.ga module

Google analytics tracking

```
tardis.analytics.ga.track_download (label, session_id, ip, user, total_size=None,
                                     num_files=None, ua=None)
tardis.analytics.ga.track_login (label, session_id, ip, user)
tardis.analytics.ga.track_logout (label, session_id, ip, user)
```

tardis.analytics.tracker module

Generic tracking and analytics interface Supports Google Analytics through ga.py, others may follow

```
class tardis.analytics.tracker.IteratorTracker (iterator, tracker_data=None)
    Bases: object
    wraps file iterator to track successful and incomplete downloads
    close ()
    next ()
```

```
tardis.analytics.tracker.service = <module 'tardis.analytics.ga' from '/home/docs/checkouts/...>
    This can become a setting to other service in the future
```

Module contents

tardis.apps package

Subpackages

tardis.apps.deep_storage_download_mapper package

Submodules

tardis.apps.deep_storage_download_mapper.mapper module

File mapper that works for files stored in deep directory structures. It recreates the structure as stored in the datafile directory

```
tardis.apps.deep_storage_download_mapper.mapper.deep_storage_mapper(obj,  
                                                                    root-  
                                                                    dir=None)
```

If rootdir is None, just return a filesystem-safe representation of the object, e.g. “DatasetDescription_123” or “strange %2F filename.txt”

For now, only DataFiles are supported when rootdir is not None.

Parameters

- **obj** (`DataFile`, `Dataset` or `Experiment`) – The model instance (`DataFile`, `Dataset` or `Experiment`) to generate a path for.
- **rootdir** (`basestring`) – The top-level directory name, or None

Returns Filesystem-safe path for the object in the archive or SFTP view.

Return type `basestring`

Raises

- `Exception` –
- `NotImplementedError` –

tardis.apps.deep_storage_download_mapper.urls module

Module contents

tardis.apps.dl_mapper_df_dir_only package

Submodules

tardis.apps.dl_mapper_df_dir_only.mapper module

File mapper that works for files stored in deep directory structures. It recreates the structure as stored in the datafile directory

```
tardis.apps.dl_mapper_df_dir_only.mapper.df_dir_only(datafile, rootdir)
```

tardis.apps.dl_mapper_df_dir_only.urls module

Module contents

tardis.apps.filepicker package

Submodules

tardis.apps.filepicker.filepicker_settings module

tardis.apps.filepicker.urls module

tardis.apps.filepicker.utils module

taken from https://raw.githubusercontent.com/Filepicker/django-filepicker/master/django_filepicker/utils.py on 11 Apr 2013

```
class tardis.apps.filepicker.utils.FilepickerFile (url)
    Bases: object

    cleanup ()
        Removes any downloaded objects and closes open files.

    filepicker_url_regex = <_sre.SRE_Pattern object>

    get_file ()
        Downloads the file from filepicker.io and returns a Django File wrapper object
```

tardis.apps.filepicker.views module

Filepicker.io button view and upload handler

Module contents

tardis.apps.oaipmh package

Subpackages

tardis.apps.oaipmh.provider package

Submodules

tardis.apps.oaipmh.provider.base module

```
class tardis.apps.oaipmh.provider.base.BaseProvider (site)
    Bases: oaipmh.interfaces.IOAI, object

    A base provider which roughly implements the PyOAI interface for OAI-PMH servers.

    Extend this if you're writing your own provider for a new type or a different metadata format.
```

getRecord (*metadataPrefix*, *identifier*)

Get a record for a metadataPrefix and identifier.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **identifier** (*string*) –
 - repository-unique identifier of record

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is unknown or not supported by identifier.
- **oaipmh.error.IdDoesNotExistError** – if identifier is unknown or illegal.

Returns a header, metadata, about tuple describing the record.

identify ()

Retrieve information about the repository.

Returns an Identify object describing the repository.

listIdentifiers (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return headers in set
- **from** (*datetime*) – only retrieve headers from **from_** date forward (in naive UTC)
- **until** (*datetime*) – only retrieve headers with dates up to and including until date (in naive UTC)

Raises

- **error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of headers.

listMetadataFormats (*identifier=None*)

List metadata formats supported by repository or record.

Parameters **identifier** (*string*) – identify record for which we want to know all supported metadata formats. If absent, list all metadata formats supported by repository.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record.

Returns an iterable of metadataPrefix, schema, metadataNamespace tuples (each entry in the tuple is a string).

listRecords (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header, metadata and about information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return records in set
- **from** (*datetime*) – only retrieve records from *from_* date forward (in naive UTC)
- **until** (*datetime*) – only retrieve records with dates up to and including until date (in naive UTC)

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if *metadataPrefix* is not supported by the repository.
- **oaipmh.error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of *header*, *metadata*, *about* tuples.

listSets ()

Get a list of sets in the repository.

Raises **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of *setSpec*, *setName* tuples (strings).

writeMetadata (*element*, *metadata*)

Create XML elements under the given element, using the provided metadata.

Should avoid doing any model-lookups, as they should be done when creating the metadata.

Parameters

- **element** (*lxml.etree.Element*) – element to put all content under (as *SubElements*)
- **metadata** (*oaipmh.common.Metadata*) – metadata to turn into XML

Raises **NotImplementedError** – not implemented

tardis.apps.oaipmh.provider.experiment module

class `tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider` (*site*)

Bases: `tardis.apps.oaipmh.provider.base.BaseProvider`

NS_CC = 'http://www.tardis.edu.au/schemas/creative_commons/2011/05/17'

getRecord (*metadataPrefix*, *identifier*)

Return record if we handle it.

static get_id (*obj*)

listIdentifiers (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Return identifiers in range, provided we handle this metadata prefix.

listRecords (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Return records in range, provided we handle this metadata prefix.

listSets ()

No support for sets.

class `tardis.apps.oaipmh.provider.experiment.DcExperimentProvider` (*site*)

Bases: `tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider`

listMetadataFormats (*identifier=None*)

Return metadata format if no identifier, or identifier is a valid experiment.

```
class tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider (site)
    Bases: tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider

    class ExperimentWriter (root, metadata, site)

        write ()
        writeRegistryObjectsWrapper ()
        writeRelatedAuthor (element, obj, relation)
        writeRelatedInfo (element, obj)
        writeRelatedUser (element, obj, relation)
        writeSubject (element, obj)

    static get_rifcs_id (id_, site_=None)

    listMetadataFormats (identifier=None)
        Return metadata format if no identifier, or identifier is a valid experiment.

    static writeExperimentMetadata (element, metadata, site=None, writer=None)
        Wrapper around experiment writer.

    static writeUserMetadata (element, metadata, site=None)
```

Module contents

tardis.apps.oaipmh.tests package

Subpackages

tardis.apps.oaipmh.tests.provider package

Submodules

tardis.apps.oaipmh.tests.provider.test_base module

```
class tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    testGetRecord ()
        Default behaviour should be to not handle the identifier.

    testIdentify ()
        There can be only one provider that responds. By default, don't.

    testListIdentifiers ()
        By default a provider cannot handle the given metadata prefix.

    testListMetadataFormats ()
        By default a provider handles no metadata formats.
```

testListRecords ()

By default a provider cannot handle the given metadata prefix.

testListSets ()

By default a provider does not implement sets.

tardis.apps.oaipmh.tests.provider.test_experiment module

class tardis.apps.oaipmh.tests.provider.test_experiment.**AbstractExperimentProviderTC** (methodNames: `testGetRecord`, `testListRecords`, `testListSets`)
Bases: `object`

setUp ()

tearDown ()

testGetRecordHandlesInvalidIdentifiers ()

testIdentify ()

There can be only one provider that responds. This one does not.

testListIdentifiers ()

testListIdentifiersDoesNotHandleSets ()

testListMetadataFormats ()

testListSets ()

class tardis.apps.oaipmh.tests.provider.test_experiment.**DcExperimentProviderTestCase** (methodNames: `testGetRecord`, `testListRecords`, `testListSets`)
Bases: `tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTC`, `django.test.testcases.TestCase`

testGetRecord ()

testListRecords ()

class tardis.apps.oaipmh.tests.provider.test_experiment.**RifCsExperimentProviderTestCase** (methodNames: `testGetRecord`, `testListRecords`, `testListSets`)
Bases: `tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTC`, `django.test.testcases.TestCase`

tearDown ()

Hook method for deconstructing the test fixture after testing it.

testGetRecord ()

testListRecords ()

Module contents

Submodules

tardis.apps.oaipmh.tests.test_oai module

class tardis.apps.oaipmh.tests.test_oai.**EndpointTestCase** (methodName='runTest')
Bases: `django.test.testcases.TestCase`

setUp ()

Hook method for setting up the test fixture before exercising it.

```
tearDown()  
    Hook method for deconstructing the test fixture after testing it.  
  
testGetRecord()  
  
testIdentify()  
  
testListIdentifiers()  
  
testListMetadataFormats()  
  
testListRecords()
```

Module contents

Submodules

tardis.apps.oaipmh.models module

tardis.apps.oaipmh.server module

```
class tardis.apps.oaipmh.server.ProxyingMetadataRegistry(providers)  
    Bases: oaipmh.metadata.MetadataRegistry
```

A registry that only writes, and does so by proxying to Providers.

hasReader (*metadata_prefix*)

hasWriter (*metadata_prefix*)

readMetadata (*metadata_prefix, element*)
 Turn XML into metadata object.

element - element to read in

returns - metadata object

registerReader (*metadata_prefix, reader*)

registerWriter (*metadata_prefix, writer*)

writeMetadata (*metadata_prefix, element, metadata*)
 Write metadata as XML.

element - ElementTree element to write under metadata - metadata object to write

```
class tardis.apps.oaipmh.server.ProxyingServer(providers)  
    Bases: oaipmh.interfaces.IOAI
```

getRecord (*metadataPrefix, identifier*)
 Get a record for a metadataPrefix and identifier.

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if no provider returns a result, but at least one provider responds with `oaipmh.error.CannotDisseminateFormatError` (meaning the identifier exists)
- **oaipmh.error.IdDoesNotExistError** – if all providers fail with `oaipmh.error.IdDoesNotExistError`

Returns first successful provider response

Return type response

identify()

Retrieve information about the repository.

Returns an `oaipmh.common.Identify` object describing the repository.

Return type `oaipmh.common.Identify`

listIdentifiers (*metadataPrefix*, ***kwargs*)

Lists identifiers from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set.Set` of headers.

Return type `set`

listMetadataFormats (***kwargs*)

List metadata formats from all providers in a single set.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record, but it does exist.

Returns a `frozenset` of `metadataPrefix`, `schema`, `metadataNamespace` tuples (each entry in the tuple is a string).

Return type `frozenset`

listRecords (*metadataPrefix*, ***kwargs*)

Lists records from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set.Set` of header, metadata, about tuples.

Return type `set`

listSets()

List sets.

Raises `oaipmh.error.NoSetHierarchyError` – because set hierarchies are currently not implemented

`tardis.apps.oaipmh.server.get_server(current_site)`

tardis.apps.oaipmh.urls module

tardis.apps.oaipmh.views module

tardis.apps.oaipmh.views.**endpoint** (*request*)

Module contents

tardis.apps.openid_migration package

Subpackages

tardis.apps.openid_migration.migrations package

Submodules

tardis.apps.openid_migration.migrations.0001_initial module

```
class tardis.apps.openid_migration.migrations.0001_initial.Migration (name,  
                                                                app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0012_userauthentication_approved'), (u'auth', u'  
    initial = True  
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'ac
```

Module contents

tardis.apps.openid_migration.tests package

Submodules

tardis.apps.openid_migration.tests.test_forms module

Tests related to OpenID migration forms

```
class tardis.apps.openid_migration.tests.test_forms.OpenIDMigrationFormTestCase (methodName='runTest')  
    Bases: django.test.testcases.TestCase  
    setUp ()  
        Hook method for setting up the test fixture before exercising it.  
    test_init ()
```

tardis.apps.openid_migration.tests.test_migration module

Tests related to OpenID migration

```
class tardis.apps.openid_migration.tests.test_migration.OpenIDMigrationTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_do_migration ()
```

tardis.apps.openid_migration.tests.test_models module

```
class tardis.apps.openid_migration.tests.test_models.ModelTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    create_OpenidUserMigration ()

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_OpenidUserMigration_creation ()
```

tardis.apps.openid_migration.tests.test_views module

Tests related to OpenID migration views

```
class tardis.apps.openid_migration.tests.test_views.OpenIDMigrationViewTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_migrate_accounts (**kwargs)
```

Module contents

Submodules

tardis.apps.openid_migration.apps module

```
class tardis.apps.openid_migration.apps.OpenidMigrationConfig (app_name,
                                                             app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.openid_migration'

    verbose_name = 'OpenID migrations'
```

tardis.apps.openid_migration.context_processors module

```
tardis.apps.openid_migration.context_processors.openid_migration_processor (request)
    adds context for openid_migration
```

tardis.apps.openid_migration.default_settings module

tardis.apps.openid_migration.email_text module

```
tardis.apps.openid_migration.email_text.email_migration_success (user,
                                                                new_username,
                                                                auth_method)

tardis.apps.openid_migration.email_text.interpolate_template (template_name,
                                                             **kwargs)
```

tardis.apps.openid_migration.forms module

```
tardis.apps.openid_migration.forms.openid_user_migration_form()
    Create a user migration form with username and password field.
```

tardis.apps.openid_migration.migration module

```
tardis.apps.openid_migration.migration.acl_migration (userIdToBeReplaced,
                                                       replacementUserId,
                                                       user_migration_record)

tardis.apps.openid_migration.migration.confirm_migration (request)

tardis.apps.openid_migration.migration.do_migration (request)
    Migrating account from the account that the logged in user has provided in the Authentication Form. Migration
    involve relinking the UserAuthentication table entries, transferring ObjectACL entries to the migrated account,
    changing the Group memberships and making the old account inactive.
```

Parameters **request** (*Request*) – the HTTP request object

Returns The HttpResponse which contains request.user's new list of authentication methods

Return type HttpResponse

```
tardis.apps.openid_migration.migration.getSupportedAuthMethods ()
    Return the list of authentication methods.

tardis.apps.openid_migration.migration.get_api_key (user)

tardis.apps.openid_migration.migration.get_matching_auth_provider (backend)

tardis.apps.openid_migration.migration.migrate_api_key (old_user, new_user)

tardis.apps.openid_migration.migration.migrate_user_permissions (old_user,
                                                                new_user)

tardis.apps.openid_migration.migration.openid_migration_method (request)
```

tardis.apps.openid_migration.models module

```
class tardis.apps.openid_migration.models.OpenidACLMigration (id, user_migration,
                                                            acl_id)
    Bases: django.db.models.base.Model

exception DoesNotExist
    Bases: django.core.exceptions.ObjectDoesNotExist
```

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

acl_id

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

acl_id_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

user_migration

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_migration_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.apps.openid_migration.models.OpenidACLMigrationAdmin(model, admin_site)
Bases: django.contrib.admin.options.ModelAdmin
```

list_display = `['user_migration_obj', 'acl_id']`

media

user_migration_obj (*obj*)

```
class tardis.apps.openid_migration.models.OpenidUserMigration(id, old_user,
old_user_auth_method,
new_user,
new_user_auth_method,
migration_timestamp,
migration_status)
Bases: django.db.models.base.Model
```

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

get_next_by_migration_timestamp (***morekwargs*)

get_previous_by_migration_timestamp (***morekwargs*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

migration_status

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

migration_timestamp

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

new_user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

new_user_auth_method

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

new_user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

old_user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

old_user_auth_method

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

old_user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

openidaclmigration_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.apps.openid_migration.models.OpenidUserMigrationAdmin(model, admin_site):
    Bases: django.contrib.admin.options.ModelAdmin
    list_display = ['__str__', 'old_user', 'old_user_auth_method', 'new_user_id', 'new_user_auth_method']
    media
```

tardis.apps.openid_migration.tasks module

tardis.apps.openid_migration.urls module

tardis.apps.openid_migration.user_menu_modifiers module

```
tardis.apps.openid_migration.user_menu_modifiers.add_migrate_account_menu_item(request, user_menu)
```

Add a ‘Migrate My Account’ item to the user menu

Parameters

- **request** (`django.http.HttpRequest`) – an HTTP Request instance
- **user_menu** (`list`) – user menu context to modify

Returns user_menu list

Return type `list`

tardis.apps.openid_migration.utils module

```
tardis.apps.openid_migration.utils.rollback_migration(user_migration_obj)
```

tardis.apps.openid_migration.views module

```
tardis.apps.openid_migration.views.migrate_accounts(request, *args, **kwargs)
```

Manage user migration using AJAX.

Module contents

tardis.apps.push_to package

Subpackages

tardis.apps.push_to.migrations package

Submodules

tardis.apps.push_to.migrations.0001_initial module

```
class tardis.apps.push_to.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'auth', u'__first__'), (u'auth', u'0006_require_contenttypes_0002')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'key
```

tardis.apps.push_to.migrations.0002_auto_20160518_1953 module

```
class tardis.apps.push_to.migrations.0002_auto_20160518_1953.Migration (name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'push_to', u'0001_initial')]
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'key_type',
```

Module contents

tardis.apps.push_to.tests package

Submodules

tardis.apps.push_to.tests.test_models module

```
class tardis.apps.push_to.tests.test_models.ModelsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_credential_generation ()

    test_get_allowed_signing_services ()

    test_keys_from_private_key_only ()

    test_pkey_to_credential ()
```

Module contents

Submodules

tardis.apps.push_to.apps module

```
class tardis.apps.push_to.apps.PushToConfig (app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.push_to'
```

```
verbose_name = 'Push To'
```

tardis.apps.push_to.exceptions module

exception `tardis.apps.push_to.exceptions.NoSuitableCredential`

Bases: `exceptions.Exception`

This exception is thrown when attempting to find a suitable credential for a remote host but none is found

tardis.apps.push_to.models module

class `tardis.apps.push_to.models.Credential(*args, **kwargs)`

Bases: `tardis.apps.push_to.models.KeyPair`

A credential that may contain a password and/or key. The auth method chosen depends on the credentials available, allowed auth methods, and priorities defined by the SSH client.

exception `DoesNotExist`

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception `MultipleObjectsReturned`

Bases: `django.core.exceptions.MultipleObjectsReturned`

static `generate_keypair_credential(tardis_user, remote_user, remote_hosts, bit_length=2048)`

Generates and saves an RSA key pair credential. Credentials returned by this method are intended to be registered on remote systems before being used. @type tardis_user: User @type remote_user: str @type bit_length: int @type remote_hosts: list[RemoteHost] :return: the generated credential :rtype: object

get_client_for_host (*remote_host*)

Attempts to establish a connection with the remote_host using this credential object. The remote_host may be any host, but only those in the remote_hosts field are expected to work. @type remote_host: RemoteHost :return: a connected SSH client :rtype: SSHClient

static `get_suitable_credential(tardis_user, remote_host, remote_user=None)`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

password

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

remote_hosts

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

remote_user

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verify_remote_access (*remote_host=None*)

@type remote_host: RemoteHost

```
class tardis.apps.push_to.models.CredentialAdmin(model, admin_site)
```

Bases: django.contrib.admin.options.ModelAdmin

form

alias of *CredentialForm*

media

```
class tardis.apps.push_to.models.CredentialForm(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
instance=None,
use_required_attribute=None)
```

Bases: django.forms.models.ModelForm

class Meta

fields = '__all__'

model

alias of *Credential*

widgets = {'password': <django.forms.widgets.PasswordInput object>}

base_fields = {'key_type': <django.forms.fields.CharField object>, 'password': <djan

declared_fields = {}

media

```
class tardis.apps.push_to.models.DBHostKeyPolicy
```

Bases: paramiko.client.MissingHostKeyPolicy

Host key verification policy based on the host key stored in the database.

missing_host_key (*client, hostname, key*)

@type key: PKey

```
class tardis.apps.push_to.models.KeyPair(*args, **kwargs)
    Bases: django.db.models.base.Model

    A key pair

    class Meta

        abstract = False

    key

        Returns a subclass of PKey of the appropriate key type

        Return type PKey

        Raises ValidationError –

    key_type
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    private_key
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    public_key
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    save(*args, **kwargs)
```

```
class tardis.apps.push_to.models.OAuthSSHCertSigningService(*args, **kwargs)
    Bases: django.db.models.base.Model

    Connection parameters for an OAuth2 SSH certificate signing service. Supports certificate signing server avail-
    able here: https://github.com/monash-merc/ssh-authz

    exception DoesNotExist
        Bases: django.core.exceptions.ObjectDoesNotExist

    exception MultipleObjectsReturned
        Bases: django.core.exceptions.MultipleObjectsReturned

    allow_for_all
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    allowed_groups
        Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

        In the example:



```
class Pizza(Model):
 toppings = ManyToManyField(Topping, related_name='pizzas')
```



        pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

        Most of the implementation is delegated to a dynamically defined manager class built by
        create_forward_many_to_many_manager() defined below.

    allowed_remote_hosts
        Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

        In the example:
```

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

allowed_users

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

cert_signing_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

static get_available_signing_services (*user*)

Gets all SSH cert signing services available for a given user :param User user: User :return: allowed signing services :rtype: User

static get_oauth_service (*user, service_id*)

@type user: User @type service_id: int

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

nickname

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_authorize_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_check_token_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_client_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_client_secret

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauth_token_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

class tardis.apps.push_to.models.RemoteHost (*args, **kwargs)

Bases: `tardis.apps.push_to.models.KeyPair`

A remote host that may be connected to via SSH

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

administrator

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

administrator_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

credential_set

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

host_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

logo_img

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

nickname

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

oauthsshcertsigningservice_set

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

objects = <django.db.models.manager.Manager object>

port

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class `tardis.apps.push_to.models.RemoteHostAdmin` (*model, admin_site*)

Bases: `django.contrib.admin.options.ModelAdmin`

Hides the private key field, which is not necessary for host keys

fields = ['nickname', 'administrator', 'host_name', 'port', 'key_type', 'public_key',

media

tardis.apps.push_to.oauth_tokens module

`tardis.apps.push_to.oauth_tokens.get_token` (*request, oauth_service*)

Returns the OAuth2 token from the current session :param Request request: django session object :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Returns

Return type string

`tardis.apps.push_to.oauth_tokens.get_token_data` (*oauth_service, token*)

Gets the OAuth2 user attributes using the supplied token :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Parameters **token** (*basestring*) – an OAuth2 token

Returns a json object of user attributes

Return type dict

`tardis.apps.push_to.oauth_tokens.set_token` (*request, oauth_service, token*)

Stores the OAuth2 token in the current session :param Request request: django request object :param OAuthSSHCertSigningService oauth_service: an

OAuthSSHCertSigningService object

Parameters **token** (*basestring*) – the OAuth2 token

tardis.apps.push_to.ssh_authz module

`tardis.apps.push_to.ssh_authz.sign_certificate` (*credential, token, url*)

An interface to the OAuth2 SSH certificate signing service @type credential: models.Credential

tardis.apps.push_to.tasks module

`tardis.apps.push_to.tasks.do_file_copy` (*credential_id*, *remote_host_id*, *datafile_map*,
base_dir=None)

`tardis.apps.push_to.tasks.make_dirs` (*sftp_client*, *dir_list*)

`tardis.apps.push_to.tasks.notify_user` (*user_id*, *remote_host_id*, *success=True*)

tardis.apps.push_to.urls module**tardis.apps.push_to.utils module**

`tardis.apps.push_to.utils.bytes_available` (*ssh_client*, *path*)

`tardis.apps.push_to.utils.can_copy` (*ssh_client*, *object_type*, *object_id*, *path*)

`tardis.apps.push_to.utils.get_default_push_location` (*sftp_client*)

`tardis.apps.push_to.utils.get_object_size` (*type*, *id*)

`tardis.apps.push_to.utils.is_directory` (*sftp_client*, *path*)

`tardis.apps.push_to.utils.list_subdirectories` (*sftp_client*, *path*, *show_hidden=False*)

`tardis.apps.push_to.utils.shell_escape` (*s*)

tardis.apps.push_to.views module

`tardis.apps.push_to.views.authorize_remote_access` (*request*, **args*, ***kwargs*)

Generates an SSH certificate using an OAuth2 SSH signing service :param Request request: request object
:param basestring remote_host_id: remote host id :param basestring service_id: OAuth2 SSH certificate signing
service id :return: an error message or OAuth2 redirects :rtype: HttpResponseRedirect

`tardis.apps.push_to.views.get_accessible_hosts` (*request*, **args*, ***kwargs*)

Retrieves all accessible hosts (i.e. hosts for which the user already has credentials for) including push-to trigger
URLs if the object type and id are supplied :param Request request: request object :param object obj_type: data
type to be copied

(experiment, dataset or datafile)

Parameters `push_obj_id` (*int*) – the database object id

Returns json object with accessible hosts

Return type HttpResponse

`tardis.apps.push_to.views.get_credential` (*request*, *remote_host*)

Fetches a suitable credential for the remote host, or raises an exception if none found :param Request request:
request object :param RemoteHost remote_host: the RemoteHost for which a credential
should be found

Returns the credential

Return type object

Raises `NoSuitableCredential` – raised when no credential is found

`tardis.apps.push_to.views.get_push_url_for_host` (*remote_host, obj_type, push_obj_id*)
Constructs a push-to URL to trigger data transfer :param RemoteHost remote_host: the RemoteHost to which data should be copied :param obj_type: data type to be copied (experiment, dataset or datafile) :type obj_type: object :param int push_obj_id: the database object id :return: a push-to URL :rtype: basestring

`tardis.apps.push_to.views.get_signing_services` (*request, *args, **kwargs*)
Retrieves all certificate signing services and associated hosts including push-to trigger URLs if the object type and id are supplied :param Request request: request object :param class obj_type: data type to be copied (experiment, dataset or datafile) :param int push_obj_id: the database object id :return: json object with signing services and hosts :rtype: HttpResponse

`tardis.apps.push_to.views.oauth_callback` (*request, *args, **kwargs*)
OAuth2 callback endpoint to continue the SSH certificate signing process :param Request request: request object :return: error message or redirect to the signing service with access token :rtype: HttpResponse

`tardis.apps.push_to.views.oauth_callback_url` (*request*)
Builds the oauth callback URL :param Request request: request object :return: callback URL :rtype: basestring

`tardis.apps.push_to.views.render_error_message` (*request, message, status=500*)

`tardis.apps.push_to.views.render_success_message` (*request, message, status=200*)

`tardis.apps.push_to.views.validate_remote_path` (*request, *args, **kwargs*)

Module contents

tardis.apps.related_info package

Subpackages

tardis.apps.related_info.tests package

Submodules

tardis.apps.related_info.tests.test_oaipmh module

```
class tardis.apps.related_info.tests.test_oaipmh.RifCSTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testExistsInOaipmh ()
```

tardis.apps.related_info.tests.tests module

```
class tardis.apps.related_info.tests.tests.CreateTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanCreate ()

    testDetectsBadInput ()
```

```
testMustHaveWrite (**kwargs)

class tardis.apps.related_info.tests.tests.DeleteTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanDelete ()

    testMustHaveWrite (**kwargs)

class tardis.apps.related_info.tests.tests.GetTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testHandlesFound ()

    testHandlesNotFound (**kwargs)

class tardis.apps.related_info.tests.tests.ListTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testHandlesEmptySet ()

    testHandlesMultipleEntries ()

    testHandlesSingleEntry ()

class tardis.apps.related_info.tests.tests.TabTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testAccessWithReadPerms (**kwargs)

    testAccessWithoutReadPerms (**kwargs)

class tardis.apps.related_info.tests.tests.UpdateTestCase (methodName='runTest')
    Bases: django.test.testcases.TransactionTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testDetectsBadInput ()

    testMustHaveWrite (**kwargs)
```

Module contents

Submodules

tardis.apps.related_info.forms module

```
class tardis.apps.related_info.forms.RelatedInfoForm (data=None,      files=None,
                                                    auto_id=u'id_%s',      pre-
                                                    fix=None,      initial=None,
                                                    error_class=<class
                                                    'django.forms.utils.ErrorList'>,
                                                    label_suffix=None,
                                                    empty_permitted=False,
                                                    field_order=None,
                                                    use_required_attribute=None,
                                                    renderer=None)

Bases: django.forms.forms.Form

base_fields = {'identifier':  <django.forms.fields.URLField object>, 'notes':  <django
declared_fields = {'identifier':  <django.forms.fields.URLField object>, 'notes':  <dj
media
```

tardis.apps.related_info.models module

tardis.apps.related_info.settings module

tardis.apps.related_info.urls module

tardis.apps.related_info.views module

Module contents

tardis.apps.s3utils package

Subpackages

tardis.apps.s3utils.tests package

Submodules

tardis.apps.s3utils.tests.test_api module

Testing the s3util app's extensions to the tastypie-based mytardis api

```
class tardis.apps.s3utils.tests.test_api.S3UtilsAppApiTestCase (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_download_dfo ()
        Test downloading a DataFileObject using the s3util app's extensions to the MyTardis REST API.
```

tardis.apps.s3utils.tests.test_app_config module

```
class tardis.apps.s3utils.tests.test_app_config.S3UtilsConfigTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_app_config()
```

tardis.apps.s3utils.tests.test_checksums module

Testing the s3util app's ability to calculate checksums for S3 objects

```
class tardis.apps.s3utils.tests.test_checksums.S3UtilsAppChecksumsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_checksums()
        Ensure that we can calculate an MD5 sum and a SHA512 sum for a file in S3 object storage
```

Module contents

Submodules

tardis.apps.s3utils.api module

Additions to MyTardis's REST API

```
class tardis.apps.s3utils.api.ReplicaAppResource (api_name=None)
    Bases: tardis.tardis_portal.api.ReplicaResource

    Extends MyTardis's API for DFOs, adding in a download method for S3 objects

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        authorization
            Authorisation class for Tastypie.

        object_class
            alias of tardis.tardis_portal.models.datafile.DataFileObject

        queryset

        resource_name = 'replica'

    base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'datafile': <
    declared_fields = {}

    download_dfo (request, **kwargs)
        Download DataFileObject from S3 Object Store

    prepend_urls()
```

tardis.apps.s3utils.apps module

```
class tardis.apps.s3utils.apps.S3UtilsConfig(app_name, app_module)
    Bases: django.apps.config.AppConfig
    name = u's3utils'
```

tardis.apps.s3utils.default_settings module

Default settings for s3utils app

```
tardis.apps.s3utils.default_settings.S3_SIGNED_URL_EXPIRY = 30
```

A short expiry (30 seconds) is used, because it is only intended to provide access long enough for an authenticated MyTardis user to be redirected to the signed URL.

tardis.apps.s3utils.urls module

Minimal urls.py, so we can do a reverse lookup for the 's3_api_download_dfo' URL pattern.

's3_api_download_dfo' is defined in the prepend_urls method of the ReplicaAppResource class in api.py

The API endpoint defined in this app is mapped to a URL in tardis/urls/api.py (along with API endpoints defined by other MyTardis apps).

tardis.apps.s3utils.utils module

Utilities for S3 objects

```
tardis.apps.s3utils.utils.calculate_checksums(dfo, compute_md5=True, compute_sha512=False)
```

Calculates checksums for an S3 DataFileObject instance. For files in S3, using the django-storages abstraction is inefficient - we end up with a clash of chunking algorithms between the download from S3 and MyTardis's Python-based checksum calculation. So for S3 files, we calculate checksums using external binaries (md5sum and shasum) instead.

:param dfo : The DataFileObject instance :type dfo: DataFileObject :param compute_md5: whether to compute md5 default=True :type compute_md5: bool :param compute_sha512: whether to compute sha512, default=True :type compute_sha512: bool

Returns the checksums as {'md5sum': result, 'sha512sum': result}

Return type dict

```
tardis.apps.s3utils.utils.generate_presigned_url(dfo, expiry=None)
```

Generate a presigned URL for an S3 object

boto3 must be installed if you are using the storages.backends.s3boto3.S3Boto3Storage storage class, defined in the django-storages package

dfo [DataFileObject] The DataFileObject to generate the pre-signed URL for

expiry [int] The signed URL's expiry in seconds

string The pre-signed URL

Module contents

tardis.apps.search package

Subpackages

tardis.apps.search.tests package

Submodules

tardis.apps.search.tests.test_api module

```
class tardis.apps.search.tests.test_api.SimpleSearchTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_advance_search_authenticated_user()

    test_advance_search_unauthenticated_user()

    test_simple_search_authenticated_user()

    test_simple_search_unauthenticated_user()
```

tardis.apps.search.tests.test_index module

```
class tardis.apps.search.tests.test_index.IndexExperimentTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_create_index()
```

Module contents

Submodules

tardis.apps.search.api module

RESTful API for MyTardis search. Implemented with Tastypie.

```
class tardis.apps.search.api.AdvanceSearchAppResource (api_name=None)
    Bases: tastypie.resources.Resource

    class Meta

        always_return_data = True

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>

        list_allowed_methods = ['post']
```

```
    object_class
        alias of SearchObject

    resource_name = 'advance-search'

    serializer = <tardis.apps.search.api.PrettyJSONSerializer object>

    base_fields = {'hits': <tastypie.fields.ApiField object>, u'resource_uri': <tastypie
    declared_fields = {'hits': <tastypie.fields.ApiField object>}
    detail_uri_kwargs (bundle_or_obj)
    get_object_list (request)
    obj_create (bundle, **kwargs)
    obj_get_list (bundle, **kwargs)

class tardis.apps.search.api.PrettyJSONSerializer (formats=None,                con-
                                                tent_types=None,            date-
                                                time_formatting=None)

    Bases: tastypie.serializers.Serializer

    json_indent = 2

    to_json (data, options=None)

class tardis.apps.search.api.SearchAppResource (api_name=None)
    Bases: tastypie.resources.Resource

    Tastypie resource for simple-search

    class Meta

        always_return_data = True

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>

        list_allowed_methods = ['get']

        object_class
            alias of SearchObject

        resource_name = 'simple-search'

        serializer = <tardis.apps.search.api.PrettyJSONSerializer object>

        base_fields = {'hits': <tastypie.fields.ApiField object>, u'resource_uri': <tastypie
        declared_fields = {'hits': <tastypie.fields.ApiField object>}
        detail_uri_kwargs (bundle_or_obj)
        get_object_list (request)
        obj_get_list (bundle, **kwargs)

class tardis.apps.search.api.SearchObject (hits=None, id=None)
    Bases: object

tardis.apps.search.api.simple_search_public_data (query_text)
```

tardis.apps.search.apps module

```
class tardis.apps.search.apps.SearchConfig(app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig
    name = 'tardis.apps.search'
    verbose_name = 'Search'
```

tardis.apps.search.documents module

```
class tardis.apps.search.documents.DataFileDocument(related_instance_to_ignore=None,
                                                    **kwargs)
    Bases: django_elasticsearch_dsl.documents.DocType
    class Django

        model
            alias of tardis.tardis_portal.models.datafile.DataFile
        queryset_pagination = 100000
        related_models = [<class 'tardis.tardis_portal.models.dataset.Dataset'>, <class 'ta

    class Index

        name = 'datafile'
        settings = {'number_of_replicas': 0, 'number_of_shards': 1}
        django = {'queryset_pagination': 100000, 'model': <class 'tardis.tard...
        get_instances_from_related(related_instance)

class tardis.apps.search.documents.DatasetDocument(related_instance_to_ignore=None,
                                                    **kwargs)
    Bases: django_elasticsearch_dsl.documents.DocType
    class Django

        model
            alias of tardis.tardis_portal.models.dataset.Dataset
        related_models = [<class 'tardis.tardis_portal.models.experiment.Experiment'>, <cla

    class Index

        name = 'dataset'
        settings = {'number_of_replicas': 0, 'number_of_shards': 1}
        django = {'queryset_pagination': None, 'model': <class 'tardis.tardis...
        get_instances_from_related(related_instance)

class tardis.apps.search.documents.ExperimentDocument(related_instance_to_ignore=None,
                                                        **kwargs)
    Bases: django_elasticsearch_dsl.documents.DocType
```

```
class Django
```

```
    model
```

```
        alias of tardis.tardis_portal.models.experiment.Experiment
```

```
    related_models = [<class 'django.contrib.auth.models.User'>, <class 'tardis.tardis...
```

```
class Index
```

```
    name = 'experiments'
```

```
    settings = {'number_of_replicas': 0, 'number_of_shards': 1}
```

```
    django = {'queryset_pagination': None, 'model': <class 'tardis.tardis...}
```

```
    get_instances_from_related(related_instance)
```

tardis.apps.search.urls module

tardis.apps.search.views module

views relevant to search

```
class tardis.apps.search.views.SearchView(**kwargs)
```

```
    Bases: django.views.generic.base.TemplateView
```

```
    template_name = 'search.html'
```

Module contents

tardis.apps.sftp package

Subpackages

tardis.apps.sftp.management package

Subpackages

tardis.apps.sftp.management.commands package

Submodules

tardis.apps.sftp.management.commands.sftpd module

```
class tardis.apps.sftp.management.commands.sftpd.Command(stdout=None,  
                                                         stderr=None,  
                                                         no_color=False)
```

```
    Bases: django.core.management.base.BaseCommand
```

```
    add_arguments(parser)
```

```
    handle(*args, **options)
```

Module contents

Module contents

tardis.apps.sftp.migrations package

Submodules

tardis.apps.sftp.migrations.0001_initial module

```
class tardis.apps.sftp.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0011_auto_20160505_1643'), (u'auth', u'__first__')]
    initial = True
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'na
```

Module contents

tardis.apps.sftp.tests package

Submodules

tardis.apps.sftp.tests.test_sftp module

```
class tardis.apps.sftp.tests.test_sftp.SFTPDManagementTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    testSFTPDWithoutHostKey ()
        Attempting to start the SFTPD service without a host key should raise an SSHException

class tardis.apps.sftp.tests.test_sftp.SFTPTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_cyberduck_connection_window ()

    test_sftp ()

    test_sftp_dynamic_docs_dataset (**keywargs)

    test_sftp_dynamic_docs_experiment (**keywargs)

    test_sftp_key_connect ()
```

Module contents

Submodules

tardis.apps.sftp.admin module

tardis.apps.sftp.api module

```
class tardis.apps.sftp.api.SFTPAuthorization
    Bases: tastypie.authorization.Authorization

    create_detail(object_list, bundle)

    delete_detail(object_list, bundle)

    read_detail(object_list, bundle)

    read_list(object_list, bundle)

class tardis.apps.sftp.api.SFTPPublicKeyAppResource(api_name=None)
    Bases: tastypie.resources.ModelResource

    Tastypie model resource for SFTPPublicKey model

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
        detail_allowed_methods = ['get', 'delete']
        filtering = {'id': ('exact',), 'name': ('exact',)}
        list_allowed_methods = ['get', 'post']
        object_class
            alias of tardis.apps.sftp.models.SFTPPublicKey
        queryset
        resource_name = 'sftp/key'
        validation = <tastypie.validation.FormValidation object>
        base_fields = {'added': <tastypie.fields.DateField object>, u'id': <tastypie.fields.
        declared_fields = {}
        dehydrate(bundle)
        hydrate(bundle)
```

tardis.apps.sftp.apps module

```
class tardis.apps.sftp.apps.SFTPConfig(app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.sftp'

    verbose_name = 'SFTP'
```

tardis.apps.sftp.default_settings module

`tardis.apps.sftp.default_settings.REQUIRE_SSL_TO_GENERATE_KEY = True`

Require a secure connection (i.e., HTTPS) to allow key generation.

`tardis.apps.sftp.default_settings.SFTP_USERNAME_ATTRIBUTE = 'email'`

The attribute from the User model ('email' or 'username') used to generate the SFTP login example on the sftp_access help page.

tardis.apps.sftp.forms module

```
class tardis.apps.sftp.forms.KeyAddForm(data=None, files=None, auto_id=u'id_%s', pre-
                                     fix=None, initial=None, error_class=<class
                                     'django.forms.utils.ErrorList'>, la-
                                     bel_suffix=None, empty_permitted=False,
                                     field_order=None, use_required_attribute=None,
                                     renderer=None)
```

Bases: `django.forms.forms.Form`

```
base_fields = {'key_type': <django.forms.fields.CharField object>, 'name': <django.f
```

```
clean()
```

```
declared_fields = {'key_type': <django.forms.fields.CharField object>, 'name': <djan
```

```
media
```

```
class tardis.apps.sftp.forms.KeyGenerateForm(data=None, files=None,
                                             auto_id=u'id_%s', prefix=None,
                                             initial=None, error_class=<class
                                             'django.forms.utils.ErrorList'>,
                                             label_suffix=None,
                                             empty_permitted=False, field_order=None,
                                             use_required_attribute=None, ren-
                                             derer=None)
```

Bases: `django.forms.forms.Form`

```
base_fields = {'name': <django.forms.fields.CharField object>}
```

```
declared_fields = {'name': <django.forms.fields.CharField object>}
```

```
media
```

tardis.apps.sftp.models module

```
class tardis.apps.sftp.models.SFTPPublicKey(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

Model for associated SFTP public keys with users

Parameters

- **user** (*ForeignKey for User*) – user who owns this public key
- **name** (*string*) – name for this public key
- **public_key** (*string*) – OpenSSH formatted public key
- **added** (*date*) – date the public key was added (Optional)

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

added

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_next_by_added (***morekwargs*)

get_previous_by_added (***morekwargs*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

public_key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.apps.sftp.sftp module

SFTP Server

class `tardis.apps.sftp.sftp.DynamicTree` (*host_obj=None*)

Bases: `object`

add_child (*name, obj=None*)

add_path (*path*)

add_path_elems (*elems*)

clear_children ()

```

get_leaf (path, update=False)

update_all_files ()

update_dataset_files ()

update_datasets ()

update_experiments ()

update_nothing ()

class tardis.apps.sftp.sftp.MyTSFTPHandle (df, flags=0, optional_args=None)
    Bases: paramiko.sftp_handle.SFTPHandle

    SFTP File Handle

    stat ()
        Return an L{SFTPAttributes} object referring to this open file, or an error code. This is equivalent to
        L{SFTPServerInterface.stat}, except it's called on an open file instead of a path.

        @return: an attributes object for the given file, or an SFTP error code (like
        L{SFTP_PERMISSION_DENIED}). @rtype: L{SFTPAttributes} I{or error code}

class tardis.apps.sftp.sftp.MyTSFTPRequestHandler (request, client_address, server)
    Bases: SocketServer.BaseRequestHandler

    auth_timeout = 60

    handle ()

    handle_timeout ()

    setup ()

    timeout = 60

class tardis.apps.sftp.sftp.MyTSFTPServer (*args, **kwargs)
    Bases: paramiko.sftp_server.SFTPServer

    override SFTPServer to provide channel information to the SFTP subsystem

class tardis.apps.sftp.sftp.MyTSFTPServerInterface (server, *args, **kwargs)
    Bases: paramiko.sftp_si.SFTPServerInterface

    MyTardis data via SFTP

    canonicalize (path)
        Return the canonical form of a path on the server.

    experiments

    list_folder (path)
        Returns a list of files within a given folder. The C{path} will use posix notation (C{" / " } separates folder
        names) and may be an absolute or relative path.

        The list of files is expected to be a list of L{SFTPAttributes} objects, which are similar in structure to the
        objects returned by C{os.stat}. In addition, each object should have its C{filename} field filled in, since
        this is important to a directory listing and not normally present in C{os.stat} results.

        In case of an error, you should return one of the C{SFTP_*} error codes, such as
        L{SFTP_PERMISSION_DENIED}.

        @param path: the requested path (relative or absolute) to be listed. @type path: str @return: a list of the
        files in the given folder, using L{SFTPAttributes} objects. @rtype: list of L{SFTPAttributes} I{or error
        code}

```

lstat (*path*)

symbolic links are not supported

open (*path, flags, attr*)

Open a file on the server and create a handle for future operations on that file. On success, a new object subclassed from L{SFTPHandle} should be returned. This handle will be used for future operations on the file (read, write, etc). On failure, an error code such as L{SFTP_PERMISSION_DENIED} should be returned.

C{flags} contains the requested mode for opening (read-only, write-append, etc) as a bitset of flags from the C{os} module:

- C{os.O_RDONLY}
- C{os.O_WRONLY}
- C{os.O_RDWR}
- C{os.O_APPEND}
- C{os.O_CREAT}
- C{os.O_TRUNC}
- C{os.O_EXCL}

(One of C{os.O_RDONLY}, C{os.O_WRONLY}, or C{os.O_RDWR} will always be set.)

The C{attr} object contains requested attributes of the file if it has to be created. Some or all attribute fields may be missing if the client didn't specify them.

@note: The SFTP protocol defines all files to be in "binary" mode. There is no equivalent to python's "text" mode.

Parameters

- **path** (*basestring*) – the requested datafile path
- **flags** (*int*) – flags or'd together from the C{os} module indicating the requested mode for opening the file.
- **attr** (*SFTPAttributes*) – requested attributes of the file if it is newly created.

Returns a new L{SFTPHandle} I{or error code}.

Return type SFTPHandle

session_ended ()

run cleanup on exceptions or disconnection. idea: collect stats and store them in this function

session_started ()

run on connection initialisation

stat (*path*)

Return an L{SFTPAttributes} object for a path on the server, or an error code. If your server supports symbolic links (also known as "aliases"), you should follow them. (L{lstat} is the corresponding call that doesn't follow symlinks/aliases.)

@param path: the requested path (relative or absolute) to fetch file statistics for. @type path: str

@return: an attributes object for the given file, or an SFTP error code (like L{SFTP_PERMISSION_DENIED}). @rtype: L{SFTPAttributes} I{or error code}

```
class tardis.apps.sftp.sftp.MyTSFTPTCPServer (address, host_key, RequestHandler-  
                                              Class=None)
```

Bases: SocketServer.TCPServer

```
allow_reuse_address = True
```

```
close_request(request)
```

```
shutdown_request(request)
```

```
class tardis.apps.sftp.sftp.MyTServerInterface
```

```
Bases: paramiko.server.ServerInterface
```

```
check_auth_interactive(username, submethods)
```

Begin an interactive authentication challenge, if supported. You should override this method in server mode if you want to support the "keyboard-interactive" auth type, which requires you to send a series of questions for the client to answer.

Return AUTH_FAILED if this auth method isn't supported. Otherwise, you should return an *InteractiveQuery* object containing the prompts and instructions for the user. The response will be sent via a call to *check_auth_interactive_response*.

The default implementation always returns AUTH_FAILED.

Parameters

- **username** (*str*) – the username of the authenticating client
- **submethods** (*str*) – a comma-separated list of methods preferred by the client (usually empty)

Returns AUTH_FAILED if this auth method isn't supported; otherwise an object containing queries for the user

Return type int or *InteractiveQuery*

```
check_auth_interactive_response(responses)
```

Continue or finish an interactive authentication challenge, if supported. You should override this method in server mode if you want to support the "keyboard-interactive" auth type.

Return AUTH_FAILED if the responses are not accepted, AUTH_SUCCESSFUL if the responses are accepted and complete the authentication, or AUTH_PARTIALLY_SUCCESSFUL if your authentication is stateful, and this set of responses is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

If you wish to continue interactive authentication with more questions, you may return an *InteractiveQuery* object, which should cause the client to respond with more answers, calling this method again. This cycle can continue indefinitely.

The default implementation always returns AUTH_FAILED.

Parameters **responses** – list of *str* responses from the client

Returns AUTH_FAILED if the authentication fails; AUTH_SUCCESSFUL if it succeeds; AUTH_PARTIALLY_SUCCESSFUL if the interactive auth is successful, but authentication must continue; otherwise an object containing queries for the user

Return type int or *InteractiveQuery*

```
check_auth_password(username, password)
```

Determine if a given username and password supplied by the client is acceptable for use in authentication.

Return AUTH_FAILED if the password is not accepted, AUTH_SUCCESSFUL if the password is accepted and completes the authentication, or AUTH_PARTIALLY_SUCCESSFUL if your authentication is stateful, and this key is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

The default implementation always returns `AUTH_FAILED`.

Parameters

- **username** (*str*) – the username of the authenticating client.
- **password** (*str*) – the password given by the client.

Returns `AUTH_FAILED` if the authentication fails; `AUTH_SUCCESSFUL` if it succeeds; `AUTH_PARTIALLY_SUCCESSFUL` if the password auth is successful, but authentication must continue.

Return type `int`

check_auth_publickey (*username, key*)

Determine if a given key supplied by the client is acceptable for use in authentication. You should override this method in server mode to check the username and key and decide if you would accept a signature made using this key.

Return `AUTH_FAILED` if the key is not accepted, `AUTH_SUCCESSFUL` if the key is accepted and completes the authentication, or `AUTH_PARTIALLY_SUCCESSFUL` if your authentication is stateful, and this password is accepted for authentication, but more authentication is required. (In this latter case, *get_allowed_auths* will be called to report to the client what options it has for continuing the authentication.)

Note that you don't have to actually verify any key signature here. If you're willing to accept the key, Paramiko will do the work of verifying the client's signature.

The default implementation always returns `AUTH_FAILED`.

Parameters

- **username** (*str*) – the username of the authenticating client
- **key** (*PKey*) – the key object provided by the client

Returns `AUTH_FAILED` if the client can't authenticate with this key; `AUTH_SUCCESSFUL` if it can; `AUTH_PARTIALLY_SUCCESSFUL` if it can authenticate with this key but must continue with authentication

Return type `int`

check_channel_request (*kind, chanid*)

Determine if a channel request of a given type will be granted, and return `OPEN_SUCCEEDED` or an error code. This method is called in server mode when the client requests a channel, after authentication is complete.

If you allow channel requests (and an ssh server that didn't would be useless), you should also override some of the channel request methods below, which are used to determine which services will be allowed on a given channel:

- *check_channel_pty_request*
- *check_channel_shell_request*
- *check_channel_subsystem_request*
- *check_channel_window_change_request*
- *check_channel_x11_request*
- *check_channel_forward_agent_request*

The `chanid` parameter is a small number that uniquely identifies the channel within a `.Transport`. A `.Channel` object is not created unless this method returns `OPEN_SUCCEEDED` – once a `.Channel` object is created, you can call `.Channel.get_id` to retrieve the channel ID.

The return value should either be `OPEN_SUCCEEDED` (or 0) to allow the channel request, or one of the following error codes to reject it:

- `OPEN_FAILED_ADMINISTRATIVELY_PROHIBITED`
- `OPEN_FAILED_CONNECT_FAILED`
- `OPEN_FAILED_UNKNOWN_CHANNEL_TYPE`
- `OPEN_FAILED_RESOURCE_SHORTAGE`

The default implementation always returns `OPEN_FAILED_ADMINISTRATIVELY_PROHIBITED`.

Parameters

- **kind** (*str*) – the kind of channel the client would like to open (usually "session").
- **chanid** (*int*) – ID of the channel

Returns an *int* success or failure code (listed above)

`get_allowed_auths` (*username*)

Return a list of authentication methods supported by the server. This list is sent to clients attempting to authenticate, to inform them of authentication methods that might be successful.

The “list” is actually a string of comma-separated names of types of authentication. Possible values are "password", "publickey", and "none".

The default implementation always returns "password".

Parameters **username** (*str*) – the username requesting authentication.

Returns a comma-separated *str* of authentication types

`myt_auth` (*username, password*)

`tardis.apps.sftp.sftp.start_server` (*host=None, port=None, keyfile=None*)

The `SFTP_HOST_KEY` setting is required for configuring SFTP access. The `SFTP_PORT` setting defaults to 2200.

See: `tardis/default_settings/sftp.py`

tardis.apps.sftp.urls module

tardis.apps.sftp.user_menu_modifiers module

`tardis.apps.sftp.user_menu_modifiers.add_ssh_keys_menu_item` (*request, user_menu*)

Add a ‘Manage SSH Keys’ item to the user menu

Parameters

- **request** (`django.http.HttpRequest`) – an HTTP Request instance
- **user_menu** (*list*) – user menu context to modify

Returns *user_menu* list

Return type *list*

tardis.apps.sftp.views module

tardis.apps.sftp.views.**cybderduck_connection_window**(request, *args, **kwargs)

tardis.apps.sftp.views.**sftp_access**(request, *args, **kwargs)

Show dynamically generated instructions on how to connect to SFTP :param Request request: HttpRequest
:return: HttpResponse :rtype: HttpResponse

tardis.apps.sftp.views.**sftp_keys**(request, *args, **kwargs)

Generate an RSA key pair for a user.

Generates a key pair, stores the public part of the key and provides a one time opportunity for the user to download the private part of the key.

Parameters **request** (*HttpRequest*) – http request

Returns either returns form on GET request or private key download on POST request

Return type HttpResponse

Module contents

tardis.apps.social_auth package

Subpackages

tardis.apps.social_auth.auth package

Submodules

tardis.apps.social_auth.auth.authorisation module

tardis.apps.social_auth.auth.social_auth module

tardis.apps.social_auth.auth.social_auth.**add_authentication_method**(**kwargs)

Creates an authentication record for OpenID authenticated user

tardis.apps.social_auth.auth.social_auth.**add_migration_permission**(**kwargs)

Adds permission to migrate account for OpenID authenticated user

tardis.apps.social_auth.auth.social_auth.**add_user_permissions**(**kwargs)

Adds default permission to OpenID authenticated user

tardis.apps.social_auth.auth.social_auth.**approve_user_auth**(**kwargs)

Sets approved status to True in user authentication This will add user permissions as well.

tardis.apps.social_auth.auth.social_auth.**configure_social_auth_user**(**kwargs)

Applies configuration used for external (non-Django) accounts.

Adds user to settings.NEW_USER_INITIAL_GROUPS and sets isDjangoAccount to False in their UserProfile, so that MyTardis won't allow them to change their password.

tardis.apps.social_auth.auth.social_auth.**get_auth_method**(authenticatedBackendName)

Return matching user authentication method from list of authentication methods in settings

tardis.apps.social_auth.auth.social_auth.**is_openid_migration_enabled**()

```
tardis.apps.social_auth.auth.social_auth.migrate_user_message (**kwargs)
    Automatically detects if a user has an account with the same email address and prompts user to perform migration.

tardis.apps.social_auth.auth.social_auth.requires_admin_approval (authenticationBackend)

tardis.apps.social_auth.auth.social_auth.send_admin_email (**kwargs)
    Sends MyTardis admins an email for approving account
```

Module contents

Submodules

tardis.apps.social_auth.apps module

```
class tardis.apps.social_auth.apps.SocialAuthConfig(app_name, app_module)
    Bases: tardis.app_config.AbstractTardisAppConfig

    name = 'tardis.apps.social_auth'

    verbose_name = 'Social Auth'
```

tardis.apps.social_auth.default_settings module

tardis.apps.social_auth.urls module

Module contents

Module contents

tardis.default_settings package

Submodules

tardis.default_settings.admins module

```
tardis.default_settings.admins.ADMINS = []
```

A list of all the people who get code error notifications. When `DEBUG=False` and `AdminEmailHandler` is configured in `LOGGING` (done by default), Django emails these people the details of exceptions raised in the request/response cycle.

Each item in the list should be a tuple of (Full name, email address). Example:

```
[('John', 'john@example.com'), ('Mary', 'mary@example.com')]
```

tardis.default_settings.analytics module

tardis.default_settings.apps module

```
tardis.default_settings.apps.USER_MENU_MODIFIERS = ['tardis.apps.sftp.user_menu_modifiers...
    A list of methods which can modify the user menu defined in
```

`tardis.tardis_portal.context_processors.user_menu_processor` The modifications will be applied in order, so it is possible for one app to overwrite changes made by another app whose modifier method is earlier in the list.

Each modifier method should take a `django.http.HttpRequest` object and a list of user menu items, and return a modified list of user menu items.

An example from the SFTP app is below:

```
USER_MENU_MODIFIERS.extend([
    'tardis.apps.sftp.user_menu_modifiers.add_ssh_keys_menu_item'
])
```

tardis.default_settings.auth module

`tardis.default_settings.auth.AUTOGENERATE_API_KEY = False`

Generate a tastypie API key with user post_save (`tardis/tardis_portal/models/hooks.py`)

`tardis.default_settings.auth.REGISTRATION_OPEN = True`

Enable/disable the self-registration link and form in the UI. Note - this does not actually disable the URL endpoints for registration. You must also remove the *registration* app from *INSTALLED_APPS* to disable registration.

tardis.default_settings.caches module

`tardis.default_settings.caches.CACHES = {'celery-locks': {'BACKEND': 'django.core.cache.backends.memcached.MemcachedCache'}}`
change the CACHES setting to memcached if you prefer. Requires additional dependencies.

tardis.default_settings.celery_settings module

tardis.default_settings.custom_views module

`tardis.default_settings.custom_views.DATASET_VIEWS = []`

Dataset view overrides ('contextual views') are specified as tuples mapping a Schema namespace to a class-based view (or view function). See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#dataset-and-experiment-views

e.g.:

```
DATASET_VIEWS = [
    ('http://example.org/schemas/dataset/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomDatasetViewSubclass'),
]
```

`tardis.default_settings.custom_views.EXPERIMENT_VIEWS = []`

Experiment view overrides ('contextual views') are specified as tuples mapping a Schema namespace to a class-based view (or view function). See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#dataset-and-experiment-views

e.g.:

```
EXPERIMENT_VIEWS = [
    ('http://example.org/schemas/expt/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomExptViewSubclass'),
]
```

`tardis.default_settings.custom_views.INDEX_VIEWS = {}`

A custom index page override is defined in as dictionary mapping a class-based view (or view function) to a Django Site, specified by `SITE_ID` (an integer) or the domain name of the incoming request. See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#custom-index-view

e.g.:

```
INDEX_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomIndexSubclass',
    'store.example.com': 'tardis.apps.myapp.AnotherCustomIndexSubclass'
}
```

`tardis.default_settings.custom_views.LOGIN_VIEWS = {}`

A custom login page override is defined in as dictionary mapping a class-based view (or view function) to a Django Site, specified by `SITE_ID` (an integer) or the domain name of the incoming request. See: https://mytardis.readthedocs.io/en/develop/apps/contextual_views.html#custom-login-view

e.g.:

```
LOGIN_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomLoginSubclass',
    'store.example.com': 'tardis.apps.myapp.AnotherCustomLoginSubclass'
}
```

tardis.default_settings.database module

tardis.default_settings.debug module

`tardis.default_settings.debug.ALLOWED_HOSTS = ['*']`

For security reasons this needs to be set to your hostname and/or IP address in production.

`tardis.default_settings.debug.DEBUG = True`

Set to false for production use

`tardis.default_settings.debug.INTERNAL_IPS = ('127.0.0.1',)`

A list of IP addresses, as strings, that: Allow the `debug()` context processor to add some variables to the template context.

tardis.default_settings.downloads module

`tardis.default_settings.downloads.DEFAULT_ARCHIVE_FORMATS = ['tar']`

Site's preferred archive types, with the most preferred first other available option: 'tgz'. Add to list if desired

`tardis.default_settings.downloads.DOWNLOAD_URI_TEMPLATES = {}`

When a file download is requested, by default, MyTardis will create a `StreamingHttpResponse` to serve the download which requires reading the file from a file-like object. For some storage backends, e.g. `S3Boto3Storage` provided by the `django-storages` package, it is more efficient to redirect the request directly to the storage provider.

Or the download request could be handled by an API which is aware of HSM (Hierarchical Storage Management) status for files which could be either on disk or on tape.

The `DOWNLOAD_URI_TEMPLATES` dictionary can be used to specify a URI template (e.g. `/api/v1/s3utils_replica/{dfo_id}/download/` which can be used to download a `DataFileObject`, instead of using the default `/api/v1/dataset_file/[datafile_id]/download/` endpoint.

For example,

```
DOWNLOAD_URI_TEMPLATES = { 'storages.backends.s3boto3.S3Boto3Storage':  
    '/api/v1/s3utils_replica/{dfo_id}/download/'  
}
```

The `/api/v1/s3utils_replica/{dfo_id}/download/` endpoint is provided by the `'s3utils'` tardis app which needs to be in your `INSTALLED_APPS`

tardis.default_settings.email module

```
tardis.default_settings.email.DEFAULT_FROM_EMAIL = 'webmaster@localhost'
```

This can be set as : “MyTardis Admins <admins@mytardis.org>”

```
tardis.default_settings.email.EMAIL_HOST = 'localhost'
```

Set this to your local SMTP server, e.g. `'smtp.example.edu'` or to a remote SMTP server, e.g. `'smtp.gmail.com'`

```
tardis.default_settings.email.EMAIL_HOST_PASSWORD = ''
```

When using a local SMTP server, you probably don't need to authenticate, so you can leave this blank.

If using a remote SMTP server, this can be set to the password used to authenticate.

```
tardis.default_settings.email.EMAIL_HOST_USER = ''
```

When using a local SMTP server, you probably don't need to authenticate, so you can leave this blank.

If using a remote SMTP server, this can be set to the email address used to authenticate, e.g. `'bob@bobmail.com'`

```
tardis.default_settings.email.EMAIL_PORT = 25
```

Some SMTP servers require a different port, e.g. 587. Django's default value for this setting is 25.

```
tardis.default_settings.email.EMAIL_USE_TLS = False
```

Some SMTP servers require this to be set to True. Django's default value for this setting is False.

tardis.default_settings.filters module

```
tardis.default_settings.filters.FILTERS_TASK_PRIORITY = 4
```

The default RabbitMQ task priority for messages sent to the filters microservice. Priority 4 is slightly less than the overall default task priority of 5, defined in `tardis/default_settings/celery_settings.py`

```
tardis.default_settings.filters.USE_FILTERS = False
```

If enabled, a task will be sent to RabbitMQ after a file is saved and verified, requesting post-processing, e.g. extracting metadata from file headers and/or generating thumbnail images.

tardis.default_settings.frontend module

```
tardis.default_settings.frontend.BLEACH_ALLOWED_ATTRIBUTES = {'a': ['href', 'title'], 'ab
```

These are the default bleach values and shown here as an example.

```
tardis.default_settings.frontend.BLEACH_ALLOWED_TAGS = ['a', 'abbr', 'acronym', 'b', 'bloc
```

These are the default bleach values and shown here as an example.

```
tardis.default_settings.frontend.MAX_IMAGES_IN_CAROUSEL = 100
```

Max number of images in dataset view's carousel: zero means no limit

```
tardis.default_settings.frontend.RENDER_IMAGE_DATASET_SIZE_LIMIT = 0
```

Render image dataset size limit: zero means no limit

In order to display a dataset thumbnail image, MyTardis queries the dataset's files for image MIME types. These queries can be very slow for large datasets, making page load times slow. In future versions, the dataset thumbnails will be generated asynchronously (not at response time), but for now, we can set `RENDER_IMAGE_DATASET_SIZE_LIMIT` to the maximum number of files a dataset can have for MyTardis to scan it for image files at response time.

```
tardis.default_settings.frontend.RENDER_IMAGE_SIZE_LIMIT = 0
```

Render image file size limit: zero means no limit

`tardis.default_settings.i18n` module

`tardis.default_settings.localisation` module

`tardis.default_settings.logging` module

`tardis.default_settings.middlewares` module

`tardis.default_settings.publication` module

`tardis.default_settings.search` module

Settings for search

```
tardis.default_settings.search.MAX_SEARCH_RESULTS = 100
```

Limits the maximum number of search results for each model (Experiment, Dataset and DataFile). The default value of 100 means that a query could potentially return 300 results in total, i.e. 100 experiments, 100 datasets and 100 datafiles.

```
tardis.default_settings.search.MIN_CUTOFF_SCORE = 0.0
```

Filters results based on this value. The default value of 0.0 means that nothing will be excluded from search results. Set it to any number greater than 0.0 to filter out results.

```
tardis.default_settings.search.SINGLE_SEARCH_ENABLED = False
```

To enable search:

```
SINGLE_SEARCH_ENABLED = True
INSTALLED_APPS += ('django_elasticsearch_dsl',
'tardis.app.search')
ELASTICSEARCH_DSL = {
    'default': { 'hosts': os.environ.get('ELASTICSEARCH_URL', 'http://localhost:9200')
    }
}
ELASTICSEARCH_DSL_INDEX_SETTINGS = {
    'number_of_shards': 1
}
```

`tardis.default_settings.sharing` module

tardis.default_settings.site_customisations module

`tardis.default_settings.site_customisations.SITE_TITLE = 'MyTardis'`
customise the title of your site

`tardis.default_settings.site_customisations.SPONSORED_TEXT = None`
add text to the footer to acknowledge someone

tardis.default_settings.static_files module

tardis.default_settings.storage module

`tardis.default_settings.storage.CALCULATE_CHECKSUMS_METHODS = {}`
A custom method can be provided for calculating checksums for a storage class, e.g.

```
CALCULATE_CHECKSUMS_METHODS = {  
    'storages.backends.s3boto3.S3Boto3Storage': 'tardis.apps.s3utils.utils.calculate_checksums'  
}
```

The `DataFileObject` class's `calculate_checksums` method checks for a storage class match in the `CALCULATE_CHECKSUMS_METHODS` dict, and if one is not found, it calls the classic `compute_checksums` method which uses the `file_object` to calculate the checksums one chunk at a time. For some storage backends (e.g. S3), representing the file as file-like object with Django's file storage API is not the most efficient way to calculate the checksum.

`tardis.default_settings.storage.METADATA_STORE_PATH = '/home/docs/checkouts/readthedocs.org'`
storage path for image paths stored in parameters. Better to set to another location if possible

`tardis.default_settings.storage.REUSE_DATASET_STORAGE_BOX = True`
If a new `DataFile` is created in a `Dataset` whose files are all stored in the same storage box, then the new file will be stored in the same storage box, irrespective of the “default” `StorageBoxAttribute`.

The `mytardis-app-mydata` app has its own logic for determining the appropriate storage box for uploads from a `MyData` instance. When a `MyData` instance (an “Uploader”) is approved, it will be assigned a storage box which should be used for `DataFileObjects` created from `MyData` uploads.

tardis.default_settings.templates module

tardis.default_settings.uploads module

`tardis.default_settings.uploads.UPLOAD_METHOD = False`
Old version: `UPLOAD_METHOD = “uploadify”`. This can be changed to an app that provides an `upload_button` function, eg. “`tardis.apps.filepicker.views.upload_button`” to use a fancy commercial uploader. To use `filepicker`, please also get an API key at <http://filepicker.io>

tardis.default_settings.urls module

Module contents

`tardis.default_settings.get_git_version()`

tardis.tardis_portal package

Subpackages

tardis.tardis_portal.auth package

Submodules

tardis.tardis_portal.auth.authentication module

A module containing helper methods for the `manage_auth_methods` function in `views.py`.

`tardis.tardis_portal.auth.authentication.add_auth_method(request)`

Add a new authentication method to `request.user`'s existing list of authentication methods. This method will ask for a confirmation if the user wants to merge two accounts if the authentication method he provided already exists as a method for another user.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.edit_auth_method(request)`

Change the local DB (Django) password for `request.user`.

`tardis.tardis_portal.auth.authentication.list_auth_methods(request)`

Generate a list of authentication methods that `request.user` uses to authenticate to the system and send it back in a `HttpResponse`.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.merge_auth_method(request)`

Merge the account that the user is logged in as and the account that he provided in the Authentication Form. Merging accounts involve relinking the `UserAuthentication` table entries, transferring `ObjectACL` entries to the merged account, changing the Group memberships and deleting the unneeded account.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

`tardis.tardis_portal.auth.authentication.remove_auth_method(request)`

Removes the non-local DB auth method from the `UserAuthentication` model.

Parameters `request` (*Request*) – the HTTP request object

Returns The `HttpResponse` which contains `request.user`'s new list of authentication methods

Return type `HttpResponse`

tardis.tardis_portal.auth.authorisation module

Object-level authorisation backend

```
class tardis.tardis_portal.auth.authorisation.ACLAwareBackend
```

Bases: `object`

```
app_label = 'tardis_acls'
```

```
authenticate(request)
```

do not use this backend for authentication

```
get_perm_bool(verb)
```

relates ACLs to permissions

```
has_perm(user_obj, perm, obj=None)
```

main method, calls other methods based on permission type queried

```
supports_anonymous_user = True
```

```
supports_object_permissions = True
```

tardis.tardis_portal.auth.authservice module

models.py

```
class tardis.tardis_portal.auth.authservice.AuthService(settings=<LazySettings
                                                         "tardis.test_settings">)
```

The AuthService provides an interface for querying the auth(n/z) framework within MyTardis. The auth service works by reading the class path to plugins from the settings file.

Parameters `settings` (`django.conf.settings`) – the settings object that contains the list of user and group plugins.

```
authenticate(authMethod, **credentials)
```

Try and authenticate the user using the auth type he/she specified to use and if authentication didn't work using that

Parameters

- **authMethod** (`string`) – the shortname of the auth method.
- **credentials** (`kwargs`) – the credentials as expected by the auth plugin

Returns authenticated User or None

Return type User or None

```
getGroups(user)
```

Parameters `user` (`User`) – User

Returns a list of tuples containing pluginname and group id

Return type list

```
getGroupsForEntity(entity)
```

Return a list of the groups an entity belongs to

Parameters `entity` (`string`) – the entity to earch for, user or group.

Returns groups

Return type Group

The groups will be returned as a list similar to:

```
[{'name': 'Group 456', 'id': '2'},
 {'name': 'Group 123', 'id': '1'}]
```

getUser (*authMethod, user_id, force_user_create=False*)

Return a user model based on the given auth method and user id.

This function is responsible for creating the user within the Django DB and returning the resulting user model.

getUsernameByEmail (*authMethod, email*)

Return a username given the auth method and email address of a user.

get_or_create_user (*user_obj_or_dict, authMethod=None*)

refactored out for external use by AAF and possibly others

searchEntities (*filter*)

Return a list of users and/or groups

searchGroups (***kw*)

basestring id: the value of the id to search for basestring name: the value of the displayname to search for int max_results: the maximum number of elements to return basestring sort_by: the attribute the users should be sorted on basestring plugin: restrict the search to the specific group provider

returns: a list of users and/or groups rtype: list

searchUsers (*filter*)

Return a list of users and/or groups

tardis.tardis_portal.auth.decorators module

tardis.tardis_portal.auth.decorators.**datafile_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_download_required** (*f*)

tardis.tardis_portal.auth.decorators.**dataset_write_permissions_required** (*f*)

tardis.tardis_portal.auth.decorators.**delete_permissions_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_access_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_download_required** (*f*)

tardis.tardis_portal.auth.decorators.**experiment_ownership_required** (*f*)

A decorator for Django views that validates if a user is an owner of an experiment or ‘superuser’ prior to further processing the request. Unauthenticated requests are redirected to the login page. If the user making the request satisfies none of these criteria, an error response is returned.

Parameters *f* (*types.FunctionType*) – A Django view function

Returns A Django view function

Return type *types.FunctionType*

tardis.tardis_portal.auth.decorators.**get_accessible_datafiles_for_user** (*request*)

tardis.tardis_portal.auth.decorators.**get_accessible_experiments** (*request*)

tardis.tardis_portal.auth.decorators.**get_accessible_experiments_for_dataset** (*request, dataset_id*)

tardis.tardis_portal.auth.decorators.**get_owned_experiments** (*request*)

tardis.tardis_portal.auth.decorators.**get_shared_experiments** (*request*)

`tardis.tardis_portal.auth.decorators.group_ownership_required(f)`

A decorator for Django views that validates if a user is a group admin or 'superuser' prior to further processing the request. Unauthenticated requests are redirected to the login page. If the user making the request satisfies none of these criteria, an error response is returned.

Parameters *f* (*types.FunctionType*) – A Django view function

Returns A Django view function

Return type *types.FunctionType*

`tardis.tardis_portal.auth.decorators.has_datafile_access(request, datafile_id)`

`tardis.tardis_portal.auth.decorators.has_datafile_download_access(request, datafile_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_access(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_download_access(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_ownership(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_dataset_write(request, dataset_id)`

`tardis.tardis_portal.auth.decorators.has_delete_permissions(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_access(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_download_access(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_ownership(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_experiment_write(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.has_read_or_owner_ACL(request, experiment_id)`

Check whether the user has read access to the experiment - this means either they have been granted read access, or that they are the owner.

NOTE: This does not check whether the experiment is public or not, which means even when the experiment is public, this method does not automatically returns true.

As such, this method should NOT be used to check whether the user has general read permission.

`tardis.tardis_portal.auth.decorators.has_write_permissions(request, experiment_id)`

`tardis.tardis_portal.auth.decorators.is_group_admin(request, *args, **kwargs)`

`tardis.tardis_portal.auth.decorators.upload_auth(f)`

`tardis.tardis_portal.auth.decorators.write_permissions_required(f)`

tardis.tardis_portal.auth.fix_circular module

`tardis.tardis_portal.auth.fix_circular.getGroups(user)`

tardis.tardis_portal.auth.interfaces module

class tardis.tardis_portal.auth.interfaces.**AuthProvider**

authenticate (*request*)

from a request authenticate try to authenticate the user. return a user dict if successful.

getUsernameByEmail (*email*)

returns the username (format string) from the auth domain

Implementing this function is optional- it is needed for resolving experiment owner email addresses to usernames during ingestion.

get_user (*user_id*)

class tardis.tardis_portal.auth.interfaces.**GroupProvider**

getGroupById (*id*)

return the group associated with the id

getGroups (*user*)

return an iteration of the available groups.

getGroupsForEntity (*id*)

return a list of groups associated with a particular entity id

searchGroups (***filter*)

return a list of groups that match the filter

class tardis.tardis_portal.auth.interfaces.**UserProvider**

getUserById (*id*)

return the user dictionary in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

getUsernameByEmail (*email*)

returns the username (format string) from the auth domain needed for resolving experiment owners during ingestion

searchUsers (***filter*)

return a list of user descriptions from the auth domain.

each user is in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

tardis.tardis_portal.auth.ldap_auth module

tardis.tardis_portal.auth.localdb_auth module

Local DB Authentication module.

class tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend

Bases: *tardis.tardis_portal.auth.interfaces.AuthProvider*

Authenticate against Django's Model Backend.

authenticate (*request*)

authenticate a user, this expect the user will be using form based auth and the *username* and *password* will be passed in as **POST** variables.

Parameters *request* (*django.http.HttpRequest*) – a HTTP Request instance

Returns authenticated User

Return type User

get_user (*user_id*)

class tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider

Bases: *tardis.tardis_portal.auth.interfaces.GroupProvider*

getGroupById (*id*)

return the group associated with the id:

```
{ "id": 123,
```

```
  "display": "Group Name", }
```

getGroups (*user*)

return an iteration of the available groups.

name = u'django_group'

searchGroups (***filter*)

class tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider

Bases: *tardis.tardis_portal.auth.interfaces.UserProvider*

getUserById (*id*)

return the user dictionary in the format of:

```
{ "id": 123,
  "first_name": "John",
  "last_name": "Smith",
  "email": "john@example.com" }
```

name = u'django_user'

tardis.tardis_portal.auth.token_auth module

token authentication module

class tardis.tardis_portal.auth.token_auth.TokenAuthMiddleware (*get_response*)

Bases: *object*

adds tokens to the user object and the session from a GET query

process_request (*request*)

```
class tardis.tardis_portal.auth.token_auth.TokenGroupProvider
    Bases: tardis.tardis_portal.auth.interfaces.GroupProvider

    Transforms tokens into auth groups

    getGroups (user)

    name = u'token_group'

    searchGroups (**kwargs)
        return nothing because these are not groups in the standard sense
```

tardis.tardis_portal.auth.utils module

Created on 15/03/2011

@author: gerson

```
tardis.tardis_portal.auth.utils.configure_user (user)
    Configure a user account that has just been created by adding the user to the default groups and marking it as a
    not a Django account.

    Parameters user (User) – the User instance for the newly created account

    Returns User profile for user

    Return type UserProfile
```

```
tardis.tardis_portal.auth.utils.create_user (auth_method, user_id, email=")
```

```
tardis.tardis_portal.auth.utils.get_or_create_user (auth_method, user_id, email=")
```

Module contents

tardis.tardis_portal.management package

Subpackages

tardis.tardis_portal.management.commands package

Submodules

tardis.tardis_portal.management.commands.createuser module

Management utility to create regular users.

```
class tardis.tardis_portal.management.commands.createuser.Command (stdout=None,
                                                                    stderr=None,
                                                                    no_color=False)

    Bases: django.core.management.base.BaseCommand

    add_arguments (parser)

    handle (*args, **options)

    help = 'Used to create a MyTardis user.'

tardis.tardis_portal.management.commands.createuser.is_valid_email (value)
```

tardis.tardis_portal.management.commands.dumpschemas module

Command for dumping soft schema definitions

```
class tardis.tardis_portal.management.commands.dumpschemas.Command(stdout=None,  
                                                                    stderr=None,  
                                                                    no_color=False)  
  
    Bases: django.core.management.base.BaseCommand  
  
    add_arguments (parser)  
  
    args = '[namespace...]'  
  
    handle (*args, **options)  
  
    help = 'Dump soft schema definitions. No namespace = dump all schemas'
```

tardis.tardis_portal.management.commands.loadschemas module

Command for loading soft schema definitions

```
class tardis.tardis_portal.management.commands.loadschemas.Command(stdout=None,  
                                                                    stderr=None,  
                                                                    no_color=False)  
  
    Bases: django.core.management.base.BaseCommand  
  
    add_arguments (parser)  
  
    args = 'schema [schema ...]'  
  
    handle (*args, **options)  
  
    help = 'Load soft schema definitions'
```

tardis.tardis_portal.management.commands.rmexperiment module

Management command to delete the specified experiment and its associated datasets, datafiles and parameters.

The operation is atomic, either the entire experiment is deleted, or nothing.

rmexperiment was introduced due to the Oracle DISTINCT workaround causing sql delete cascading to fail. The current implementation of rmexperiment still relies on some cascading.

```
class tardis.tardis_portal.management.commands.rmexperiment.Command(stdout=None,  
                                                                    stderr=None,  
                                                                    no_color=False)  
  
    Bases: django.core.management.base.BaseCommand  
  
    add_arguments (parser)  
  
    args = '<MyTardis Exp ID>'  
  
    handle (*args, **options)  
  
    help = 'Delete the supplied MyTardis Experiment ID'
```

Module contents

Module contents

tardis.tardis_portal.migrations package

Submodules

tardis.tardis_portal.migrations.0001_initial module

```
class tardis.tardis_portal.migrations.0001_initial.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'contenttypes', u'0002_remove_content_type_name'), (u'auth', u'__first__')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'first_name', <django.db.models.fields.CharField>), (u'last_name', <django.db.models.fields.CharField>), (u'email', <django.db.models.fields.EmailField>), (u'password', <django.db.models.fields.CharField>), (u'is_staff', <django.db.models.fields.BooleanField>), (u'is_superuser', <django.db.models.fields.BooleanField>), (u'groups', <django.db.models.fields.related.ManyToManyField>), (u'user_permissions', <django.db.models.fields.related.ManyToManyField>)]>]
```

tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643 module

```
class tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'contenttypes', u'0002_remove_content_type_name'), (u'auth', u'__first__')]
    operations = [<CreateModel fields=[(u'id', <django.db.models.fields.AutoField>), (u'first_name', <django.db.models.fields.CharField>), (u'last_name', <django.db.models.fields.CharField>), (u'email', <django.db.models.fields.EmailField>), (u'password', <django.db.models.fields.CharField>), (u'is_staff', <django.db.models.fields.BooleanField>), (u'is_superuser', <django.db.models.fields.BooleanField>), (u'groups', <django.db.models.fields.related.ManyToManyField>), (u'user_permissions', <django.db.models.fields.related.ManyToManyField>)]>, <AlterModelOptions options={'ordering': ('first_name', 'last_name')}>]
    replaces = [(u'tardis_portal', u'0001_initial'), (u'tardis_portal', u'0002_auto_20150528_1128'), (u'tardis_portal', u'0003_auto_20150907_1315')]

tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160505_1643.cast_string_to_integer
```

tardis.tardis_portal.migrations.0002_auto_20150528_1128 module

```
class tardis.tardis_portal.migrations.0002_auto_20150528_1128.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0001_initial')]
    operations = [<AlterField field=<django.db.models.fields.related.OneToOneField>, name='first_name', to_type=django.db.models.CharField, to_kwargs={'max_length': 30}, to_preserve_max_length=True>]
```

tardis.tardis_portal.migrations.0003_auto_20150907_1315 module

```
class tardis.tardis_portal.migrations.0003_auto_20150907_1315.Migration (name, app_label)
    Bases: django.db.migrations.migration.Migration

    dependencies = [(u'tardis_portal', u'0002_auto_20150528_1128')]
    operations = [<AlterField field=<django.db.models.fields.IntegerField>, name=u'data_type', to_type=django.db.models.CharField, to_kwargs={'max_length': 30}, to_preserve_max_length=True>]
```

tardis.tardis_portal.migrations.0004_storageboxoption_value_type module

```
class tardis.tardis_portal.migrations.0004_storageboxoption_value_type.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0003_auto_20150907_1315')]
    operations = [<AddField field=<django.db.models.fields.CharField>, name=u'value_type',
```

tardis.tardis_portal.migrations.0005_datafile_add_size_int_column module

```
class tardis.tardis_portal.migrations.0005_datafile_add_size_int_column.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0004_storageboxoption_value_type')]
    operations = [<AddField field=<django.db.models.fields.BigIntegerField>, name=u'_size'
tardis.tardis_portal.migrations.0005_datafile_add_size_int_column.cast_string_to_integer(ap
sc
```

tardis.tardis_portal.migrations.0006_datafile_remove_size_string_column module

```
class tardis.tardis_portal.migrations.0006_datafile_remove_size_string_column.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0005_datafile_add_size_int_column')]
    operations = [<RemoveField name=u'size', model_name=u'datafile'>, <RenameField new_name=
```

tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index module

```
class tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0006_datafile_remove_size_string_column')]
    operations = [<AlterField field=<django.db.models.fields.TextField>, name=u'string_val
```

tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres module

```
class tardis.tardis_portal.migrations.0008_string_value_partial_index_postgres.Migration(name,
                                                                    app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0007_remove_parameter_string_value_index')]
    operations = []
```

tardis.tardis_portal.migrations.0009_auto_20160128_1119 module

```
class tardis.tardis_portal.migrations.0009_auto_20160128_1119.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0008_string_value_partial_index_postgres')]  
    operations = [<AlterUniqueTogether unique_together=set([(u'name', u'facility')]), name=
```

tardis.tardis_portal.migrations.0010_auto_20160503_1443 module

```
class tardis.tardis_portal.migrations.0010_auto_20160503_1443.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0009_auto_20160128_1119')]  
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'mimetype',
```

tardis.tardis_portal.migrations.0011_auto_20160505_1643 module

```
class tardis.tardis_portal.migrations.0011_auto_20160505_1643.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0010_auto_20160503_1443')]  
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'directory'
```

tardis.tardis_portal.migrations.0012_userauthentication_approved module

```
class tardis.tardis_portal.migrations.0012_userauthentication_approved.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0011_auto_20160505_1643')]  
    operations = [<AddField field=<django.db.models.fields.BooleanField>, name=u'approved'
```

tardis.tardis_portal.migrations.0013_auto_20181002_1136 module

```
class tardis.tardis_portal.migrations.0013_auto_20181002_1136.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration  
    dependencies = [(u'tardis_portal', u'0012_userauthentication_approved')]  
    operations = [<AlterModelOptions options={u'ordering': (u'name',), u'verbose_name_plu
```

tardis.tardis_portal.migrations.0014_auto_20181002_1154 module

```
class tardis.tardis_portal.migrations.0014_auto_20181002_1154.Migration(name,  
                                                                    app_label)  
    Bases: django.db.migrations.migration.Migration
```

```
dependencies = [(u'tardis_portal', u'0013_auto_20181002_1136')]
operations = [<AlterField field=<django.db.models.fields.BigIntegerField>, name=u'max_
```

`tardis.tardis_portal.migrations.0015_dataset_created_time` module

```
class tardis.tardis_portal.migrations.0015_dataset_created_time.Migration(name,
                                                                           app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0014_auto_20181002_1154')]
    operations = [<AddField field=<django.db.models.fields.DateTimeField>, name=u'created_
```

`tardis.tardis_portal.migrations.0016_add_timestamps` module

```
class tardis.tardis_portal.migrations.0016_add_timestamps.Migration(name,
                                                                       app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0015_dataset_created_time')]
    operations = [<AddField field=<django.db.models.fields.DateTimeField>, name=u'created_
```

`tardis.tardis_portal.migrations.0017_add_cc_licenses` module

```
class tardis.tardis_portal.migrations.0017_add_cc_licenses.Migration(name,
                                                                       app_label)
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0016_add_timestamps'), (u'auth', u'0008_alter_user_
    operations = [<RunPython <function forwards_func>, <function reverse_func>>]

tardis.tardis_portal.migrations.0017_add_cc_licenses.forwards_func(apps,
                                                                    schema_editor)
tardis.tardis_portal.migrations.0017_add_cc_licenses.load_licenses(apps,
                                                                    schema_editor)
tardis.tardis_portal.migrations.0017_add_cc_licenses.remove_licenses(apps,
                                                                    schema_editor)
tardis.tardis_portal.migrations.0017_add_cc_licenses.reverse_func(apps,
                                                                    schema_editor)
```

`tardis.tardis_portal.migrations.0018_make_default_storage_box_status_online` module

```
class tardis.tardis_portal.migrations.0018_make_default_storage_box_status_online.Migration
    Bases: django.db.migrations.migration.Migration
    dependencies = [(u'tardis_portal', u'0017_add_cc_licenses')]
    operations = [<AlterField field=<django.db.models.fields.CharField>, name=u'status', m
```

Module contents

tardis.tardis_portal.models package

Submodules

tardis.tardis_portal.models.access_control module

class tardis.tardis_portal.models.access_control.**GroupAdmin** (*args, **kwargs)
 Bases: django.db.models.base.Model

GroupAdmin links the Django User and Group tables for group administrators

Attribute user a foreign key to the `django.contrib.auth.models.User`

Attribute group a foreign key to the `django.contrib.auth.models.Group`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

group

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

group_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.access_control.ObjectACL(*args, **kwargs)
    Bases: django.db.models.base.Model
```

The ObjectACL (formerly ExperimentACL) table is the core of the [Tardis Authorisation framework](#)

Attribute pluginId the the name of the auth plugin being used

Attribute entityId a foreign key to auth plugins

Attribute object_type a foreign key to ContentType

Attribute object_id the primary key/id of the object_type

Attribute canRead gives the user read access

Attribute canWrite gives the user write access

Attribute canDelete gives the user delete permission

Attribute isOwner the experiment owner flag.

Attribute effectiveDate the date when access takes into effect

Attribute expiryDate the date when access ceases

Attribute aclOwnershipType system-owned or user-owned.

System-owned ACLs will prevent users from removing or editing ACL entries to a particular experiment they own. User-owned ACLs will allow experiment owners to remove/add/edit ACL entries to the experiments they own.

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

OWNER_OWNED = 1

SYSTEM_OWNED = 2

aclOwnershipType

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canDelete

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canRead

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

canWrite

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

content_object

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

content_type

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

content_type_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

effectiveDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

entityId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

expiryDate

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_aclOwnershipType_display (***morekwargs*)

classmethod get_effective_query ()

get_related_object ()

If possible, resolve the pluginId/entityId combination to a user or group object.

get_related_object_group ()

If possible, resolve the pluginId/entityId combination to a user or group object.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isOwner

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

object_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

openidaclmigration_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

pluginId

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.access_control.UserAuthentication(id, user-  
Profile,  
user-  
name,  
authen-  
tication-  
Method,  
ap-  
proved)
```

Bases: `django.db.models.base.Model`

CHOICES = ()

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

approved

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

authenticationMethod

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getAuthMethodDescription()

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <`django.db.models.manager.Manager` object>

save (*args, **kwargs)

userProfile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):  
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

userProfile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

username

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.access_control.UserProfile(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

`UserProfile` class is an extension to the Django standard user model.

Attribute isDjangoAccount is the user a local DB user

Attribute user a foreign key to the `django.contrib.auth.models.User`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

ext_groups

getUserAuthentications()

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isDjangoAccount

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

isValidPublicContact()

Checks if there's enough information on the user for it to be used as a public contact.

Note: Last name can't be required, because people don't necessarily have a last (or family) name.

objects = <django.db.models.manager.Manager object>

rapidConnectEduPersonTargetedID

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a one-to-one relation.

In the example:

```
class Restaurant(Model):
    place = OneToOneField(Place, related_name='restaurant')
```

`restaurant.place` is a `ForwardOneToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

userauthentication_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToManyDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
tardis.tardis_portal.models.access_control.create_user_api_key(sender,
                                                                **kwargs)
```

Auto-create ApiKey objects using Tastypie's `create_api_key`

```
tardis.tardis_portal.models.access_control.create_user_profile(sender, instance, created,
                                                             **kwargs)
```

tardis.tardis_portal.models.datafile module

```
class tardis.tardis_portal.models.datafile.DataFile(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

A `DataFile` is a record of a file which includes its filename, its size in bytes, its relative directory, and various other meta-data. Each `DataFile` belongs to a `Dataset` which usually represents the files from one folder on an instrument PC.

The physical copy (or copies) of a file are described by distinct `DataFileObject` records.

Attribute dataset The foreign key to the `tardis.tardis_portal.models.Dataset` the file belongs to.

Attribute filename The name of the file, excluding the path.

Attribute size The size of the file.

Attribute created_time Should be populated with the file's creation time from the instrument PC.

Attribute modification_time Should be populated with the file's last modification time from the instrument PC.

Attribute mimetype For example 'application/pdf'

Attribute md5sum Digest of length 32, containing only hexadecimal digits

Attribute sha512sum Digest of length 128, containing only hexadecimal digits

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

cache_file()

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

dataset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

dataset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

deleted

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

deleted_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

directory

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

file_object

file_objects

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

filename

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getParameterSets()

Return datafile parametersets associated with this datafile.

get_absolute_filepath()

get_as_temporary_file(kws)**

Returns a traditional file-system-based file object that is a copy of the original data. The file is deleted when the context is destroyed.

Parameters `directory` (*basestring*) – the directory in which to create the temp file

Returns the temporary file object

Return type `NamedTemporaryFile`

get_default_storage_box()

try to guess appropriate box from dataset or use global default

get_download_url()

get_file(verified_only=True)

Returns the file as a readable file-like object from the best available storage box.

If `verified_only=False`, the return of files without a verified checksum is allowed, otherwise `None` is returned for unverified files.

Parameters `verified_only` (*bool*) – if `False` return files without verified checksums

Returns Python file object

Return type Python File object

`get_image_data()`

`get_mimetype()`

`get_preferred_dfo` (*verified_only=True*)

`get_receiving_storage_box()`

`get_size()`

`get_view_url()`

`has_image()`

`id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`is_image()`

returns `True` if it's an image and not an x-icon and not an img the image/img mimetype is made up though and may need revisiting if there is an official img mimetype that does not refer to diffraction images

`is_local()`

`is_online`

return `False` if a file is on tape. At this stage it checks it returns `true` for no file objects, because those files are offline through other checks

`is_public()`

`md5sum`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`mimetype`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`modification_time`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`objects = <django.db.models.manager.Manager object>`

`save(*args, **kwargs)`

`sha512sum`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`size`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`status`

returns information about the status of the file. States are defined in `StorageBox`

classmethod `sum_sizes (datafiles)`

Takes a query set of datafiles and returns their total size.

update_mimetype (*mimetype=None, force=False, save=True*)

verified

Return True if at least one DataFileObject is verified

verify (*reverify=False*)

version

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class `tardis.tardis_portal.models.datafile.DataFileObject (*args, **kwargs)`

Bases: `django.db.models.base.Model`

The physical copy (or copies) of a *DataFile* are described by distinct *DataFileObject* records.

Attribute datafile The *DataFile* record which this DataFileObject is storing a copy of.

Attribute storage_box The *StorageBox* containing this copy of the file. The *StorageBox* could represent a directory on a mounted filesystem, or a bucket in an Object Store.

Attribute uri The relative path of the file location within the the *StorageBox*, e.g. `dataset1-12345/file1.txt` for a copy of a *DataFile* with filename `file1.txt` which belongs to a *Dataset* with a description of `dataset1` and an ID of `12345`.

exception `DoesNotExist`

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception `MultipleObjectsReturned`

Bases: `django.core.exceptions.MultipleObjectsReturned`

apply_filters ()

cache_file ()

calculate_checksums (*compute_md5=True, compute_sha512=False*)

Calculates checksums for a DataFileObject instance

Parameters

- **compute_md5** (*bool*) – whether to compute md5 default=True
- **compute_sha512** (*bool*) – whether to compute sha512, default=True

Returns the checksums as `{‘md5sum’: result, ‘sha512sum’: result}`

Return type `dict`

copy_file (*dest_box=None, verify=True*)

copies verified file to new storage box checks for existing copy triggers async verification if not disabled
:param *StorageBox* dest_box: *StorageBox* instance :param *bool* verify: :returns: *DataFileObject* of copy
:rtype: *DataFileObject*

create_set_uri (*force=False, save=False*)

sets the uri as well as building it :param *bool* force: :param *bool* save: :return: :rtype: *basestring*

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

datafile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

delete_data()**file_object**

A set of accessor functions that convert the file information to a standard Python file object for reading and copy the contents of an existing file_object into the storage backend.

Returns a file object

Return type Python File object

get_full_path()**get_next_by_created_time(**kwargs)****get_previous_by_created_time(**kwargs)****id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

last_verified_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

modified_time**move_file(dest_box=None)**

moves a file copies first, then synchronously verifies deletes file if copy is true copy and has been verified

Parameters **dest_box** (StorageBox) – StorageBox instance

Returns moved file dfo

Return type *DataFileObject*

objects = <django.db.models.manager.Manager object>

priority

Default priority for tasks which take this DFO as an argument

save(*args, **kwargs)**storage_box**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

storage_type

Returns `storage_box` type

Return type `StorageBox` type constant

uri

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verified

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

verify (*add_checksums=True, add_size=True*)

```
tardis.tardis_portal.models.datafile.compute_checksums (file_object,           com-
                                                         pute_md5=True,       com-
                                                         pute_sha512=False,
                                                         close_file=True)
```

Computes checksums for a python file object

Parameters

- **file_object** (*object*) – Python File object
- **compute_md5** (*bool*) – whether to compute md5 default=True
- **compute_sha512** (*bool*) – whether to compute sha512, default=True
- **close_file** (*bool*) – whether to close the file_object, default=True

Returns the checksums as { 'md5sum': result, 'sha512sum': result }

Return type `dict`

```
tardis.tardis_portal.models.datafile.delete_dfo (sender, instance, **kwargs)
```

Deletes the actual file / object, before deleting the database record

tardis.tardis_portal.models.dataset module

```
class tardis.tardis_portal.models.dataset.Dataset (*args, **kwargs)
```

Bases: `django.db.models.base.Model`

A dataset represents a collection files usually associated with a folder on an instrument PC. Each file within the dataset is represented by a `tardis.tardis_portal.models.DataFile` record. A dataset can appear in one or more *Experiment* records. Access controls are configured at the *Experiment* level by creating *ObjectACL* records. Each dataset can be associated with an *Instrument* record, but it is possible to create a dataset without specifying an instrument.

Attribute experiment A foreign key to the one ore more *Experiment* records which contain this dataset

Attribute instrument The foreign key to the instrument that generated this data

Attribute description Description of this dataset, which usually corresponds to the folder name on the instrument PC

Attribute immutable Whether this dataset is read-only

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafile_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

directory

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experiments

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

getParameterSets()

Return the dataset parametersets associated with this experiment.

get_absolute_url (***kwargs*)
Return the absolute url to the current Dataset

get_all_storage_boxes_used ()

get_datafiles ()

get_download_urls ()

get_edit_url (***kwargs*)
Return the absolute url to the edit view of the current Dataset

get_first_experiment ()

get_images ()

get_path ()

get_size ()

get_thumbnail_url ()

id
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

image

immutable
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrument
Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.
In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a ForwardManyToOneDescriptor instance.

instrument_id
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_online

modified_time
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <tardis.tardis_portal.managers.OracleSafeManager object>

save (*force_insert=False, force_update=False, using=None, update_fields=None*)

tardis.tardis_portal.models.experiment module

```
class tardis.tardis_portal.models.experiment.Experiment (*args, **kwargs)
    Bases: django.db.models.base.Model
```

An `Experiment` is a collection of `Dataset` records. A `Dataset` record can appear in multiple `Experiment` records. Access controls are configured at the `Experiment` level by creating `ObjectACL` records.

Attribute url An optional URL associated with the data collection

Attribute approved An optional field indicating whether the collection is approved

Attribute title The title of the experiment.

Attribute description The description of the experiment.

Attribute institution_name The name of the institution who created the experiment.

Attribute start_time Undocumented

Attribute end_time Undocumented

Attribute created_time Undocumented

Attribute handle Undocumented

Attribute public Whether the experiment is publicly accessible

Attribute objects Default model manager

Attribute safe ACL aware model manager

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

`PUBLICATION_DETAILS_SCHEMA = 'http://www.tardis.edu.au/schemas/publication/details/'`

`PUBLICATION_DRAFT_SCHEMA = 'http://www.tardis.edu.au/schemas/publication/draft/'`

`PUBLICATION_SCHEMA_ROOT = 'http://www.tardis.edu.au/schemas/publication/'`

`PUBLIC_ACCESS_CHOICES = ((1, 'No public access (hidden)'), (25, 'Ready to be released'))`

`PUBLIC_ACCESS_EMBARGO = 25`

`PUBLIC_ACCESS_FULL = 100`

`PUBLIC_ACCESS_METADATA = 50`

`PUBLIC_ACCESS_NONE = 1`

approved

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

created_by

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

created_by_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datasets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

end_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentauthor_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experimentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

getParameterSets()

Return the experiment parametersets associated with this experiment.

get_absolute_url(kwargs)**

Return the absolute url to the current Experiment

get_create_token_url(kwargs)**

Return the absolute url to the create token view of the current Experiment

get_ct()

get_datafiles()

get_download_urls()

get_edit_url(kwargs)**

Return the absolute url to the edit view of the current Experiment

get_groups()

get_images()

get_next_by_created_time(morekwargs)**

get_next_by_update_time(morekwargs)**

get_or_create_directory()

get_owners()

get_previous_by_created_time(morekwargs)**

get_previous_by_update_time(morekwargs)**

get_public_access_display(morekwargs)**

get_size()

handle

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

institution_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_publication()

is_publication_draft()

license

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

license_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

locked

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objectac1s

Accessor to the related objects manager on the one-to-many relation created by GenericRelation.

In the example:

```
class Post(Model):
    comments = GenericRelation(Comment)
```

`post.comments` is a `ReverseGenericManyToOneDescriptor` instance.

objects = <tardis.tardis_portal.managers.OracleSafeManager object>

public_access

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

classmethod public_access_implies_distribution (*public_access_level*)

Determines if a level of public access implies that distribution should be allowed, or alternately if it should not be allowed. Used to prevent free-distribution licences for essentially private data, and overly-restrictive licences for public data.

public_download_allowed ()

instance method version of 'public_access_implies_distribution'

safe = <tardis.tardis_portal.managers.ExperimentManager object>

save (*args, **kwargs)

start_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

title

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

token_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

update_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.experiment.ExperimentAuthor(id, experiment,
                                                                author, institution, email, order,
                                                                url)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

author

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

email

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

institution

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

order

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

save (**args*, ***kwargs*)

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.facility module

class `tardis.tardis_portal.models.facility.Facility` (**args*, ***kwargs*)

Bases: `django.db.models.base.Model`

Represents a facility that produces data.

Each *Instrument* record must belong to exactly one facility. Many *Instrument* records can be associated with the same facility.

Attribute name The name of the facility, e.g. “Test Facility”

Attribute `manager_group` The group of users who can access the Facility Overview for this facility.

exception `DoesNotExist`

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception `MultipleObjectsReturned`

Bases: `django.core.exceptions.MultipleObjectsReturned`

`created_time`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`instrument_set`

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

`manager_group`

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

`manager_group_id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`modified_time`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`name`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`objects` = `<django.db.models.manager.Manager object>`

`save` (**args*, ***kwargs*)

`tardis.tardis_portal.models.facility.facilities_managed_by(user)`

Returns a list of facilities managed by a user

`tardis.tardis_portal.models.facility.is_facility_manager(user)`

Returns true if the user manages one or more facilities

tardis.tardis_portal.models.hooks module

```
tardis.tardis_portal.models.hooks.post_save_experiment(sender, **kwargs)
tardis.tardis_portal.models.hooks.post_save_experiment_parameter(sender,
                                                                    **kwargs)
tardis.tardis_portal.models.hooks.post_save_experimentauthor(sender, **kwargs)
tardis.tardis_portal.models.hooks.publish_public_expt_rifcs(experiment)
```

tardis.tardis_portal.models.instrument module

class tardis.tardis_portal.models.instrument.Instrument(*args, **kwargs)

Bases: django.db.models.base.Model

Represents an instrument belonging to a facility that produces data

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

dataset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

facility

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

facility_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getParameterSets()

Return the instrument parametersets associated with this instrument.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

modified_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

save (*args, **kwargs)

tardis.tardis_portal.models.jti module

class tardis.tardis_portal.models.jti.**JTI** (*id, jti, created_time*)

Bases: django.db.models.base.Model

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

created_time

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_next_by_created_time (**morekwargs)

get_previous_by_created_time (**morekwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

jti

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

tardis.tardis_portal.models.license module

class tardis.tardis_portal.models.license.**License** (*args, **kwargs)

Bases: django.db.models.base.Model

Represents a licence for experiment content.

Instances should provide enough detail for both researchers to select the licence, and for the users of their data to divine correct usage of experiment content.

(Non-US developers: We're using US spelling in the code.)

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

allows_distribution

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experiment_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

classmethod get_none_option_license()

classmethod get_suitable_licenses (public_access_method=None)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

image_url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

internal_description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_active

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

url

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.parameters module

```
class tardis.tardis_portal.models.parameters.DatafileParameter(id, name,
                                                             string_value,
                                                             numerical_value,
                                                             datetime_value,
                                                             link_id, link_ct,
                                                             parameterset)
```

Bases: `tardis.tardis_portal.models.parameters.Parameter`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to ForwardManyToOneDescriptor) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a ForwardManyToOneDescriptor instance.

parameter_type = 'Datafile'**parameterset**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.DatafileParameterSet(id, schema,
                                                                    datafile)
```

Bases: `tardis.tardis_portal.models.parameters.ParameterSet`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

datafile

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

datafile_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of `DatafileParameter`

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.DatasetParameter(id, name,
                                                              string_value,
                                                              numerical_value,
                                                              datetime_value,
                                                              link_id, link_ct,
                                                              parameterset)
```

Bases: `tardis.tardis_portal.models.parameters.Parameter`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameter_type = 'Dataset'

parameterset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class `tardis.tardis_portal.models.parameters.DatasetParameterSet` (*id*, *schema*,
dataset)

Bases: `tardis.tardis_portal.models.parameters.ParameterSet`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

dataset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

dataset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datasetparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of *DatasetParameter*

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.ExperimentParameter(id, name,
                                                                    string_value,
                                                                    numerical_value,
                                                                    date_time_value,
                                                                    link_id,
                                                                    link_ct, parameterset)
```

Bases: *tardis.tardis_portal.models.parameters.Parameter*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the `content_type` and `object_id` fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameter_type = 'Experiment'**parameterset**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

save (*args, **kwargs)

```
class tardis.tardis_portal.models.parameters.ExperimentParameterSet(id,
                                                                    schema,
                                                                    experi-
                                                                    ment)
```

Bases: `tardis.tardis_portal.models.parameters.ParameterSet`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of `ExperimentParameter`

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.FreeTextSearchField(id, parameter_name)
```

Bases: `django.db.models.base.Model`

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

parameter_name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameter_name_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.InstrumentParameter(id, name,
                                                                string_value,
                                                                numeri-
                                                                cal_value,
                                                                date-
                                                                time_value,
                                                                link_id,
                                                                link_ct, pa-
                                                                rameterset)
```

Bases: *tardis.tardis_portal.models.parameters.Parameter*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_ct

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

link_gfk

Provide a generic many-to-one relation through the content_type and object_id fields.

This class also doubles as an accessor to the related object (similar to ForwardManyToOneDescriptor) by adding itself as a model attribute.

name

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameter_type = 'Instrument'

parameterset

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

parameterset_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.InstrumentParameterSet(id,
                                                                    schema,
                                                                    instru-
                                                                    ment)
```

Bases: *tardis.tardis_portal.models.parameters.ParameterSet*

exception DoesNotExist

Bases: *django.core.exceptions.ObjectDoesNotExist*

exception MultipleObjectsReturned

Bases: *django.core.exceptions.MultipleObjectsReturned*

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrument

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

instrument_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToOneDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

objects = <django.db.models.manager.Manager object>

parameter_class

alias of *InstrumentParameter*

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

pizza.toppings and topping.pizzas are ManyToManyDescriptor instances.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

```
class tardis.tardis_portal.models.parameters.Parameter(*args, **kwargs)
```

Bases: django.db.models.base.Model

class Meta

abstract = False

app_label = 'tardis_portal'

ordering = ['name']

datetime_value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get()**link_ct**

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

link_ct_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

link_gfk

Provide a generic many-to-one relation through the content_type and object_id fields.

This class also doubles as an accessor to the related object (similar to `ForwardManyToOneDescriptor`) by adding itself as a model attribute.

`link_id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`link_url`

`name`

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

`name_id`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`numerical_value`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

`objects`

`parameter_type = 'Abstract'`

`set_value(value)`

Sets the parameter value, converting into the appropriate data type. Deals with date/time strings that are timezone naive or aware, based on the `USE_TZ` setting.

Parameters `value` (*basestring*) – a string (or string-like) repr of the value

Raises `SuspiciousOperation` –

`string_value`

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

```
class tardis.tardis_portal.models.parameters.ParameterName(id, schema, name,
                                                            full_name, units,
                                                            data_type, immutable,
                                                            comparison_type,
                                                            is_searchable,
                                                            choices, order)
```

Bases: `django.db.models.base.Model`

`CONTAINS_COMPARISON = 8`

`DATETIME = 6`

exception `DoesNotExist`

Bases: `django.core.exceptions.ObjectDoesNotExist`

`EXACT_VALUE_COMPARISON = 1`

`FILENAME = 5`

`GREATER_THAN_COMPARISON = 4`

GREATER_THAN_EQUAL_COMPARISON = 5

JSON = 8

LESS_THAN_COMPARISON = 6

LESS_THAN_EQUAL_COMPARISON = 7

LINK = 4

LONGSTRING = 7

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

NOT_EQUAL_COMPARISON = 2

NUMERIC = 1

RANGE_COMPARISON = 3

STRING = 2

URL = 3

choices

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

comparison_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

data_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

datafileparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experimentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

freetextsearchfield_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

full_name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

getUniqueShortName()**get_comparison_type_display(**morekwargs)****get_data_type_display(**morekwargs)****id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

immutable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameter_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

isDateTime()**isFilename()****isLink()****isLongString()**

isNumeric()

isString()

isURL()

is_json()

is_searchable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

natural_key()

objects = <tardis.tardis_portal.managers.ParameterNameManager object>

order

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

schema_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

units

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class tardis.tardis_portal.models.parameters.**ParameterSet** (*args, **kwargs)

Bases: django.db.models.base.Model, *tardis.tardis_portal.models.parameters.ParameterSetManagerMixin*

class Meta

abstract = False

app_label = 'tardis_portal'

ordering = ['id']

parameter_class = None

save (*args, **kwargs)

schema

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

schema_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

storage_box

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class tardis.tardis_portal.models.parameters.ParameterSetManagerMixin(parameterset=None,
                                                                    par-
                                                                    en-
                                                                    tOb-
                                                                    ject=None,
                                                                    schema=None)
```

Bases: `tardis.tardis_portal.ParameterSetManager.ParameterSetManager`

for clarity's sake and for future extension this class makes `ParameterSetManager` local to this file. At the moment its only function is increasing the line count

```
class tardis.tardis_portal.models.parameters.Schema(id, namespace, name, type, sub-
                                                    type, immutable, hidden)
```

Bases: `django.db.models.base.Model`

DATAFILE = 3

DATASET = 2

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

EXPERIMENT = 1

INSTRUMENT = 5

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

NONE = 4

exception UnsupportedType (*msg*)

Bases: `exceptions.Exception`

datafileparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

experimentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

get_type_display (***morekwargs*)**hidden**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

immutable

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparameterset_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

name

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

namespace

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

natural_key()

objects = <tardis.tardis_portal.managers.SchemaManager object>

parametername_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

parent.children is a ReverseManyToManyDescriptor instance.

Most of the implementation is delegated to a dynamically defined manager class built by create_forward_many_to_many_manager() defined below.

subtype

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.storage module

class tardis.tardis_portal.models.storage.StorageBox(*args, **kwargs)

Bases: django.db.models.base.Model

table that holds storage boxes of any type. to extend to new types, add fields if necessary

Attribute max_size max size in bytes

BUNDLE = 6

CACHE = 3

DISK = 1

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

TAPE = 2

TEMPORARY = 4

TYPES = {'bundle': 6, 'cache': 3, 'disk': 1, 'receiving': 4, 'tape': 2}

TYPE_UNKNOWN = 5

attributes

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

autocache

Whether to automatically copy data into faster storage

Returns True if data should be automatically cached

Return type `bool`

cache_box

Get cache box if set up

child_boxes

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

copy_files (*dest_box=None*)**copy_to_master** ()**classmethod create_local_box** (*location=None*)**datafileparametersets**

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

datasetparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

description

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

django_storage_class

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

experimentparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

file_objects

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

classmethod get_default_storage (*location=None, user=None*)

gets default storage box or get local storage box with given base location or create one if it doesn't exist.

policies: Have a `StorageBoxAttribute`: `key='default', value=True` find a storage box where location is `DEFAULT_STORAGE_BASE_DIR` create a default storage box at `DEFAULT_STORAGE_BASE_DIR` lowest id storage box is default no storage box defined, use hard coded default for now TODO: consider removing this

Would be nice: get largest free space one, test for authorisation

get_initialised_storage_instance()**get_options_as_dict()****id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

instrumentparametersets

Accessor to the related objects manager on the forward and reverse sides of a many-to-many relation.

In the example:

```
class Pizza(Model):
    toppings = ManyToManyField(Topping, related_name='pizzas')
```

`pizza.toppings` and `topping.pizzas` are `ManyToManyDescriptor` instances.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

master_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

master_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

max_size

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

move_files (*dest_box=None*)**move_to_master** ()**name**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>**offline_types** = [2]**online_types** = [3, 1, 4, 6]**options**

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

priority

Default priority for tasks which take this box as an argument

status

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

storage_type**type_order** = [3, 6, 1, 2, 4, 5]

```
class tardis.tardis_portal.models.storage.StorageBoxAttribute(*args, **kwargs)
```

Bases: `django.db.models.base.Model`

Can hold attributes/metadata about different storage locations.

Attribute key The key used to look up the attribute (e.g. “type”).

Attribute value The value of the attribute e.g. “cache”.

The “type” key has three values support by the core MyTardis code: “permanent”, “receiving” and “cache”.

Adding an attribute with key “type” and value “permanent” preserves the default behaviour of a storage box, i.e. it is equivalent to not adding the attribute.

Adding an attribute with key “type” and value “receiving” means that the storage box will be treated as a staging area which receives files intended to be transfered to a permanent storage box. If a storage box has the “type: receiving” attribute, it must link to a permanent storage box (via its master_box foreign key).

Adding an attribute with key “type” and value “cache” means that the storage box will be used to copy data from slow-access storage to fast-access storage. If a storage box has the “type: cache” attribute, it must link to a permanent storage box (via its master_box foreign key).

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

storage_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

class `tardis.tardis_portal.models.storage.StorageBoxOption(*args, **kwargs)`

Bases: `django.db.models.base.Model`

holds the options passed to the storage class defined in StorageBox. key->value store with support for typed values through pickling when value_type is set to ‘pickle’

exception DoesNotExist

Bases: `django.core.exceptions.ObjectDoesNotExist`

exception MultipleObjectsReturned

Bases: `django.core.exceptions.MultipleObjectsReturned`

PICKLE = 'pickle'

STRING = 'string'

TYPE_CHOICES = (('string', 'String value'), ('pickle', 'Pickled value'))

get_value_type_display (**morekwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

storage_box

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

child.parent is a ForwardManyToOneDescriptor instance.

storage_box_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

unpickled_value

value

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

value_type

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

tardis.tardis_portal.models.token module

class tardis.tardis_portal.models.token.**Token** (*id, token, experiment, expiry_date, user*)

Bases: django.db.models.base.Model

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

experiment

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

experiment_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

expiry_date

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

get_next_by_expiry_date (**morekwargs)

get_previous_by_expiry_date (**morekwargs)

get_session_expiry ()

A token login should expire at the earlier of a) tomorrow at 4am b) the (end of) the token's expiry date

It is the responsibility of `token_auth` to set the session expiry

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

is_expired ()

objects = <tardis.tardis_portal.managers.OracleSafeManager object>

save_with_random_token ()

token

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`child.parent` is a `ForwardManyToOneDescriptor` instance.

user_id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

Module contents

`models/__init__.py`

`tardis.tardis_portal.publish` package

Subpackages

tardis.tardis_portal.publish.provider package

Submodules

tardis.tardis_portal.publish.provider.rifcsprovider module

```
class tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider
    Bases: object

    can_publish (experiment)
    get_rifcs_context (experiment)
    get_template (experiment)
    is_schema_valid (experiment)
```

Module contents

Submodules

tardis.tardis_portal.publish.publishservice module

```
class tardis.tardis_portal.publish.publishservice.PublishService (providers, ex-
                                                                periment)

    get_context ()
    get_template ()
    manage_rifcs (oaipath)
```

Module contents

tardis.tardis_portal.storage package

Submodules

tardis.tardis_portal.storage.file_system module

```
class tardis.tardis_portal.storage.file_system.MyTardisLocalFileSystemStorage (location=None,
                                                                base_url=None)
    Bases: django.core.files.storage.FileSystemStorage

    Simply changes the FileSystemStorage default store location to the MyTardis file store location. Makes it easier
    to migrate 2.5 installations.
```

Module contents

```
class tardis.tardis_portal.storage.DummyStorage
    Bases: django.core.files.storage.Storage

    Does nothing except serve as a place holder for Storage classes not implemented yet
```

tardis.tardis_portal.templatetags package

Submodules

tardis.tardis_portal.templatetags.approved_user_tags module

tardis.tardis_portal.templatetags.approved_user_tags.**check_if_user_not_approved**(*request*)
Custom template filter to identify whether a user account is approved.

tardis.tardis_portal.templatetags.approved_user_tags.**get_matching_authmethod**(*backend*)

tardis.tardis_portal.templatetags.basiccomparisonfilters module

tardis.tardis_portal.templatetags.basiccomparisonfilters.**gt**(*value, arg*)
Returns a boolean of whether the value is greater than the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**gte**(*value, arg*)
Returns a boolean of whether the value is greater than or equal to the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**length_gt**(*value, arg*)
Returns a boolean of whether the value's length is greater than the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**length_gte**(*value, arg*)
Returns a boolean of whether the value's length is greater than or equal to the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**length_lt**(*value, arg*)
Returns a boolean of whether the value's length is less than the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**length_lte**(*value, arg*)
Returns a boolean of whether the value's length is less than or equal to the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**lt**(*value, arg*)
Returns a boolean of whether the value is less than the argument.

tardis.tardis_portal.templatetags.basiccomparisonfilters.**lte**(*value, arg*)
Returns a boolean of whether the value is less than or equal to the argument.

tardis.tardis_portal.templatetags.bleach_tag module

tardis.tardis_portal.templatetags.bleach_tag.**bleach_value**(*value*)

tardis.tardis_portal.templatetags.capture module

class tardis.tardis_portal.templatetags.capture.**CaptureNode**(*odelist, varname*)
Bases: django.template.base.Node

render(*context*)

tardis.tardis_portal.templatetags.capture.**capture**(*parser, token*)
{% capture as [foo] %}

tardis.tardis_portal.templatetags.dataset_tags module

tardis.tardis_portal.templatetags.dataset_tags.**dataset_datafiles_badge** (*dataset=None, count=None*)

Displays an badge with the number of datafiles for this experiment

tardis.tardis_portal.templatetags.dataset_tags.**dataset_experiments_badge** (*dataset*)

Displays an badge with the number of datasets for this experiment

tardis.tardis_portal.templatetags.dataset_tags.**dataset_size_badge** (*dataset=None, size=None*)

Displays an badge with the total size of the files in this experiment

tardis.tardis_portal.templatetags.dataset_tags.**dataset_tiles** (*experiment, include_thumbnails*)

tardis.tardis_portal.templatetags.dynurl module

class tardis.tardis_portal.templatetags.dynurl.**DynUrlNode** (**args*)

Bases: django.template.base.Node

render (*context*)

tardis.tardis_portal.templatetags.dynurl.**dynurl** (*parser, token*)

tardis.tardis_portal.templatetags.experiment_tags module

tardis.tardis_portal.templatetags.experiment_tags.**experiment_authors** (*experiment, **kwargs*)

Displays an experiment's authors in an experiment list view

tardis.tardis_portal.templatetags.experiment_tags.**experiment_badges** (*experiment, **kwargs*)

Displays badges for an experiment for displaying in an experiment list view

tardis.tardis_portal.templatetags.experiment_tags.**experiment_browse_item** (*experiment, **kwargs*)

Displays an experiment for a browsing view.

tardis.tardis_portal.templatetags.experiment_tags.**experiment_datafiles_badge** (*experiment*)

Displays an badge with the number of datafiles for this experiment

tardis.tardis_portal.templatetags.experiment_tags.**experiment_datasets_badge** (*experiment*)

Displays an badge with the number of datasets for this experiment

tardis.tardis_portal.templatetags.experiment_tags.**experiment_download_link** (*experiment, **kwargs*)

Displays a download link for an experiment in a list view

tardis.tardis_portal.templatetags.experiment_tags.**experiment_last_updated_badge** (*experiment*)

tardis.tardis_portal.templatetags.experiment_tags.**experiment_public_access_badge** (*experiment*)

Displays an badge the level of public access for this experiment

tardis.tardis_portal.templatetags.experiment_tags.**experiment_size_badge** (*experiment*)

Displays an badge with the total size of the files in this experiment

tardis.tardis_portal.template_tags.experimentstats module

`tardis.tardis_portal.template_tags.experimentstats.experiment_file_count` (*value*)

tardis.tardis_portal.template_tags.facility_tags module

`tardis.tardis_portal.template_tags.facility_tags.check_if_facility_manager` (*request*)
Custom template filter to identify whether a user is a facility manager.

tardis.tardis_portal.template_tags.feed module

`tardis.tardis_portal.template_tags.feed.todatetime` (*value*)

tardis.tardis_portal.template_tags.formfieldfilters module

This module holds filters that can be used in postprocessing a form field.

@author: Gerson Galang

`tardis.tardis_portal.template_tags.formfieldfilters.parametername_form` (*value*)
Removes all values of arg from the given string

`tardis.tardis_portal.template_tags.formfieldfilters.sanitize_html` (*html*,
bad_tags=['body'])
Removes identified malicious HTML content from the given string.

`tardis.tardis_portal.template_tags.formfieldfilters.size` (*value*, *actualSize*)
Add the size attribute to the text field.

tardis.tardis_portal.template_tags.lookupfilters module

`tardis.tardis_portal.template_tags.lookupfilters.get_item` (*dictionary*, *key*)
Returns a value from a dictionary.

tardis.tardis_portal.template_tags.pagination module

`tardis.tardis_portal.template_tags.pagination.pagination` (*data_list*, *paginator*,
page_num, *query_string*)
Generates the series of links to the pages in a paginated list.

`tardis.tardis_portal.template_tags.pagination.paginator_number` (*data_list*, *paginator*,
page_num,
query_string,
page_index)
Generates an individual page index link in a paginated list.

tardis.tardis_portal.template_tags.xmldate module

`tardis.tardis_portal.template_tags.xmldate.toxmldatetime` (*value*)

Module contents

tardis.tardis_portal.tests package

Subpackages

tardis.tardis_portal.tests.api package

Submodules

tardis.tardis_portal.tests.api.test_auth module

Testing authentication and authorization in the Tastypie-based MyTardis REST API

```
class tardis.tardis_portal.tests.api.test_auth.ACLAuthorizationTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

class tardis.tardis_portal.tests.api.test_auth.MyTardisAuthenticationTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_apikey_authentication()
    test_bad_credentials()
```

tardis.tardis_portal.tests.api.test_datafile_metadata_resources module

Testing the DatafileParameter and DatafileParameterSet resources in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_datafile_metadata_resources.DatafileParameterRes
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_datafile_metadata_resources.DatafileParameterSet
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_datafile_resource module

Testing the DataFile resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_create_df_for_staging()

    test_download_file()
        Re-run the upload test in order to create a verified file to download - it will be verified immediately because
        CELERY_ALWAYS_EAGER is True in test_settings.py

        Then download the file, check the HTTP status code and check the file content.

    test_post_single_file()

    test_shared_fs_many_files()
        tests sending many files with known permanent location (useful for Australian Synchrotron ingestions)
```

```
test_shared_fs_single_file()
```

tardis.tardis_portal.tests.api.test_dataset_metadata_resources module

Testing the DatasetParameter and DatasetParameterSet resources in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterResource
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterSetResource
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_create_dataset_pset()
        Test creating a dataset parameter set

    test_create_dataset_pset_no_auth()
        Test attempting to create a dataset parameter set without access

    test_post_dataset_with_params()
        Test creating a dataset with metadata
```

tardis.tardis_portal.tests.api.test_dataset_resource module

Testing the Dataset resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    test_get_dataset_files()

    test_get_dataset_filter_instrument()

    test_get_dataset_no_instrument()

    test_get_dataset_with_instrument()

    test_post_dataset()
```

tardis.tardis_portal.tests.api.test_experiment_metadata_resources module

Testing the ExperimentParameter and ExperimentParameterSet resources in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_experiment_metadata_resources.ExperimentParameterResource
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

class tardis.tardis_portal.tests.api.test_experiment_metadata_resources.ExperimentParameterSetResource
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_experiment_resource module

Testing the Experiment resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTest (method=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_get_experiment ()

    test_get_experiment_author ()

    test_post_experiment ()
```

tardis.tardis_portal.tests.api.test_facility_resource module

Testing the Facility resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_facility_resource.FacilityResourceTest (methodName=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_facility_by_id ()

    test_get_facility_by_manager_group_id ()
        This type of query can be used to iterate through a user's groups, and use each group's id to de-
        termine which facilities a user manages, i.e. a way to obtain the functionality implemented by
        facilities_managed_by() via the API

    test_get_facility_by_name ()
```

tardis.tardis_portal.tests.api.test_group_resource module

Testing the Group resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_group_resource.GroupResourceTest (methodName='runTest
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_group_by_id ()

    test_get_group_by_name ()
```

tardis.tardis_portal.tests.api.test_instrument_resource module

Testing the Instrument resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTest (method=
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_instrument_by_id ()

    test_get_instrument_by_name ()

    test_post_instrument ()

    test_rename_instrument ()

    test_unauthorized_instrument_access_attempt ()
```

tardis.tardis_portal.tests.api.test_replica_resource module

Testing the Replica resource in MyTardis's Tastypie-based REST API

“Replica” was the old name for what is now known as a DataFileObject in MyTardis. The API v1 endpoint is still /api/v1/replica/

```
class tardis.tardis_portal.tests.api.test_replica_resource.ReplicaResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase
```

tardis.tardis_portal.tests.api.test_schema_resource module

Testing the Schema resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_schema_resource.SchemaResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_get_schema_by_id()

    test_get_schema_by_namespace()
```

tardis.tardis_portal.tests.api.test_serializer module

Testing the serializer in the Tastypie-based MyTardis REST API

```
class tardis.tardis_portal.tests.api.test_serializer.SerializerTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_debug_serializer()

    test_pretty_serializer()
```

tardis.tardis_portal.tests.api.test_storagebox_resources module

Testing the StorageBox resources in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxAttributeResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_storage_box_attr_list_from_box_id()

class tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxOptionResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_storage_box_option_by_id()

    test_get_storage_box_option_list_from_box_id()

class tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_storage_box_by_id()
```

tardis.tardis_portal.tests.api.test_user_resource module

Testing the User resource in MyTardis's Tastypie-based REST API

```
class tardis.tardis_portal.tests.api.test_user_resource.UserResourceTest (methodName='runTest')
    Bases: tardis.tardis_portal.tests.api.MyTardisResourceTestCase

    test_get_user_by_id()
    test_get_user_by_username()
```

Module contents

Testing the tastypie-based mytardis api

```
class tardis.tardis_portal.tests.api.MyTardisResourceTestCase (methodName='runTest')
    Bases: tastypie.test.ResourceTestCaseMixin, django.test.testcases.TestCase

    abstract class without tests to combine common settings in one place

    get_admin_credentials()
    get_apikey_credentials()
    get_credentials()
    setUp()
        Hook method for setting up the test fixture before exercising it.
```

tardis.tardis_portal.tests.auth package

Module contents

tardis.tardis_portal.tests.management package

Submodules

tardis.tardis_portal.tests.management.test_collectstatic module

```
class tardis.tardis_portal.tests.management.test_collectstatic.CollectstaticTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_collectstatic()
```

tardis.tardis_portal.tests.management.test_createuser module

```
class tardis.tardis_portal.tests.management.test_createuser.CreateUserTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase
```

testInteractive()

Just test that we can run `./manage.py createuser` without any runtime exceptions by mocking the `raw_input` username and email entry

testNoInput()

Just test that we can run `./manage.py createuser --username testuser1 --email testuser1@example.com --noinput` without any runtime exceptions

tardis.tardis_portal.tests.management.test_dumpschemas module

```
class tardis.tardis_portal.tests.management.test_dumpschemas.DumpSchemasTestCase (methodName=
```

```
    Bases: django.test.testcases.TestCase
```

setUp()

Hook method for setting up the test fixture before exercising it.

tearDown()

Hook method for deconstructing the test fixture after testing it.

testDumpSchemas()

Just test that we can run `./manage.py dumpschemas` without any runtime exceptions

tardis.tardis_portal.tests.management.test_loadschemas module

```
class tardis.tardis_portal.tests.management.test_loadschemas.LoadSchemasTestCase (methodName=
```

```
    Bases: django.test.testcases.TestCase
```

testLoadSchemas()

Test that we can run `./manage.py loadschemas tardis/tardis_portal/fixtures/jeol_metadata_schema.json`

tardis.tardis_portal.tests.management.test_rmexperiment module

```
class tardis.tardis_portal.tests.management.test_rmexperiment.RmExperimentTestCase (methodName=
```

```
    Bases: django.test.testcases.TestCase
```

testList()**testRemove()****Module contents**

This package contains tests relating to management commands, i.e. command-line tools invoked with `manage.py`

tardis.tardis_portal.tests.views package**Submodules****tardis.tardis_portal.tests.views.test_auth_views module**

`test_auth_views.py`

Tests for view methods relating to users, groups, access controls and authorization

```
class tardis.tardis_portal.tests.views.test_auth_views.ManageAccountTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_manage_account (**kwargs)

class tardis.tardis_portal.tests.views.test_auth_views.RightsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_rights_require_valid_owner ()

class tardis.tardis_portal.tests.views.test_auth_views.UserGroupListsTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_get_group_list ()

    test_get_user_list ()

class tardis.tardis_portal.tests.views.test_auth_views.UserListTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    User lists are used for autocompleting the user-to-share-with field when granting access to an experiment

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_get_user_list ()
```

tardis.tardis_portal.tests.views.test_contextual_views module

test_contextual_views.py

Tests for view methods supplying context data to templates

```
class tardis.tardis_portal.tests.views.test_contextual_views.ContextualViewTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        setting up essential objects, copied from tests above

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_details_display ()
        test display of view for an existing schema and no display for an undefined one.
```

tardis.tardis_portal.tests.views.test_experiment_views module

test_experiment_views.py

Tests for view methods relating to experiments

```
class tardis.tardis_portal.tests.views.test_experiment_views.ExperimentTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase
```

```

setUp ()
    Hook method for setting up the test fixture before exercising it.

test_create_and_edit ( **kwargs )

test_dataset_json ()

```

tardis.tardis_portal.tests.views.test_template_contexts module

test_template_contexts.py

Tests for view methods supplying context data to templates

```

class tardis.tardis_portal.tests.views.test_template_contexts.ExperimentListsTest (methodName)
    Bases: django.test.testcases.TestCase

    setUp ()
        setting up essential objects, copied from tests above

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_mydata_view ( **kwargs )
        Test My Data view

    test_shared_view ( **kwargs )
        Test Shared view

class tardis.tardis_portal.tests.views.test_template_contexts.ViewTemplateContextsTest (methodName)
    Bases: django.test.testcases.TestCase

    setUp ()
        setting up essential objects, copied from tests above

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_dataset_view ( **kwargs )
        test some context parameters for a dataset view

    test_experiment_view ( **kwargs )
        test some template context parameters for an experiment view

```

tardis.tardis_portal.tests.views.test_upload_views module

test_upload_views.py

Tests for view methods relating to uploads

```

class tardis.tardis_portal.tests.views.test_upload_views.UploadTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_file_upload ()

    test_upload_complete ()

```

Module contents

Tests for view methods in `tardis/tardis_portal/views/`

Submodules

`tardis.tardis_portal.tests.ldap_ldif` module

`tardis.tardis_portal.tests.slapd` module

Utilities for starting up a test slapd server and talking to it with `ldapsearch/ldapadd`.

class `tardis.tardis_portal.tests.slapd.Slapd`

Controller class for a slapd instance, OpenLDAP's server.

This class creates a temporary data store for slapd, runs it on a private port, and initialises it with a top-level dc and the root user.

When a reference to an instance of this class is lost, the slapd server is shut down.

PATH_LDAPADD = `None`

PATH_LDAPSEARCH = `None`

PATH_SCHEMA_DIR = `'/home/docs/checkouts/readthedocs.org/user_builds/mytardis/checkouts/'`

PATH_SLAPD = `None`

PATH_SLAPTEST = `None`

PATH_TMPDIR = `'/tmp/tmpsOrRh3'`

TEST_UTILS_DIR = `'/home/docs/checkouts/readthedocs.org/user_builds/mytardis/checkouts/'`

classmethod `check_paths()`

Checks that the configured executable paths look valid. If they don't, then logs warning messages (not errors).

configure (*cfg*)

Appends `slapd.conf` configuration lines to *cfg*. Also re-initializes any backing storage. Feel free to subclass and override this method.

get_address ()

get_dn_suffix ()

get_root_dn ()

get_root_password ()

get_tmpdir ()

get_url ()

ldapadd (*ldif*, *extra_args*=[])

Runs `ldapadd` on this slapd instance, passing it the *ldif* content

ldapsearch (*base*=`None`, *filter*=`'(objectClass=*)'`, *attrs*=[], *scope*=`'sub'`, *extra_args*=[])

restart ()

Restarts the slapd server; ERASING previous content. Starts the server even if it isn't already running.

set_debug ()

set_dn_suffix(*dn*)

set_port(*port*)

set_root_cn(*cn*)

set_root_password(*pw*)

set_slapd_debug_level(*level*)

set_tmpdir(*path*)

start()

Starts the slapd server process running, and waits for it to come up.

started()

This method is called when the LDAP server has started up and is empty. By default, this method adds the two initial objects, the domain object and the root user object.

stop()

Stops the slapd server, and waits for it to terminate

wait()

Waits for the slapd process to terminate by itself.

`tardis.tardis_portal.tests.slapd.delete_directory_content`(*path*)

`tardis.tardis_portal.tests.slapd.find_available_tcp_port`(*host*='127.0.0.1')

`tardis.tardis_portal.tests.slapd.mkdirs`(*path*)

Creates the directory path unless it already exists

`tardis.tardis_portal.tests.slapd.quote`(*s*)

Quotes the " and characters in a string and surrounds with "..."

`tardis.tardis_portal.tests.slapd.which`(*executable*)

`tardis.tardis_portal.tests.test_authentication` module

Created on 19/01/2011

class `tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase`(*methodName*='runTest')

Bases: `django.test.testcases.TestCase`

setUp()

Hook method for setting up the test fixture before exercising it.

testManageAuthMethods(***keywargs*)

testSimpleAuthenticate()

test_djangoauth()

`tardis.tardis_portal.tests.test_authorisation` module

class `tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase`(*methodName*='runTest')

Bases: `django.test.testcases.TestCase`

setUp()

Hook method for setting up the test fixture before exercising it.

```
tearDown()  
    Hook method for deconstructing the test fixture after testing it.  
  
testCantEditLockedExperiment(**kwargs)  
  
testChangeUserPermissions(**kwargs)  
  
testOwnedExperiments()  
  
testReadAccess(**kwargs)  
  
testWriteAccess(**kwargs)  
  
urls = 'tardis.urls'
```

tardis.tardis_portal.tests.test_authservice module

```
class tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase(methodName='runTest')  
    Bases: django.test.testcases.TestCase  
  
    setUp()  
        Hook method for setting up the test fixture before exercising it.  
  
    tearDown()  
        Hook method for deconstructing the test fixture after testing it.  
  
    testAuthenticate()  
  
    testGetGroupsForEntity()  
  
    testGroupProvider()  
  
    testGroupSearch()  
  
    testInitialisation()  
  
class tardis.tardis_portal.tests.test_authservice.MockAuthProvider  
  
    authenticate(request)  
  
class tardis.tardis_portal.tests.test_authservice.MockGroupProvider  
    Bases: tardis.tardis_portal.auth.interfaces.GroupProvider  
  
    getGroupById(id)  
  
    getGroups(user)  
  
    getGroupsForEntity(id)  
  
    searchGroups(**filter)  
  
class tardis.tardis_portal.tests.test_authservice.MockRequest  
    Bases: django.http.request.HttpRequest  
  
    setPost(field, value)  
  
class tardis.tardis_portal.tests.test_authservice.MockSettings  
    Bases: object
```

tardis.tardis_portal.tests.test_copy_move module

test_copy_move.py

Test copying and moving a file to another storage box

```
class tardis.tardis_portal.tests.test_copy_move.CopyMoveTestCase(methodName='runTest')
    Bases: django.test.testcases.TestCase

    Test copying and moving files between storage boxes

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_cache()
        Test caching a file from a slow-access storage box

    test_copy()
        Test copying a file to another storage box

    test_move()
        Test moving a file to another storage box
```

tardis.tardis_portal.tests.test_download module

```
class tardis.tardis_portal.tests.test_download.DownloadTestCase(methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    testDatasetFile()

    testDownload(**kwargs)

    testView(**kwargs)
```

tardis.tardis_portal.tests.test_download.get_size_and_sha512sum(*testfile*)

tardis.tardis_portal.tests.test_download_apikey module

```
class tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTestCase(methodName='runTest')
    Bases: tastypie.test.ResourceTestCaseMixin, django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_download_apikey()
```

tardis.tardis_portal.tests.test_facility_overview module

Tests relating to facility overview

```
class tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_facility_overview_datafile_list ()

    test_facility_overview_experiments ()
        Despite the name of the test_facility_overview_experiments method, it actually returns a JSON list of
        datasets (not experiments)
```

tardis.tardis_portal.tests.test_forms module

test_models.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.test_forms.RightsFormTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_ensures_suitable_license ()

    test_needs_confirmation ()
```

tardis.tardis_portal.tests.test_iiif module

```
class tardis.tardis_portal.tests.test_iiif.ExtraTestCases (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testImageCacheControl ()

    testImageHasEtags ()

    testInfoHasEtags ()

class tardis.tardis_portal.tests.test_iiif.Level0TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanGetInfoAsJSON ()

    testCanGetInfoAsXML ()

    testCanGetOriginalImage ()
```

```

class tardis.tardis_portal.tests.test_iiif.Level1TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanGetJpegFormat ()

    testHandleRegions ()

    testHandleRotation ()

    testHandleSizing ()

class tardis.tardis_portal.tests.test_iiif.Level2TestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    testCanGetRequiredFormats ()

    testHandleSizing ()

```

tardis.tardis_portal.tests.test_ldap module

```

class tardis.tardis_portal.tests.test_ldap.LDAPErrorTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_search ()

class tardis.tardis_portal.tests.test_ldap.LDAPTest (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_authenticate ()

    test_getgroupbyid ()

    test_getgroups ()

    test_getgroupsforentity ()

    test_getuserbyid ()

    test_search ()

    test_searchgroups ()

```

tardis.tardis_portal.tests.test_models module

test_models.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.test_models.ModelTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    test_authors ()

    test_create_user_automatically_generate_api_key ()

    test_datafile (**kwargs)

    test_dataset ()

    test_deleting_dfo_without_uri ()

    test_experiment ()

    test_instrument ()

    test_parameter ()
```

tardis.tardis_portal.tests.test_parameters module

test_parameters.py

```
class tardis.tardis_portal.tests.test_parameters.ParametersTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    Tests for the different parameter types, defined in the tardis.tardis_portal.models.parameters.ParameterName
    class:

    NUMERIC, STRING, URL, LINK, FILENAME, DATETIME, LONGSTRING and JSON

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_experiment_parameter_get ()
        Test the Parameter class's get() method which should return an appropriate string representation of the
        parameter which depends on the parameter's data type:

        NUMERIC, STRING, URL, LINK, FILENAME, DATETIME, LONGSTRING or JSON

    test_image_filename_parameters ()
        When a FILENAME parameter refers to a thumbanil image file, MyTardis can generate a HTML for
        displaying that image.

        This method tests the generation of the image HTML

    test_link_urls ()
        Test URLs generated for parameters which link to MyTardis model records

    test_permissions_checks ()
        Test permissions checks, used by tardis.tardis_portal.auth.authorisation
```

tardis.tardis_portal.tests.test_parametersets module

test_parametersets.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```

class tardis.tardis_portal.tests.test_parametersets.EditParameterSetTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_add_datafile_params ()

    test_add_dataset_params ()

    test_add_experiment_params ()

    test_edit_datafile_params ()

    test_edit_dataset_params ()

    test_edit_experiment_params ()

class tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp ()
        Hook method for setting up the test fixture before exercising it.

    tearDown ()
        Hook method for deconstructing the test fixture after testing it.

    test_existing_parameterset ()

    test_link_parameter_type ()
        Test that Parameter.link_gfk (GenericForeignKey) is correctly assigned after using Parameter.set_value(some_url) for a LINK Parameter.

    test_link_parameter_type_extra ()

    test_new_parameterset ()

    test_parameterset_as_string ()

    test_tz_aware_date_handling ()
        Ensure that dates are handling in a timezone-aware way.

    test_tz_naive_date_handling ()
        Ensure that dates are handling in a timezone-aware way.

    test_unresolvable_link_parameter ()
        Test that LINK Parameters that can't be resolved to a model (including non-URL values) still work.

```

tardis.tardis_portal.tests.test_publishservice module

```

class tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider
    Bases: tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider

    get_beamline (experiment)

    get_license_uri (experiment)

    get_rifcs_context (experiment)

    get_template (experiment)
        tardis.test_settings adds this to the template dirs: tardis/tardis_portal/tests/rifcs/

```

```
is_schema_valid(experiment)
```

```
class tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testContext()

    testInitialisation()

    testInitialisationNoProvider()

    testManageRifCsCheckContent()

    testManageRifCsCreateAndRemove()
```

tardis.tardis_portal.tests.test_storage module

test_storage.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.test_storage.ModelTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_get_receiving_box()

    test_storageboxoption()
```

tardis.tardis_portal.tests.test_tar_download module

```
class tardis.tardis_portal.tests.test_tar_download.TarDownloadTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_tar_experiment_download()
```

tardis.tardis_portal.tests.test_tasks module

```
class tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase (methodName='runTest')
    Bases: django.test.testcases.TestCase

    As per: http://library.stanford.edu/iiif/image-api/compliance.html

    setUp()
        Hook method for setting up the test fixture before exercising it.

    testLocalFile()
```

```
test_wrong_size_verification()
```

tardis.tardis_portal.tests.test_tokens module

test_tokens.py

```
class tardis.tardis_portal.tests.test_tokens.FrozenTime(*args, **kwargs)

    classmethod freeze_time(time)
    classmethod now()

class tardis.tardis_portal.tests.test_tokens.TokenTestCase(methodName='runTest')
    Bases: django.test.testcases.TestCase

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    test_create_token(**kwargs)
    test_default_expiry()
    test_get_session_expiry()
    test_get_session_expiry_expired_token()
    test_get_session_expiry_near_expiry()
    test_is_expired()
    test_retrieve_access_list_tokens()
    test_save_with_random_token()
    test_save_with_random_token_failures()
    test_save_with_random_token_gives_up()
    test_token_delete(**kwargs)

    urls = 'tardis.tardis_portal.tests.urls'
```

tardis.tardis_portal.tests.tests module

tests.py <http://docs.djangoproject.com/en/dev/topics/testing/>

```
class tardis.tardis_portal.tests.tests.UserInterfaceTestCase(methodName='runTest')
    Bases: django.test.testcases.TestCase

    test_login()
    test_root(**kwargs)
    test_urls(**kwargs)
    test_urls_with_some_content(**kwargs)

tardis.tardis_portal.tests.tests.suite()
```

tardis.tardis_portal.tests.urls module

Module contents

tardis.tardis_portal.views package

Submodules

tardis.tardis_portal.views.ajax_actions module

views that perform some action and don't return anything very useful

tardis.tardis_portal.views.ajax_json module

views that return JSON data

```
tardis.tardis_portal.views.ajax_json.retrieve_licenses(request)
```

tardis.tardis_portal.views.ajax_pages module

views that return HTML that is injected into pages

```
tardis.tardis_portal.views.ajax_pages.experiment_public_access_badge(request,
                                                                    experi-
                                                                    ment_id)

tardis.tardis_portal.views.ajax_pages.retrieve_owned_exps_list(request, *args,
                                                                **kwargs)

tardis.tardis_portal.views.ajax_pages.retrieve_shared_exps_list(request, *args,
                                                                **kwargs)
```

tardis.tardis_portal.views.authentication module

views that have to do with authentication

```
tardis.tardis_portal.views.authentication.create_user(request, *args, **kwargs)

tardis.tardis_portal.views.authentication.login(request, *args, **kwargs)
    handler for login page

tardis.tardis_portal.views.authentication.logout(request)

tardis.tardis_portal.views.authentication.manage_auth_methods(request, *args,
                                                                **kwargs)
    Manage the user's authentication methods using AJAX.

tardis.tardis_portal.views.authentication.manage_user_account(request, *args,
                                                                **kwargs)

tardis.tardis_portal.views.authentication.rcauth(*args, **kwargs)
```

tardis.tardis_portal.views.authorisation module

views that have to do with authorisations

```
tardis.tardis_portal.views.authorisation.create_group(*args, **kwargs)
tardis.tardis_portal.views.authorisation.manage_groups(request, *args, **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_access_list_group_readonly(request,
                                                                              *args,
                                                                              **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_access_list_user_readonly(request,
                                                                              *args,
                                                                              **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_list(request, *args,
                                                             **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_list_by_user(request,
                                                                      *args,
                                                                      **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_group_userlist_readonly(request,
                                                                            *args,
                                                                            **kwargs)
tardis.tardis_portal.views.authorisation.retrieve_user_list(request, *args,
                                                            **kwargs)
tardis.tardis_portal.views.authorisation.share(request, experiment_id)
    Choose access rights and licence.
tardis.tardis_portal.views.authorisation.token_delete(request, *args, **kwargs)
```

tardis.tardis_portal.views.facilities module

views relevant for facilities and the facility view

```
tardis.tardis_portal.views.facilities.dataset_aggregate_info(dataset)
tardis.tardis_portal.views.facilities.datetime_to_us(dt)
    The datetime objects are kept as None if they aren't set, otherwise they're converted to milliseconds so AngularJS can format them nicely.
tardis.tardis_portal.views.facilities.facility_overview_data_count(request,
                                                                    *args,
                                                                    **kwargs)
    returns the total number of datasets for pagination in json format
tardis.tardis_portal.views.facilities.facility_overview_datafile_list(dataset)
tardis.tardis_portal.views.facilities.facility_overview_dataset_detail(request,
                                                                        *args,
                                                                        **kwargs)
tardis.tardis_portal.views.facilities.facility_overview_experiments(request,
                                                                        *args,
                                                                        **kwargs)
    json facility datasets
```

```
tardis.tardis_portal.views.facilities.facility_overview_facilities_list(request,  
                                                                    *args,  
                                                                    **kwargs)
```

json list of facilities managed by the current user

tardis.tardis_portal.views.images module

views that return images or route to images

```
tardis.tardis_portal.views.images.load_datafile_image(request, parameter_id)  
tardis.tardis_portal.views.images.load_dataset_image(request, parameter_id)  
tardis.tardis_portal.views.images.load_experiment_image(request, parameter_id)  
tardis.tardis_portal.views.images.load_image(request, *args, **kwargs)
```

tardis.tardis_portal.views.machine module

views that return data useful only to other machines (but not JSON)

```
tardis.tardis_portal.views.machine.site_settings(request)
```

tardis.tardis_portal.views.pages module

views that render full pages

```
class tardis.tardis_portal.views.pages.DatasetView(**kwargs)  
    Bases: django.views.generic.base.TemplateView
```

```
    find_custom_view_override(request, dataset)
```

Determines if any custom view overrides have been defined in settings.DATASET_VIEWS and returns the view function if a match to one the schemas for the dataset is found. (DATASET_VIEWS is a list of (schema_namespace, view_function) tuples).

Parameters

- **request** –
- **dataset** –

Returns

Return type

```
get(request, *args, **kwargs)  
    View an existing dataset.
```

This default view can be overridden by defining a dictionary DATASET_VIEWS in settings.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **args** (*list*) –
- **kwargs** (*dict*) –

Returns The Django response object

Return type `django.http.HttpResponse`

get_context_data (*request, dataset, **kwargs*)

Prepares the values to be passed to the default dataset view, respecting authorization rules. Returns a dict of values (the context).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **dataset** (`tardis.tardis_portal.models.dataset.Dataset`) – the Dataset model instance
- **kwargs** (*dict*) –

Returns A dictionary of values for the view/template.

Return type `dict`

`template_name = 'tardis_portal/view_dataset.html'`

class `tardis.tardis_portal.views.pages.ExperimentView` (***kwargs*)

Bases: `django.views.generic.base.TemplateView`

find_custom_view_override (*request, experiment*)

get (*request, *args, **kwargs*)

View an existing experiment.

This default view can be overridden by defining a dictionary `EXPERIMENT_VIEWS` in settings.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP Request instance
- **args** (*list*) –
- **kwargs** (*dict*) – In kwargs: param `int experiment_id`: the ID of the experiment

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

get_context_data (*request, experiment, **kwargs*)

Prepares the values to be passed to the default experiment view, respecting authorization rules. Returns a dict of values (the context).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **experiment** (`tardis.tardis_portal.models.experiment.Experiment`) – the experiment model instance
- **kwargs** (*dict*) – kwargs

Returns A dictionary of values for the view/template.

Return type `dict`

`template_name = 'tardis_portal/view_experiment.html'`

class `tardis.tardis_portal.views.pages.IndexView` (***kwargs*)

Bases: `django.views.generic.base.TemplateView`

get (*request, *args, **kwargs*)

The index view, intended to render the front page of the MyTardis site listing recent experiments.

This default view can be overridden by defining a dictionary `INDEX_VIEWS` in settings which maps `SITE_ID`'s or domain names to an alternative view function (similar to the `DATASET_VIEWS` or `EXPERIMENT_VIEWS` overrides).

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object
- **args** (*list*) –
- **kwargs** (*dict*) –

Returns The Django response object

Return type `django.http.HttpResponse`

`get_context_data(*args, **kwargs)`

`template_name = 'tardis_portal/index.html'`

`tardis.tardis_portal.views.pages.about(request)`

`tardis.tardis_portal.views.pages.add_dataset(request, *args, **kwargs)`

`tardis.tardis_portal.views.pages.create_experiment(request, *args, **kwargs)`

Create a new experiment view.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP Request instance
- **template_name** (*string*) – the path of the template to render

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

`tardis.tardis_portal.views.pages.edit_dataset(request, *args, **kwargs)`

`tardis.tardis_portal.views.pages.facility_overview(request, *args, **kwargs)`
summary of experiments in a facility

`tardis.tardis_portal.views.pages.healthz(request)`
returns that the server is alive

`tardis.tardis_portal.views.pages.my_data(request, *args, **kwargs)`
show owned data with credential-based access

`tardis.tardis_portal.views.pages.public_data(request)`
list of public experiments

`tardis.tardis_portal.views.pages.shared(request, *args, **kwargs)`
show shared data with credential-based access

`tardis.tardis_portal.views.pages.site_routed_view(request, _default_view, _site_mappings, *args, **kwargs)`

Allows a view to be overridden based on the Site (eg domain) for the current request. Takes a default fallback view (`_default_view`) and a dictionary mapping Django Sites (domain name or int `SITE_ID`) to views. If the current request matches a Site in the dictionary, that view is used instead of the default.

The intention is to define `{site: view}` mappings in `settings.py`, and use this wrapper view in `urls.py` to allow a single URL to be routed to different views depending on the Site in the request.

Parameters

- **request** (`django.http.HttpRequest`) – a HTTP request object

- **_default_view** (*types.FunctionType* | *str*) – The default view if no Site in `_site_mappings` matches the current Site.
- **_site_mappings** (*dict*) – A dictionary mapping Django sites to views (sites are specified as either a domain name *str* or int `SITE_ID`).
- **args** –
- **kwargs** –

Returns A view function

Return type *types.FunctionType*

`tardis.tardis_portal.views.pages.stats(request, *args, **kwargs)`

`tardis.tardis_portal.views.pages.use_rapid_connect(fn)`

A decorator that adds AAF Rapid Connect settings to a `get_context_data` method.

Parameters *fn* (*types.FunctionType*) – A `get_context_data` function/method.

Returns A `get_context_data` function that adds `RAPID_CONNECT_*` keys to its output context.

Return type *types.FunctionType*

`tardis.tardis_portal.views.pages.user_guide(request)`

`tardis.tardis_portal.views.parameters` module

views to do with metadata, parameters etc. Mostly ajax page inclusions

`tardis.tardis_portal.views.parameters.add_datafile_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.add_dataset_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.add_experiment_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.add_par(request, parentObject, otype, stype)`

`tardis.tardis_portal.views.parameters.edit_datafile_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.edit_dataset_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.edit_experiment_par(request, *args, **kwargs)`

`tardis.tardis_portal.views.parameters.edit_parameters(request, parameterset, otype)`

`tardis.tardis_portal.views.upload` module

views for uploading files via HTTP

`tardis.tardis_portal.views.upload.upload_complete(request, template_name='tardis_portal/upload_complete.html')`

The ajax-loaded result of a file being uploaded

Parameters

- **request** (*django.http.HttpRequest*) – a HTTP Request instance
- **template_name** (*string*) – the path of the template to render

Returns an `HttpResponse`

Return type `django.http.HttpResponse`

tardis.tardis_portal.views.utils module

helper functions used by other views

```
class tardis.tardis_portal.views.utils.HttpResponseMethodNotAllowed (*args,  
                                                                    **kwargs)  
    Bases: django.http.response.HttpResponse  
    status_code = 303
```

```
class tardis.tardis_portal.views.utils.HttpResponseSeeAlso (redirect_to, *args,  
                                                            **kwargs)  
    Bases: django.http.response.HttpResponseRedirect  
    status_code = 303
```

```
tardis.tardis_portal.views.utils.feedback (request)
```

```
tardis.tardis_portal.views.utils.get_dataset_info (dataset, include_thumbnail=False,  
                                                    exclude=None)
```

```
tardis.tardis_portal.views.utils.remove_csrf_token (request)  
    rather than fixing the form code that loops over all POST entries indiscriminately, I am removing the csrf token  
    with this hack. This is only required in certain form code and can be removed should this ever be fixed
```

Module contents

importing all views files here, so that any old code will work as expected, when importing from `tardis.tardis_portal.views`

Submodules

tardis.tardis_portal.ParameterSetManager module

```
class tardis.tardis_portal.ParameterSetManager.ParameterSetManager (parameterset=None,  
                                                                    parentOb-  
                                                                    ject=None,  
                                                                    schema=None)  
    Bases: object  
    blank_param = None  
    delete_all_params ()  
    delete_params (parname)  
    get_param (parname, value=False)  
    get_params (parname, value=False)  
    get_schema ()  
    new_param (parname, value, fullparname=None)  
    parameters = None  
    parameterset = None
```

```

set_param (parname, value, fullparname=None, example_value=None)
set_param_list (parname, value_list, fullparname=None)
set_params_from_dict (params_dict)

```

tardis.tardis_portal.admin module

```

class tardis.tardis_portal.admin.DataFileObjectInline (parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline

```

```

    extra = 0

```

```

    form
        alias of DataFileObjectInlineForm

```

```

    media

```

```

    model
        alias of tardis.tardis_portal.models.datafile.DataFileObject

```

```

class tardis.tardis_portal.admin.DataFileObjectInlineForm (data=None, files=None,
    auto_id=u'id_%s', pre-
    fix=None, initial=None,
    error_class=<class
    'django.forms.utils.ErrorList'>,
    label_suffix=None,
    empty_permitted=False,
    instance=None,
    use_required_attribute=None)

```

```

    Bases: django.forms.models.ModelForm

```

```

class Meta

```

```

    fields = '__all__'

```

```

    model
        alias of tardis.tardis_portal.models.datafile.DataFileObject

```

```

    widgets = {'uri': <django.forms.widgets.TextInput object>}

```

```

    base_fields = {'datafile': <django.forms.models.ModelChoiceField object>, 'last_verif

```

```

    declared_fields = {}

```

```

    media

```

```

class tardis.tardis_portal.admin.DatafileAdmin (model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

```

```

    form
        alias of DatafileAdminForm

```

```

    inlines = [<class 'tardis.tardis_portal.admin.DataFileObjectInline'>]

```

```

    media

```

```

    search_fields = ['filename', 'id']

```

```
class tardis.tardis_portal.admin.DatafileAdminForm(data=None, files=None,
                                                    auto_id=u'id_%s', prefix=None,
                                                    initial=None, error_class=<class
                                                    'django.forms.utils.ErrorList'>,
                                                    label_suffix=None,
                                                    empty_permitted=False,
                                                    instance=None,
                                                    use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.datafile.DataFile

    widgets = {'directory': <django.forms.widgets.TextInput object>}

    base_fields = {'created_time': <django.forms.fields.DateTimeField object>, 'dataset':
    declared_fields = {}

    media

class tardis.tardis_portal.admin.DatasetAdmin(model, admin_site)
Bases: django.contrib.admin.options.ModelAdmin

    media

    search_fields = ['description', 'id']

class tardis.tardis_portal.admin.ExperimentAdmin(model, admin_site)
Bases: django.contrib.admin.options.ModelAdmin

    inlines = [<class 'tardis.tardis_portal.admin.ObjectACLInline'>]

    media

    search_fields = ['title', 'id']

class tardis.tardis_portal.admin.ExperimentParameterInline(parent_model, ad-
                                                            min_site)
Bases: django.contrib.admin.options.TabularInline

    extra = 0

    formfield_overrides = {<class 'django.db.models.fields.TextField'>: {'widget': <clas
    media

    model
        alias of tardis.tardis_portal.models.parameters.ExperimentParameter

class tardis.tardis_portal.admin.ExperimentParameterSetAdmin(model, ad-
                                                            min_site)
Bases: django.contrib.admin.options.ModelAdmin

    inlines = [<class 'tardis.tardis_portal.admin.ExperimentParameterInline'>]

    media

class tardis.tardis_portal.admin.FacilityAdmin(model, admin_site)
Bases: django.contrib.admin.options.ModelAdmin

    media
```

```

    search_fields = ['name']
class tardis.tardis_portal.admin.FreeTextSearchFieldAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media
class tardis.tardis_portal.admin.InstrumentAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media
    search_fields = ['name']
class tardis.tardis_portal.admin.InstrumentParameterInline(parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline
    extra = 0
    media
    model
        alias of tardis.tardis_portal.models.parameters.InstrumentParameter
class tardis.tardis_portal.admin.InstrumentParameterSetAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    inlines = [<class 'tardis.tardis_portal.admin.InstrumentParameterInline'>]
    media
class tardis.tardis_portal.admin.ObjectACLAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    list_display = ['__str__', 'pluginId', 'entityId', 'canRead', 'canWrite', 'canDelete',
    media
    search_fields = ['content_type', 'object_id']
class tardis.tardis_portal.admin.ObjectACLInline(parent_model, admin_site)
    Bases: django.contrib.contenttypes.admin.GenericTabularInline
    extra = 0
    media
    model
        alias of tardis.tardis_portal.models.access_control.ObjectACL
class tardis.tardis_portal.admin.ParameterNameAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin
    media
    search_fields = ['name', 'schema__id']
class tardis.tardis_portal.admin.ParameterNameInline(parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline
    extra = 0
    media
    model
        alias of tardis.tardis_portal.models.parameters.ParameterName

```

```
class tardis.tardis_portal.admin.SchemaAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    inlines = [<class 'tardis.tardis_portal.admin.ParameterNameInline'>]

    media

    search_fields = ['name', 'namespace']

class tardis.tardis_portal.admin.StorageBoxAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    form
        alias of StorageBoxForm

    inlines = [<class 'tardis.tardis_portal.admin.StorageBoxOptionInline'>, <class 'tardis
    media

    search_fields = ['name']

class tardis.tardis_portal.admin.StorageBoxAttributeInline(parent_model, admin_site)
    Bases: django.contrib.admin.options.TabularInline

    extra = 0

    form
        alias of StorageBoxAttributeInlineForm

    media

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

class tardis.tardis_portal.admin.StorageBoxAttributeInlineForm(data=None,
                                                                files=None,
                                                                auto_id=u'id_%s',
                                                                pre-
                                                                fix=None, ini-
                                                                tial=None, er-
                                                                ror_class=<class
                                                                'django.forms.utils.ErrorList'>,
                                                                la-
                                                                bel_suffix=None,
                                                                empty_permitted=False,
                                                                instance=None,
                                                                use_required_attribute=None)
    Bases: django.forms.models.ModelForm

    class Meta

        fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

    widgets = {'key': <django.forms.widgets.TextInput object>, 'value': <django.forms
    base_fields = {'key': <django.forms.fields.CharField object>, 'storage_box': <django
    declared_fields = {}

    media
```

```

class tardis.tardis_portal.admin.StorageBoxForm(data=None,          files=None,
auto_id=u'id_%s',          prefix=None,
initial=None,          error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
instance=None,
use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBox

    widgets = {'description': <django.forms.widgets.TextInput object>, 'django_storage_box': <django.forms.widgets.TextInput object>}

    base_fields = {'description': <django.forms.fields.CharField object>, 'django_storage_box': <django.forms.fields.CharField object>}

    declared_fields = {}

    media

class tardis.tardis_portal.admin.StorageBoxOptionInline(parent_model,          ad-
min_site)

Bases: django.contrib.admin.options.TabularInline

extra = 0

form
    alias of StorageBoxOptionInlineForm

media

model
    alias of tardis.tardis_portal.models.storage.StorageBoxOption

class tardis.tardis_portal.admin.StorageBoxOptionInlineForm(data=None,
files=None,
auto_id=u'id_%s',
prefix=None, ini-
tial=None, er-
ror_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
instance=None,
use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

    fields = '__all__'

    model
        alias of tardis.tardis_portal.models.storage.StorageBoxOption

    widgets = {'key': <django.forms.widgets.TextInput object>, 'value': <django.forms.widgets.TextInput object>}

    base_fields = {'key': <django.forms.fields.CharField object>, 'storage_box': <django.forms.fields.CharField object>}

```

```
    declared_fields = {}

    media

class tardis.tardis_portal.admin.UserAuthenticationAdmin(model, admin_site)
    Bases: django.contrib.admin.options.ModelAdmin

    media

    search_fields = ['username', 'authenticationMethod', 'userProfile__user__username']
```

tardis.tardis_portal.api module

RESTful API for MyTardis models and data. Implemented with Tastypie.

```
class tardis.tardis_portal.api.ACLAuthorization
    Bases: tastypie.authorization.Authorization

    Authorisation class for Tastypie.

    create_detail(object_list, bundle)
    create_list(object_list, bundle)
    delete_detail(object_list, bundle)
    delete_list(object_list, bundle)
    read_detail(object_list, bundle)
    read_list(object_list, bundle)
    update_detail(object_list, bundle)
        Latest TastyPie requires update_detail permissions to be able to create objects. Rather than duplicating
        code here, we'll just use the same authorization rules we use for create_detail.
    update_list(object_list, bundle)

class tardis.tardis_portal.api.DataFileResource(api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'dataset': 2, 'directory': ('exact', 'startswith'), 'filename': ('exact', 'startswith')}

        object_class
            alias of tardis.tardis_portal.models.datafile.DataFile

        ordering = ['id', 'filename', 'modification_time']

        queryset

        resource_name = 'dataset_file'

    base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'datafile': <tastypie.fields.FileField object>}

    declared_fields = {'datafile': <tastypie.fields.FileField object>, 'dataset': <tastypie.fields.IntegerField object>}

    deserialize(request, data, format=None)
        from https://github.com/toastdriven/django-tastypie/issues/42 modified to deserialize json sent via POST.
        Would fail if data is sent in a different format. uses a hack to get back pure json from request.POST

    download_file(request, **kwargs)
        curl needs the -J switch to get the filename right auth needs to be added manually here
```

```

hydrate(bundle)
obj_create(bundle, **kwargs)
    Creates a new DataFile object from the provided bundle.data dict.

    If a duplicate key error occurs, responds with HTTP Error 409: CONFLICT
post_list(request, **kwargs)
prepend_urls()
put_detail(request, **kwargs)
    from https://github.com/toastdriven/django-tastypie/issues/42
temp_url = None
verify_file(request, **kwargs)
    triggers verification of file, e.g. after non-POST upload complete

class tardis.tardis_portal.api.DatafileParameterResource(api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.DatafileParameter

        queryset

    base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, u'id': <tas
    declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.DatafileParameterSetResource(api_name=None)
    Bases: tardis.tardis_portal.api.ParameterSetResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.DatafileParameterSet

        queryset

    base_fields = {'datafile': <tastypie.fields.ForeignKey object>, u'id': <tastypie.fie
    declared_fields = {'datafile': <tastypie.fields.ForeignKey object>, 'parameters': <t

class tardis.tardis_portal.api.DatasetParameterResource(api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.DatasetParameter

        queryset

    base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, u'id': <tas
    declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.DatasetParameterSetResource(api_name=None)
    Bases: tardis.tardis_portal.api.ParameterSetResource

```

```
class Meta
    Bases: tardis.tardis_portal.api.Meta

    object_class
        alias of tardis.tardis_portal.models.parameters.DatasetParameterSet

    queryset

    base_fields = {'dataset': <tastypie.fields.ForeignKey object>, u'id': <tastypie.fiel
    declared_fields = {'dataset': <tastypie.fields.ForeignKey object>, 'parameters': <ta

class tardis.tardis_portal.api.DatasetResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        always_return_data = True

        filtering = {'description': ('exact',), 'directory': ('exact',), 'experiments':
        object_class
            alias of tardis.tardis_portal.models.dataset.Dataset

        ordering = ['id', 'description']

        queryset

    base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'description':
    declared_fields = {'experiments': <tastypie.fields.ToManyField object>, 'instrument':
    get_datafiles (request, **kwargs)

    prepend_urls ()

class tardis.tardis_portal.api.ExperimentAuthorResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    API for ExperimentAuthors

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        always_return_data = True

        filtering = {'author': ('exact', 'iexact'), 'email': ('exact', 'iexact'), 'experi
        object_class
            alias of tardis.tardis_portal.models.experiment.ExperimentAuthor

        ordering = ['id', 'author', 'email', 'order']

        queryset

    base_fields = {'author': <tastypie.fields.CharField object>, 'email': <tastypie.fiel
    declared_fields = {'experiment': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.ExperimentParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.ExperimentParameter
```

```

    queryset

    base_fields = {'datetime_value': <tastypie.fields.DateTimeField object>, u'id': <tas
    declared_fields = {'parameterset': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.ExperimentParameterSetResource (api_name=None)
    Bases: tardis.tardis_portal.api.ParameterSetResource
    API for ExperimentParameterSets

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.parameters.ExperimentParameterSet

        queryset

    base_fields = {'experiment': <tastypie.fields.ForeignKey object>, u'id': <tastypie.f
    declared_fields = {'experiment': <tastypie.fields.ForeignKey object>, 'parameters':

class tardis.tardis_portal.api.ExperimentResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource
    API for Experiments also creates a default ACL and allows ExperimentParameterSets to be read and written.
    TODO: catch duplicate schema submissions for parameter sets

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        always_return_data = True

        filtering = {'id': ('exact',), 'title': ('exact',)}

        object_class
            alias of tardis.tardis_portal.models.experiment.Experiment

        ordering = ['id', 'title', 'created_time', 'update_time']

        queryset

    base_fields = {'approved': <tastypie.fields.BooleanField object>, 'created_by': <tas
    declared_fields = {'created_by': <tastypie.fields.ForeignKey object>, 'parameter_sets

    dehydrate (bundle)

    hydrate_m2m (bundle)
        create ACL before any related objects are created in order to use ACL permissions for those objects.

    obj_create (bundle, **kwargs)
        experiments need at least one ACL to be available through the ExperimentManager (Experiment.safe)
        Currently not tested for failed db transactions as sqlite does not enforce limits.

class tardis.tardis_portal.api.FacilityResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        always_return_data = True

        filtering = {'id': ('exact',), 'manager_group': 2, 'name': ('exact',)}

```

```
    object_class
        alias of tardis.tardis_portal.models.facility.Facility

    ordering = ['id', 'name']

    queryset

base_fields = {'created_time': <tastypie.fields.DateTimeField object>, u'id': <tastypie.fields.IntegerField object>}
declared_fields = {'manager_group': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.GroupResource (api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        filtering = {'id': ('exact',), 'name': ('exact',)}
        object_class
            alias of django.contrib.auth.models.Group
        queryset

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'name': <tastypie.fields.CharField object>}
declared_fields = {}

class tardis.tardis_portal.api.InstrumentResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        always_return_data = True
        filtering = {'facility': 2, 'id': ('exact',), 'name': ('exact',)}
        object_class
            alias of tardis.tardis_portal.models.instrument.Instrument
        ordering = ['id', 'name']
        queryset

base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'facility': <tastypie.fields.ForeignKey object>}
declared_fields = {'facility': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.LocationResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta
        object_class
            alias of tardis.tardis_portal.models.storage.StorageBox
        queryset

base_fields = {'description': <tastypie.fields.CharField object>, 'django_storage_class': <tastypie.fields.CharField object>}
declared_fields = {}
```

```

class tardis.tardis_portal.api.MyTardisAuthentication
    Bases: object

    custom tastypie authentication that works with both anonymous use and a number of available auth mechanisms.

    get_identifier(request)

    is_authenticated(request, **kwargs)
        handles backends explicitly so that it can return False when credentials are given but wrong and return
        Anonymous User when credentials are not given or the session has expired (web use).

class tardis.tardis_portal.api.MyTardisModelResource (api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        object_class = None
        serializer = <tardis.tardis_portal.api.PrettyJSONSerializer object>
        base_fields = {'resource_uri': <tastypie.fields.CharField object>}
        declared_fields = {}

class tardis.tardis_portal.api.ObjectACLResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta

        authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
        authorization
            Authorisation class for Tastypie.
        filtering = {'entityId': ('exact',), 'pluginId': ('exact',)}
        object_class
            alias of tardis.tardis_portal.models.access_control.ObjectACL
        ordering = ['id']
        queryset

        base_fields = {'aclOwnershipType': <tastypie.fields.IntegerField object>, 'canDelete'
        declared_fields = {'content_object': <tastypie.contrib.contenttypes.fields.GenericFor
        hydrate(bundle)

class tardis.tardis_portal.api.ParameterNameResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'schema': 2}
        object_class
            alias of tardis.tardis_portal.models.parameters.ParameterName

```

```
    queryset

    base_fields = {'choices': <tastypie.fields.CharField object>, 'comparison_type': <ta
    declared_fields = {'schema': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.ParameterResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    base_fields = {'name': <tastypie.fields.ForeignKey object>, u'resource_uri': <tastyp
    declared_fields = {'name': <tastypie.fields.ForeignKey object>, 'value': <tastypie.f
    hydrate (bundle)
        sets the parametername by uri or name if untyped value is given, set value via parameter method, otherwise
        use modelresource automatisms

class tardis.tardis_portal.api.ParameterSetResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    base_fields = {u'resource_uri': <tastypie.fields.CharField object>, 'schema': <tastyp
    declared_fields = {'schema': <tastypie.fields.ForeignKey object>}

    hydrate_schema (bundle)

class tardis.tardis_portal.api.PrettyJSONSerializer (formats=None,          con-
                                                    tent_types=None,      date-
                                                    time_formatting=None)

    Bases: tastypie.serializers.Serializer

    json_indent = 2

    to_json (data, options=None)

class tardis.tardis_portal.api.ReplicaResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'url': ('exact', 'startswith'), 'verified': ('exact',)}

        object_class
            alias of tardis.tardis_portal.models.datafile.DataFileObject

        ordering = ['id']

        queryset

    base_fields = {'created_time': <tastypie.fields.DateTimeField object>, 'datafile': <
    declared_fields = {'datafile': <tastypie.fields.ForeignKey object>}

    dehydrate (bundle)

    hydrate (bundle)

class tardis.tardis_portal.api.SchemaResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        filtering = {'id': ('exact',), 'namespace': ('exact',)}

        object_class
            alias of tardis.tardis_portal.models.parameters.Schema
```

```

        ordering = ['id']
        queryset

base_fields = {'hidden': <tastypie.fields.BooleanField object>, u'id': <tastypie.fie
declared_fields = {}

class tardis.tardis_portal.api.StorageBoxAttributeResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBoxAttribute

        ordering = ['id']
        queryset

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'key': <tastypie.fields
declared_fields = {'storage_box': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.StorageBoxOptionResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBoxOption

        ordering = ['id']
        queryset

accessible_keys = ['location']

base_fields = {u'id': <tastypie.fields.IntegerField object>, 'key': <tastypie.fields
declared_fields = {'storage_box': <tastypie.fields.ForeignKey object>}

class tardis.tardis_portal.api.StorageBoxResource (api_name=None)
    Bases: tardis.tardis_portal.api.MyTardisModelResource

    class Meta
        Bases: tardis.tardis_portal.api.Meta

        object_class
            alias of tardis.tardis_portal.models.storage.StorageBox

        ordering = ['id']
        queryset

base_fields = {'attributes': <tastypie.fields.ToManyField object>, 'description': <t
declared_fields = {'attributes': <tastypie.fields.ToManyField object>, 'options': <t

class tardis.tardis_portal.api.UserResource (api_name=None)
    Bases: tastypie.resources.ModelResource

    class Meta

        allowed_methods = ['get']

```

```
authentication = <tardis.tardis_portal.api.MyTardisAuthentication object>
authorization
    Authorisation class for Tastypie.
fields = ['username', 'first_name', 'last_name', 'email']
filtering = {'email': ('iexact',), 'username': ('exact',)}
object_class
    alias of django.contrib.auth.models.User
queryset

serializer = <tardis.tardis_portal.api.PrettyJSONSerializer object>
base_fields = {'email': <tastypie.fields.CharField object>, 'first_name': <tastypie.
declared_fields = {'groups': <tastypie.fields.ManyToManyField object>}
dehydrate(bundle)
    use cases:
```

```
public user:
    anonymous:
        name, uri, email, id
    authenticated:
        other user:
            name, uri, email, id [, username if facility manager]
        same user:
            name, uri, email, id, username
private user:
    anonymous:
        none
    authenticated:
        other user:
            name, uri, id [, username, email if facility manager]
        same user:
            name, uri, email, id, username
```

tardis.tardis_portal.constants module

constants.py

@author: Gerson Galang

tardis.tardis_portal.context_processors module

tardis.tardis_portal.context_processors.**global_contexts**(*request*)

tardis.tardis_portal.context_processors.**google_analytics**(*request*)
adds context for portal_template.html

tardis.tardis_portal.context_processors.**registration_processor**(*request*)

tardis.tardis_portal.context_processors.**single_search_processor**(*request*)

tardis.tardis_portal.context_processors.**user_details_processor**(*request*)

tardis.tardis_portal.context_processors.**user_menu_processor**(*request*)

tardis.tardis_portal.creativecommonshandler module

Creative Commons Handler

A wrapper for creative commons interactions on a ParameterSet

```
class tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler (experiment_id=None,  
                                                                    create=True)
```

```
    experiment_id = None
```

```
    get_or_create_cc_parameterset (create=True)
```

Gets the creative commons parameterset for the experiment :param create: If true, creates a new parameterset object to hold the cc license if one doesn't exist :type create: boolean :return: The parameterset manager for the cc parameterset :rtype: tardis.tardis_portal.ParameterSetManager.ParameterSetManager

```
    has_cc_license ()
```

Returns True if there's a cc license parameterset for the experiment

Return type boolean

```
    psm = None
```

```
    save_license (request)
```

Saves a license parameterset with the POST variables from the creative commons form :param request: a HTTP Request instance :type request: `django.http.HttpRequest`

```
    schema = 'http://www.tardis.edu.au/schemas/creative_commons/2011/05/17'
```

tardis.tardis_portal.deprecations module

Deprecation warnings

```
exception tardis.tardis_portal.deprecations.RemovedInMyTardis42Warning
```

Bases: `exceptions.DeprecationWarning`

Used to raise warnings about deprecated functionality.

Usage:

```
import warnings

warnings.warn(
    "This method will be removed in MyTardis 4.2. "
    "Please use method2 instead.",
    RemovedInMyTardis42Warning
)
```

```
exception tardis.tardis_portal.deprecations.RemovedInMyTardis43Warning
```

Bases: `exceptions.PendingDeprecationWarning`

Used to raise warnings about deprecated functionality.

Usage:

```
import warnings

warnings.warn(
    "This method will be removed in MyTardis 4.3. "
    "Please use method2 instead.",
    RemovedInMyTardis43Warning
)
```

tardis.tardis_portal.download module

download.py

```
class tardis.tardis_portal.download.UncachedTarStream(mapped_file_objs, filename,
                                                    do_gzip=False, buffer-
                                                    size=131072, comp_level=6,
                                                    http_buffersize=65535)
```

Bases: `tarfile.TarFile`

Stream files into a compressed tar stream on the fly

close_gzip()

compress(buf)

compute_size()

get_response(tracker_data=None)

make_tar()

main tar generator. until python 3 needs to be in one function because ‘yield’s don’t bubble up.

prepare_output(uc_buf, remainder)

tarinfo_for_df(df, name)

tardis.tardis_portal.download.classic_mapper(rootdir)

tardis.tardis_portal.download.download_api_key(request, *args, **kwargs)

tardis.tardis_portal.download.download_datafile(request, datafile_id)

tardis.tardis_portal.download.get_download_organizations()

tardis.tardis_portal.download.make_mapper(organization, rootdir)

tardis.tardis_portal.download.streaming_download_datafiles(request)

takes string parameter “comptype” for compression method. Currently implemented: “tgz” and “tar” The datafiles to be downloaded are selected using “datafile”, “dataset” or “url” parameters. An “expid” parameter may be supplied for use in the download archive name. If “url” is used, the “expid” parameter is also used to limit the datafiles to be downloaded to a given experiment.

tardis.tardis_portal.download.view_datafile(request, datafile_id)

tardis.tardis_portal.email module

tardis.tardis_portal.email.build_template_html(template_filename, context)

tardis.tardis_portal.email.build_template_text(template_filename, context)

tardis.tardis_portal.email.email_user(subject, template_filename, context, user)

tardis.tardis_portal.errors module

Created on 02/09/2010

```

exception tardis.tardis_portal.errors.ParameterChoicesFormatError(msg)
    Bases: exceptions.Exception

exception tardis.tardis_portal.errors.SearchQueryTypeUnprovidedError(msg)
    Bases: exceptions.Exception

exception tardis.tardis_portal.errors.UnsupportedSearchQueryTypeError(msg)
    Bases: exceptions.Exception

```

tardis.tardis_portal.fields module

```

class tardis.tardis_portal.fields.MultiValueCommaSeparatedField(fields=(),
                                                                *args,
                                                                **kwargs)

    Bases: django.forms.fields.MultiValueField

    compress (data_list)

```

tardis.tardis_portal.forms module

forms module

```

class tardis.tardis_portal.forms.AddUserPermissionsForm(data=None, files=None,
                                                         auto_id=u'id_%s', pre-
                                                         fix=None, initial=None,
                                                         error_class=<class
                                                         'django.forms.utils.ErrorList'>,
                                                         label_suffix=None,
                                                         empty_permitted=False,
                                                         field_order=None,
                                                         use_required_attribute=None,
                                                         renderer=None)

    Bases: django.forms.forms.Form

    base_fields = {'authMethod': <django.forms.fields.CharField object>, 'autocomp_user':
    declared_fields = {'authMethod': <django.forms.fields.CharField object>, 'autocomp_us
    media

class tardis.tardis_portal.forms.CreateUserPermissionsForm(data=None,
                                                             files=None,
                                                             auto_id=u'id_%s',
                                                             prefix=None, ini-
                                                             tial=None, er-
                                                             ror_class=<class
                                                             'django.forms.utils.ErrorList'>,
                                                             label_suffix=None,
                                                             empty_permitted=False,
                                                             field_order=None,
                                                             use_required_attribute=None,
                                                             renderer=None)

    Bases: tardis.tardis_portal.forms.RegistrationForm

```

```
base_fields = {'authMethod': <django.forms.fields.CharField object>, 'email': <django.forms.fields.CharField object>
declared_fields = {'authMethod': <django.forms.fields.CharField object>, 'email': <django.forms.fields.CharField object>
media

class tardis.tardis_portal.forms.DatasetForm(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False, instance=None,
use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

fields = ['description', 'directory', 'instrument']

model
alias of tardis.tardis_portal.models.dataset.Dataset

base_fields = {'description': <django.forms.fields.CharField object>, 'directory': <django.forms.fields.CharField object>
declared_fields = {'description': <django.forms.fields.CharField object>}
media

class tardis.tardis_portal.forms.ExperimentAuthor(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
instance=None,
use_required_attribute=None)

Bases: django.forms.models.ModelForm

class Meta

fields = ['author', 'institution', 'email', 'order', 'url']

model
alias of tardis.tardis_portal.models.experiment.ExperimentAuthor

base_fields = {'author': <django.forms.fields.CharField object>, 'email': <django.forms.fields.CharField object>
declared_fields = {}
media

class tardis.tardis_portal.forms.ExperimentForm(data=None, files=None,
auto_id='%s', prefix=None, initial=None,
error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=':',
empty_permitted=False, instance=None, extra=0)

Bases: django.forms.models.ModelForm

This handles the complex experiment forms.
```

All internal datasets forms are prefixed with *dataset_*, and all internal dataset file fields are prefixed with *file_*. These are parsed out of the post data and added to the form as internal lists.

```
class FullExperiment (**kwargs)
```

```
    Bases: UserDict.UserDict
```

This is a dict wrapper that store the values returned from the *tardis.tardis_portal.forms.ExperimentForm.save()* function. It provides a convenience method for saving the model objects.

```
    save_m2m()
```

```
        {'experiment': experiment, 'experiment_authors': experiment_authors, 'authors': authors, 'datasets': datasets, 'datafiles': datafiles}
```

```
class Meta
```

```
    fields = ('title', 'institution_name', 'description')
```

```
    model
```

```
        alias of tardis.tardis_portal.models.experiment.Experiment
```

```
base_fields = {'description': <django.forms.fields.CharField object>, 'institution_name': <django.forms.fields.CharField object>}
```

```
declared_fields = {'url': <django.forms.fields.CharField object>}
```

```
is_valid()
```

Test the validity of the form, the form may be invalid even if the error attribute has no contents. This is because the returned value is dependent on the validity of the nested forms.

This validity also takes into account foreign keys that might be dependent on an unsaved model.

Returns validity

Return type bool

```
media
```

```
save (commit=True)
```

```
class tardis.tardis_portal.forms.ImportParamsForm (data=None, files=None,
                                                    auto_id=u'id_%s', prefix=None,
                                                    initial=None, error_class=<class
                                                    'django.forms.utils.ErrorList'>,
                                                    label_suffix=None,
                                                    empty_permitted=False,
                                                    field_order=None,
                                                    use_required_attribute=None,
                                                    renderer=None)
```

```
    Bases: django.forms.forms.Form
```

```
base_fields = {'params': <django.forms.fields.FileField object>, 'password': <django.forms.fields.CharField object>}
```

```
declared_fields = {'params': <django.forms.fields.FileField object>, 'password': <django.forms.fields.CharField object>}
```

```
media
```

```
class tardis.tardis_portal.forms.LoginForm (*args, **kwargs)
```

```
    Bases: django.contrib.auth.forms.AuthenticationForm
```

```
base_fields = {'password': <django.forms.fields.CharField object>, 'username': <django.forms.fields.CharField object>}
```

```
declared_fields = {'password': <django.forms.fields.CharField object>, 'username': <django.forms.fields.CharField object>}
```

```
media
```

```
class tardis.tardis_portal.forms.ManageAccountForm(data=None,          files=None,
          auto_id=u'id_%s', prefix=None,
          initial=None, error_class=<class
          'django.forms.utils.ErrorList'>,
          label_suffix=None,
          empty_permitted=False,
          instance=None,
          use_required_attribute=None)
```

Bases: django.forms.models.ModelForm

Form for changing account details.

```
class Meta
```

```
    fields = ('first_name', 'last_name', 'email')
```

```
    model
```

```
        alias of django.contrib.auth.models.User
```

```
    base_fields = {'email': <django.forms.fields.EmailField object>, 'first_name': <djan
```

```
    declared_fields = {}
```

```
    media
```

```
class tardis.tardis_portal.forms.ManageGroupPermissionsForm(data=None,
          files=None,
          auto_id=u'id_%s',
          prefix=None, ini-
          tial=None, er-
          ror_class=<class
          'django.forms.utils.ErrorList'>,
          label_suffix=None,
          empty_permitted=False,
          field_order=None,
          use_required_attribute=None,
          renderer=None)
```

Bases: django.forms.forms.Form

```
    base_fields = {'adduser': <django.forms.fields.CharField object>, 'admin': <django.f
```

```
    declared_fields = {'adduser': <django.forms.fields.CharField object>, 'admin': <djan
```

```
    media
```

```
class tardis.tardis_portal.forms.NoInput(attrs=None)
```

Bases: django.forms.widgets.Widget

```
    media
```

```
    render (name, value, attrs=None)
```

```
class tardis.tardis_portal.forms.RegisterExperimentForm(data=None, files=None,
auto_id=u'id_%s', prefix=None, initial=None,
error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
field_order=None,
use_required_attribute=None,
renderer=None)
```

Bases: django.forms.forms.Form

```
base_fields = {'experiment_owner': <django.forms.fields.CharField object>, 'from_url'
```

```
declared_fields = {'experiment_owner': <django.forms.fields.CharField object>, 'from_url'
```

```
media
```

```
class tardis.tardis_portal.forms.RegistrationForm(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False,
field_order=None,
use_required_attribute=None,
renderer=None)
```

Bases: django.forms.forms.Form

Form for registering a new user account.

Validates that the requested username is not already in use, and requires the password to be entered twice to catch typos.

Subclasses should feel free to add any additional validation they need, but should avoid defining a `save()` method – the actual saving of collected user data is delegated to the active registration backend.

```
base_fields = {'email': <django.forms.fields.EmailField object>, 'password1': <django'
```

```
clean()
```

Verify that the values entered into the two password fields match. Note that an error here will end up in `non_field_errors()` because it doesn't apply to a single field.

```
clean_username()
```

Validate that the username is alphanumeric and is not already in use.

```
declared_fields = {'email': <django.forms.fields.EmailField object>, 'password1': <django'
```

```
media
```

```
save(**kwargs)
```

```
class tardis.tardis_portal.forms.RightsForm(data=None, files=None,
auto_id=u'id_%s', prefix=None,
initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False, instance=None,
use_required_attribute=None)
```

Bases: django.forms.models.ModelForm

Form for changing public access and licence.

```
class Meta

    fields = ('public_access', 'license', 'legal_text')

    model
        alias of tardis.tardis_portal.models.experiment.Experiment

    widgets = {'license': <django.forms.widgets.HiddenInput object>}

    base_fields = {'legal_text': <django.forms.fields.CharField object>, 'license': <dja

    clean()

    declared_fields = {'legal_text': <django.forms.fields.CharField object>}

    media

class tardis.tardis_portal.forms.StaticField(required=True, widget=None,
                                             label=None, initial=None,
                                             help_text=u'', error_messages=None,
                                             show_hidden_initial=False, valida-
                                             tors=(), localize=False, disabled=False,
                                             label_suffix=None)

    Bases: django.forms.fields.Field

    clean(value)

    widget
        alias of NoInput

tardis.tardis_portal.forms.createLinkedUserAuthenticationForm(authMethods)
    Create a LinkedUserAuthenticationForm and use the contents of authMethods to the list of options in the drop-
    down menu for authenticationMethod.

tardis.tardis_portal.forms.create_datafile_add_form(schema, parentObject, re-
                                                    quest=None)

tardis.tardis_portal.forms.create_parameterset_edit_form(parameterset, re-
                                                         quest=None)

tardis.tardis_portal.forms.getAuthMethodChoices()

tardis.tardis_portal.forms.save_datafile_add_form(schema, parentObject, request)

tardis.tardis_portal.forms.save_datafile_edit_form(parameterset, request)
```

tardis.tardis_portal.iiif module

```
tardis.tardis_portal.iiif.compliance_header(f)

tardis.tardis_portal.iiif.compute_etag(request, datafile_id, *args, **kwargs)

tardis.tardis_portal.iiif.download_image(request, *args, **kwargs)

tardis.tardis_portal.iiif.download_info(request, *args, **kwargs)
```

tardis.tardis_portal.logging_middleware module

```
class tardis.tardis_portal.logging_middleware.LoggingMiddleware(get_response)
    Bases: object

    process_exception(request, exception)
```

process_response (*request, response*)

`tardis.tardis_portal.logging_middleware.get_client_ip(request)`

tardis.tardis_portal.managers module

managers.py

class `tardis.tardis_portal.managers.ExperimentManager`

Bases: `tardis.tardis_portal.managers.OracleSafeManager`

Implements a custom manager for the Experiment model which checks the authorisation rules for the requesting user first

To make this work, the request must be passed to all class functions. The username and the group memberships are then resolved via the `user.userprofile.ext_groups` and `user` objects.

The `tardis.tardis_portal.auth.AuthService` is responsible for filling the `request.groups` object.

all (*user*)

Returns all experiments a user - either authenticated or anonymous - is allowed to see and search

Parameters *user* (*User*) – a User instance

Returns QuerySet of Experiments

Return type QuerySet

external_users (*experiment_id*)

returns a list of groups which have external ACL rules

Parameters *experiment_id* (*int*) – the ID of the experiment to be edited

Returns list of groups with external ACLs

Return type list

get (*user, experiment_id*)

Returns an experiment under the consideration of the ACL rules Raises `PermissionDenied` if the user does not have access.

Parameters

- *user* (*User*) – a User instance
- *experiment_id* (*int*) – the ID of the experiment to be edited

Returns Experiment

Return type *Experiment*

Raises `PermissionDenied` –

group_acls_system_owned (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters *experiment_id* (*int*) – the ID of the experiment

Returns QuerySet of system-owned ACLs for experiment

Return type QuerySet

group_acls_user_owned (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters *experiment_id* (*int*) – the ID of the experiment

Returns QuerySet of ACLs

Return type QuerySet

owned (*user*)

Return all experiments which are owned by a particular user, including those shared with a group of which the user is a member.

Parameters **user** (*User*) – a User instance

Returns QuerySet of Experiments owned by user

Return type QuerySet

owned_and_shared (*user*)

owned_by_group (*group*)

Return all experiments that are owned by a particular group

owned_by_user (*user*)

Return all experiments which are owned by a particular user id

Parameters **user** (*User*) – a User Object

Returns QuerySet of Experiments owned by user

Return type QuerySet

owned_by_user_id (*userId*)

Return all experiments which are owned by a particular user id

Parameters **userId** (*int*) – a User ID

Returns QuerySet of Experiments owned by user id

Return type QuerySet

public ()

shared (*user*)

system_owned_groups (*experiment_id*)

returns a list of sytem-owned groups which have ACL rules associated with this experiment

Parameters **experiment_id** (*string*) – the ID of the experiment to be edited

Returns system owned groups for experiment

Return type QuerySet

user_acls (*experiment_id*)

Returns a list of ACL rules associated with this experiment.

Parameters **experiment_id** (*string*) – the ID of the experiment

Returns QuerySet of ACLs

Return type QuerySet

user_owned_groups (*experiment_id*)

returns a list of user owned-groups which have ACL rules associated with this experiment

Parameters **experiment_id** (*int*) – the ID of the experiment to be edited

Returns QuerySet of non system Groups

Return type QuerySet

users (*experiment_id*)

Returns a list of users who have ACL rules associated with this experiment.

Parameters **experiment_id** (*int*) – the ID of the experiment

Returns QuerySet of Users with experiment access

Return type QuerySet

class tardis.tardis_portal.managers.**OracleSafeManager**

Bases: django.db.models.manager.Manager

Implements a custom manager which automatically defers the retrieval of any TextField fields on calls to `get_queryset`. This is to avoid the known issue that ‘distinct’ calls on query_sets containing TextFields fail when Oracle is being used as the backend.

get_queryset ()

Returns a new QuerySet object. Subclasses can override this method to easily customize the behavior of the Manager.

class tardis.tardis_portal.managers.**ParameterNameManager**

Bases: django.db.models.manager.Manager

get_by_natural_key (*namespace, name*)

class tardis.tardis_portal.managers.**SchemaManager**

Bases: django.db.models.manager.Manager

get_by_natural_key (*namespace*)

tardis.tardis_portal.rfc3339 module

The function `rfc3339` formats dates according to the [RFC 3339](#). `rfc3339` tries to have as much as possible sensible defaults.

`tardis.tardis_portal.rfc3339.rfc3339` (*date, utc=False, use_system_timezone=True*)

Return a string formatted according to the [RFC 3339](#). If called with `utc=True`, it normalizes *date* to the UTC date. If *date* does not have any timezone information, uses the local timezone:

```
>>> date = datetime.datetime(2008, 4, 2, 20)
>>> rfc3339(date, utc=True, use_system_timezone=False)
'2008-04-02T20:00:00Z'
>>> rfc3339(date)
'2008-04-02T20:00:00...'

```

If called with `use_system_timezone=False` don't use the local timezone and consider the offset to UTC to be zero:

```
>>> rfc3339(date, use_system_timezone=False)
'2008-04-02T20:00:00+00:00'

```

date must be a `datetime.datetime`, `datetime.date` or a timestamp as returned by `time.time()`:

```
>>> rfc3339(0, utc=True, use_system_timezone=False)
'1970-01-01T00:00:00Z'
>>> rfc3339(datetime.date(2008, 9, 6), use_system_timezone=False)
'2008-09-06T00:00:00+00:00'
>>> rfc3339('foo bar')
Traceback (most recent call last):
...
TypeError: expected datetime, got str instead

```

tardis.tardis_portal.shortcuts module

class `tardis.tardis_portal.shortcuts.RestfulExperimentParameterSet` (*schema_func*,
form_cls)

Bases: `object`

Helper class which enables a Backbone.sync-compatible interface to be created for a ExperimentParameterSet just by specifying a function which provides the schema and a form.

(A function for the schema is required rather than the actual schema, as to run unit tests effectively the object needs to be able to create the schema after instantiation.)

For UI consistency, it's best to make sure the schema has `hidden == true`.

schema

Use schema function to get the schema.

view_functions

`tardis.tardis_portal.shortcuts.get_experiment_referer` (*request*, *dataset_id*)

`tardis.tardis_portal.shortcuts.redirect_back_with_error` (*request*, *message*)

`tardis.tardis_portal.shortcuts.render_error_message` (*request*, *message*, *status=400*)

Render a simple text error message in a generic error page. Any newlines are turned into `<br>`.

`tardis.tardis_portal.shortcuts.render_response_index` (*request*, **args*, ***kwargs*)

`tardis.tardis_portal.shortcuts.render_to_file` (*template*, *filename*, *context*)

`tardis.tardis_portal.shortcuts.return_response_error` (*request*)

`tardis.tardis_portal.shortcuts.return_response_error_message` (*request*, *redirect_path*, *context*)

`tardis.tardis_portal.shortcuts.return_response_not_found` (*request*)

tardis.tardis_portal.signals module

tardis.tardis_portal.tasks module

tardis.tardis_portal.util module

`tardis.tardis_portal.util.get_filesystem_safe_dataset_name` (*dataset*)

Given a Dataset, return a filesystem safe string representing the dataset. Useful for filenames for dataset downloads, maybe URLs.

Parameters **dataset** (`tardis.tardis_portal.models.dataset.Dataset`) – A Dataset object.

Returns A filesystem safe string as a Dataset name.

Return type `basestring`

`tardis.tardis_portal.util.get_filesystem_safe_experiment_name` (*experiment*)

Given an Experiment, return a filesystem safe string representing the experiment. Useful for filenames for experiment downloads, maybe URLs.

Parameters **experiment** (`tardis.tardis_portal.models.experiment.Experiment`) – A Experiment object.

Returns A filesystem safe string as a Experiment name.

Return type basestring

`tardis.tardis_portal.util.get_local_time(dt)`

Ensure datetime is timezone-aware and in local time.

If the USE_TZ setting in the current dev version of Django comes in, this *should* keep providing correct behaviour.

`tardis.tardis_portal.util.get_utc_time(dt)`

Ensure datetime is timezone-aware and in UTC time.

If the USE_TZ setting in the current dev version of Django comes in, this *should* keep providing correct behaviour.

`tardis.tardis_portal.util.render_mustache(template_name, data)`

`tardis.tardis_portal.util.render_public_access_badge(experiment)`

`tardis.tardis_portal.util.split_path(p)`

`tardis.tardis_portal.widgets` module

class `tardis.tardis_portal.widgets.CommaSeparatedInput` (*attrs=None*)

Bases: `django.forms.widgets.TextInput`

media

render (*name, value, attrs=None, renderer=None*)

value_from_datadict (*data, files, name*)

class `tardis.tardis_portal.widgets.Label` (*attrs=None*)

Bases: `django.forms.widgets.Widget`

media

render (*name, value, attrs=None*)

tag = 'label'

class `tardis.tardis_portal.widgets.Span` (*attrs=None*)

Bases: `tardis.tardis_portal.widgets.Label`

media

tag = 'span'

`tardis.tardis_portal.xmlwriter` module

class `tardis.tardis_portal.xmlwriter.XMLWriter`

static `write_template_to_dir` (*dest_dir, dest_filename, template_path, context*)

Parameters

- **dest_dir** (*string*) – The directory to store the resulting document in
- **dest_filename** (*string*) – The name of the file to be output
- **template_path** (*string*) – The relative path to the Django template to be rendered

- **context** (`django.template.context.Context`) – The Context object (dictionary of variables for template output)

Returns The full path to the created file

Return type string

static `write_template_to_file(prefix_dir, objectprefix, uniqueid, templatepath, context)`

Parameters

- **prefix_dir** (*string*) – The subdirectory off of the OAI_DOCS_PATH to store the resulting document in
- **objectprefix** (*string*) – The name prefix of the resulting file. Files are output in the format prefix-uniqueid.xml
- **uniqueid** (*string*) – The unique ID of the file to be output
- **templatepath** (*string*) – The relative path to the Django template to be rendered
- **context** (`django.template.context.Context`) – The Context object (dictionary of variables for template output)

Returns The full path to the created file

Return type string

static `write_xml_to_file(prefix_dir, objectprefix, uniqueid, xmlstring)`

Parameters

- **prefix_dir** (*string*) – The subdirectory off of the OAI_DOCS_PATH to store the resulting document in
- **objectprefix** (*string*) – The name prefix of the resulting file. Files are output in the format prefix-uniqueid.xml
- **uniqueid** (*string*) – The unique ID of the file to be output
- **xmlstring** (*string*) – The relative path to the Django template to be rendered

Returns The full path to the created file

Return type string

`tardis.tardis_portal.xmlwriter.logger = <logging.Logger object>`
XML Writer

A set of static methods for writing xml files.

Module contents

importing all views files here, so that any old code will work as expected, when importing from `tardis.tardis_portal.views`

`models/__init__.py`

tardis.urls package

Submodules

tardis.urls.accounts module

tardis.urls.ajax module

tardis.urls.api module

tardis.urls.core module

tardis.urls.datafile module

tardis.urls.dataset module

tardis.urls.display module

tardis.urls.download module

tardis.urls.experiment module

tardis.urls.facility module

tardis.urls.group module

tardis.urls.token module

Module contents

Submodules

tardis.app_config module

class tardis.app_config.**AbstractTardisAppConfig**(*app_name*, *app_module*)

Bases: django.apps.config.AppConfig

All MyTardis app configuration classes should extend this abstract class to have their APIs and URLs automatically added to URL routing.

app_dependencies = []

tardis.app_config.**check_app_dependencies**(*app_configs*, ***kwargs*)

Checks currently installed apps for dependencies required by installed apps as defined by the `app_dependencies` attribute of the `AppConfig` object, if present.

Parameters

- **app_configs** (*AppConfig*) – a list of app_configs to check, or None for all apps to be checked
- **kwargs** (*list of args*) – unknown list of args

Returns a list of unsatisfied dependencies

Return type list of strings

`tardis.app_config.format_app_name_for_url(name)`

`tardis.app_config.get_tardis_apps()`

Gets a list of tuples where the first element is the app name, and the second is the module path

Returns a list of tardis apps

Return type list of apps

`tardis.app_config.is_tardis_app(app_config)`

Determines whether the installed app is a MyTardis app

Parameters `app_config` (*AppConfig*) – the AppConfig object of an installed app

Returns True if the app is a MyTardis app, False otherwise

Return type bool

tardis.celery module

tardis.test_on_mysql_settings module

tardis.test_on_postgresql_settings module

tardis.test_settings module

`tardis.test_settings.get_all_tardis_apps()`

tardis.views module

`tardis.views.error_handler(request, **kwargs)`

Module contents

importing all views files here, so that any old code will work as expected, when importing from
`tardis.tardis_portal.views`

`models/__init__.py`

11.4 Documentation for included Apps

11.4.1 Apps and Contextual Views

Introduction

In order to better represent specific data types and facilities, MyTardis allows apps to override the default views for Experiments, Datasets, DataFile metadata, and the main index and login pages. The following sections detail settings and requirements of apps to make this happen.

Datafile Views

Rationale

By default there exists an option to show the metadata of individual `DataFile`s in the default `Dataset` view. Some kinds of files allow for rich and useful visualisation and/or processing. For this purpose there exist contextual views, views that are available depending on the type of file they refer to.

User Guide

A default installation has no contextual views. To enable them a few steps are needed:

- an app needs to be installed either in `tardis/apps/`, or the app's configuration must subclass `AbstractTardisAppConfig` thereby enabling autodetection. `AbstractTardisAppConfig` replaces `AppConfig` as described in these [django docs](#).
- `DataFile`s need to be manually or automatically tagged with a schema that identifies them as viewable with a particular view. Filters are a convenient way to do this. See below for an example.
- settings need to be added to `settings.py`. A list called `DATAFILE_VIEWS` holds a tuple for each available view. The first entry of the tuple is a schema namespace and is matched against all schemas attached to the `DataFile`. If a match occurs, a link to the url given as second entry of the tuple is added to the Datafile Detail section of the default `Dataset` view and loaded via AJAX on demand. Example:

```
DATAFILE_VIEWS = [ ("http://example.org/schemas/datafile/my_awesome_schema",
                    "/apps/my-awesome-app/view"), ]
```

Currently, the default view is always `DataFile` metadata. This can be changed, for example, by developing a custom `Dataset` view, which is explained in the following section.

Dataset and Experiment Views

Rationale

For some specific uses the data available can be presented and/or processed in useful ways. MyTardis allows views for Experiments and Datasets to be overridden by apps on a per-schema basis, allowing custom views for specific data types. The example that this feature was built for are single-image and many-image datasets from the Australian Synchrotron. Single images can be displayed large and for a many-image dataset it is more useful to show a couple of example images taken at regular intervals not from the beginning of the set of files. These different datasets can be detected via their schema namespace and displayed differently.

User Guide

Akin to `DataFile` contextual views, `Dataset` and `Experiment` contextual views rely on matching a specific schema namespace in an attached `ParameterSet`.

Existing schemas can be used, or a special schema intended only for tagging an `Experiment` or `Dataset` for contextual view override can be attached (via an otherwise empty `ParameterSet`).

Dataset and Experiment contextual views are configured in settings by associating a schema namespace with a class-based view (or view function).

Unlike `DataFile` contextual views which inject content into the DOM via an AJAX call, these contextual views override the entire page.

Example:

```
DATASET_VIEWS = [
    ('http://example.org/schemas/dataset/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomDatasetViewSubclass'),
]

EXPERIMENT_VIEWS = [
    ('http://example.org/schemas/expt/my_awesome_schema',
     'tardis.apps.my_awesome_app.views.CustomExptViewSubclass'),
]
```

Custom Index View

Rationale

Specific sites or facilities often want to display a custom index page that presents recently ingested experiments in a way which is more meaningful for their particular domain or application. MyTardis support overriding the index page (/) on a per-domain or per-Site basis.

User Guide

Example:

```
INDEX_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomIndexSubclass',
    'facility.example.org': 'tardis.apps.myapp.AnotherCustomIndexSubclass'
}
```

A custom view override is defined in settings as dictionary mapping a class-based view (or view function) to a Django Site. A Site is specified by SITE_ID (an integer) or the domain name of the incoming request.

Developers creating custom contextual index views are encouraged to subclass `tardis.tardis_portal.views.pages.IndexView`.

Custom Login View

Rationale

Specific sites or facilities may want to display a custom login page that which is more meaningful to their particular domain or application. MyTardis supports overriding the login page (/login) on a per-domain or per-Site basis.

User Guide

Example:

```
LOGIN_VIEWS = {
    1: 'tardis.apps.my_custom_app.views.MyCustomLoginViewClass',
    'facility.example.org': 'tardis.apps.myapp.AnotherCustomLoginViewClass'
}
```

A custom view override is defined in settings as dictionary mapping a class-based view (or view function) to a Django [Site](#). A `Site` is specified by `SITE_ID` (an integer) or the domain name of the incoming request.

For an example MyTardis app which provides a login view, see <https://github.com/mytardis/mytardis-aaf-google-login>

Good practice for app developers

In order to benefit from future bug and security fixes in core MyTardis, app developers are strongly encouraged to override `IndexView`, `DatasetView` and `ExperimentView` (from `tardis.tardis_portal.pages`) when creating custom contextual views.

The default and well-tested `index.html`, `login.html`, `view_dataset.html` and `view_experiment.html` templates can be used as a basis for these custom contextual views.

New versions may change the default templates and view functions. If you copy and paste parts for your application, please check with each upgrade that you are still using up to date code.

11.4.2 OAI-PMH Producer

Using to provide RIF-CS

Minimal providers for Dublin Core and RIF-CS are included in the app.

To enable the app, include `tardis.apps.oaipmh` in `settings.INSTALLED_APPS`.

Your OAI-PMH query endpoint will be on: <http://mytardis-example.com/apps/oaipmh/>

Implementing your own providers

To allow multiple metadata formats (and types within them) the `tardis.apps.oaipmh.server.ProxyingServer` handles all requests and proxies them to the providers specified in `settings.OAIPMH_PROVIDERS`.

You should extend `tardis.apps.oaipmh.provider.base.BaseProvider` or one of the existing providers if you wish to extend the functionality in a site-specific way.

class `tardis.apps.oaipmh.provider.base.BaseProvider` (*site*)

A base provider which roughly implements the PyOAI interface for OAI-PMH servers.

Extend this if you're writing your own provider for a new type or a different metadata format.

getRecord (*metadataPrefix*, *identifier*)

Get a record for a `metadataPrefix` and `identifier`.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **identifier** (*string*) –
– repository-unique identifier of record

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if `metadataPrefix` is unknown or not supported by `identifier`.
- **oaipmh.error.IdDoesNotExistError** – if `identifier` is unknown or illegal.

Returns a header, metadata, about tuple describing the record.

identify()

Retrieve information about the repository.

Returns an Identify object describing the repository.

listIdentifiers (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return headers in set
- **from** (*datetime*) – only retrieve headers from **from_** date forward (in naive UTC)
- **until** (*datetime*) – only retrieve headers with dates up to and including until date (in naive UTC)

Raises

- **error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of headers.

listMetadataFormats (*identifier=None*)

List metadata formats supported by repository or record.

Parameters **identifier** (*string*) – identify record for which we want to know all supported metadata formats. If absent, list all metadata formats supported by repository.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record.

Returns an iterable of metadataPrefix, schema, metadataNamespace tuples (each entry in the tuple is a string).

listRecords (*metadataPrefix*, *set=None*, *from_=None*, *until=None*)

Get a list of header, metadata and about information on records.

Parameters

- **metadataPrefix** (*string*) – identifies metadata set to retrieve
- **set** (*string*) – set identifier; only return records in set
- **from** (*datetime*) – only retrieve records from *from_* date forward (in naive UTC)
- **until** (*datetime*) – only retrieve records with dates up to and including until date (in naive UTC)

Raises

- **oaipmh.error.CannotDisseminateFormatError** – if metadataPrefix is not supported by the repository.
- **oaipmh.error.NoSetHierarchyError** – if the repository does not support sets.

Returns an iterable of header, metadata, about tuples.

listSets()

Get a list of sets in the repository.

Raises `error.NoSetHierarchyError` – if the repository does not support sets.

Returns an iterable of `setSpec`, `setName` tuples (strings).

writeMetadata(*element*, *metadata*)

Create XML elements under the given element, using the provided metadata.

Should avoid doing any model-lookups, as they should be done when creating the metadata.

Parameters

- **element** (`lxml.etree.Element`) – element to put all content under (as SubElements)
- **metadata** (`oaipmh.common.Metadata`) – metadata to turn into XML

Raises `NotImplementedError` – not implemented

class `tardis.apps.oaipmh.server.ProxyingServer` (*providers*)

getRecord(*metadataPrefix*, *identifier*)

Get a record for a `metadataPrefix` and `identifier`.

Raises

- `oaipmh.error.CannotDisseminateFormatError` – if no provider returns a result, but at least one provider responds with `oaipmh.error.CannotDisseminateFormatError` (meaning the identifier exists)
- `oaipmh.error.IdDoesNotExistError` – if all providers fail with `oaipmh.error.IdDoesNotExistError`

Returns first successful provider response

Return type `response`

identify()

Retrieve information about the repository.

Returns an `oaipmh.common.Identify` object describing the repository.

Return type `oaipmh.common.Identify`

listIdentifiers(*metadataPrefix*, *kwargs*)**

Lists identifiers from all providers as a single set.

Raises

- `error.CannotDisseminateFormatError` – if `metadataPrefix` is not supported by the repository.
- `error.NoSetHierarchyError` – if a set is provided, as the repository does not support sets.

Returns a `set.Set` of headers.

Return type `set`

listMetadataFormats(*kwargs*)**

List metadata formats from all providers in a single set.

Raises

- **error.IdDoesNotExistError** – if record with identifier does not exist.
- **error.NoMetadataFormatsError** – if no formats are available for the indicated record, but it does exist.

Returns a *frozenset* of `metadataPrefix`, `schema`, `metadataNamespace` tuples (each entry in the tuple is a string).

Return type `frozenset`

listRecords (*metadataPrefix*, ***kwargs*)

Lists records from all providers as a single set.

Raises

- **error.CannotDisseminateFormatError** – if `metadataPrefix` is not supported by the repository.
- **error.NoSetHierarchyError** – if a set is provided, as the repository does not support sets.

Returns a `set`. Set of header, metadata, about tuples.

Return type `set`

listSets ()

List sets.

Raises `oaipmh.error.NoSetHierarchyError` – because set hierarchies are currently not implemented

11.4.3 MyTardis Social Authentication

Overview

The MyTardis social auth app allows MyTardis deployments to accept logins using OAuth and OpenID Connect. It builds on the [Python social auth package](#), and uses the [Django social auth app](#).

Usage

To enable the app, include `social_django` and `tardis.apps.social_auth` in `settings.INSTALLED_APPS`:

```
INSTALLED_APPS += (
    'social_django',
    'tardis.apps.social_auth',
)
```

Adding backends

You will need to add authentication backends that you want to enable. To enable Google authentication add following `AUTHENTICATION_BACKENDS` to `settings.py`

```
AUTHENTICATION_BACKENDS += (
    'social_core.backends.open_id.OpenIdAuth',
    'social_core.backends.google.GoogleOpenId',
)
```

(continues on next page)

(continued from previous page)

```
'social_core.backends.google.GoogleOAuth2',
)
```

To enable Australian Access federation(AAF) OpenID connect Provider(OIDC) authentication add following AUTHENTICATION_BACKENDS to *settings.py*

```
AUTHENTICATION_BACKENDS += (
    'tardis.apps.social_auth.auth.authorisation.AAFOpenId',
)
```

Adding authentication providers

You will need add authentication providers that you want to enable.

```
AUTH_PROVIDERS += (
    ('Google', 'Google',
     'social_core.backends.google.GoogleOAuth2'),
    ('AAF', 'AAF',
     'tardis.apps.social_auth.auth.authorisation.AAFOpenId'),
)
```

Adding Exception Middleware

You may want to add exception middleware provided by *python-social-auth*. To do this add following to *settings.py*

```
MIDDLEWARE += (
    'social_django.middleware.SocialAuthExceptionMiddleware',
)
```

Adding Context Processor

You will need to add following context processor to *settings.py*

```
TEMPLATES[0]['OPTIONS']['context_processors'].extend([
    'social_django.context_processors.backends',
    'social_django.context_processors.login_redirect'])
```

Application setup

Once the application is enabled and installed define the following settings to enable authentication behaviour.

```
SOCIAL_AUTH_AAF_PIPELINE = (
    'social_core.pipeline.social_auth.social_details',
    'social_core.pipeline.social_auth.social_uid',
    'social_core.pipeline.social_auth.social_user',
    'social_core.pipeline.user.get_username',
    'social_core.pipeline.user.create_user',
    'tardis.apps.social_auth.auth.social_auth.configure_social_auth_user',
    'tardis.apps.social_auth.auth.social_auth.add_authentication_method',
    'tardis.apps.social_auth.auth.social_auth.approve_user_auth',
```

(continues on next page)

(continued from previous page)

```
'tardis.apps.social_auth.auth.social_auth.add_user_permissions',
'social_core.pipeline.social_auth.associate_user',
'social_core.pipeline.social_auth.load_extra_data',
'social_core.pipeline.user.user_details',
)
```

```
SOCIAL_AUTH_GOOGLE_OAUTH2_PIPELINE = (
'social_core.pipeline.social_auth.social_details',
'social_core.pipeline.social_auth.social_uid',
'social_core.pipeline.social_auth.social_user',
'social_core.pipeline.user.get_username',
'social_core.pipeline.user.create_user',
'tardis.apps.social_auth.auth.social_auth.configure_social_auth_user',
'tardis.apps.social_auth.auth.social_auth.add_authentication_method',
'social_core.pipeline.social_auth.associate_user',
'social_core.pipeline.social_auth.load_extra_data',
'social_core.pipeline.user.user_details',
'tardis.apps.social_auth.auth.social_auth.send_admin_email',
)
```

Get key and secrets from the OIDC provider that you want to enable and add following settings.

```
SOCIAL_AUTH_URL_NAMESPACE_BEGIN = 'social:begin',
SOCIAL_AUTH_GOOGLE_OAUTH2_KEY = 'Get this from Google'
SOCIAL_AUTH_GOOGLE_OAUTH2_SECRET = 'Get this from Google'
SOCIAL_AUTH_AAF_KEY = 'Get this from AAF'
SOCIAL_AUTH_AAF_SECRET = 'Get this from AAF'
SOCIAL_AUTH_AAF_AUTH_URL = 'Get this from AAF'
SOCIAL_AUTH_AAF_TOKEN_URL = 'Get this from AAF'
SOCIAL_AUTH_AAF_USER_INFO_URL = 'Get this from AAF'
```

To override MyTardis’s default login page (Username / Password) with a more appropriate page for AAF and Google authentication, you can use <https://github.com/mytardis/mytardis-aaf-google-login>

11.5 Releases

11.5.1 4.1

- Added React search components and django-elasticsearch-dsl backend
- Removed post-save filters middleware, replaced with microservice architecture
- Added RabbitMQ task priorities support, dropped support for Redis as a broker
- Upgraded Bootstrap CSS framework from v2.3.2 to v3.4.1
- Added Python 3 support
- Added webpack to collect static assets (JS / CSS), supporting ES6, JSX etc.
- Annotated storage box related tasks with their storage box name, visible in “celery inspect active”
- Added task for clearing Django sessions
- Added timestamps (created and modified) in facility and instrument models
- Updated built-in Creative Commons licenses to v4

- Added django-storages and boto3 to requirements to support S3 storage boxes and storing static assets in S3
- Improved efficiency of checksums and downloads for files in S3 storage
- COMPUTE_SHA512 now defaults to False. COMPUTE_MD5 still defaults to True.
- Legal text for publishing can now be specified in settings
- Now using Dataset created_time in facility overview instead of experiment created time
- Added a new setting to prevent large datasets (many files) from being scanned for image files at page load time
- API v1's instrument resource now allows any authenticated user to list the instrument names, which is used in the new search interface
- The ExperimentAuthor model now exposed in API v1
- MyTardis no longer tries to guess an appropriate storage box for new DataFileObjects unless REUSE_DATASET_STORAGE_BOX is True
- Improved BDD test coverage, now measuring template coverage with django-coverage-plugin
- Bug fixes (GitHub Issue numbers below) - Fixed #1503 - Fixed #1568 - Removed bob@bobmail.com from default ADMINS, fixing #1613 - Fixed #1664 - Fixed #1708 - Fixed #1857 - Fixed #1853 - Fixed concatenated messages issue in user sharing and group sharing dialogs - Fixed #1790 - Fixed truncated TAR download issue with unverified files - Fixed sharing with AAF/Google issue - Fixed some broken Font Awesome icons

11.5.2 4.0

- Django 1.11
- jQuery 3.3.1
- Improved test coverage
- Continuous Integration tests run against Ubuntu 18.04 (MyTardis v3.x used 14.04)
- ChromeDriver is used for BDD (Behaviour Driven Development) tests
- Social Auth, including AAF and Google Auth via OpenID Connect
- Migrating user accounts from LDAP or localdb to OpenID Connect
- Customizable user menu
- Using message.level_tag instead of message.tags in portal_template, so that extra tags can be added to Django messages without interfering with the Bootstrap alert class.
- My Data page (which previously contained Owned and Shared experiments) has been split into two pages - "My Data" and "Shared" - Each page loads thumbnails asynchronously for faster initial page load time - An improved pagination widget allows for a very large number of pages.
- Index page's thumbnails are loaded asynchronously for faster initial page load time.
- Login page can be replaced with a site-specific page
- SFTP can now be used with keys instead of passwords
- Upgraded Bootstrap from 2.0.4 to 2.3.2 (further upgrades coming soon)
- Fixed some bugs in single search
- jQuery code is being moved out of HTML templates and into JS files which can be linted (with ESLint) and tested (with QUnit).
- **Removed old broken code and unnecessary code which is duplicated in other repositories.**

- Import via staging with jsTree
 - Uploadify
- **Updated or removed (as appropriate) some out-of-date JS dependencies bundled within the MyTardis repository**
 - Most JS dependences are installed by npm now, so we can run security checks with npm audit
- manage.py can now be used instead of mytardis.py and mytardis.py will soon be deprecated
- New support email setting can be used in email templates or HTML templates.
- Updating loadschemas management command for Django 1.11 and adding test for it
- Updated the dumpschemas management command for Django 1.11 and added a test for it
- **Bug fixes (GitHub Issue numbers below)** Fixed #243. Bug in tardis_acls.change_experiment permissions check Fixed #516 - only show “Add files” button if user has permission to upload files Fixed #636 Fixed #637 - “()” is added to “Author” line every time an experiment is edited Fixed #779 Fixed #868 Fixed #893 Fixed #988 Fixed #1083 Fixed #1185
- Added docs on X-Forwarded-Proto HTTP header for HTTPS deployments
- Added docs on configuring services in systemd or supervisor
- Removed password length restriction in linked user authentication form
- Removed settings_changeme - use default_settings instead
- Removed backslash from set of characters used to generate secret key.
- Removed django-celery - it is no longer necessary to run Celery via Django
- Improved forwards compatibility with Python 3, but we’re not fully Python 3 compatible yet.
- Switched to PEP 328 relative imports
- Tests no longer require the unmaintained “compare” module
- Added a default value for DATA_UPLOAD_MAX_MEMORY_SIZE (required by Django 1.10+) to default settings
- Removed some unused dependencies, e.g. PyYAML
- Removed the createmysuperuser which is no longer needed
- Removed the checkhashes management command
- Removed the diffraction image filter
- Removed the backupdb management command
- Removed the old publication form - a new publication workflow is coming soon.

11.5.3 3.9

- Added deprecation warnings for functionality which will be removed in 4.0
- Added INTERNAL_IPS to default settings for template debugging on localhost
- Disabled the old publication forms app in default settings, and ensured that MyTardis didn’t attempt to access its static content when disabled
- Removed apps code from ExperimentView’s get_context_data which assumed that each app would provide a views module with an index

- Fixed a bug where creating a group which already existed gave a 500 error
- Fixed a bug where non-ASCII characters in experiment names could break SFTP
- Made dataset thumbnails optional - disabling them can improve page load times
- Fixed a bug which had made it difficult to delete a DataFileObject without a URI from the Django shell
- Fixed a bug which made search indexing fail when there were users with non-ASCII characters in their first or last name

11.5.4 3.8.1

- Fix regression in Push To app

11.5.5 3.8

- Refactored settings
- Added pagination to My Data view
- BDD tests using behave and phantomjs
- Added download MD5 checksum buttons to Dataset View
- Add *autocaching* task that allows data from a StorageBox to be cached to another StorageBox
- Re-wrote user documentation and switched to hosting docs on RTD
- Switched to using NPM to manage JS deps.
- Facility and instrument are now visible on Experiment and dataset views - thanks @avrljk
- Added setting that allows datasets ordered by id on the Experiment page.
- Added setting to make sha512 checksums optional.

11.5.6 3.7 - 17 March 2016

- DataFile size is now a BigInteger field
- New settings for customisations, contextual view overrides (eg INDEX_VIEWS).
- A new AbstractTardisAppConfig class that all new tardis apps should subclass
- Third-party tardis app dependency checking
- Removed database index from Parameter.string_value to allow longer strings in Postgres. Migrations add a Postgres partial index for string_values shorter than 256 characters.
- Changed constraints on the instrument model; facility and instrument name are now unique together
- changed method tasks to task functions, pre-empting the removal of methods tasks in new celery versions
- RESTful API now supports ordering, e.g. &order_by=-title, for Experiments, Datasets and DataFiles.
- Allowed groups to be 'owners' of an Experiment. Enforce rule in views for web UI requiring every Experiment to have at least one user owner.
- Registration support updated for latest django-registration-redux package
- Speed-ups for dataset view page loading for datasets with large numbers of images. The carousel is now limited to a maximum of 100 preview images.

- Reorganised and updated documentation

11.5.7 3.6 - 16 March 2015

- removed legacy operations files (foreman, apache, uwsgi, etc)
- moved CI from Travis CI to Semaphore app
- removed buildout build system and setup.py dependency management
- build instructions in build.sh, using requirements.txt for dependencies now
- gunicorn instead of uwsgi
- updated Django to version 1.6.10
- removed migrations app
- renamed `Dataset_File` to `DataFile`
- `DataFile` have a `deleted` and a `version` flag, for upcoming support of these features.
- verifying files does not have side-effects anymore
- renamed `Author_Experiment` to `ExperimentAuthor`
- an `ExperimentAuthor` can now have an email and or a URL
- recoded `Replica` and `Location` as `DataFileObject` with associated `StorageBox`, based on the Django File API
- API v1 got some additions, largely or fully backwards-compatible
- a publication workflow app, guided publication of data
- download data via SFTP using a built-in SFTP server
- removed most traces of METS
- AAF authentication support
- parameters that can store a generic foreign key (link to any database object)
- new models `Instrument` and `Facility`
- basic support for SquashFS archives as `StorageBox`. Probably requires installation-specific code such as what is used at the [Australian Synchrotron](#).
- error pages are no normal-sized
- new view “Facility Overview”, for facility administrators to have overview over data.
- “MyData” includes owned and shared data
- safely allowing HTML in descriptions now. Achieved by “bleaching” of tags
- stats page faster through DB-server-side aggregation
- layout improvements
- pep8 and pylint improvements
- bug fixes

11.5.8 3.5 - 26 August 2013

- REST API
- REST API keys
- Authorisation now supports object-level permissions
- Front page overview
- Contextual views for Datafiles, Datasets and Experiments
- Backwards incompatible database changes
- Replica multi file location support
- Migration of replicas
- Streaming downloads
- Django 1.5
- REDIS option for celery queue
- auto-verify files
- provisional directory support
- Pylint testing on Travis CI
- Some error pages are now functional
- optionally upload comfortably with Filepicker.io
- Experiment view page load speedup
- Removed ancient XML ingest format.

11.5.9 3.0 - unreleased

- Twitter Bootstrap
- javascript templates
- backbone.js rendering of datasets
- UI for transferring datasets
- bpython shell
- celery queue

11.5.10 2.0 - Unreleased

- Auth/Auth redesign [Gerson, Uli, Russel]
 - Authorisation. Support for several pluggable authorisation plugins (Django internal, LDAP, VBL). The added AuthService middleware provides a mechanism to query all available auth modules to determine what group memberships a users has.
 - Alternative authorisation. Rule based experiment access control engine was implemented with the following access attributes for individual users and groups: canRead, canWrite, canDelete, isOwner. Additionally, a time stamp can be specified for each access rule.

Further information can be found at the wiki: [Authorisation Engine design](#)

- Metadata Editing [Steve, Grischa]
- New METS parser & METS exporter [Gerson]
- Dist/Buildout infrastructure [Russell]
- Through the web creation and editing of experiments [Steve, Russell]
- Through the web upload of files [Steve]
- Download protocol handler [Russel, Uli]
- Logging framework [Uli]
- Django 1.3

11.5.11 1.07 - 01/06/2010

- Publish to tardis.edu.au interface created, though not implemented, pending legal text

11.5.12 1.06 - 15/03/2010

- Parameter import interface for creation of new parameter/schema definitions
- iPhone Interface

11.5.13 1.05 - 01/03/2010

- Images as parameters supported
- Data / metadata transfer from synchrotron is now ‘threaded’ using asynchronous web service transfers.

11.5.14 1.0 - 01/02/2010

- MyTardis created from existin MyTardis python / django codebase
- Allows private data to be stored
- Open key/value parameter model, replacing current crystallography one
- Internal data store for data
- LDAP Login
- Pagination of files
- Creation of synchrotron-tardis from MyTardis codebase including specific code for the VBL login service and data transfer to MyTardis deployments.
- Web server changed to apache and mod_wsgi

11.5.15 0.5 - 2009

- Re-wrote federated index (python / django)
- Federated stores are now simple web server based with optional FTP access
- Runs on Jython / Tomcat

11.5.16 0.1 - 2007

- Federated index (php) running on Apache HTTP Server
- Crystallography data deposition and packaging tools for Fedora Commons (java swing desktop)
- Search Interface via web

CHAPTER 12

Indices and tables

- `genindex`
- `modindex`
- `search`

Python Module Index

t

tardis, 238

tardis.analytics, 76

tardis.analytics.apps, 75

tardis.analytics.ga, 75

tardis.analytics.tracker, 75

tardis.app_config, 237

tardis.apps, 117

tardis.apps.deep_storage_download_mapper, 76

tardis.apps.deep_storage_download_mapper.mapper, 76

tardis.apps.deep_storage_download_mapper.urls, 76

tardis.apps.dl_mapper_df_dir_only, 77

tardis.apps.dl_mapper_df_dir_only.mapper, 76

tardis.apps.dl_mapper_df_dir_only.urls, 77

tardis.apps.filepicker, 77

tardis.apps.filepicker.filepicker_settings, 77

tardis.apps.filepicker.urls, 77

tardis.apps.filepicker.utils, 77

tardis.apps.filepicker.views, 77

tardis.apps.oaipmh, 84

tardis.apps.oaipmh.models, 82

tardis.apps.oaipmh.provider, 80

tardis.apps.oaipmh.provider.base, 77

tardis.apps.oaipmh.provider.experiment, 79

tardis.apps.oaipmh.server, 82

tardis.apps.oaipmh.tests, 82

tardis.apps.oaipmh.tests.provider, 81

tardis.apps.oaipmh.tests.provider.test_base, 80

tardis.apps.oaipmh.tests.provider.test_experiment, 81

tardis.apps.oaipmh.tests.test_oai, 81

tardis.apps.oaipmh.urls, 84

tardis.apps.oaipmh.views, 84

tardis.apps.openid_migration, 89

tardis.apps.openid_migration.apps, 85

tardis.apps.openid_migration.context_processors, 85

tardis.apps.openid_migration.default_settings, 86

tardis.apps.openid_migration.email_text, 86

tardis.apps.openid_migration.forms, 86

tardis.apps.openid_migration.migration, 86

tardis.apps.openid_migration.migrations, 84

tardis.apps.openid_migration.migrations.0001_initial, 84

tardis.apps.openid_migration.models, 86

tardis.apps.openid_migration.tasks, 89

tardis.apps.openid_migration.tests, 85

tardis.apps.openid_migration.tests.test_forms, 84

tardis.apps.openid_migration.tests.test_migration, 84

tardis.apps.openid_migration.tests.test_models, 85

tardis.apps.openid_migration.tests.test_views, 85

tardis.apps.openid_migration.urls, 89

tardis.apps.openid_migration.user_menu_modifiers, 89

tardis.apps.openid_migration.utils, 89

tardis.apps.openid_migration.views, 89

tardis.apps.push_to, 98

tardis.apps.push_to.apps, 90

tardis.apps.push_to.exceptions, 91

tardis.apps.push_to.migrations, 90

tardis.apps.push_to.migrations.0001_initial, 90

tardis.apps.push_to.migrations.0002_auto_20160518_1

90
tardis.apps.push_to.models, 91
tardis.apps.push_to.oauth_tokens, 96
tardis.apps.push_to.ssh_authz, 96
tardis.apps.push_to.tasks, 97
tardis.apps.push_to.tests, 90
tardis.apps.push_to.tests.test_models, 90
tardis.apps.push_to.urls, 97
tardis.apps.push_to.utils, 97
tardis.apps.push_to.views, 97
tardis.apps.related_info, 100
tardis.apps.related_info.forms, 100
tardis.apps.related_info.models, 100
tardis.apps.related_info.settings, 100
tardis.apps.related_info.tests, 99
tardis.apps.related_info.tests.test_oaipmh, 98
tardis.apps.related_info.tests.tests, 98
tardis.apps.related_info.urls, 100
tardis.apps.related_info.views, 100
tardis.apps.s3utils, 103
tardis.apps.s3utils.api, 101
tardis.apps.s3utils.apps, 102
tardis.apps.s3utils.default_settings, 102
tardis.apps.s3utils.tests, 101
tardis.apps.s3utils.tests.test_api, 100
tardis.apps.s3utils.tests.test_app_config, 101
tardis.apps.s3utils.tests.test_checksums, 101
tardis.apps.s3utils.urls, 102
tardis.apps.s3utils.utils, 102
tardis.apps.search, 106
tardis.apps.search.api, 103
tardis.apps.search.apps, 105
tardis.apps.search.documents, 105
tardis.apps.search.tests, 103
tardis.apps.search.tests.test_api, 103
tardis.apps.search.tests.test_index, 103
tardis.apps.search.urls, 106
tardis.apps.search.views, 106
tardis.apps.sftp, 116
tardis.apps.sftp.admin, 108
tardis.apps.sftp.api, 108
tardis.apps.sftp.apps, 108
tardis.apps.sftp.default_settings, 109
tardis.apps.sftp.forms, 109
tardis.apps.sftp.management, 107
tardis.apps.sftp.management.commands, 107
tardis.apps.sftp.management.commands.sftpd, 106
tardis.apps.sftp.migrations, 107
tardis.apps.sftp.migrations.0001_initial, 107
tardis.apps.sftp.models, 109
tardis.apps.sftp.sftp, 110
tardis.apps.sftp.tests, 107
tardis.apps.sftp.tests.test_sftp, 107
tardis.apps.sftp.urls, 115
tardis.apps.sftp.user_menu_modifiers, 115
tardis.apps.sftp.views, 116
tardis.apps.social_auth, 117
tardis.apps.social_auth.apps, 117
tardis.apps.social_auth.auth, 117
tardis.apps.social_auth.auth.social_auth, 116
tardis.apps.social_auth.default_settings, 117
tardis.celery, 238
tardis.default_settings, 122
tardis.default_settings.admins, 117
tardis.default_settings.analytics, 117
tardis.default_settings.apps, 117
tardis.default_settings.auth, 118
tardis.default_settings.caches, 118
tardis.default_settings.celery_settings, 118
tardis.default_settings.custom_views, 118
tardis.default_settings.database, 119
tardis.default_settings.debug, 119
tardis.default_settings.downloads, 119
tardis.default_settings.email, 120
tardis.default_settings.filters, 120
tardis.default_settings.frontend, 120
tardis.default_settings.i18n, 121
tardis.default_settings.localisation, 121
tardis.default_settings.logging, 121
tardis.default_settings.middlewares, 121
tardis.default_settings.publication, 121
tardis.default_settings.search, 121
tardis.default_settings.sharing, 121
tardis.default_settings.site_customisations, 122
tardis.default_settings.static_files, 122
tardis.default_settings.storage, 122
tardis.default_settings.templates, 122
tardis.default_settings.uploads, 122
tardis.default_settings.urls, 122
tardis.tardis_portal, 236

tardis.tardis_portal.admin, 209	131
tardis.tardis_portal.api, 214	tardis.tardis_portal.migrations.0004_storageboxopt
tardis.tardis_portal.auth, 129	132
tardis.tardis_portal.auth.authentication, 123	tardis.tardis_portal.migrations.0005_datafile_add
tardis.tardis_portal.auth.authorisation, 123	132
tardis.tardis_portal.auth.authservice, 124	tardis.tardis_portal.migrations.0006_datafile_remove
tardis.tardis_portal.auth.decorators, 125	132
tardis.tardis_portal.auth.fix_circular, 126	tardis.tardis_portal.migrations.0007_remove_paramet
tardis.tardis_portal.auth.interfaces, 127	132
tardis.tardis_portal.auth.localdb_auth, 128	tardis.tardis_portal.migrations.0008_string_value_p
tardis.tardis_portal.auth.token_auth, 128	132
tardis.tardis_portal.auth.utils, 129	tardis.tardis_portal.migrations.0009_auto_20160128
tardis.tardis_portal.constants, 222	133
tardis.tardis_portal.context_processors, 222	tardis.tardis_portal.migrations.0010_auto_20160503
tardis.tardis_portal.creativecommonshandling, 223	133
tardis.tardis_portal.deprecations, 223	tardis.tardis_portal.migrations.0011_auto_20160505
tardis.tardis_portal.download, 224	133
tardis.tardis_portal.email, 224	tardis.tardis_portal.migrations.0012_userauthentic
tardis.tardis_portal.errors, 225	133
tardis.tardis_portal.fields, 225	tardis.tardis_portal.migrations.0013_auto_20181002
tardis.tardis_portal.forms, 225	133
tardis.tardis_portal.iiif, 230	tardis.tardis_portal.migrations.0014_auto_20181002
tardis.tardis_portal.logging_middleware, 230	133
tardis.tardis_portal.management, 131	tardis.tardis_portal.migrations.0015_dataset_create
tardis.tardis_portal.management.commands, 131	134
tardis.tardis_portal.management.commands.add_dataset, 129	tardis.tardis_portal.migrations.0016_add_timestamps
tardis.tardis_portal.management.commands.add_experiment, 130	134
tardis.tardis_portal.management.commands.add_facility, 130	tardis.tardis_portal.migrations.0017_add_cc_license
tardis.tardis_portal.management.commands.add_instrument, 130	134
tardis.tardis_portal.management.commands.add_parameter, 130	tardis.tardis_portal.migrations.0018_make_default_s
tardis.tardis_portal.managers, 231	134
tardis.tardis_portal.migrations, 135	tardis.tardis_portal.models, 179
tardis.tardis_portal.migrations.0001_initial, 131	tardis.tardis_portal.models.access_control,
tardis.tardis_portal.migrations.0001_schema, 131	135
tardis.tardis_portal.migrations.0002_auto_20150228_1128, 131	tardis.tardis_portal.models.datafile,
tardis.tardis_portal.migrations.0003_auto_20150907_1315, 131	140
	tardis.tardis_portal.models.dataset, 145
	tardis.tardis_portal.models.experiment,
	147
	tardis.tardis_portal.models.facility,
	152
	tardis.tardis_portal.models.hooks, 154
	tardis.tardis_portal.models.instrument,
	154
	tardis.tardis_portal.models.jti, 155
	tardis.tardis_portal.models.license, 156
	tardis.tardis_portal.models.parameters,
	157
	tardis.tardis_portal.models.storage, 173
	tardis.tardis_portal.models.token, 178
	tardis.tardis_portal.ParameterSetManager,
	208
	tardis.tardis_portal.publish, 180
	tardis.tardis_portal.publish.provider,

tardis.tardis_portal.publish.provider.rifasprovider,180	tardis.tardis_portal.tests.api.test_experiment_resource,185
tardis.tardis_portal.publish.publishservicetardis.tardis_portal.tests.api.test_facility_resource,180	tardis.tardis_portal.tests.api.test_group_resource,186
tardis.tardis_portal.rfc3339,233	tardis.tardis_portal.tests.api.test_instrument_resource,186
tardis.tardis_portal.shortcuts,234	tardis.tardis_portal.tests.api.test_replica_resource,187
tardis.tardis_portal.signals,234	tardis.tardis_portal.tests.api.test_schema_resource,187
tardis.tardis_portal.storage,180	tardis.tardis_portal.tests.api.test_serializer,187
tardis.tardis_portal.storage.file_systemtardis.tardis_portal.tests.api.test_storagebox_resource,180	tardis.tardis_portal.tests.api.test_user_resource,188
tardis.tardis_portal.tasks,234	tardis.tardis_portal.tests.auth,188
tardis.tardis_portal.templatetags,184	tardis.tardis_portal.tests.ldap_ldif,189
tardis.tardis_portal.templatetags.approvetardis.tardis_portal.tests.management,181	tardis.tardis_portal.tests.management.test_collect,188
tardis.tardis_portal.templatetags.basiccompardis.tardis_portal.tests.management.test_createus,181	tardis.tardis_portal.tests.management.test_dumpsche,189
tardis.tardis_portal.templatetags.bleachtardis.tardis_portal.tests.management.test_loadsche,181	tardis.tardis_portal.tests.management.test_rmexper,189
tardis.tardis_portal.templatetags.capturetardis.tardis_portal.tests.slapd,181	tardis.tardis_portal.tests.test_authentication,193
tardis.tardis_portal.templatetags.dataset_tags,192	tardis.tardis_portal.tests.test_authorisation,193
tardis.tardis_portal.templatetags.dynurl,182	tardis.tardis_portal.tests.test_authservice,194
tardis.tardis_portal.templatetags.experiment_tags,182	tardis.tardis_portal.tests.test_copy_move,195
tardis.tardis_portal.templatetags.experimentstats,183	tardis.tardis_portal.tests.test_download,195
tardis.tardis_portal.templatetags.facility_tags,189	tardis.tardis_portal.tests.test_download_apikey,195
tardis.tardis_portal.templatetags.feed,183	tardis.tardis_portal.tests.test_facility_overview,196
tardis.tardis_portal.templatetags.formfieldfilters,183	tardis.tardis_portal.tests.test_forms,196
tardis.tardis_portal.templatetags.lookupfilters,183	tardis.tardis_portal.tests.test_iiif,196
tardis.tardis_portal.templatetags.pagination,183	tardis.tardis_portal.tests.test_ldap,196
tardis.tardis_portal.templatetags.xmldate,183	
tardis.tardis_portal.tests,202	
tardis.tardis_portal.tests.api,188	
tardis.tardis_portal.tests.api.test_auth,184	
tardis.tardis_portal.tests.api.test_data,184	
tardis.tardis_portal.tests.api.test_data,184	
tardis.tardis_portal.tests.api.test_data,185	
tardis.tardis_portal.tests.api.test_data,185	
tardis.tardis_portal.tests.api.test_experiment,185	

197 tardis.test_settings, 238
tardis.tardis_portal.tests.test_models, tardis.views, 238
197
tardis.tardis_portal.tests.test_parameters,
198
tardis.tardis_portal.tests.test_parametersets,
198
tardis.tardis_portal.tests.test_publishservice,
199
tardis.tardis_portal.tests.test_storage,
200
tardis.tardis_portal.tests.test_tar_download,
200
tardis.tardis_portal.tests.test_tasks,
200
tardis.tardis_portal.tests.test_tokens,
201
tardis.tardis_portal.tests.tests, 201
tardis.tardis_portal.tests.views, 192
tardis.tardis_portal.tests.views.test_auth_views,
189
tardis.tardis_portal.tests.views.test_contextual_views,
190
tardis.tardis_portal.tests.views.test_experiment_views,
190
tardis.tardis_portal.tests.views.test_template_contexts,
191
tardis.tardis_portal.tests.views.test_upload_views,
191
tardis.tardis_portal.util, 234
tardis.tardis_portal.views, 208
tardis.tardis_portal.views.ajax_actions,
202
tardis.tardis_portal.views.ajax_json,
202
tardis.tardis_portal.views.ajax_pages,
202
tardis.tardis_portal.views.authentication,
202
tardis.tardis_portal.views.authorisation,
203
tardis.tardis_portal.views.facilities,
203
tardis.tardis_portal.views.images, 204
tardis.tardis_portal.views.machine, 204
tardis.tardis_portal.views.pages, 204
tardis.tardis_portal.views.parameters,
207
tardis.tardis_portal.views.upload, 207
tardis.tardis_portal.views.utils, 208
tardis.tardis_portal.widgets, 235
tardis.tardis_portal.xmlwriter, 235
tardis.test_on_mysql_settings, 238
tardis.test_on_postgresql_settings, 238

A

- `about()` (in module `tardis.tardis_portal.views.pages`), 206
- `abstract` (`tardis.apps.push_to.models.KeyPair.Meta` attribute), 93
- `abstract` (`tardis.tardis_portal.models.parameters.ParameterSet.Meta` attribute), 166
- `abstract` (`tardis.tardis_portal.models.parameters.ParameterSet.Meta` attribute), 170
- `AbstractExperimentProvider` (class in `tardis.apps.oaipmh.provider.experiment`), 79
- `AbstractExperimentProviderTC` (class in `tardis.apps.oaipmh.tests.provider.test_experiment`), 81
- `AbstractTardisAppConfig` (class in `tardis.app_config`), 237
- `accessible_keys` (`tardis.tardis_portal.api.StorageBoxOptionResource` attribute), 221
- `acl_id` (`tardis.apps.openid_migration.models.OpenidACLMigration` attribute), 87
- `acl_id_id` (`tardis.apps.openid_migration.models.OpenidACLMigration` attribute), 87
- `acl_migration()` (in module `tardis.apps.openid_migration.migration`), 86
- `ACLAuthorization` (class in `tardis.tardis_portal.api`), 214
- `ACLAuthorizationTest` (class in `tardis.tardis_portal.tests.api.test_auth`), 184
- `ACLAwareBackend` (class in `tardis.tardis_portal.auth.authorisation`), 123
- `aclOwnershipType` (`tardis.tardis_portal.models.access_control.ObjectACL` attribute), 136
- `add_arguments()` (`tardis.apps.sftp.management.commands.sftpd.Command` method), 106
- `add_arguments()` (`tardis.tardis_portal.management.commands.createuser.Command` method), 129
- `add_arguments()` (`tardis.tardis_portal.management.commands.dumpschemas.Command` method), 130
- `add_arguments()` (`tardis.tardis_portal.management.commands.loadschema.Command` method), 130
- `add_arguments()` (`tardis.tardis_portal.management.commands.rmexperiment.Command` method), 130
- `add_auth_method()` (in module `tardis.tardis_portal.auth.authentication`), 123
- `add_authentication_method()` (in module `tardis.apps.social_auth.auth.social_auth`), 116
- `add_child()` (`tardis.apps.sftp.sftp.DynamicTree` method), 110
- `add_datafile_par()` (in module `tardis.tardis_portal.views.parameters`), 207
- `add_dataset()` (in module `tardis.tardis_portal.views.pages`), 206
- `add_dataset_par()` (in module `tardis.tardis_portal.views.parameters`), 207
- `add_experiment_par()` (in module `tardis.tardis_portal.views.parameters`), 207
- `add_migrate_account_menu_item()` (in module `tardis.apps.openid_migration.user_menu_modifiers`), 89
- `add_migration_permission()` (in module `tardis.apps.social_auth.auth.social_auth`), 116
- `add_par()` (in module `tardis.tardis_portal.views.parameters`), 207
- `add_path()` (`tardis.apps.sftp.sftp.DynamicTree` method), 110
- `add_path_elems()` (`tardis.apps.sftp.sftp.DynamicTree` method), 110
- `add_ssh_keys_menu_item()` (in module `tardis.apps.sftp.user_menu_modifiers`), 115
- `add_user_permissions()` (in module `tardis.apps.social_auth.auth.social_auth`), 116
- `added` (`tardis.apps.sftp.models.SFTPPublicKey` attribute), 110
- `AddUserPermissionsForm` (class in `tardis.tardis_portal.forms`), 225

administrator (*tardis.apps.push_to.models.RemoteHost*
 attribute), 95
 administrator_id (*tardis.apps.push_to.models.RemoteHost*
 attribute), 95
 ADMINS (in module *tardis.default_settings.admins*), 117
 AdvanceSearchAppResource (class in
 tardis.apps.search.api), 103
 AdvanceSearchAppResource.Meta (class in
 tardis.apps.search.api), 103
 all () (*tardis.tardis_portal.managers.ExperimentManager*
 method), 231
 allow_for_all (*tardis.apps.push_to.models.OAuthSSHCertSigningService*
 attribute), 93
 allow_reuse_address
 (*tardis.apps.sftp.sftp.MyTSFTPTCPServer*
 attribute), 112
 allowed_groups (*tardis.apps.push_to.models.OAuthSSHCertSigningService*
 attribute), 93
 ALLOWED_HOSTS, 45
 ALLOWED_HOSTS (in module
 tardis.default_settings.debug), 119
 allowed_methods (*tardis.tardis_portal.api.UserResource.Meta*
 attribute), 221
 allowed_remote_hosts
 (*tardis.apps.push_to.models.OAuthSSHCertSigningService*
 attribute), 93
 allowed_users (*tardis.apps.push_to.models.OAuthSSHCertSigningService*
 attribute), 94
 allows_distribution
 (*tardis.tardis_portal.models.license.License*
 attribute), 156
 always_return_data
 (*tardis.apps.search.api.AdvanceSearchAppResource.Meta*
 attribute), 103
 always_return_data
 (*tardis.apps.search.api.SearchAppResource.Meta*
 attribute), 104
 always_return_data
 (*tardis.tardis_portal.api.DatasetResource.Meta*
 attribute), 216
 always_return_data
 (*tardis.tardis_portal.api.ExperimentAuthorResource.Meta*
 attribute), 216
 always_return_data
 (*tardis.tardis_portal.api.ExperimentResource.Meta*
 attribute), 217
 always_return_data
 (*tardis.tardis_portal.api.FacilityResource.Meta*
 attribute), 217
 always_return_data
 (*tardis.tardis_portal.api.InstrumentResource.Meta*
 attribute), 218
 AnalyticsConfig (class in *tardis.analytics.apps*), 75
 ApiKeyDownloadTestCase (class in
 tardis.tardis_portal.tests.test_download_apikey),
 195
 app_dependencies (*tardis.app_config.AbstractTardisAppConfig*
 attribute), 237
 app_label (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend*
 attribute), 124
 app_label (*tardis.tardis_portal.models.parameters.Parameter.Meta*
 attribute), 166
 app_label (*tardis.tardis_portal.models.parameters.ParameterSet.Meta*
 attribute), 170
 apply_filters () (*tardis.tardis_portal.models.datafile.DataFileObject*
 method), 143
 approve_user_auth () (in module
 tardis.apps.social_auth.auth.social_auth),
 116
 approved (*tardis.tardis_portal.models.access_control.UserAuthentication*
 attribute), 138
 approved (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 args (*tardis.tardis_portal.management.commands.dumpschemas.Command*
 attribute), 130
 args (*tardis.tardis_portal.management.commands.loadschemas.Command*
 attribute), 130
 args (*tardis.tardis_portal.management.commands.rmexperiment.Command*
 attribute), 130
 attributes (*tardis.tardis_portal.models.storage.StorageBox*
 attribute), 173
 auth_timeout (*tardis.apps.sftp.sftp.MyTSFTPRequestHandler*
 attribute), 111
 authenticate () (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend*
 method), 124
 authenticate () (*tardis.tardis_portal.auth.authservice.AuthService*
 method), 124
 authenticate () (*tardis.tardis_portal.auth.interfaces.AuthProvider*
 method), 127
 authenticate () (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend*
 method), 128
 authenticate () (*tardis.tardis_portal.tests.test_authservice.MockAuthService*
 method), 194
 authentication (*tardis.apps.search.api.AdvanceSearchAppResource.Meta*
 attribute), 103
 authentication (*tardis.apps.search.api.SearchAppResource.Meta*
 attribute), 104
 authentication (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta*
 attribute), 108
 authentication (*tardis.tardis_portal.api.GroupResource.Meta*
 attribute), 218
 authentication (*tardis.tardis_portal.api.MyTardisModelResource.Meta*
 attribute), 219
 authentication (*tardis.tardis_portal.api.ObjectACLResource.Meta*
 attribute), 219
 authentication (*tardis.tardis_portal.api.UserResource.Meta*
 attribute), 221
 authenticationMethod

(*tardis.tardis_portal.models.access_control.UserAuthentication* attribute), 138

AuthenticationTests (*tardis.tardis_portal.admin.DataFileObjectInlineForm* attribute), 209

AuthenticationTestCase (class in *base_fields* (*tardis.tardis_portal.admin.StorageBoxAttributeInlineForm* attribute), 212

193 *base_fields* (*tardis.tardis_portal.admin.StorageBoxForm* attribute), 213

author (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 152

authorization (*tardis.apps.s3utils.api.ReplicaAppResource.Meta* attribute), 213

attribute), 101 *base_fields* (*tardis.tardis_portal.api.DatafileParameterResource* attribute), 215

authorization (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta* attribute), 108

attribute), 108 *base_fields* (*tardis.tardis_portal.api.DatafileParameterSetResource* attribute), 215

authorization (*tardis.tardis_portal.api.GroupResource.Meta* attribute), 215

attribute), 218 *base_fields* (*tardis.tardis_portal.api.DataFileResource* attribute), 214

authorization (*tardis.tardis_portal.api.MyTardisModelResource.Meta* attribute), 219

attribute), 219 *base_fields* (*tardis.tardis_portal.api.DatasetParameterResource* attribute), 215

authorization (*tardis.tardis_portal.api.ObjectACLResource.Meta* attribute), 219

attribute), 219 *base_fields* (*tardis.tardis_portal.api.DatasetParameterSetResource* attribute), 216

authorization (*tardis.tardis_portal.api.UserResource.Meta* attribute), 222

attribute), 222 *base_fields* (*tardis.tardis_portal.api.DatasetResource* attribute), 216

authorize_remote_access() (in module *tardis.apps.push_to.views*), 97

AuthProvider (class in *tardis.tardis_portal.auth.interfaces*), 127

AuthService (class in *tardis.tardis_portal.auth.authservice*), 124

AuthServiceTestCase (class in *tardis.tardis_portal.tests.test_authservice*), 194

autocache (*tardis.tardis_portal.models.storage.StorageBox* attribute), 174

AUTOGENERATE_API_KEY (in module *tardis.default_settings.auth*), 118

B

BackgroundTaskTestCase (class in *base_fields* (*tardis.tardis_portal.tests.test_tasks*), 200

attribute), 92 *base_fields* (*tardis.tardis_portal.api.MyTardisModelResource* attribute), 219

base_fields (*tardis.apps.push_to.models.CredentialForm* attribute), 100

attribute), 100 *base_fields* (*tardis.tardis_portal.api.ObjectACLResource* attribute), 219

base_fields (*tardis.apps.related_info.forms.RelatedInfoForm* attribute), 101

attribute), 101 *base_fields* (*tardis.tardis_portal.api.ParameterNameResource* attribute), 220

base_fields (*tardis.apps.s3utils.api.ReplicaAppResource* attribute), 104

attribute), 104 *base_fields* (*tardis.tardis_portal.api.ParameterResource* attribute), 220

base_fields (*tardis.apps.search.api.AdvanceSearchAppResource* attribute), 104

attribute), 104 *base_fields* (*tardis.tardis_portal.api.ParameterSetResource* attribute), 220

base_fields (*tardis.apps.search.api.SearchAppResource* attribute), 108

attribute), 108 *base_fields* (*tardis.tardis_portal.api.ReplicaResource* attribute), 220

base_fields (*tardis.apps.sftp.api.SFTPPublicKeyAppResource* attribute), 109

attribute), 109 *base_fields* (*tardis.tardis_portal.api.SchemaResource* attribute), 221

base_fields (*tardis.apps.sftp.forms.KeyAddForm* attribute), 109

attribute), 109 *base_fields* (*tardis.tardis_portal.api.StorageBoxAttributeResource* attribute), 221

base_fields (*tardis.apps.sftp.forms.KeyGenerateForm* attribute), 210

attribute), 210 *base_fields* (*tardis.tardis_portal.api.StorageBoxOptionResource* attribute), 221

base_fields (*tardis.tardis_portal.api.StorageBoxResource* attribute), 221
 base_fields (*tardis.tardis_portal.models.storage.StorageBox* attribute), 174
 base_fields (*tardis.tardis_portal.api.UserResource* attribute), 222
 cache_file () (*tardis.tardis_portal.models.datafile.DataFile* method), 140
 base_fields (*tardis.tardis_portal.forms.AddUserPermissionsForm* attribute), 225
 clone_file () (*tardis.tardis_portal.models.datafile.DataFileObject* method), 143
 base_fields (*tardis.tardis_portal.forms.CreateUserPermissionsForm* attribute), 225
 CLOSERS (*in module tardis.default_settings.caches*), 118
 calculate_checksums () (*in module tardis.apps.s3utils.utils*), 102
 base_fields (*tardis.tardis_portal.forms.DatasetForm* attribute), 226
 calculate_checksums () (*tardis.tardis_portal.models.datafile.DataFileObject* method), 143
 base_fields (*tardis.tardis_portal.forms.ExperimentAuthor* attribute), 226
 CALCULATE_CHECKSUMS_METHODS (*in module tardis.default_settings.storage*), 122
 base_fields (*tardis.tardis_portal.forms.ExperimentForm* attribute), 227
 form_copy () (*in module tardis.apps.push_to.utils*), 97
 base_fields (*tardis.tardis_portal.forms.ImportParamsForm* attribute), 227
 can_publish () (*tardis.tardis_portal.publish.provider.rifcsprovider.Rifc* method), 180
 base_fields (*tardis.tardis_portal.forms.LoginForm* attribute), 227
 canDelete (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 136
 base_fields (*tardis.tardis_portal.forms.ManageAccountForm* attribute), 228
 canonicalize () (*tardis.apps.sftp.sftp.MyTSFTPServerInterface* method), 111
 base_fields (*tardis.tardis_portal.forms.ManageGroupPermissionsForm* attribute), 228
 canRead (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 136
 base_fields (*tardis.tardis_portal.forms.RegisterExperimentForm* attribute), 229
 canWrite (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 136
 base_fields (*tardis.tardis_portal.forms.RegistrationForm* attribute), 229
 capture () (*in module tardis.tardis_portal.templatetags.capture*), 181
 base_fields (*tardis.tardis_portal.forms.RightsForm* attribute), 230
 BaseProvider (*class in tardis.apps.oaipmh.provider.base*), 77, 241
 CaptureNode (*class in tardis.tardis_portal.templatetags.capture*), 181
 BaseProviderTestCase (*class in tardis.apps.oaipmh.tests.provider.test_base*), 80
 cast_string_to_integer () (*in module tardis.tardis_portal.migrations.0001_squashed_0011_auto_2016*), 132
 blank_param (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* attribute), 208
 cast_string_to_integer () (*in module tardis.tardis_portal.migrations.0005_datafile_add_size_int_column*), 132
 BLEACH_ALLOWED_ATTRIBUTES (*in module tardis.default_settings.frontend*), 120
 cert_signing_url (*tardis.apps.push_to.models.OAuthSSHCertSigning* attribute), 94
 BLEACH_ALLOWED_TAGS (*in module tardis.default_settings.frontend*), 120
 check_app_dependencies () (*in module tardis.app_config*), 237
 bleach_value () (*in module tardis.tardis_portal.templatetags.bleach_tag*), 181
 check_auth_interactive () (*tardis.apps.sftp.sftp.MyTServerInterface* method), 113
 build_template_html () (*in module tardis.tardis_portal.email*), 224
 check_auth_interactive_response () (*tardis.apps.sftp.sftp.MyTServerInterface* method), 113
 build_template_text () (*in module tardis.tardis_portal.email*), 224
 BUNDLE (*tardis.tardis_portal.models.storage.StorageBox* attribute), 173
 check_auth_password () (*tardis.apps.sftp.sftp.MyTServerInterface* method), 113
 bytes_available () (*in module tardis.apps.push_to.utils*), 97
 check_auth_publickey () (*tardis.apps.sftp.sftp.MyTServerInterface* method), 114
 check_channel_request ()

C

CACHE (*tardis.tardis_portal.models.storage.StorageBox* attribute), 173

(*tardis.apps.sftp.sftp.MyTServerInterface*
method), 114
 check_if_facility_manager() (in module
tardis.tardis_portal.templatetags.facility_tags),
 183
 check_if_user_not_approved() (in module
tardis.tardis_portal.templatetags.approved_user_tags),
 181
 check_paths() (*tardis.tardis_portal.tests.slapd.Slapd*
class method), 192
 child_boxes (*tardis.tardis_portal.models.storage.StorageBox*
attribute), 174
 CHOICES (*tardis.tardis_portal.models.access_control.UserAuthentication*
attribute), 138
 choices (*tardis.tardis_portal.models.parameters.ParameterName*
attribute), 168
 classic_mapper() (in module
tardis.tardis_portal.download), 224
 clean() (*tardis.apps.sftp.forms.KeyAddForm* *method*),
 109
 clean() (*tardis.tardis_portal.forms.RegistrationForm*
method), 229
 clean() (*tardis.tardis_portal.forms.RightsForm*
method), 230
 clean() (*tardis.tardis_portal.forms.StaticField*
method), 230
 clean_username() (*tardis.tardis_portal.forms.RegistrationForm*
method), 229
 cleanup() (*tardis.apps.filepicker.utils.FilepickerFile*
method), 77
 clear_children() (*tardis.apps.sftp.sftp.DynamicTree*
method), 110
 close() (*tardis.analytics.tracker.IteratorTracker*
method), 75
 close_gzip() (*tardis.tardis_portal.download.UncachedTarStream*
method), 224
 close_request() (*tardis.apps.sftp.sftp.MyTSFTPTCPServer*
method), 113
 CollectstaticTest (class in *tardis.tardis_portal.tests.management.test_collectstatic*),
 188
 Command (class in *tardis.apps.sftp.management.commands.sftpd*),
 106
 Command (class in *tardis.tardis_portal.management.commands.create_user*),
 129
 Command (class in *tardis.tardis_portal.management.commands.dump_schemas*),
 130
 Command (class in *tardis.tardis_portal.management.commands.load_schemas*),
 130
 Command (class in *tardis.tardis_portal.management.commands.experiment*),
 130
 CommaSeparatedInput (class in *tardis.tardis_portal.widgets*), 235
 comparison_type (*tardis.tardis_portal.models.parameters.ParameterName*
attribute), 168
 compliance_header() (in module
tardis.tardis_portal.iiif), 230
 compress() (*tardis.tardis_portal.download.UncachedTarStream*
method), 224
 compress() (*tardis.tardis_portal.fields.MultiValueCommaSeparatedField*
method), 225
 compute_checksums() (in module
tardis.tardis_portal.models.datafile), 145
 compute_etag() (in module *tardis.tardis_portal.iiif*),
 230
 compute_size() (*tardis.tardis_portal.download.UncachedTarStream*
method), 224
 configure() (*tardis.tardis_portal.tests.slapd.Slapd*
method), 192
 configure_social_auth_user() (in module
tardis.apps.social_auth.auth.social_auth), 116
 configure_user() (in module
tardis.tardis_portal.auth.utils), 129
 confirm_migration() (in module
tardis.apps.openid_migration.migration),
 86
 CONTAINS_COMPARISON
 (*tardis.tardis_portal.models.parameters.ParameterName*
attribute), 167
 content_object (*tardis.tardis_portal.models.access_control.ObjectACL*
attribute), 136
 content_type (*tardis.tardis_portal.models.access_control.ObjectACL*
attribute), 136
 content_type_id (*tardis.tardis_portal.models.access_control.ObjectACL*
attribute), 137
 ContextualViewTest (class in
tardis.tardis_portal.tests.views.test_contextual_views),
 190
 create_datafile() (*tardis.tardis_portal.models.datafile.DataFileObject*
method), 143
 copy_files() (*tardis.tardis_portal.models.storage.StorageBox*
method), 174
 copy_to_master() (*tardis.tardis_portal.models.storage.StorageBox*
method), 174
 CopyMoveTestCase (class in
tardis.tardis_portal.tests.test_copy_move),
 195
 create_user() (*tardis.tardis_portal.forms*), 230
 dump_schemas() (*tardis.apps.sftp.api.SFTPAuthorization*
method), 108
 load_schemas() (*tardis.tardis_portal.api.ACLAuthorization*
method), 214
 experiment() (in module
tardis.tardis_portal.views.pages), 206
 create_group() (in module
tardis.tardis_portal.views.authorisation),
 206

[create_list\(\)](#) (*tardis.tardis_portal.api.ACLAuthorization* credential.DoesNotExist, 91
 method), 214 [Credential.MultipleObjectsReturned](#), 91
[create_local_box\(\)](#) (*tardis.tardis_portal.models.storage.StorageBox* credential_set (*tardis.apps.push_to.models.RemoteHost*
 class method), 174 attribute), 95
[create_OpenidUserMigration\(\)](#) (*tardis.apps.openid_migration.tests.test_models.ModelTestCase* CredentialAdmin (class in
 method), 85 *tardis.apps.push_to.models*), 92
[create_parameterset_edit_form\(\)](#) (in module *tardis.tardis_portal.forms*), 230 CredentialForm (class in
tardis.apps.push_to.models), 92
[create_set_uri\(\)](#) (*tardis.tardis_portal.models.datafile.DataFileObject* CredentialForm.Meta (class in
 method), 143 *tardis.apps.push_to.models*), 92
[create_user\(\)](#) (in module *tardis.tardis_portal.auth.utils*), 129 [create_connection_window\(\)](#) (in module
tardis.apps.sftp.views), 116
[create_user\(\)](#) (in module *tardis.tardis_portal.views.authentication*), 202
[create_user_api_key\(\)](#) (in module *tardis.tardis_portal.models.access_control*), 139
[create_user_profile\(\)](#) (in module *tardis.tardis_portal.models.access_control*), 139
[created_by](#) (*tardis.tardis_portal.models.experiment.Experiment* attribute), 148
[created_by_id](#) (*tardis.tardis_portal.models.experiment.Experiment* attribute), 148
[created_time](#) (*tardis.tardis_portal.models.datafile.DataFile* attribute), 140
[created_time](#) (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 158
[created_time](#) (*tardis.tardis_portal.models.dataset.Dataset* attribute), 171
[created_time](#) (*tardis.tardis_portal.models.experiment.Experiment* attribute), 149
[created_time](#) (*tardis.tardis_portal.models.experiment.Experiment* attribute), 149
[created_time](#) (*tardis.tardis_portal.models.facility.Facility* attribute), 153
[created_time](#) (*tardis.tardis_portal.models.instrument.Instrument* attribute), 154
[created_time](#) (*tardis.tardis_portal.models.jti.JTI* attribute), 155
[createLinkedUserAuthenticationForm\(\)](#) (in module *tardis.tardis_portal.forms*), 230
[CreateTestCase](#) (class in *tardis.apps.related_info.tests.tests*), 98
[CreateUserPermissionsForm](#) (class in *tardis.tardis_portal.forms*), 225
[CreateUserTestCase](#) (class in *tardis.tardis_portal.tests.management.test_createuser*), 188
[CreativeCommonsHandler](#) (class in *tardis.tardis_portal.creativecommonshandler*), 223
[Credential](#) (class in *tardis.apps.push_to.models*), 91

D

[data_type](#) (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168
[DATABASE_ENGINE](#) (*tardis.default_settings* attribute), 45
[DATABASE_HOST](#) (*tardis.default_settings* attribute), 45
[DATABASE_NAME](#) (*tardis.default_settings* attribute), 45
[DATABASE_PASSWORD](#) (*tardis.default_settings* attribute), 45
[DATABASE_PORT](#) (*tardis.default_settings* attribute), 45
[DATABASE_USER](#) (*tardis.default_settings* attribute), 45
[DataFile](#) (class in *tardis.tardis_portal.models.datafile*), 140
[datafile](#) (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 143
[datafile](#) (*tardis.tardis_portal.models.parameters.DatafileParameterSet* attribute), 158
[DATAFILE](#) (*tardis.tardis_portal.models.parameters.Schema* attribute), 171
[DataFile.DoesNotExist](#), 140
[DataFile.MultipleObjectsReturned](#), 140
[datafile_access_required\(\)](#) (in module *tardis.tardis_portal.auth.decorators*), 125
[datafile_id](#) (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 144
[datafile_id](#) (*tardis.tardis_portal.models.parameters.DatafileParameterSet* attribute), 158
[datafile_set](#) (*tardis.tardis_portal.models.dataset.Dataset* attribute), 146
[DatafileAdmin](#) (class in *tardis.tardis_portal.admin*), 209
[DatafileAdminForm](#) (class in *tardis.tardis_portal.admin*), 209
[DatafileAdminForm.Meta](#) (class in *tardis.tardis_portal.admin*), 210
[DataFileDocument](#) (class in *tardis.apps.search.documents*), 105
[DataFileDocument.Django](#) (class in *tardis.apps.search.documents*), 105
[DataFileDocument.Index](#) (class in *tardis.apps.search.documents*), 105

DataFileObject	(class in <i>tardis.tardis_portal.models.datafile</i>), 143	DataFileResource.Meta	(class in <i>tardis.tardis_portal.api</i>), 214
DataFileObject.DoesNotExist	, 143	DataFileResourceTest	(class in <i>tardis.tardis_portal.tests.api.test_datafile_resource</i>), 184
DataFileObject.MultipleObjectsReturned	, 143	Dataset	(class in <i>tardis.tardis_portal.models.dataset</i>), 145
DataFileObjectInline	(class in <i>tardis.tardis_portal.admin</i>), 209	dataset	(<i>tardis.tardis_portal.models.datafile.DataFile</i> attribute), 140
DataFileObjectInlineForm	(class in <i>tardis.tardis_portal.admin</i>), 209	dataset	(<i>tardis.tardis_portal.models.parameters.DatasetParameterSet</i> attribute), 160
DataFileObjectInlineForm.Meta	(class in <i>tardis.tardis_portal.admin</i>), 209	DATASET	(<i>tardis.tardis_portal.models.parameters.Schema</i> attribute), 171
DatafileParameter	(class in <i>tardis.tardis_portal.models.parameters</i>), 157	Dataset.DoesNotExist	, 146
DatafileParameter.DoesNotExist	, 157	Dataset.MultipleObjectsReturned	, 146
DatafileParameter.MultipleObjectsReturned	, 157	dataset_access_required()	(in module <i>tardis.tardis_portal.auth.decorators</i>), 125
datafileparameter_set	(<i>tardis.tardis_portal.models.parameters.DatafileParameterSet</i> attribute), 158	dataset_aggregate_info()	(in module <i>tardis.tardis_portal.views.facilities</i>), 203
datafileparameter_set	(<i>tardis.tardis_portal.models.parameters.ParameterName</i> attribute), 168	dataset_datafiles_badge()	(in module <i>tardis.tardis_portal.templatetags.dataset_tags</i>), 182
DatafileParameterResource	(class in <i>tardis.tardis_portal.api</i>), 215	dataset_download_required()	(in module <i>tardis.tardis_portal.auth.decorators</i>), 125
DatafileParameterResource.Meta	(class in <i>tardis.tardis_portal.api</i>), 215	dataset_experiments_badge()	(in module <i>tardis.tardis_portal.templatetags.dataset_tags</i>), 182
DatafileParameterResourceTest	(class in <i>tardis.tardis_portal.tests.api.test_datafile_metadata_resource</i>), 184	dataset_id	(<i>tardis.tardis_portal.models.datafile.DataFile</i> attribute), 141
DatafileParameterSet	(class in <i>tardis.tardis_portal.models.parameters</i>), 158	dataset_id	(<i>tardis.tardis_portal.models.parameters.DatasetParameterSet</i> attribute), 160
DatafileParameterSet.DoesNotExist	, 158	dataset_set	(<i>tardis.tardis_portal.models.instrument.Instrument</i> attribute), 154
DatafileParameterSet.MultipleObjectsReturned	, 158	dataset_size_badge()	(in module <i>tardis.tardis_portal.templatetags.dataset_tags</i>), 182
datafileparameterset_set	(<i>tardis.tardis_portal.models.datafile.DataFile</i> attribute), 140	dataset_tiles()	(in module <i>tardis.tardis_portal.templatetags.dataset_tags</i>), 182
datafileparameterset_set	(<i>tardis.tardis_portal.models.parameters.Schema</i> attribute), 171	DATASET_VIEWS	(in module <i>tardis.default_settings.custom_views</i>), 118
DatafileParameterSetResource	(class in <i>tardis.tardis_portal.api</i>), 215	dataset_write_permissions_required()	(in module <i>tardis.tardis_portal.auth.decorators</i>), 125
DatafileParameterSetResource.Meta	(class in <i>tardis.tardis_portal.api</i>), 215	DatasetAdmin	(class in <i>tardis.tardis_portal.admin</i>), 210
DatafileParameterSetResourceTest	(class in <i>tardis.tardis_portal.tests.api.test_datafile_metadata_resource</i>), 184	DatasetDocument	(class in <i>tardis.apps.search.documents</i>), 105
datafileparametersets	(<i>tardis.tardis_portal.models.storage.StorageBox</i> attribute), 174	DatasetDocument.Django	(class in <i>tardis.apps.search.documents</i>), 105
DataFileResource	(class in <i>tardis.tardis_portal.api</i>), 214	DatasetDocument.Index	(class in <i>tardis.apps.search.documents</i>), 105
		DatasetForm	(class in <i>tardis.tardis_portal.forms</i>), 226
		DatasetForm.Meta	(class in <i>tardis.tardis_portal.forms</i>), 226

tardis.tardis_portal.forms), 226

DatasetParameter (class in *tardis.tardis_portal.models.parameters*), 159

DatasetParameter.DoesNotExist, 159

*DatasetParameter.MultipleObjectsReturned*DBHostKeyPolicy (class in *tardis.apps.push_to.models*), 92

datasetparameter_set (*tardis.tardis_portal.models.parameters.DatasetParameterSet* attribute), 160

datasetparameter_set (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168

DatasetParameterResource (class in *tardis.tardis_portal.api*), 215

DatasetParameterResource.Meta (class in *tardis.tardis_portal.api*), 215

DatasetParameterResourceTest (class in *tardis.tardis_portal.tests.api.test_dataset_metadata_resources*), 185

DatasetParameterSet (class in *tardis.tardis_portal.models.parameters*), 160

DatasetParameterSet.DoesNotExist, 160

DatasetParameterSet.MultipleObjectsReturned, 160

datasetparameterset_set (*tardis.tardis_portal.models.dataset.Dataset* attribute), 146

datasetparameterset_set (*tardis.tardis_portal.models.parameters.Schema* attribute), 172

DatasetParameterSetResource (class in *tardis.tardis_portal.api*), 215

DatasetParameterSetResource.Meta (class in *tardis.tardis_portal.api*), 215

DatasetParameterSetResourceTest (class in *tardis.tardis_portal.tests.api.test_dataset_metadata_resources*), 185

datasetparametersets (*tardis.tardis_portal.models.storage.StorageBox* attribute), 174

DatasetResource (class in *tardis.tardis_portal.api*), 216

DatasetResource.Meta (class in *tardis.tardis_portal.api*), 216

DatasetResourceTest (class in *tardis.tardis_portal.tests.api.test_dataset_resource*), 185

datasets (*tardis.tardis_portal.models.experiment.Experiment* attribute), 149

DatasetView (class in *tardis.tardis_portal.views.pages*), 204

DATETIME (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 167

datetime_to_us() (in module *tardis.tardis_portal.views.facilities*), 203

datetime_value (*tardis.tardis_portal.models.parameters.Parameter* attribute), 166

DcExperimentProvider (class in *tardis.apps.oaipmh.provider.experiment*), 79

DcExperimentProviderTestCase (class in *tardis.apps.oaipmh.tests.provider.test_experiment*), 81

DEBUG (in module *tardis.default_settings.debug*), 119

declared_fields (*tardis.apps.push_to.models.CredentialForm* attribute), 92

declared_fields (*tardis.apps.related_info.forms.RelatedInfoForm* attribute), 100

declared_fields (*tardis.apps.s3utils.api.ReplicaAppResource* attribute), 101

declared_fields (*tardis.apps.search.api.AdvanceSearchAppResource* attribute), 104

declared_fields (*tardis.apps.search.api.SearchAppResource* attribute), 104

declared_fields (*tardis.apps.sftp.api.SFTPPublicKeyAppResource* attribute), 108

declared_fields (*tardis.apps.sftp.forms.KeyAddForm* attribute), 109

declared_fields (*tardis.apps.sftp.forms.KeyGenerateForm* attribute), 109

declared_fields (*tardis.tardis_portal.admin.DatafileAdminForm* attribute), 210

declared_fields (*tardis.tardis_portal.admin.DataFileObjectInlineForm* attribute), 209

declared_fields (*tardis.tardis_portal.admin.StorageBoxAttributeInlineForm* attribute), 212

declared_fields (*tardis.tardis_portal.admin.StorageBoxForm* attribute), 213

declared_fields (*tardis.tardis_portal.admin.StorageBoxOptionInlineForm* attribute), 214

declared_fields (*tardis.tardis_portal.api.DatafileParameterResource* attribute), 215

declared_fields (*tardis.tardis_portal.api.DatafileParameterSetResource* attribute), 215

declared_fields (*tardis.tardis_portal.api.DataFileResource* attribute), 214

declared_fields (*tardis.tardis_portal.api.DatasetParameterResource* attribute), 215

declared_fields (*tardis.tardis_portal.api.DatasetParameterSetResource* attribute), 216

declared_fields (*tardis.tardis_portal.api.DatasetResource* attribute), 216

declared_fields (*tardis.tardis_portal.api.ExperimentAuthorResource* attribute), 216

[declared_fields \(tardis.tardis_portal.api.ExperimentResource attribute\), 217](#)
[declared_fields \(tardis.tardis_portal.api.ExperimentResource attribute\), 217](#)
[declared_fields \(tardis.tardis_portal.api.ExperimentResource attribute\), 217](#)
[declared_fields \(tardis.tardis_portal.api.FacilityResource attribute\), 218](#)
[declared_fields \(tardis.tardis_portal.api.GroupResource attribute\), 218](#)
[declared_fields \(tardis.tardis_portal.api.InstrumentResource attribute\), 218](#)
[declared_fields \(tardis.tardis_portal.api.LocationResource attribute\), 218](#)
[declared_fields \(tardis.tardis_portal.api.MyTardisModelResource attribute\), 219](#)
[declared_fields \(tardis.tardis_portal.api.ObjectACLResource attribute\), 219](#)
[declared_fields \(tardis.tardis_portal.api.ParameterNameResource attribute\), 220](#)
[declared_fields \(tardis.tardis_portal.api.ParameterResource attribute\), 220](#)
[declared_fields \(tardis.tardis_portal.api.ParameterSetResource attribute\), 220](#)
[declared_fields \(tardis.tardis_portal.api.ReplicaResource attribute\), 220](#)
[declared_fields \(tardis.tardis_portal.api.SchemaResource attribute\), 221](#)
[declared_fields \(tardis.tardis_portal.api.StorageBoxAttributeResource attribute\), 221](#)
[declared_fields \(tardis.tardis_portal.api.StorageBoxOptionResource attribute\), 221](#)
[declared_fields \(tardis.tardis_portal.api.StorageBoxResource attribute\), 221](#)
[declared_fields \(tardis.tardis_portal.api.UserResource attribute\), 222](#)
[declared_fields \(tardis.tardis_portal.forms.AddUserPermissionsForm attribute\), 225](#)
[declared_fields \(tardis.tardis_portal.forms.CreateUserPermissionsForm attribute\), 226](#)
[declared_fields \(tardis.tardis_portal.forms.DatasetForm attribute\), 226](#)
[declared_fields \(tardis.tardis_portal.forms.ExperimentAuthorForm attribute\), 226](#)
[declared_fields \(tardis.tardis_portal.forms.ExperimentForm attribute\), 227](#)
[declared_fields \(tardis.tardis_portal.forms.ImportParametersForm attribute\), 227](#)
[declared_fields \(tardis.tardis_portal.forms.LoginForm attribute\), 227](#)
[declared_fields \(tardis.tardis_portal.forms.ManageAccountForm attribute\), 228](#)
[declared_fields \(tardis.tardis_portal.forms.ManageGroupPermissionsForm attribute\), 228](#)
[declared_fields \(tardis.tardis_portal.forms.RegisterExperimentForm attribute\), 229](#)
[declared_fields \(tardis.tardis_portal.forms.RegistrationForm attribute\), 229](#)
[declared_fields \(tardis.tardis_portal.forms.RightsForm attribute\), 230](#)
[deep_storage_mapper \(\) \(in module tardis.apps.deep_storage_download_mapper.mapper\), 76](#)
[DEFAULT_ARCHIVE_FORMATS \(in module tardis.default_settings.downloads\), 119](#)
[DEFAULT_FROM_EMAIL \(in module tardis.default_settings.email\), 120](#)
[DEFAULT_STORAGE_BASE_DIR \(in module tardis.default_settings\), 46](#)
[dehydrate \(\) \(tardis.apps.sftp.api.SFTPPublicKeyAppResource method\), 108](#)
[dehydrate \(\) \(tardis.tardis_portal.api.ExperimentResource method\), 217](#)
[dehydrate \(\) \(tardis.tardis_portal.api.ReplicaResource method\), 220](#)
[dehydrate \(\) \(tardis.tardis_portal.api.UserResource method\), 222](#)
[delete_all_params \(\) \(tardis.tardis_portal.ParameterSetManager.ParameterSetManager method\), 208](#)
[delete_data \(\) \(tardis.tardis_portal.models.datafile.DataFileObject method\), 144](#)
[delete \(\) \(tardis.apps.sftp.api.SFTPAuthorization method\), 108](#)
[detail \(\) \(tardis.tardis_portal.api.ACLAuthorization method\), 214](#)
[dfo \(\) \(in module tardis.tardis_portal.models.datafile\), 145](#)
[delete_directory_content \(\) \(in module tardis.tardis_portal.tests.slapped\), 193](#)
[permissions_required \(\) \(tardis.tardis_portal.api.ACLAuthorization method\), 214](#)
[permissions_required \(\) \(tardis.tardis_portal.ParameterSetManager.ParameterSetManager method\), 208](#)
[permissions_required \(\) \(in module tardis.tardis_portal.auth.decorators\), 125](#)
[DataFile \(tardis.tardis_portal.models.datafile.DataFile attribute\), 141](#)
[DataFile \(tardis.tardis_portal.models.datafile.DataFile attribute\), 141](#)
[TestCase \(class in tardis.apps.related_info.tests.tests\), 99](#)
[dependencies \(tardis.apps.openid_migration.migrations.0001_initial.Migration attribute\), 84](#)
[dependencies \(tardis.apps.push_to.migrations.0001_initial.Migration attribute\), 90](#)
[dependencies \(tardis.apps.push_to.migrations.0002_auto_20160518_14.Migration attribute\), 90](#)

DynamicTree (class in *tardis.apps.sftp.sftp*), 110
 dynurl() (in module *tardis.tardis_portal.templatetags.dynurl*), 182

DynUrlNode (class in module *tardis.tardis_portal.templatetags.dynurl*), 182

E

edit_auth_method() (in module *tardis.tardis_portal.auth.authentication*), 123

edit_datafile_par() (in module *tardis.tardis_portal.views.parameters*), 207

edit_dataset() (in module *tardis.tardis_portal.views.pages*), 206

edit_dataset_par() (in module *tardis.tardis_portal.views.parameters*), 207

edit_experiment_par() (in module *tardis.tardis_portal.views.parameters*), 207

edit_parameters() (in module *tardis.tardis_portal.views.parameters*), 207

EditParameterSetTestCase (class in module *tardis.tardis_portal.tests.test_parametersets*), 198

effectiveDate (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 137

email (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 152

EMAIL_HOST (in module *tardis.default_settings.email*), 120

EMAIL_HOST_PASSWORD (in module *tardis.default_settings.email*), 120

EMAIL_HOST_USER (in module *tardis.default_settings.email*), 120

email_migration_success() (in module *tardis.apps.openid_migration.email_text*), 86

EMAIL_PORT (in module *tardis.default_settings.email*), 120

EMAIL_USE_TLS (in module *tardis.default_settings.email*), 120

email_user() (in module *tardis.tardis_portal.email*), 224

end_time (*tardis.tardis_portal.models.experiment.Experiment* attribute), 149

endpoint() (in module *tardis.apps.oaipmh.views*), 84

EndpointTestCase (class in module *tardis.apps.oaipmh.tests.test_oai*), 81

entityId (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 137

error_handler() (in module *tardis.views*), 238

EXACT_VALUE_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName*

attribute), 167

Experiment (class in module *tardis.tardis_portal.models.experiment*), 147

experiment (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 152

experiment (*tardis.tardis_portal.models.parameters.ExperimentParameter* attribute), 162

EXPERIMENT (*tardis.tardis_portal.models.parameters.Schema* attribute), 171

experiment (*tardis.tardis_portal.models.token.Token* attribute), 178

Experiment.DoesNotExist, 148

Experiment.MultipleObjectsReturned, 148

experiment_access_required() (in module *tardis.tardis_portal.auth.decorators*), 125

experiment_authors() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_badges() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_browse_item() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_datafiles_badge() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_datasets_badge() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_download_link() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_download_required() (in module *tardis.tardis_portal.auth.decorators*), 125

experiment_file_count() (in module *tardis.tardis_portal.templatetags.experimentstats*), 183

experiment_id (*tardis.tardis_portal.creativecommonshandler.CreativeCommons* attribute), 223

experiment_id (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 152

experiment_id (*tardis.tardis_portal.models.parameters.ExperimentParameter* attribute), 162

experiment_id (*tardis.tardis_portal.models.token.Token* attribute), 179

experiment_last_updated_badge() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

experiment_ownership_required() (in module *tardis.tardis_portal.auth.decorators*), 125

experiment_public_access_badge() (in module *tardis.tardis_portal.templatetags.experiment_tags*), 182

182

`experiment_public_access_badge()` (in module `tardis.tardis_portal.views.ajax_pages`), 202

`experiment_set` (`tardis.tardis_portal.models.license.License` attribute), 156

`experiment_size_badge()` (in module `tardis.tardis_portal.templatetags.experiment_tags`), 182

`EXPERIMENT_VIEWS` (in module `tardis.default_settings.custom_views`), 118

`ExperimentAdmin` (class in `tardis.tardis_portal.admin`), 210

`ExperimentAuthor` (class in `tardis.tardis_portal.forms`), 226

`ExperimentAuthor` (class in `tardis.tardis_portal.models.experiment`), 151

`ExperimentAuthor.DoesNotExist`, 151

`ExperimentAuthor.Meta` (class in `tardis.tardis_portal.forms`), 226

`ExperimentAuthor.MultipleObjectsReturned`, 152

`experimentauthor_set` (`tardis.tardis_portal.models.experiment.Experiment` attribute), 149

`ExperimentAuthorResource` (class in `tardis.tardis_portal.api`), 216

`ExperimentAuthorResource.Meta` (class in `tardis.tardis_portal.api`), 216

`ExperimentDocument` (class in `tardis.apps.search.documents`), 105

`ExperimentDocument.Django` (class in `tardis.apps.search.documents`), 105

`ExperimentDocument.Index` (class in `tardis.apps.search.documents`), 106

`ExperimentForm` (class in `tardis.tardis_portal.forms`), 226

`ExperimentForm.FullExperiment` (class in `tardis.tardis_portal.forms`), 227

`ExperimentForm.Meta` (class in `tardis.tardis_portal.forms`), 227

`ExperimentListsTest` (class in `tardis.tardis_portal.tests.views.test_template_contexts`), 191

`ExperimentManager` (class in `tardis.tardis_portal.managers`), 231

`ExperimentParameter` (class in `tardis.tardis_portal.models.parameters`), 161

`ExperimentParameter.DoesNotExist`, 161

`ExperimentParameter.MultipleObjectsReturned`, 161

`experimentparameter_set` (`tardis.tardis_portal.models.parameters.ExperimentParameter` attribute), 162

`experimentparameter_set` (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 168

`ExperimentParameterInline` (class in `tardis.tardis_portal.admin`), 210

`ExperimentParameterResource` (class in `tardis.tardis_portal.api`), 216

`ExperimentParameterResource.Meta` (class in `tardis.tardis_portal.api`), 216

`ExperimentParameterResourceTest` (class in `tardis.tardis_portal.tests.api.test_experiment_metadata_resources`), 185

`ExperimentParameterSet` (class in `tardis.tardis_portal.models.parameters`), 162

`ExperimentParameterSet.DoesNotExist`, 162

`ExperimentParameterSet.MultipleObjectsReturned`, 162

`experimentparameterset_set` (`tardis.tardis_portal.models.experiment.Experiment` attribute), 149

`experimentparameterset_set` (`tardis.tardis_portal.models.parameters.Schema` attribute), 172

`ExperimentParameterSetAdmin` (class in `tardis.tardis_portal.admin`), 210

`ExperimentParameterSetResource` (class in `tardis.tardis_portal.api`), 217

`ExperimentParameterSetResource.Meta` (class in `tardis.tardis_portal.api`), 217

`ExperimentParameterSetResourceTest` (class in `tardis.tardis_portal.tests.api.test_experiment_metadata_resources`), 185

`experimentparametersets` (`tardis.tardis_portal.models.storage.StorageBox` attribute), 175

`ExperimentResource` (class in `tardis.tardis_portal.api`), 217

`ExperimentResource.Meta` (class in `tardis.tardis_portal.api`), 217

`ExperimentResourceTest` (class in `tardis.tardis_portal.tests.api.test_experiment_resource`), 186

`experiments` (`tardis.apps.sftp.sftp.MyTSFTPServerInterface` attribute), 111

`experiments` (`tardis.tardis_portal.models.dataset.Dataset` attribute), 146

`ExperimentTestCase` (class in `tardis.tardis_portal.tests.views.test_experiment_views`), 190

`ExperimentView` (class in `tardis.tardis_portal.views.pages`), 205

`experimenttoken_set` (`tardis.tardis_portal.models.token.Token` attribute), 162

attribute), 179
 expiryDate (tardis.tardis_portal.models.access_control.ObjectACLResource (class in
 attribute), 137 tardis.tardis_portal.api), 217
 ext_groups (tardis.tardis_portal.models.access_control.UserProfileResource.Meta (class in
 attribute), 139 tardis.tardis_portal.api), 217
 external_users() (tardis.tardis_portal.managers.ExperimentManagerResourceTest (class in
 method), 231 tardis.tardis_portal.tests.api.test_facility_resource),
 extra (tardis.tardis_portal.admin.DataFileObjectInline 186
 attribute), 209 feedback() (in module
 extra (tardis.tardis_portal.admin.ExperimentParameterInline tardis.tardis_portal.views.utils), 208
 attribute), 210 fields (tardis.apps.push_to.models.CredentialForm.Meta
 extra (tardis.tardis_portal.admin.InstrumentParameterInline attribute), 92
 attribute), 211 fields (tardis.apps.push_to.models.RemoteHostAdmin
 extra (tardis.tardis_portal.admin.ObjectACLInline attribute), 96
 attribute), 211 fields (tardis.tardis_portal.admin.DatafileAdminForm.Meta
 extra (tardis.tardis_portal.admin.ParameterNameInline attribute), 210
 attribute), 211 fields (tardis.tardis_portal.admin.DataFileObjectInlineForm.Meta
 extra (tardis.tardis_portal.admin.StorageBoxAttributeInline attribute), 209
 attribute), 212 fields (tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta
 extra (tardis.tardis_portal.admin.StorageBoxOptionInline attribute), 212
 attribute), 213 fields (tardis.tardis_portal.admin.StorageBoxForm.Meta
 ExtraTestCases (class in attribute), 213
 tardis.tardis_portal.tests.test_iif), 196 fields (tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta
 attribute), 213
 fields (tardis.tardis_portal.api.UserResource.Meta attribute), 222
 fields (tardis.tardis_portal.forms.DatasetForm.Meta attribute), 226
 fields (tardis.tardis_portal.forms.ExperimentAuthor.Meta attribute), 226
 fields (tardis.tardis_portal.forms.ExperimentForm.Meta attribute), 227
 fields (tardis.tardis_portal.forms.ManageAccountForm.Meta attribute), 228
 fields (tardis.tardis_portal.forms.RightsForm.Meta attribute), 230
 file_object (tardis.tardis_portal.models.datafile.DataFile attribute), 141
 file_object (tardis.tardis_portal.models.datafile.DataFileObject attribute), 144
 file_objects (tardis.tardis_portal.models.datafile.DataFile attribute), 141
 file_objects (tardis.tardis_portal.models.storage.StorageBox attribute), 175
 filename (tardis.tardis_portal.models.datafile.DataFile attribute), 141
 FILENAME (tardis.tardis_portal.models.parameters.ParameterName attribute), 167
 filepicker_url_regex (tardis.apps.filepicker.utils.FilepickerFile attribute), 77
 FilepickerFile (class in tardis.apps.filepicker.utils, 77
 filtering (tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta

F
 facilities_managed_by() (in module
 tardis.tardis_portal.models.facility), 153
 Facility (class in tardis.tardis_portal.models.facility),
 152
 facility (tardis.tardis_portal.models.instrument.Instrument
 attribute), 154
 Facility.DoesNotExist, 153
 Facility.MultipleObjectsReturned, 153
 facility_id (tardis.tardis_portal.models.instrument.Instrument
 attribute), 154
 facility_overview() (in module
 tardis.tardis_portal.views.pages), 206
 facility_overview_data_count() (in module
 tardis.tardis_portal.views.facilities), 203
 facility_overview_datafile_list() (in
 module tardis.tardis_portal.views.facilities),
 203
 facility_overview_dataset_detail() (in
 module tardis.tardis_portal.views.facilities),
 203
 facility_overview_experiments() (in mod-
 ule tardis.tardis_portal.views.facilities), 203
 facility_overview_facilities_list() (in
 module tardis.tardis_portal.views.facilities),
 203
 FacilityAdmin (class in tardis.tardis_portal.admin),
 210
 FacilityOverviewTestCase (class in
 tardis.tardis_portal.tests.test_facility_overview),

[attribute](#)), 108
[filtering \(tardis.tardis_portal.api.DataFileResource.Metaattribute\)](#), 214
[filtering \(tardis.tardis_portal.api.DatasetResource.Metaattribute\)](#), 216
[filtering \(tardis.tardis_portal.api.ExperimentAuthorResource.Metaattribute\)](#), 216
[filtering \(tardis.tardis_portal.api.ExperimentResource.Metaattribute\)](#), 217
[filtering \(tardis.tardis_portal.api.FacilityResource.Metaattribute\)](#), 217
[filtering \(tardis.tardis_portal.api.GroupResource.Metaattribute\)](#), 218
[filtering \(tardis.tardis_portal.api.InstrumentResource.Metaattribute\)](#), 218
[filtering \(tardis.tardis_portal.api.ObjectACLResource.Metaattribute\)](#), 219
[filtering \(tardis.tardis_portal.api.ParameterNameResource.Metaattribute\)](#), 219
[filtering \(tardis.tardis_portal.api.ReplicaResource.Metaattribute\)](#), 220
[filtering \(tardis.tardis_portal.api.SchemaResource.Metaattribute\)](#), 220
[filtering \(tardis.tardis_portal.api.UserResource.Metaattribute\)](#), 222
[FILTERS_TASK_PRIORITY \(in module tardis.default_settings.filters\)](#), 120
[find_available_tcp_port\(\) \(in module tardis.tardis_portal.tests.slapped\)](#), 193
[find_custom_view_override\(\) \(tardis.tardis_portal.views.pages.DatasetView method\)](#), 204
[find_custom_view_override\(\) \(tardis.tardis_portal.views.pages.ExperimentView method\)](#), 205
[form \(tardis.apps.push_to.models.CredentialAdmin attribute\)](#), 92
[form \(tardis.tardis_portal.admin.DatafileAdmin attribute\)](#), 209
[form \(tardis.tardis_portal.admin.DataFileObjectInline attribute\)](#), 209
[form \(tardis.tardis_portal.admin.StorageBoxAdmin attribute\)](#), 212
[form \(tardis.tardis_portal.admin.StorageBoxAttributeInline attribute\)](#), 212
[form \(tardis.tardis_portal.admin.StorageBoxOptionInline attribute\)](#), 213
[format_app_name_for_url\(\) \(in module tardis.app_config\)](#), 237
[formfield_overrides \(tardis.tardis_portal.admin.ExperimentParameterInline attribute\)](#), 210
[forwards_func\(\) \(in module tardis.tardis_portal.migrations.0017_add_cc_licenses\)](#), 134
[FreeTextField \(class in tardis.tardis_portal.models.parameters\)](#), 163
[FreeTextField.DoesNotExist](#), 163
[FreeTextField.MultipleObjectsReturned](#), 163
[FreeTextsearchfield_set \(tardis.tardis_portal.models.parameters.ParameterName attribute\)](#), 169
[FreeTextFieldAdmin \(class in tardis.tardis_portal.admin\)](#), 211
[freeze_time\(\) \(tardis.tardis_portal.tests.test_tokens.FrozenTime class method\)](#), 201
[FrozenTime \(class in tardis.tardis_portal.tests.test_tokens\)](#), 201
[full_name \(tardis.tardis_portal.models.parameters.ParameterName attribute\)](#), 169

G

[generate_keypair_credential\(\) \(tardis.apps.push_to.models.Credential static method\)](#), 91
[generate_presigned_url\(\) \(in module tardis.apps.s3utils.utils\)](#), 102
[get\(\) \(tardis.tardis_portal.managers.ExperimentManager method\)](#), 231
[get\(\) \(tardis.tardis_portal.models.parameters.Parameter method\)](#), 166
[get\(\) \(tardis.tardis_portal.views.pages.DatasetView method\)](#), 204
[get\(\) \(tardis.tardis_portal.views.pages.ExperimentView method\)](#), 205
[get\(\) \(tardis.tardis_portal.views.pages.IndexView method\)](#), 205
[get_absolute_filepath\(\) \(tardis.tardis_portal.models.datafile.DataFile method\)](#), 141
[get_absolute_url\(\) \(tardis.tardis_portal.models.dataset.Dataset method\)](#), 146
[get_absolute_url\(\) \(tardis.tardis_portal.models.experiment.Experiment method\)](#), 149
[get_accessible_datafiles_for_user\(\) \(in module tardis.tardis_portal.auth.decorators\)](#), 125
[get_accessible_experiments\(\) \(in module tardis.tardis_portal.auth.decorators\)](#), 125
[get_accessible_experiments_for_dataset\(\) \(in module tardis.tardis_portal.auth.decorators\)](#), 125
[get_accessible_hosts\(\) \(in module tardis.apps.push_to.views\)](#), 97

[get_aclOwnershipType_display\(\)](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) method), 137
[get_address\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapd](#) method), 192
[get_admin_credentials\(\)](#) ([tardis.tardis_portal.tests.api.MyTardisResourceTestCase](#) method), 188
[get_all_storage_boxes_used\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 147
[get_all_tardis_apps\(\)](#) (in module [tardis.test_settings](#)), 238
[get_allowed_auths\(\)](#) ([tardis.apps.sftp.sftp.MyTServerInterface](#) method), 115
[get_api_key\(\)](#) (in module [tardis.apps.openid_migration.migration](#)), 86
[get_apikey_credentials\(\)](#) ([tardis.tardis_portal.tests.api.MyTardisResourceTestCase](#) method), 188
[get_as_temporary_file\(\)](#) ([tardis.tardis_portal.models.datafile.DataFile](#) method), 141
[get_auth_method\(\)](#) (in module [tardis.apps.social_auth.auth.social_auth](#)), 116
[get_available_signing_services\(\)](#) ([tardis.apps.push_to.models.OAuthSSHCertSigningService](#) static method), 94
[get_beamline\(\)](#) ([tardis.tardis_portal.tests.test_publishservice.MockRiftCsProvider](#) method), 199
[get_by_natural_key\(\)](#) ([tardis.tardis_portal.managers.ParameterNameManager](#) method), 233
[get_by_natural_key\(\)](#) ([tardis.tardis_portal.managers.SchemaManager](#) method), 233
[get_client_for_host\(\)](#) ([tardis.apps.push_to.models.Credential](#) method), 91
[get_client_ip\(\)](#) (in module [tardis.tardis_portal.logging_middleware](#)), 231
[get_comparison_type_display\(\)](#) ([tardis.tardis_portal.models.parameters.ParameterName](#) method), 169
[get_context\(\)](#) ([tardis.tardis_portal.publish.publishservice.PublishService](#) method), 180
[get_context_data\(\)](#) ([tardis.tardis_portal.views.pages.DatasetView](#) method), 204
[get_context_data\(\)](#) ([tardis.tardis_portal.views.pages.ExperimentView](#) method), 205
[get_context_data\(\)](#) ([tardis.tardis_portal.views.pages.IndexView](#) method), 206
[get_create_token_url\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 149
[get_credential\(\)](#) (in module [tardis.apps.push_to.views](#)), 97
[get_credentials\(\)](#) ([tardis.tardis_portal.tests.api.MyTardisResourceTestCase](#) method), 188
[get_ct\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 150
[get_data_type_display\(\)](#) ([tardis.tardis_portal.models.parameters.ParameterName](#) method), 169
[get_datafiles\(\)](#) ([tardis.tardis_portal.api.DatasetResource](#) method), 216
[get_datafiles\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 147
[get_datafiles\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 150
[get_dataset_info\(\)](#) (in module [tardis.tardis_portal.views.utils](#)), 208
[get_default_push_location\(\)](#) (in module [tardis.apps.push_to.utils](#)), 97
[get_default_storage\(\)](#) ([tardis.tardis_portal.models.storage.StorageBox](#) class method), 175
[get_experiment_box\(\)](#) ([tardis.tardis_portal.models.datafile.DataFile](#) method), 141
[get_experiment_suffix\(\)](#) ([tardis.tardis_portal.tests.slapped.Slapd](#) method), 192
[get_download_organizations\(\)](#) (in module [tardis.tardis_portal.download](#)), 224
[get_download_url\(\)](#) ([tardis.tardis_portal.models.datafile.DataFile](#) method), 141
[get_download_urls\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 147
[get_download_urls\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 150
[get_edit_url\(\)](#) ([tardis.tardis_portal.models.dataset.Dataset](#) method), 147
[get_edit_url\(\)](#) ([tardis.tardis_portal.models.experiment.Experiment](#) method), 150
[get_effective_query\(\)](#) ([tardis.tardis_portal.models.access_control.ObjectACL](#) class method), 137

```

get_experiment_referer() (in module tardis.tardis_portal.templatetags.approved_user_tags),
    tardis.tardis_portal.shortcuts), 234 181
get_file() (tardis.apps.filepicker.utils.FilepickerFile get_mimetype() (tardis.tardis_portal.models.datafile.DataFile
    method), 77 method), 142
get_file() (tardis.tardis_portal.models.datafile.DataFile get_next_by_added()
    method), 141 (tardis.apps.sftp.models.SFTPPublicKey
    method), 110
get_filesystem_safe_dataset_name() (in method), 110
    module tardis.tardis_portal.util), 234 get_next_by_created_time()
    (tardis.tardis_portal.models.datafile.DataFileObject
    method), 144
get_filesystem_safe_experiment_name() (in module tardis.tardis_portal.util), 234
get_first_experiment() get_next_by_created_time()
    (tardis.tardis_portal.models.dataset.Dataset (tardis.tardis_portal.models.experiment.Experiment
    method), 147 method), 150
get_full_path() (tardis.tardis_portal.models.datafile.DataFileObject get_next_by_created_time()
    method), 144 (tardis.tardis_portal.models.jti.JTI method),
    155
get_git_version() (in module get_next_by_expiry_date()
    tardis.default_settings), 122 (tardis.tardis_portal.models.token.Token
    method), 179
get_groups() (tardis.tardis_portal.models.experiment.Experiment
    method), 150
get_id() (tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider
    static method), 79 get_registration_timestamp()
    (tardis.apps.openid_migration.models.OpenidUserMigration
    method), 88
get_identifier() (tardis.tardis_portal.api.MyTardisAuthentication
    method), 219 get_next_by_update_time()
    (tardis.tardis_portal.models.experiment.Experiment
    method), 150
get_image_data() (tardis.tardis_portal.models.datafile.DataFile
    method), 142 get_none_option_license()
    (tardis.tardis_portal.models.license.License
    class method), 156
get_images() (tardis.tardis_portal.models.dataset.Dataset
    method), 147 get_oauth_service()
    (tardis.apps.push_to.models.OAuthSSHCertSigningService
    static method), 94
get_images() (tardis.tardis_portal.models.experiment.Experiment
    method), 150 get_object_list()
    (tardis.apps.search.api.AdvanceSearchAppResource
    method), 104
get_initialised_storage_instance() (tardis.tardis_portal.models.storage.StorageBox
    method), 175 get_object_list()
    (tardis.apps.search.api.SearchAppResource
    method), 104
get_instances_from_related() (tardis.apps.search.documents.DataFileDocument
    method), 105 get_object_size() (in module
    tardis.apps.push_to.utils), 97
get_instances_from_related() (tardis.apps.search.documents.DatasetDocument
    method), 105 get_options_as_dict()
    (tardis.tardis_portal.models.storage.StorageBox
    method), 175
get_instances_from_related() (tardis.apps.search.documents.ExperimentDocument
    method), 106
get_item() (in module get_or_create_cc_parameterset()
    tardis.tardis_portal.templatetags.lookupfilters), 183 (tardis.tardis_portal.creativecommonshandler.CreativeCommons
    method), 223
get_leaf() (tardis.apps.sftp.sftp.DynamicTree
    method), 110 get_or_create_directory()
    (tardis.tardis_portal.models.experiment.Experiment
    method), 150
get_license_uri() (tardis.tardis_portal.tests.test_publishservice.MockRifCsProm
    method), 199 get_or_create_user() (in module
    tardis.tardis_portal.auth.utils), 129
get_local_time() (in module get_or_create_user()
    (tardis.tardis_portal.auth.authservice.AuthService
    method), 125
    tardis.tardis_portal.util), 235 get_owned_experiments() (in module
    tardis.apps.openid_migration.migration), 86
get_matching_auth_provider() (in module
    tardis.tardis_portal.auth.authservice.AuthService
    method), 125
get_matching_authmethod() (in module

```

tardis.tardis_portal.auth.decorators), 125
get_owners() (*tardis.tardis_portal.models.experiment.Experiment* method), 180
method), 150
get_param() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 208
method), 208
get_params() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* static method), 80
method), 208
get_path() (*tardis.tardis_portal.models.dataset.Dataset* method), 147
method), 192
get_perm_bool() (*tardis.tardis_portal.auth.authorisation.ACLAwareBackend* method), 124
method), 192
get_preferred_dfo() (*tardis.tardis_portal.models.datafile.DataFile* method), 142
method), 142
get_previous_by_added() (*tardis.apps.sftp.models.SFTPPublicKey* method), 110
method), 110
get_previous_by_created_time() (*tardis.tardis_portal.models.datafile.DataFileObject* method), 144
method), 144
get_previous_by_created_time() (*tardis.tardis_portal.models.experiment.Experiment* method), 150
method), 150
get_previous_by_created_time() (*tardis.tardis_portal.models.jti.JTI* method), 155
method), 155
get_previous_by_expiry_date() (*tardis.tardis_portal.models.token.Token* method), 179
method), 179
get_previous_by_migration_timestamp() (*tardis.apps.openid_migration.models.OpenidUserMigration* method), 88
method), 88
get_previous_by_update_time() (*tardis.tardis_portal.models.experiment.Experiment* method), 150
method), 150
get_public_access_display() (*tardis.tardis_portal.models.experiment.Experiment* method), 150
method), 150
get_push_url_for_host() (in module *tardis.apps.push_to.views*), 97
method), 233
get_queryset() (*tardis.tardis_portal.managers.OracleSftpManager* method), 233
method), 233
get_receiving_storage_box() (*tardis.tardis_portal.models.datafile.DataFile* method), 142
method), 142
get_related_object() (*tardis.tardis_portal.models.access_control.ObjectACL* method), 137
method), 137
get_related_object_group() (*tardis.tardis_portal.models.access_control.ObjectACL* method), 137
method), 137
get_response() (*tardis.tardis_portal.download.UncachedTarStream* method), 224
method), 224
get_rifcs_context() (*tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider* method), 180
method), 180
get_rifcs_context() (*tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider* method), 199
method), 199
get_rifcs_context() (*tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider* method), 199
method), 199
get_root_dn() (*tardis.tardis_portal.tests.slapped.Slapped* method), 192
method), 192
get_schema() (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 208
method), 208
get_server() (in module *tardis.apps.oaipmh.server*), 83
method), 83
get_session_expiry() (*tardis.tardis_portal.models.token.Token* method), 179
method), 179
get_shared_experiments() (in module *tardis.tardis_portal.auth.decorators*), 125
method), 125
get_signing_services() (in module *tardis.apps.push_to.views*), 98
method), 98
get_size() (*tardis.tardis_portal.models.datafile.DataFile* method), 142
method), 142
get_size() (*tardis.tardis_portal.models.dataset.Dataset* method), 147
method), 147
get_size() (*tardis.tardis_portal.models.experiment.Experiment* method), 150
method), 150
get_size_and_sha512sum() (in module *tardis.tardis_portal.tests.test_download*), 195
method), 195
get_suitable_credential() (*tardis.apps.push_to.models.Credential* static method), 91
method), 91
get_suitable_licenses() (*tardis.tardis_portal.models.license.License* class method), 156
method), 156
get_tardis_apps() (in module *tardis.app_config*), 238
method), 238
get_template() (*tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider* method), 180
method), 180
get_template() (*tardis.tardis_portal.publish.publishservice.PublishService* method), 180
method), 180
get_template() (*tardis.tardis_portal.tests.test_publishservice.MockRifCsProvider* method), 199
method), 199
get_thumbnail_url() (*tardis.tardis_portal.models.dataset.Dataset* method), 147
method), 147
get_tmpdir() (*tardis.tardis_portal.tests.slapped.Slapped* method), 192
method), 192
get_tar_stream() (in module *tardis.apps.push_to.oauth_tokens*), 96
method), 96
get_token_data() (in module *tardis.apps.push_to.oauth_tokens*), 96
method), 96

tardis.apps.push_to.oauth_tokens), 96
get_type_display() (*tardis.tardis_portal.models.parameters.Schema* method), 172
get_url() (*tardis.tardis_portal.tests.slapi.Slapd* method), 192
get_user() (*tardis.tardis_portal.auth.interfaces.AuthProvider* method), 127
get_user() (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend* method), 128
get_utc_time() (in module *tardis.tardis_portal.util*), 235
get_value_type_display() (*tardis.tardis_portal.models.storage.StorageBoxOptions* method), 178
get_view_url() (*tardis.tardis_portal.models.datafile.DataFile* method), 142
getAuthMethodChoices() (in module *tardis.tardis_portal.forms*), 230
getAuthMethodDescription() (*tardis.tardis_portal.models.access_control.UserAuthentication* method), 138
getGroupById() (*tardis.tardis_portal.auth.interfaces.GroupProvider* method), 127
getGroupById() (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend* method), 128
getGroupById() (*tardis.tardis_portal.tests.test_authservice.MockGroupProvider* method), 194
getGroups() (in module *tardis.tardis_portal.auth.fix_circular*), 126
getGroups() (*tardis.tardis_portal.auth.authservice.AuthService* method), 124
getGroups() (*tardis.tardis_portal.auth.interfaces.GroupProvider* method), 127
getGroups() (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend* method), 128
getGroups() (*tardis.tardis_portal.auth.token_auth.TokenAuthGroupProvider* method), 129
getGroups() (*tardis.tardis_portal.tests.test_authservice.MockGroupProvider* method), 194
getGroupsForEntity() (*tardis.tardis_portal.auth.authservice.AuthService* method), 124
getGroupsForEntity() (*tardis.tardis_portal.auth.interfaces.GroupProvider* method), 127
getGroupsForEntity() (*tardis.tardis_portal.tests.test_authservice.MockGroupProvider* method), 194
getParameterSets() (*tardis.tardis_portal.models.datafile.DataFile* method), 141
getParameterSets() (*tardis.tardis_portal.models.dataset.Dataset* method), 146
getParameterSets() (*tardis.tardis_portal.models.experiment.Experiment* method), 149
getParameterSets() (*tardis.tardis_portal.models.instrument.Instrument* method), 154
getRecord() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 77, 241
getRecord() (*tardis.apps.oaipmh.provider.experiment.AbstractExperiment* method), 79
getRecord() (*tardis.apps.oaipmh.server.ProxyingServer* method), 82, 243
getSupportedAuthMethods() (in module *tardis.apps.openid_migration.migration*), 86
GetTestCase (class in *tardis.apps.related_info.tests.tests*), 99
getUniqueShortName() (*tardis.tardis_portal.models.parameters.ParameterName* method), 169
getUser() (*tardis.tardis_portal.auth.authservice.AuthService* method), 124
getUserAuthentications() (*tardis.tardis_portal.models.access_control.UserProfile* method), 139
getUserById() (*tardis.tardis_portal.auth.localdb_auth.DjangoAuthBackend* method), 128
getUserByEmail() (*tardis.tardis_portal.auth.authservice.AuthService* method), 125
getUserByEmail() (*tardis.tardis_portal.auth.interfaces.AuthProvider* method), 127
getUserByEmail() (*tardis.tardis_portal.auth.interfaces.UserProvider* method), 127
global_contexts() (in module *tardis.tardis_portal.context_processors*), 222
google_analytics() (in module *tardis.tardis_portal.context_processors*), 222
GREATER_THAN_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 167
GREATER_THAN_EQUAL_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 167
group (*tardis.tardis_portal.models.access_control.GroupAdmin* attribute), 135
group_acls_system_owned()

(tardis.tardis_portal.managers.ExperimentManager
 method), 231
 group_acls_user_owned() (in module
 (tardis.tardis_portal.managers.ExperimentManager
 method), 231
 group_id (tardis.tardis_portal.models.access_control.GroupAdmin
 attribute), 135
 group_ownership_required() (in module
 tardis.tardis_portal.auth.decorators), 125
 GroupAdmin (class in
 tardis.tardis_portal.models.access_control),
 135
 GroupAdmin.DoesNotExist, 135
 GroupAdmin.MultipleObjectsReturned, 135
 GroupProvider (class in
 tardis.tardis_portal.auth.interfaces), 127
 GroupResource (class in tardis.tardis_portal.api),
 218
 GroupResource.Meta (class in
 tardis.tardis_portal.api), 218
 GroupResourceTest (class in
 tardis.tardis_portal.tests.api.test_group_resource),
 186
 gt() (in module tardis.tardis_portal.templatetags.basiccomparisonfilters),
 181
 gte() (in module tardis.tardis_portal.templatetags.basiccomparisonfilters),
 181
H
 handle (tardis.tardis_portal.models.experiment.Experiment
 attribute), 150
 handle() (tardis.apps.sftp.management.commands.sftpd.Command
 attribute), 129
 handle() (tardis.apps.sftp.sftp.MyTSFTPRequestHandler
 method), 111
 handle() (tardis.tardis_portal.management.commands.createuser.Command
 attribute), 130
 handle() (tardis.tardis_portal.management.commands.createuser.Command
 method), 129
 handle() (tardis.tardis_portal.management.commands.dumpschemas.Command
 attribute), 120
 handle() (tardis.tardis_portal.management.commands.dumpschemas.Command
 method), 130
 handle() (tardis.tardis_portal.management.commands.loadschemas.Command
 attribute), 120
 handle() (tardis.tardis_portal.management.commands.loadschemas.Command
 method), 130
 handle() (tardis.tardis_portal.management.commands.rmexperiment.Command
 attribute), 120
 handle() (tardis.tardis_portal.management.commands.rmexperiment.Command
 method), 130
 handle_timeout() (tardis.apps.sftp.sftp.MyTSFTPRequestHandler
 method), 111
 has_cc_license() (tardis.tardis_portal.creativecommonshandle.CreativeCommonsPortalView
 method), 223
 has_datafile_access() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_datafile_download_access() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_dataset_access() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_dataset_download_access() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_dataset_ownership() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_dataset_write() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_delete_permissions() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_experiment_access() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_experiment_download_access() (in mod-
 ule tardis.tardis_portal.auth.decorators), 126
 has_experiment_ownership() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_experiment_write() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_image() (tardis.tardis_portal.models.datafile.DataFile
 method), 142
 has_perm() (tardis.tardis_portal.auth.authorisation.ACLAwareBackend
 method), 124
 has_read_or_owner_ACL() (in module
 tardis.tardis_portal.auth.decorators), 126
 has_write_permissions() (in module
 tardis.tardis_portal.auth.decorators), 126
 hasReader() (tardis.apps.oaipmh.server.ProxyingMetadataRegistry
 method), 82
 hasWriter() (tardis.apps.oaipmh.server.ProxyingMetadataRegistry
 method), 82
 healthz() (in module
 tardis.tardis_portal.views.pages), 206
 help (tardis.tardis_portal.management.commands.createuser.Command
 attribute), 129
 help (tardis.tardis_portal.management.commands.dumpschemas.Command
 attribute), 130
 help (tardis.tardis_portal.management.commands.loadschemas.Command
 attribute), 120
 help (tardis.tardis_portal.management.commands.rmexperiment.Command
 attribute), 120
 hidden (tardis.tardis_portal.models.parameters.Schema
 attribute), 172
 host_name (tardis.apps.push_to.models.RemoteHost
 attribute), 93
 HttpResponseRedirectNotAllowed (class in
 tardis.tardis_portal.views.utils), 208
 HttpResponseRedirect (class in
 tardis.tardis_portal.views.utils), 208
 hydrate() (tardis.apps.sftp.api.SFTPPublicKeyAppResource
 method), 108
 hydrate() (tardis.tardis_portal.api.DataFileResource
 method), 214
 hydrate() (tardis.tardis_portal.api.ObjectACLResource
 method), 219
 hydrate() (tardis.tardis_portal.api.ParameterResource
 method), 220

hydrate() (*tardis.tardis_portal.api.ReplicaResource* method), 220

hydrate_m2m() (*tardis.tardis_portal.api.ExperimentResource* method), 217

hydrate_schema() (*tardis.tardis_portal.api.ParameterSetResource* method), 220

I

id (*tardis.apps.openid_migration.models.OpenidACLMigration* attribute), 87

id (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 88

id (*tardis.apps.push_to.models.Credential* attribute), 91

id (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94

id (*tardis.apps.push_to.models.RemoteHost* attribute), 95

id (*tardis.apps.sftp.models.SFTPPublicKey* attribute), 110

id (*tardis.tardis_portal.models.access_control.GroupAdmin* attribute), 135

id (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 137

id (*tardis.tardis_portal.models.access_control.UserAuthentication* attribute), 138

id (*tardis.tardis_portal.models.access_control.UserProfile* attribute), 139

id (*tardis.tardis_portal.models.datafile.DataFile* attribute), 142

id (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 144

id (*tardis.tardis_portal.models.dataset.Dataset* attribute), 147

id (*tardis.tardis_portal.models.experiment.Experiment* attribute), 150

id (*tardis.tardis_portal.models.experiment.ExperimentAuthor* attribute), 152

id (*tardis.tardis_portal.models.facility.Facility* attribute), 153

id (*tardis.tardis_portal.models.instrument.Instrument* attribute), 154

id (*tardis.tardis_portal.models.jti.JTI* attribute), 155

id (*tardis.tardis_portal.models.license.License* attribute), 156

id (*tardis.tardis_portal.models.parameters.DatafileParameterSet* attribute), 157

id (*tardis.tardis_portal.models.parameters.DatafileParameterSet* attribute), 158

id (*tardis.tardis_portal.models.parameters.DatasetParameterSet* attribute), 159

id (*tardis.tardis_portal.models.parameters.DatasetParameterSet* attribute), 160

id (*tardis.tardis_portal.models.parameters.ExperimentParameterSet* attribute), 161

id (*tardis.tardis_portal.models.parameters.ExperimentParameterSet* attribute), 163

id (*tardis.tardis_portal.models.parameters.FreeTextSearchField* attribute), 163

id (*tardis.tardis_portal.models.parameters.InstrumentParameterSet* attribute), 164

id (*tardis.tardis_portal.models.parameters.InstrumentParameterSet* attribute), 165

id (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169

id (*tardis.tardis_portal.models.parameters.Schema* attribute), 172

id (*tardis.tardis_portal.models.storage.StorageBox* attribute), 175

id (*tardis.tardis_portal.models.storage.StorageBoxAttribute* attribute), 177

id (*tardis.tardis_portal.models.storage.StorageBoxOption* attribute), 178

id (*tardis.tardis_portal.models.token.Token* attribute), 179

identify() (*tardis.apps.oaipmh.provider.base.BaseProvider* method), 78, 241

identify() (*tardis.apps.oaipmh.server.ProxyingServer* method), 83, 243

image (*tardis.tardis_portal.models.dataset.Dataset* attribute), 147

image_url (*tardis.tardis_portal.models.license.License* attribute), 156

immutable (*tardis.tardis_portal.models.dataset.Dataset* attribute), 147

immutable (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169

immutable (*tardis.tardis_portal.models.parameters.Schema* attribute), 172

ImportParamsForm (class in *tardis.tardis_portal.forms*), 227

INDEX_VIEWS (in module *tardis.default_settings.custom_views*), 119

IndexExperimentTestCase (class in *tardis.apps.search.tests.test_index*), 103

IndexView (class in *tardis.tardis_portal.views.pages*), 205

initial (*tardis.apps.openid_migration.migrations.0001_initial.Migration* attribute), 84

initial (*tardis.apps.sftp.migrations.0001_initial.Migration* attribute), 107

inlines (*tardis.tardis_portal.admin.DatafileAdmin* attribute), 209

inlines (*tardis.tardis_portal.admin.ExperimentAdmin* attribute), 210

inlines (*tardis.tardis_portal.admin.ExperimentParameterSetAdmin* attribute), 210

inlines (*tardis.tardis_portal.admin.InstrumentParameterSetAdmin* attribute), 211

`inlines (tardis.tardis_portal.admin.SchemaAdmin attribute), 212`
`inlines (tardis.tardis_portal.admin.StorageBoxAdmin attribute), 212`
`institution (tardis.tardis_portal.models.experiment.ExperimentAdmin attribute), 152`
`institution_name (tardis.tardis_portal.models.experiment.ExperimentAdmin attribute), 150`
`Instrument (class in tardis.tardis_portal.models.instrument), 154`
`instrument (tardis.tardis_portal.models.dataset.Dataset attribute), 147`
`instrument (tardis.tardis_portal.models.parameters.InstrumentParameterSet attribute), 165`
`INSTRUMENT (tardis.tardis_portal.models.parameters.Schema attribute), 171`
`Instrument.DoesNotExist, 154`
`Instrument.MultipleObjectsReturned, 154`
`instrument_id (tardis.tardis_portal.models.dataset.Dataset attribute), 147`
`instrument_id (tardis.tardis_portal.models.parameters.InstrumentParameterSet attribute), 165`
`instrument_set (tardis.tardis_portal.models.facility.Facility attribute), 153`
`InstrumentAdmin (class in tardis.tardis_portal.admin), 211`
`InstrumentParameter (class in tardis.tardis_portal.models.parameters), 164`
`InstrumentParameter.DoesNotExist, 164`
`InstrumentParameter.MultipleObjectsReturned, 164`
`instrumentparameter_set (tardis.tardis_portal.models.parameters.InstrumentParameterSet attribute), 165`
`instrumentparameter_set (tardis.tardis_portal.models.parameters.ParameterName attribute), 169`
`InstrumentParameterInline (class in tardis.tardis_portal.admin), 211`
`InstrumentParameterSet (class in tardis.tardis_portal.models.parameters), 165`
`InstrumentParameterSet.DoesNotExist, 165`
`InstrumentParameterSet.MultipleObjectsReturned, 165`
`instrumentparameterset_set (tardis.tardis_portal.models.instrument.Instrument attribute), 155`
`instrumentparameterset_set (tardis.tardis_portal.models.parameters.Schema attribute), 172`
`InstrumentParameterSetAdmin (class in tardis.tardis_portal.admin), 211`
`instrumentparametersets (tardis.tardis_portal.models.storage.StorageBox attribute), 175`
`InstrumentResource (class in tardis.tardis_portal.api), 218`
`InstrumentResource.Meta (class in tardis.tardis_portal.api), 218`
`InstrumentResourceTest (class in tardis.tardis_portal.tests.api.test_instrument_resource), 186`
`internal_description (tardis.tardis_portal.models.license.License attribute), 156`
`INTERNAL_IPS (in module tardis.default_settings.debug), 119`
`interpolate_template () (in module tardis.apps.openid_migration.email_text), 86`
`is_active (tardis.tardis_portal.models.license.License attribute), 156`
`is_authenticated () (tardis.tardis_portal.api.MyTardisAuthentication method), 219`
`is_directory () (in module tardis.apps.push_to.utils), 97`
`is_expired () (tardis.tardis_portal.models.token.Token method), 179`
`is_facility_manager () (in module tardis.tardis_portal.models.facility), 153`
`is_group_admin () (in module tardis.tardis_portal.auth.decorators), 126`
`is_image () (tardis.tardis_portal.models.datafile.DataFile method), 142`
`is_image () (tardis.tardis_portal.models.parameters.ParameterName method), 170`
`is_local () (tardis.tardis_portal.models.datafile.DataFile method), 142`
`is_online (tardis.tardis_portal.models.datafile.DataFile attribute), 142`
`is_online (tardis.tardis_portal.models.dataset.Dataset attribute), 147`
`is_openid_migration_enabled () (in module tardis.apps.social_auth.auth.social_auth), 116`
`is_public () (tardis.tardis_portal.models.datafile.DataFile method), 142`
`is_publication () (tardis.tardis_portal.models.experiment.Experiment method), 150`
`is_publication_draft () (tardis.tardis_portal.models.experiment.Experiment method), 150`
`is_schema_valid () (tardis.tardis_portal.publish.provider.rifcsprovider.RifCsProvider method), 180`
`is_schema_valid ()`

- (*tardis.tardis_portal.tests.test_publishservice.MockKeyProvider* attribute), 199
- is_searchable* (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 170
- is_tardis_app* () (in module *tardis.app_config*), 238
- is_valid* () (*tardis.tardis_portal.forms.ExperimentForm* attribute), 227
- is_valid_email* () (in module *tardis.tardis_portal.management.commands.createuser*), 129
- isDateTime* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169
- isDjangoAccount* (*tardis.tardis_portal.models.access_control.UserProfile* attribute), 139
- isFilename* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169
- isLink* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169
- isLongString* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169
- isNumeric* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 169
- isOwner* (*tardis.tardis_portal.models.access_control.ObjectACL* attribute), 137
- isString* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 170
- isURL* () (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 170
- isValidPublicContact* () (*tardis.tardis_portal.models.access_control.UserProfile* attribute), 139
- IteratorTracker* (class in *tardis.analytics.tracker*), 75
- J**
- JSON* (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168
- json_indent* (*tardis.apps.search.api.PrettyJSONSerializer* attribute), 104
- json_indent* (*tardis.tardis_portal.api.PrettyJSONSerializer* attribute), 220
- JTI* (class in *tardis.tardis_portal.models.jti*), 155
- jti* (*tardis.tardis_portal.models.jti.JTI* attribute), 155
- JTI.DoesNotExist*, 155
- JTI.MultipleObjectsReturned*, 155
- K**
- key* (*tardis.apps.push_to.models.KeyPair* attribute), 93
- key* (*tardis.tardis_portal.models.storage.StorageBoxAttribute* attribute), 177
- key* (*tardis.tardis_portal.models.storage.StorageBoxOption* attribute), 178
- key_type* (*tardis.apps.push_to.models.KeyPair* attribute), 93
- KeyGenerateForm* (class in *tardis.apps.sftp.forms*), 109
- KeyPair* (class in *tardis.apps.push_to.models*), 92
- KeyPair.Meta* (class in *tardis.apps.push_to.models*), 93
- last_verified_time* (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 144
- LDAP_ATTR_MAP* (*tardis.default_settings* attribute), 54
- LDAP_GROUP_ATTR_MAP* (*tardis.default_settings* attribute), 54
- LDAP_GROUP_BASE* (*tardis.default_settings* attribute), 54
- LDAP_GROUP_ID_ATTR* (*tardis.default_settings* attribute), 54
- LDAP_TLS* (*tardis.default_settings* attribute), 54
- LDAP_URL* (*tardis.default_settings* attribute), 54
- LDAP_USER_ATTR_MAP* (*tardis.default_settings* attribute), 54
- LDAP_USER_BASE* (*tardis.default_settings* attribute), 54
- LDAP_USER_LOGIN_ATTR* (*tardis.default_settings* attribute), 54
- LDAPErrorTest* (class in *tardis.tardis_portal.tests.test_ldap*), 197
- ldapsearch* () (*tardis.tardis_portal.tests.slapi.Slapd* attribute), 192
- LDAPTest* (class in *tardis.tardis_portal.tests.test_ldap*), 197
- length_gt* () (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 181
- length_gte* () (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 181
- length_lt* () (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 181
- length_lte* () (in module *tardis.tardis_portal.templatetags.basiccomparisonfilters*), 181
- LESS_THAN_COMPARISON* (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168
- LESS_THAN_EQUAL_COMPARISON* (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168

[attribute](#)), 168
 Level0TestCase (class in [tardis.tardis_portal.tests.test_iiif](#)), 196
 Level1TestCase (class in [tardis.tardis_portal.tests.test_iiif](#)), 196
 Level2TestCase (class in [tardis.tardis_portal.tests.test_iiif](#)), 197
 License (class in [tardis.tardis_portal.models.license](#)), 156
 license ([tardis.tardis_portal.models.experiment.Experiment](#) attribute), 150
 License.DoesNotExist, 156
 License.MultipleObjectsReturned, 156
 license_id ([tardis.tardis_portal.models.experiment.Experiment](#) attribute), 150
 LINK ([tardis.tardis_portal.models.parameters.ParameterName](#) attribute), 168
 link_ct ([tardis.tardis_portal.models.parameters.DatafileParameter](#) attribute), 157
 link_ct ([tardis.tardis_portal.models.parameters.DatasetParameter](#) attribute), 159
 link_ct ([tardis.tardis_portal.models.parameters.ExperimentParameter](#) attribute), 161
 link_ct ([tardis.tardis_portal.models.parameters.InstrumentParameter](#) attribute), 164
 link_ct ([tardis.tardis_portal.models.parameters.Parameter](#) attribute), 166
 link_ct_id ([tardis.tardis_portal.models.parameters.Parameter](#) attribute), 166
 link_gfk ([tardis.tardis_portal.models.parameters.DatafileParameter](#) attribute), 157
 link_gfk ([tardis.tardis_portal.models.parameters.DatasetParameter](#) attribute), 159
 link_gfk ([tardis.tardis_portal.models.parameters.ExperimentParameter](#) attribute), 161
 link_gfk ([tardis.tardis_portal.models.parameters.InstrumentParameter](#) attribute), 164
 link_gfk ([tardis.tardis_portal.models.parameters.Parameter](#) attribute), 166
 link_id ([tardis.tardis_portal.models.parameters.Parameter](#) attribute), 167
 link_url ([tardis.tardis_portal.models.parameters.Parameter](#) attribute), 167
 list_allowed_methods ([tardis.apps.search.api.AdvanceSearchAppResource.Meta](#) attribute), 103
 list_allowed_methods ([tardis.apps.search.api.SearchAppResource.Meta](#) attribute), 104
 list_allowed_methods ([tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta](#) attribute), 108
 list_auth_methods () (in module [tardis.tardis_portal.auth.authentication](#)), 123
 list_display ([tardis.apps.openid_migration.models.OpenidACLMigration](#) attribute), 87
 list_display ([tardis.apps.openid_migration.models.OpenidUserMigration](#) attribute), 89
 list_display ([tardis.tardis_portal.admin.ObjectACLAdmin](#) attribute), 211
 list_folder () ([tardis.apps.sftp.sftp.MyTSFTPServerInterface](#) method), 111
 list_subdirectories () (in module [tardis.apps.push_to.utils](#)), 97
 listIdentifiers () ([tardis.apps.oaipmh.provider.base.BaseProvider](#) method), 78, 242
 listIdentifiers () ([tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider](#) method), 79
 listIdentifiers () ([tardis.apps.oaipmh.server.ProxyingServer](#) method), 83, 243
 listMetadataFormats () ([tardis.apps.oaipmh.provider.base.BaseProvider](#) method), 78, 242
 listMetadataFormats () ([tardis.apps.oaipmh.provider.experiment.DcExperimentProvider](#) method), 79
 listMetadataFormats () ([tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider](#) method), 80
 listRecords () ([tardis.apps.oaipmh.provider.base.BaseProvider](#) method), 78, 242
 listRecords () ([tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider](#) method), 79
 listRecords () ([tardis.apps.oaipmh.server.ProxyingServer](#) method), 83, 244
 listSets () ([tardis.apps.oaipmh.provider.base.BaseProvider](#) method), 79, 242
 listSets () ([tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider](#) method), 79
 listSets () ([tardis.apps.oaipmh.server.ProxyingServer](#) method), 83, 244
 TestCase (class in [tardis.apps.related_info.tests.tests](#)), 99
 load_datafile_image () (in module [tardis.tardis_portal.views.images](#)), 204
 load_dataset_image () (in module [tardis.tardis_portal.views.images](#)), 204
 load_experiment_image () (in module [tardis.tardis_portal.views.images](#)), 204
 load_image () (in module [tardis.tardis_portal.views.images](#)), 204

load_licenses()	(in module <code>tardis.tardis_portal.migrations.0017_add_cc_licenses</code>), 134	ManageAccountForm (class in <code>tardis.tardis_portal.forms</code>), 227
LoadSchemasTestCase	(class in <code>tardis.tardis_portal.tests.management.test_loadschemas</code>), 189	ManageAccountForm.Meta (class in <code>tardis.tardis_portal.forms</code>), 228
LocationResource	(class in <code>tardis.tardis_portal.api</code>), 218	ManageAccountTestCase (class in <code>tardis.tardis_portal.tests.views.test_auth_views</code>), 189
LocationResource.Meta	(class in <code>tardis.tardis_portal.api</code>), 218	ManageGroupPermissionsForm (class in <code>tardis.tardis_portal.forms</code>), 228
locked	(<code>tardis.tardis_portal.models.experiment.Experiment</code> attribute), 150	manager_group (<code>tardis.tardis_portal.models.facility.Facility</code> attribute), 153
logger	(in module <code>tardis.tardis_portal.xmlwriter</code>), 236	manager_group_id (<code>tardis.tardis_portal.models.facility.Facility</code> attribute), 153
LoggingMiddleware	(class in <code>tardis.tardis_portal.logging_middleware</code>), 230	master_box (<code>tardis.tardis_portal.models.storage.StorageBox</code> attribute), 176
login()	(in module <code>tardis.tardis_portal.views.authentication</code>), 202	master_box_id (<code>tardis.tardis_portal.models.storage.StorageBox</code> attribute), 176
LOGIN_VIEWS	(in module <code>tardis.default_settings.custom_views</code>), 119	MAX_IMAGES_IN_CAROUSEL (in module <code>tardis.default_settings.frontend</code>), 120
LoginForm	(class in <code>tardis.tardis_portal.forms</code>), 227	MAX_SEARCH_RESULTS (in module <code>tardis.default_settings.search</code>), 121
logo_img	(<code>tardis.apps.push_to.models.RemoteHost</code> attribute), 95	max_size (<code>tardis.tardis_portal.models.storage.StorageBox</code> attribute), 176
logout()	(in module <code>tardis.tardis_portal.views.authentication</code>), 202	md5sum (<code>tardis.tardis_portal.models.datafile.DataFile</code> attribute), 142
LONGSTRING	(<code>tardis.tardis_portal.models.parameters.ParameterName</code> attribute), 168	media (<code>tardis.apps.openid_migration.models.OpenidACLMigrationAdmin</code> attribute), 87
lstat()	(<code>tardis.apps.sftp.sftp.MyTSFTPServerInterface</code> method), 111	media (<code>tardis.apps.openid_migration.models.OpenidUserMigrationAdmin</code> attribute), 89
lt()	(in module <code>tardis.tardis_portal.templatetags.basiccomparison_filters</code>), 181	media (<code>tardis.apps.push_to.models.CredentialAdmin</code> attribute), 92
lte()	(in module <code>tardis.tardis_portal.templatetags.basiccomparison_filters</code>), 181	media (<code>tardis.apps.push_to.models.CredentialForm</code> attribute), 92
		media (<code>tardis.apps.push_to.models.RemoteHostAdmin</code> attribute), 96
		media (<code>tardis.apps.related_info.forms.RelatedInfoForm</code> attribute), 100
make_dirs()	(in module <code>tardis.apps.push_to.tasks</code>), 97	media (<code>tardis.apps.sftp.forms.KeyAddForm</code> attribute), 109
make_mapper()	(in module <code>tardis.tardis_portal.download</code>), 224	media (<code>tardis.apps.sftp.forms.KeyGenerateForm</code> attribute), 109
make_tar()	(<code>tardis.tardis_portal.download.UncachedTarStream</code> method), 224	media (<code>tardis.tardis_portal.admin.DatafileAdmin</code> attribute), 209
manage_auth_methods()	(in module <code>tardis.tardis_portal.views.authentication</code>), 202	media (<code>tardis.tardis_portal.admin.DatafileAdminForm</code> attribute), 210
manage_groups()	(in module <code>tardis.tardis_portal.views.authorisation</code>), 203	media (<code>tardis.tardis_portal.admin.DataFileObjectInline</code> attribute), 209
manage_rifcs()	(<code>tardis.tardis_portal.publish.publishservices.PublishService</code> method), 180	media (<code>tardis.tardis_portal.admin.DataFileObjectInlineForm</code> attribute), 209
manage_user_account()	(in module <code>tardis.tardis_portal.views.authentication</code>), 202	media (<code>tardis.tardis_portal.admin.DatasetAdmin</code> attribute), 210
		media (<code>tardis.tardis_portal.admin.ExperimentAdmin</code> attribute), 210
		media (<code>tardis.tardis_portal.admin.ExperimentParameterInline</code> attribute), 210

M

- attribute), 210
- media (tardis.tardis_portal.admin.ExperimentParameterSetAdmin attribute), 210
- media (tardis.tardis_portal.admin.FacilityAdmin attribute), 210
- media (tardis.tardis_portal.admin.FreeTextSearchFieldAdmin attribute), 211
- media (tardis.tardis_portal.admin.InstrumentAdmin attribute), 211
- media (tardis.tardis_portal.admin.InstrumentParameterInline attribute), 211
- media (tardis.tardis_portal.admin.InstrumentParameterSetAdmin attribute), 211
- media (tardis.tardis_portal.admin.ObjectACLAdmin attribute), 211
- media (tardis.tardis_portal.admin.ObjectACLInline attribute), 211
- media (tardis.tardis_portal.admin.ParameterNameAdmin attribute), 211
- media (tardis.tardis_portal.admin.ParameterNameInline attribute), 211
- media (tardis.tardis_portal.admin.SchemaAdmin attribute), 212
- media (tardis.tardis_portal.admin.StorageBoxAdmin attribute), 212
- media (tardis.tardis_portal.admin.StorageBoxAttributeInline attribute), 212
- media (tardis.tardis_portal.admin.StorageBoxAttributeInlineForm attribute), 212
- media (tardis.tardis_portal.admin.StorageBoxForm attribute), 213
- media (tardis.tardis_portal.admin.StorageBoxOptionInline attribute), 213
- media (tardis.tardis_portal.admin.StorageBoxOptionInlineForm attribute), 214
- media (tardis.tardis_portal.admin.UserAuthenticationAdmin attribute), 214
- media (tardis.tardis_portal.forms.AddUserPermissionsForm attribute), 225
- media (tardis.tardis_portal.forms.CreateUserPermissionsForm attribute), 226
- media (tardis.tardis_portal.forms.DatasetForm attribute), 226
- media (tardis.tardis_portal.forms.ExperimentAuthor attribute), 226
- media (tardis.tardis_portal.forms.ExperimentForm attribute), 227
- media (tardis.tardis_portal.forms.ImportParamsForm attribute), 227
- media (tardis.tardis_portal.forms.LoginForm attribute), 227
- media (tardis.tardis_portal.forms.ManageAccountForm attribute), 228
- media (tardis.tardis_portal.forms.ManageGroupPermissionsForm attribute), 228
- media (tardis.tardis_portal.forms.NoInput attribute), 228
- media (tardis.tardis_portal.forms.RegisterExperimentForm attribute), 229
- media (tardis.tardis_portal.forms.RegistrationForm attribute), 229
- media (tardis.tardis_portal.forms.RightsForm attribute), 230
- media (tardis.tardis_portal.widgets.CommaSeparatedInput attribute), 235
- media (tardis.tardis_portal.widgets.Label attribute), 235
- media (tardis.tardis_portal.widgets.Span attribute), 235
- merge_auth_method() (in module tardis.tardis_portal.auth.authentication), 123
- METADATA_STORE_PATH (in module tardis.default_settings.storage), 122
- migrate_accounts() (in module tardis.apps.openid_migration.views), 89
- migrate_api_key() (in module tardis.apps.openid_migration.migration), 86
- migrate_user_message() (in module tardis.apps.social_auth.auth.social_auth), 116
- migrate_user_permissions() (in module tardis.apps.openid_migration.migration), 86
- Migration (class in tardis.apps.openid_migration.migrations.0001_initial), 84
- Migration (class in tardis.apps.push_to.migrations.0001_initial), 90
- Migration (class in tardis.apps.push_to.migrations.0002_auto_20160518_1953), 90
- Migration (class in tardis.apps.sftp.migrations.0001_initial), 107
- Migration (class in tardis.tardis_portal.migrations.0001_initial), 131
- Migration (class in tardis.tardis_portal.migrations.0001_squashed_0011_auto_20160518_1953), 131
- Migration (class in tardis.tardis_portal.migrations.0002_auto_20150528_1128), 131
- Migration (class in tardis.tardis_portal.migrations.0003_auto_20150907_1315), 131
- Migration (class in tardis.tardis_portal.migrations.0004_auto_20150907_1315), 131

[tardis.tardis_portal.migrations.0004_storageboxoption_value_index](#) (class in [tardis.apps.push_to.models.DBHostKeyPolicy](#)), 92
[tardis.tardis_portal.migrations.0004_storageboxoption_value_index](#) (method), 92
 Migration (class in [tardis.tardis_portal.tests.slapp](#)), 132
[tardis.tardis_portal.migrations.0005_datafile_add_size_int_index](#) (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0005_datafile_add_size_int_index](#) (MockAuthProvider (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0006_datafile_remove_size_int_index](#) (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0006_datafile_remove_size_int_index](#) (MockGroupProvider (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index](#) (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0007_remove_parameter_string_value_index](#) (MockRequest (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0008_string_value_partial_index](#) (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0008_string_value_partial_index](#) (MockRifCsProvider (class in [tardis.tardis_portal.tests.test_authservice](#)), 132
[tardis.tardis_portal.migrations.0009_auto_20160128_1119](#) (class in [tardis.tardis_portal.tests.test_publishservice](#)), 133
[tardis.tardis_portal.migrations.0009_auto_20160128_1119](#) (MockSettings (class in [tardis.tardis_portal.tests.test_authservice](#)), 133
[tardis.tardis_portal.migrations.0010_auto_20160503_1443](#) (class in [tardis.tardis_portal.tests.test_authservice](#)), 133
[tardis.tardis_portal.migrations.0010_auto_20160503_1443](#) (model ([tardis.apps.push_to.models.CredentialForm.Meta](#) attribute), 92
[tardis.tardis_portal.migrations.0011_auto_20160503_1443](#) (class in [tardis.apps.search.documents.DataFileDocument.Django](#) attribute), 105
[tardis.tardis_portal.migrations.0011_auto_20160503_1443](#) (model ([tardis.apps.search.documents.DatasetDocument.Django](#) attribute), 105
[tardis.tardis_portal.migrations.0012_userauthentication_app_provider](#) (class in [tardis.apps.search.documents.ExperimentDocument.Django](#) attribute), 106
[tardis.tardis_portal.migrations.0012_userauthentication_app_provider](#) (model ([tardis.apps.search.documents.ExperimentDocument.Django](#) attribute), 106
[tardis.tardis_portal.migrations.0013_auto_20181002_1136](#) (class in [tardis.tardis_portal.admin.DatafileAdminForm.Meta](#) attribute), 210
[tardis.tardis_portal.migrations.0013_auto_20181002_1136](#) (model ([tardis.tardis_portal.admin.DatafileObjectInline](#) attribute), 209
[tardis.tardis_portal.migrations.0014_auto_20181002_1154](#) (class in [tardis.tardis_portal.admin.DatafileObjectInlineForm.Meta](#) attribute), 209
[tardis.tardis_portal.migrations.0014_auto_20181002_1154](#) (model ([tardis.tardis_portal.admin.DatafileObjectInlineForm.Meta](#) attribute), 209
[tardis.tardis_portal.migrations.0015_dataset_created_time](#) (class in [tardis.tardis_portal.admin.ExperimentParameterInline](#) attribute), 210
[tardis.tardis_portal.migrations.0015_dataset_created_time](#) (model ([tardis.tardis_portal.admin.ExperimentParameterInline](#) attribute), 210
[tardis.tardis_portal.migrations.0016_add_timestamps](#) (class in [tardis.tardis_portal.admin.InstrumentParameterInline](#) attribute), 211
[tardis.tardis_portal.migrations.0016_add_timestamps](#) (model ([tardis.tardis_portal.admin.InstrumentParameterInline](#) attribute), 211
[tardis.tardis_portal.migrations.0017_add_cc_licenses](#) (class in [tardis.tardis_portal.admin.ObjectACLInline](#) attribute), 211
[tardis.tardis_portal.migrations.0017_add_cc_licenses](#) (model ([tardis.tardis_portal.admin.ObjectACLInline](#) attribute), 211
[tardis.tardis_portal.migrations.0018_add_cc_licenses](#) (class in [tardis.tardis_portal.admin.ParameterNameInline](#) attribute), 211
[tardis.tardis_portal.migrations.0018_add_cc_licenses](#) (model ([tardis.tardis_portal.admin.ParameterNameInline](#) attribute), 211
[tardis.tardis_portal.migrations.0018_make_default_storage_box_attribute_online](#) (class in [tardis.tardis_portal.admin.StorageBoxAttributeInline](#) attribute), 213
[tardis.tardis_portal.migrations.0018_make_default_storage_box_attribute_online](#) (model ([tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta](#) attribute), 213
[migration_status](#) ([tardis.apps.openid_migration.models.OpenidUserMigration](#) attribute), 88
[migration_status](#) (model ([tardis.tardis_portal.admin.StorageBoxForm.Meta](#) attribute), 213
[migration_timestamp](#) ([tardis.apps.openid_migration.models.OpenidUserMigration](#) attribute), 88
[migration_timestamp](#) (model ([tardis.tardis_portal.admin.StorageBoxOptionInline](#) attribute), 213
[mimetype](#) ([tardis.tardis_portal.models.datafile.DataFile](#) model ([tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta](#) attribute), 142
[mimetype](#) (model ([tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta](#) attribute), 213
[MIN_CUTOFF_SCORE](#) (in module [tardis.default_settings.search](#)), 121
[MIN_CUTOFF_SCORE](#) (model ([tardis.tardis_portal.forms.DatasetForm.Meta](#) attribute), 226
[missing_host_key](#) () (model ([tardis.tardis_portal.forms.ExperimentAuthor.Meta](#) attribute), 226

- attribute), 226
- model (tardis.tardis_portal.forms.ExperimentForm.Meta attribute), 227
- model (tardis.tardis_portal.forms.ManageAccountForm.Meta attribute), 228
- model (tardis.tardis_portal.forms.RightsForm.Meta attribute), 230
- ModelsTestCase (class in tardis.apps.push_to.tests.test_models), 90
- ModelTestCase (class in tardis.apps.openid_migration.tests.test_models), 85
- ModelTestCase (class in tardis.tardis_portal.tests.test_models), 197
- ModelTestCase (class in tardis.tardis_portal.tests.test_storage), 200
- modification_time (tardis.tardis_portal.models.datafile.DataFile attribute), 142
- modified_time (tardis.tardis_portal.models.datafile.DataFileObject attribute), 144
- modified_time (tardis.tardis_portal.models.dataset.Dataset attribute), 147
- modified_time (tardis.tardis_portal.models.facility.Facility attribute), 153
- modified_time (tardis.tardis_portal.models.instrument.Instrument attribute), 155
- move_file() (tardis.tardis_portal.models.datafile.DataFileObject method), 144
- move_files() (tardis.tardis_portal.models.storage.StorageBox method), 176
- move_to_master() (tardis.tardis_portal.models.storage.StorageBox method), 176
- MultiValueCommaSeparatedField (class in tardis.tardis_portal.fields), 225
- my_data() (in module tardis.tardis_portal.views.pages), 206
- myt_auth() (tardis.apps.sftp.sftp.MyTServerInterface method), 115
- MyTardisAuthentication (class in tardis.tardis_portal.api), 218
- MyTardisAuthenticationTest (class in tardis.tardis_portal.tests.api.test_auth), 184
- MyTardisLocalFileSystemStorage (class in tardis.tardis_portal.storage.file_system), 180
- MyTardisModelResource (class in tardis.tardis_portal.api), 219
- MyTardisModelResource.Meta (class in tardis.tardis_portal.api), 219
- MyTardisResourceTestCase (class in tardis.tardis_portal.tests.api), 188
- MyTServerInterface (class in tardis.apps.sftp.sftp), 113
- MyTSFTPHandle (class in tardis.apps.sftp.sftp), 111
- MyTSFTPRequestHandler (class in tardis.apps.sftp.sftp), 111
- MyTSFTPServer (class in tardis.apps.sftp.sftp), 111
- MyTSFTPServerInterface (class in tardis.apps.sftp.sftp), 111
- MyTSFTPTCPServer (class in tardis.apps.sftp.sftp), 112
- ## N
- name (tardis.analytics.apps.AnalyticsConfig attribute), 75
- name (tardis.apps.openid_migration.apps.OpenidMigrationConfig attribute), 85
- name (tardis.apps.push_to.apps.PushToConfig attribute), 90
- name (tardis.apps.s3utils.apps.S3UtilsConfig attribute), 102
- name (tardis.apps.search.apps.SearchConfig attribute), 105
- name (tardis.apps.search.documents.DataFileDocument.Index attribute), 105
- name (tardis.apps.search.documents.DatasetDocument.Index attribute), 105
- name (tardis.apps.search.documents.ExperimentDocument.Index attribute), 106
- name (tardis.apps.sftp.apps.SFTPConfig attribute), 108
- name (tardis.apps.sftp.models.SFTPPublicKey attribute), 110
- name (tardis.apps.social_auth.apps.SocialAuthConfig attribute), 117
- name (tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider attribute), 128
- name (tardis.tardis_portal.auth.localdb_auth.DjangoUserProvider attribute), 128
- name (tardis.tardis_portal.auth.token_auth.TokenGroupProvider attribute), 129
- name (tardis.tardis_portal.models.facility.Facility attribute), 153
- name (tardis.tardis_portal.models.instrument.Instrument attribute), 155
- name (tardis.tardis_portal.models.license.License attribute), 156
- name (tardis.tardis_portal.models.parameters.DatafileParameter attribute), 157
- name (tardis.tardis_portal.models.parameters.DatasetParameter attribute), 159
- name (tardis.tardis_portal.models.parameters.ExperimentParameter attribute), 162
- name (tardis.tardis_portal.models.parameters.InstrumentParameter attribute), 164
- name (tardis.tardis_portal.models.parameters.Parameter attribute), 167
- name (tardis.tardis_portal.models.parameters.ParameterName attribute), 170

name (*tardis.tardis_portal.models.parameters.Schema* attribute), 172
 name (*tardis.tardis_portal.models.storage.StorageBox* attribute), 176
 name_id (*tardis.tardis_portal.models.parameters.Parameter* attribute), 167
 namespace (*tardis.tardis_portal.models.parameters.Schema* attribute), 172
 natural_key () (*tardis.tardis_portal.models.parameters.ParameterName* method), 170
 natural_key () (*tardis.tardis_portal.models.parameters.Schema* method), 173
 new_param () (*tardis.tardis_portal.ParameterSetManager.ParameterSetManager* method), 208
 new_user (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 88
 new_user_auth_method (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 88
 new_user_id (*tardis.apps.openid_migration.models.OpenidUserMigration* attribute), 88
 next () (*tardis.analytics.tracker.IteratorTracker* method), 75
 nickname (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 nickname (*tardis.apps.push_to.models.RemoteHost* attribute), 95
 NoInput (class in *tardis.tardis_portal.forms*), 228
 NONE (*tardis.tardis_portal.models.parameters.Schema* attribute), 171
 NoSuitableCredential, 91
 NOT_EQUAL_COMPARISON (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168
 notify_user () (in module *tardis.apps.push_to.tasks*), 97
 now () (*tardis.tardis_portal.tests.test_tokens.FrozenTime* class method), 201
 NS_CC (*tardis.apps.oaipmh.provider.experiment.AbstractExperimentProvider* attribute), 79
 NUMERIC (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168
 numerical_value (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 167
O
 oauth_authorize_url (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 oauth_callback () (in module *tardis.apps.push_to.views*), 98
 oauth_callback_url () (in module *tardis.apps.push_to.views*), 98
 oauth_check_token_url (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 oauth_client_id (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 oauth_client_secret (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 oauth_sshcertsigningservice_url (*tardis.apps.push_to.models.OAuthSSHCertSigningService* attribute), 94
 OAuthSSHCertSigningService (class in *tardis.apps.push_to.models*), 93
 OAuthSSHCertSigningService.DoesNotExist, 93
 OAuthSSHCertSigningService.MultipleObjectsReturned, 93
 oauthsshcertsigningservice_set (*tardis.apps.push_to.models.RemoteHost* attribute), 95
 obj_create () (*tardis.tardis_portal.api.DataFileResource* method), 215
 obj_create () (*tardis.tardis_portal.api.ExperimentResource* method), 217
 obj_get_list () (*tardis.apps.search.api.AdvanceSearchAppResource* method), 104
 obj_get_list () (*tardis.apps.search.api.SearchAppResource* method), 104
 object_class (*tardis.apps.s3utils.api.ReplicaAppResource.Meta* attribute), 101
 object_class (*tardis.apps.search.api.AdvanceSearchAppResource.Meta* attribute), 103
 object_class (*tardis.apps.search.api.SearchAppResource.Meta* attribute), 104
 object_class (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta* attribute), 108
 object_class (*tardis.tardis_portal.api.DatafileParameterResource.Meta* attribute), 215
 object_class (*tardis.tardis_portal.api.DatafileParameterSetResource.Meta* attribute), 215
 object_class (*tardis.tardis_portal.api.DataFileResource.Meta* attribute), 214
 object_class (*tardis.tardis_portal.api.DatasetParameterResource.Meta* attribute), 215
 object_class (*tardis.tardis_portal.api.DatasetParameterSetResource.Meta* attribute), 216
 object_class (*tardis.tardis_portal.api.DatasetResource.Meta* attribute), 216
 object_class (*tardis.tardis_portal.api.ExperimentAuthorResource.Meta* attribute), 216
 object_class (*tardis.tardis_portal.api.ExperimentParameterResource.Meta* attribute), 216
 object_class (*tardis.tardis_portal.api.ExperimentParameterSetResource.Meta* attribute), 216

attribute), 217
 object_class (tardis.tardis_portal.api.ExperimentResource.Meta attribute), 217
 object_class (tardis.tardis_portal.api.FacilityResource.Meta attribute), 217
 object_class (tardis.tardis_portal.api.GroupResource.Meta attribute), 218
 object_class (tardis.tardis_portal.api.InstrumentResource.Meta attribute), 218
 object_class (tardis.tardis_portal.api.LocationResource.Meta attribute), 218
 object_class (tardis.tardis_portal.api.MyTardisModelResource.Meta attribute), 219
 object_class (tardis.tardis_portal.api.ObjectACLResource.Meta attribute), 219
 object_class (tardis.tardis_portal.api.ParameterNameResource.Meta attribute), 219
 object_class (tardis.tardis_portal.api.ReplicaResource.Meta attribute), 220
 object_class (tardis.tardis_portal.api.SchemaResource.Meta attribute), 220
 object_class (tardis.tardis_portal.api.StorageBoxAttributeResource.Meta attribute), 221
 object_class (tardis.tardis_portal.api.StorageBoxOptionResource.Meta attribute), 221
 object_class (tardis.tardis_portal.api.StorageBoxResource.Meta attribute), 221
 object_class (tardis.tardis_portal.api.UserResource.Meta attribute), 222
 object_id (tardis.tardis_portal.models.access_control.ObjectACL attribute), 137
 ObjectACL (class in objects (tardis.tardis_portal.models.access_control), 135
 ObjectACL.DoesNotExist, 136
 ObjectACL.MultipleObjectsReturned, 136
 ObjectACLAdmin (class in tardis.tardis_portal.admin), 211
 ObjectACLInline (class in tardis.tardis_portal.admin), 211
 ObjectACLResource (class in tardis.tardis_portal.api), 219
 ObjectACLResource.Meta (class in tardis.tardis_portal.api), 219
 objectacls (tardis.tardis_portal.models.experiment.Experiment attribute), 150
 ObjectACLTestCase (class in tardis.tardis_portal.tests.test_authorisation), 193
 objects (tardis.apps.openid_migration.models.OpenidACLMigration attribute), 87
 objects (tardis.apps.openid_migration.models.OpenidUserMigration attribute), 88
 objects (tardis.apps.push_to.models.Credential attribute), 91
 objects (tardis.apps.push_to.models.OAuthSSHCertSigningService attribute), 94
 objects (tardis.apps.push_to.models.RemoteHost attribute), 96
 objects (tardis.apps.sftp.models.SFTPPublicKey attribute), 110
 objects (tardis.tardis_portal.models.access_control.GroupAdmin attribute), 135
 objects (tardis.tardis_portal.models.access_control.ObjectACL attribute), 137
 objects (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 138
 objects (tardis.tardis_portal.models.access_control.UserProfile attribute), 139
 objects (tardis.tardis_portal.models.datafile.DataFile attribute), 142
 objects (tardis.tardis_portal.models.datafile.DataFileObject attribute), 144
 objects (tardis.tardis_portal.models.dataset.Dataset attribute), 147
 objects (tardis.tardis_portal.models.experiment.Experiment attribute), 151
 objects (tardis.tardis_portal.models.experiment.ExperimentAuthor attribute), 152
 objects (tardis.tardis_portal.models.facility.Facility attribute), 153
 objects (tardis.tardis_portal.models.instrument.Instrument attribute), 155
 objects (tardis.tardis_portal.models.jti.JTI attribute), 155
 objects (tardis.tardis_portal.models.license.License attribute), 156
 objects (tardis.tardis_portal.models.parameters.DatafileParameterSet attribute), 158
 objects (tardis.tardis_portal.models.parameters.DatasetParameterSet attribute), 160
 objects (tardis.tardis_portal.models.parameters.ExperimentParameterSet attribute), 163
 objects (tardis.tardis_portal.models.parameters.FreeTextSearchField attribute), 163
 objects (tardis.tardis_portal.models.parameters.InstrumentParameterSet attribute), 165
 objects (tardis.tardis_portal.models.parameters.Parameter attribute), 167
 objects (tardis.tardis_portal.models.parameters.ParameterName attribute), 170
 objects (tardis.tardis_portal.models.parameters.Schema attribute), 173
 objects (tardis.tardis_portal.models.storage.StorageBox attribute), 176
 objects (tardis.tardis_portal.models.storage.StorageBoxAttribute attribute), 177
 objects (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 177

`attribute`), 178
`objects` (`tardis.tardis_portal.models.token.Token` `attribute`), 179
`offline_types` (`tardis.tardis_portal.models.storage.StorageBox` `attribute`), 176
`old_user` (`tardis.apps.openid_migration.models.OpenidUserMigration` `attribute`), 88
`old_user_auth_method` (`tardis.apps.openid_migration.models.OpenidUserMigration` `attribute`), 88
`old_user_id` (`tardis.apps.openid_migration.models.OpenidUserMigration` `attribute`), 88
`online_types` (`tardis.tardis_portal.models.storage.StorageBox` `attribute`), 176
`open()` (`tardis.apps.sftp.sftp.MyTSFTPServerInterface` `method`), 112
`openid_migration_method()` (in module `tardis.apps.openid_migration.migration`), 86
`openid_migration_processor()` (in module `tardis.apps.openid_migration.context_processors`), 85
`openid_user_migration_form()` (in module `tardis.apps.openid_migration.forms`), 86
`OpenidACLMigration` (class in `tardis.apps.openid_migration.models`), 86
`OpenidACLMigration.DoesNotExist`, 86
`OpenidACLMigration.MultipleObjectsReturned`, 86
`openidaclmigration_set` (`tardis.apps.openid_migration.models.OpenidUserMigration` `attribute`), 88
`openidaclmigration_set` (`tardis.tardis_portal.models.access_control.ObjectACL` `attribute`), 137
`OpenidACLMigrationAdmin` (class in `tardis.apps.openid_migration.models`), 87
`OpenidMigrationConfig` (class in `tardis.apps.openid_migration.apps`), 85
`OpenIDMigrationFormTestCase` (class in `tardis.apps.openid_migration.tests.test_forms`), 84
`OpenIDMigrationTestCase` (class in `tardis.apps.openid_migration.tests.test_migration`), 84
`OpenIDMigrationViewTestCase` (class in `tardis.apps.openid_migration.tests.test_views`), 85
`OpenidUserMigration` (class in `tardis.apps.openid_migration.models`), 87
`OpenidUserMigration.DoesNotExist`, 87
`OpenidUserMigration.MultipleObjectsReturned`, 87
`OpenidUserMigrationAdmin` (class in `tardis.apps.openid_migration.models`), 89
`operations` (`tardis.apps.openid_migration.migrations.0001_initial.Migration` `attribute`), 84
`operations` (`tardis.apps.push_to.migrations.0001_initial.Migration` `attribute`), 90
`operations` (`tardis.apps.push_to.migrations.0002_auto_20160518_1953` `attribute`), 90
`operations` (`tardis.apps.sftp.migrations.0001_initial.Migration` `attribute`), 107
`operations` (`tardis.tardis_portal.migrations.0001_initial.Migration` `attribute`), 131
`operations` (`tardis.tardis_portal.migrations.0001_squashed_0011_auto` `attribute`), 131
`operations` (`tardis.tardis_portal.migrations.0002_auto_20150528_1128` `attribute`), 131
`operations` (`tardis.tardis_portal.migrations.0003_auto_20150907_1315` `attribute`), 131
`operations` (`tardis.tardis_portal.migrations.0004_storageboxoption_val` `attribute`), 132
`operations` (`tardis.tardis_portal.migrations.0005_datafile_add_size_int` `attribute`), 132
`operations` (`tardis.tardis_portal.migrations.0006_datafile_remove_size` `attribute`), 132
`operations` (`tardis.tardis_portal.migrations.0007_remove_parameter_s` `attribute`), 132
`operations` (`tardis.tardis_portal.migrations.0008_string_value_partial` `attribute`), 132
`operations` (`tardis.tardis_portal.migrations.0009_auto_20160128_1119` `attribute`), 133
`operations` (`tardis.tardis_portal.migrations.0010_auto_20160503_1443` `attribute`), 133
`operations` (`tardis.tardis_portal.migrations.0011_auto_20160505_1643` `attribute`), 133
`operations` (`tardis.tardis_portal.migrations.0012_userauthentication_ap` `attribute`), 133
`operations` (`tardis.tardis_portal.migrations.0013_auto_20181002_1136` `attribute`), 133
`operations` (`tardis.tardis_portal.migrations.0014_auto_20181002_1154` `attribute`), 134
`operations` (`tardis.tardis_portal.migrations.0015_dataset_created_time` `attribute`), 134
`operations` (`tardis.tardis_portal.migrations.0016_add_timestamps.Migr` `attribute`), 134
`operations` (`tardis.tardis_portal.migrations.0017_add_cc_licenses.Migr` `attribute`), 134
`operations` (`tardis.tardis_portal.migrations.0018_make_default_storag` `attribute`), 134
`options` (`tardis.tardis_portal.models.storage.StorageBox` `attribute`), 176
`OracleSafeManager` (class in `tardis.tardis_portal.managers`), 233
`order` (`tardis.tardis_portal.models.experiment.ExperimentAuthor` `attribute`), 152
`order` (`tardis.tardis_portal.models.parameters.ParameterName`

attribute), 170
 ordering (tardis.tardis_portal.api.DataFileResource.Meta attribute), 214
 ordering (tardis.tardis_portal.api.DatasetResource.Meta attribute), 216
 ordering (tardis.tardis_portal.api.ExperimentAuthorResource.Meta attribute), 216
 ordering (tardis.tardis_portal.api.ExperimentResource.Meta attribute), 217
 ordering (tardis.tardis_portal.api.FacilityResource.Meta attribute), 218
 ordering (tardis.tardis_portal.api.InstrumentResource.Meta attribute), 218
 ordering (tardis.tardis_portal.api.ObjectACLResource.Meta attribute), 219
 ordering (tardis.tardis_portal.api.ReplicaResource.Meta attribute), 220
 ordering (tardis.tardis_portal.api.SchemaResource.Meta attribute), 221
 ordering (tardis.tardis_portal.api.StorageBoxAttributeResource.Meta attribute), 221
 ordering (tardis.tardis_portal.api.StorageBoxOptionResource.Meta attribute), 221
 ordering (tardis.tardis_portal.api.StorageBoxResource.Meta attribute), 221
 ordering (tardis.tardis_portal.models.parameters.Parameter.Meta attribute), 166
 ordering (tardis.tardis_portal.models.parameters.ParameterSet.Meta attribute), 170
 owned () (tardis.tardis_portal.managers.ExperimentManager method), 232
 owned_and_shared () (tardis.tardis_portal.managers.ExperimentManager method), 232
 owned_by_group () (tardis.tardis_portal.managers.ExperimentManager method), 232
 owned_by_user () (tardis.tardis_portal.managers.ExperimentManager method), 232
 owned_by_user_id () (tardis.tardis_portal.managers.ExperimentManager method), 232
 OWNER_OWNED (tardis.tardis_portal.models.access_control.ObjectACL attribute), 136

P

pagination () (in module tardis.tardis_portal.templatetags.pagination), 183
 paginator_number () (in module tardis.tardis_portal.templatetags.pagination), 183
 Parameter (class in tardis.tardis_portal.models.parameters), 166
 Parameter.Meta (class in tardis.tardis_portal.models.parameters), 166
 ParameterClass (tardis.tardis_portal.models.parameters.DatafileParameterClass attribute), 158
 ParameterClass (tardis.tardis_portal.models.parameters.DatasetParameterClass attribute), 160
 ParameterClass (tardis.tardis_portal.models.parameters.ExperimentParameterClass attribute), 163
 ParameterClass (tardis.tardis_portal.models.parameters.InstrumentParameterClass attribute), 165
 ParameterClass (tardis.tardis_portal.models.parameters.ParameterSetClass attribute), 170
 ParameterName (tardis.tardis_portal.models.parameters.FreeTextSearchField attribute), 163
 ParameterName (tardis.tardis_portal.models.parameters.FreeTextSearchField attribute), 164
 ParameterName (tardis.tardis_portal.models.parameters.DatafileParameterClass attribute), 157
 ParameterName (tardis.tardis_portal.models.parameters.DatasetParameterClass attribute), 160
 ParameterName (tardis.tardis_portal.models.parameters.ExperimentParameterClass attribute), 162
 ParameterName (tardis.tardis_portal.models.parameters.InstrumentParameterClass attribute), 164
 ParameterName (tardis.tardis_portal.models.parameters.ParameterClass attribute), 166
 ParameterName (tardis.tardis_portal.models.parameters.ParameterSetClass attribute), 167
 ParameterName (ParameterChoicesFormatError, 225
 ParameterName (class in tardis.tardis_portal.models.parameters), 167
 ParameterName.DoesNotExist, 167
 ParameterName.MultipleObjectsReturned, 168
 parametername_form () (in module tardis.tardis_portal.templatetags.formfieldfilters), 183
 parametername_set (tardis.tardis_portal.models.parameters.Schema attribute), 173
 ParameterNameAdmin (class in tardis.tardis_portal.admin), 211
 ParameterNameInline (class in tardis.tardis_portal.admin), 211
 ParameterNameManager (class in tardis.tardis_portal.managers), 233
 ParameterNameResource (class in tardis.tardis_portal.api), 219
 ParameterNameResource.Meta (class in tardis.tardis_portal.api), 219
 ParameterResource (class in tardis.tardis_portal.api), 220
 parameters (tardis.tardis_portal.ParameterSetManager.ParameterSetManager attribute), 220

[attribute](#)), 208
 ParameterSet (class in [pluginId \(tardis.tardis_portal.models.access_control.ObjectACL attribute\)](#), 137
[tardis.tardis_portal.models.parameters](#)), 170
[parameterset \(tardis.tardis_portal.models.parameters.DatafileParameter attribute\)](#), 96
[parameterset \(tardis.tardis_portal.models.parameters.DatasetParameter attribute\)](#), 157
[parameterset \(tardis.tardis_portal.models.parameters.ExperimentParameter attribute\)](#), 160
[parameterset \(tardis.tardis_portal.models.parameters.InstrumentParameter attribute\)](#), 162
[parameterset \(tardis.tardis_portal.models.parameters.InstrumentParameter attribute\)](#), 164
[parameterset \(tardis.tardis_portal.ParameterSetManager.ParameterSetManager attribute\)](#), 208
 ParameterSet.Meta (class in [tardis.tardis_portal.models.parameters](#)), 170
[parameterset_id \(tardis.tardis_portal.models.parameters.DatafileParameter attribute\)](#), 158
[parameterset_id \(tardis.tardis_portal.models.parameters.DatasetParameter attribute\)](#), 160
[parameterset_id \(tardis.tardis_portal.models.parameters.ExperimentParameter attribute\)](#), 162
[parameterset_id \(tardis.tardis_portal.models.parameters.InstrumentParameter attribute\)](#), 165
 ParameterSetManager (class in [tardis.tardis_portal.ParameterSetManager](#)), 208
 ParameterSetManagerMixin (class in [tardis.tardis_portal.models.parameters](#)), 171
 ParameterSetManagerTestCase (class in [tardis.tardis_portal.tests.test_parametersets](#)), 199
 ParameterSetResource (class in [tardis.tardis_portal.api](#)), 220
 ParametersTestCase (class in [tardis.tardis_portal.tests.test_parameters](#)), 198
 password ([tardis.apps.push_to.models.Credential attribute](#)), 91
 PATH_LDAPADD ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PATH_LDAPSEARCH ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PATH_SCHEMA_DIR ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PATH_SLAPD ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PATH_SLAPTEST ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PATH_TMPDIR ([tardis.tardis_portal.tests.slapped.Slapped attribute](#)), 192
 PICKLE ([tardis.tardis_portal.models.storage.StorageBoxOption attribute](#)), 177
[pluginId \(tardis.tardis_portal.models.access_control.ObjectACL attribute\)](#), 137
 port ([tardis.apps.push_to.models.RemoteHost attribute](#)), 96
[post_list \(\) \(tardis.tardis_portal.api.DataFileResource method\)](#), 215
[post_save_experiment \(\) \(in module tardis.tardis_portal.models.hooks\)](#), 154
[post_save_experiment_parameter \(\) \(in module tardis.tardis_portal.models.hooks\)](#), 154
[post_save_experimentauthor \(\) \(in module tardis.tardis_portal.models.hooks\)](#), 154
 POST_SAVE_FILTERS ([tardis.default_settings attribute](#)), 46
[prepare_output \(\) \(tardis.tardis_portal.download.UncachedTarStream method\)](#), 224
[push_to \(tardis.apps.s3utils.api.ReplicaAppResource method\)](#), 101
[push_to \(tardis.tardis_portal.api.DataFileResource method\)](#), 215
[push_to \(tardis.tardis_portal.api.DatasetResource method\)](#), 216
 PushToSearchParameterizer (class in [tardis.apps.search.api](#)), 104
 PrettyJSONSerializer (class in [tardis.tardis_portal.api](#)), 220
[priority \(tardis.tardis_portal.models.datafile.DataFileObject attribute\)](#), 144
[priority \(tardis.tardis_portal.models.storage.StorageBox attribute\)](#), 176
[private_key \(tardis.apps.push_to.models.KeyPair attribute\)](#), 93
[process_exception \(\) \(tardis.tardis_portal.logging_middleware.LoggingMiddleware method\)](#), 230
[process_request \(\) \(tardis.tardis_portal.auth.token_auth.TokenAuthMiddleware method\)](#), 128
[process_response \(\) \(tardis.tardis_portal.logging_middleware.LoggingMiddleware method\)](#), 231
 ProxyingMetadataRegistry (class in [tardis.apps.oaipmh.server](#)), 82
 ProxyingServer (class in [tardis.apps.oaipmh.server](#)), 82, 243
[psm \(tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler attribute\)](#), 223
[public \(\) \(tardis.tardis_portal.managers.ExperimentManager method\)](#), 232
[public_access \(tardis.tardis_portal.models.experiment.Experiment attribute\)](#), 151
 PUBLIC_ACCESS_CHOICES ([tardis.tardis_portal.models.experiment.Experiment](#)

attribute), 148
 PUBLIC_ACCESS_EMBARGO
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 PUBLIC_ACCESS_FULL
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 public_access_implies_distribution()
 (*tardis.tardis_portal.models.experiment.Experiment*
 class method), 151
 PUBLIC_ACCESS_METADATA
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 PUBLIC_ACCESS_NONE
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 public_data() (in module *tardis.tardis_portal.views.pages*), 206
 public_download_allowed()
 (*tardis.tardis_portal.models.experiment.Experiment*
 method), 151
 public_key (*tardis.apps.push_to.models.KeyPair* at-
 tribute), 93
 public_key (*tardis.apps.sftp.models.SFTPPublicKey*
 attribute), 110
 PUBLICATION_DETAILS_SCHEMA
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 PUBLICATION_DRAFT_SCHEMA
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 PUBLICATION_SCHEMA_ROOT
 (*tardis.tardis_portal.models.experiment.Experiment*
 attribute), 148
 publish_public_expt_rifcs() (in module *tardis.tardis_portal.models.hooks*), 154
 PublishService (class in *tardis.tardis_portal.publish.publishservice*),
 180
 PublishServiceTestCase (class in *tardis.tardis_portal.tests.test_publishservice*),
 200
 PushToConfig (class in *tardis.apps.push_to.apps*), 90
 put_detail() (*tardis.tardis_portal.api.DataFileResource*
 method), 215
 queryset (*tardis.apps.s3utils.api.ReplicaAppResource.Meta*
 attribute), 101
 queryset (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta*
 attribute), 108
 queryset (*tardis.tardis_portal.api.DatafileParameterResource.Meta*
 attribute), 215
 queryset (*tardis.tardis_portal.api.DatafileParameterSetResource.Meta*
 attribute), 215
 queryset (*tardis.tardis_portal.api.DataFileResource.Meta*
 attribute), 214
 queryset (*tardis.tardis_portal.api.DatasetParameterResource.Meta*
 attribute), 215
 queryset (*tardis.tardis_portal.api.DatasetParameterSetResource.Meta*
 attribute), 216
 queryset (*tardis.tardis_portal.api.DatasetResource.Meta*
 attribute), 216
 queryset (*tardis.tardis_portal.api.ExperimentAuthorResource.Meta*
 attribute), 216
 queryset (*tardis.tardis_portal.api.ExperimentParameterResource.Meta*
 attribute), 216
 queryset (*tardis.tardis_portal.api.ExperimentParameterSetResource.Meta*
 attribute), 217
 queryset (*tardis.tardis_portal.api.ExperimentResource.Meta*
 attribute), 217
 queryset (*tardis.tardis_portal.api.FacilityResource.Meta*
 attribute), 218
 queryset (*tardis.tardis_portal.api.GroupResource.Meta*
 attribute), 218
 queryset (*tardis.tardis_portal.api.InstrumentResource.Meta*
 attribute), 218
 queryset (*tardis.tardis_portal.api.LocationResource.Meta*
 attribute), 218
 queryset (*tardis.tardis_portal.api.ObjectACLResource.Meta*
 attribute), 219
 queryset (*tardis.tardis_portal.api.ParameterNameResource.Meta*
 attribute), 219
 queryset (*tardis.tardis_portal.api.ReplicaResource.Meta*
 attribute), 220
 queryset (*tardis.tardis_portal.api.SchemaResource.Meta*
 attribute), 221
 queryset (*tardis.tardis_portal.api.StorageBoxAttributeResource.Meta*
 attribute), 221
 queryset (*tardis.tardis_portal.api.StorageBoxOptionResource.Meta*
 attribute), 221
 queryset (*tardis.tardis_portal.api.StorageBoxResource.Meta*
 attribute), 221
 queryset (*tardis.tardis_portal.api.UserResource.Meta*
 attribute), 222
 queryset_pagination
 (*tardis.apps.search.documents.DataFileDocument.Django*
 attribute), 105
 quote() (in module *tardis.tardis_portal.tests.slapped*),
 193
 Q
 queryset (*tardis.apps.s3utils.api.ReplicaAppResource.Meta*
 attribute), 101
 queryset (*tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta*
 attribute), 108
 queryset (*tardis.tardis_portal.api.DatafileParameterResource.Meta*
 attribute), 215
 RANGE_COMPARISON (*tardis.tardis_portal.models.parameters.Parameter*
 attribute), 168
 name_id
 ConnectEduPersonTargetedID
 (*tardis.tardis_portal.models.access_control.UserProfile*
 attribute), 139

<code>rcauth()</code>	(in module <code>tardis.tardis_portal.views.authentication</code>), 202	<code>RemovedInMyTardis43Warning</code> , 223	<code>render()</code> (tardis.tardis_portal.forms.NoInput method), 228
<code>read_detail()</code> (tardis.apps.sftp.api.SFTPAuthorization method), 108	<code>render()</code> (tardis.tardis_portal.templatetags.capture.CaptureNode method), 181		
<code>read_detail()</code> (tardis.tardis_portal.api.ACLAuthorization method), 214	<code>render()</code> (tardis.tardis_portal.templatetags.dynurl.DynUrlNode method), 182		
<code>read_list()</code> (tardis.apps.sftp.api.SFTPAuthorization method), 108	<code>render()</code> (tardis.tardis_portal.widgets.CommaSeparatedInput method), 235		
<code>read_list()</code> (tardis.tardis_portal.api.ACLAuthorization method), 214	<code>render()</code> (tardis.tardis_portal.widgets.Label method), 235		
<code>readMetadata()</code> (tardis.apps.oaipmh.server.ProxyingMetadataRegistry method), 82	<code>render_error_message()</code> (in module <code>tardis.apps.push_to.views</code>), 98		
<code>redirect_back_with_error()</code> (in module <code>tardis.tardis_portal.shortcuts</code>), 234	<code>render_error_message()</code> (in module <code>tardis.tardis_portal.shortcuts</code>), 234		
<code>RegisterExperimentForm</code> (class in <code>tardis.tardis_portal.forms</code>), 228	<code>RENDER_IMAGE_DATASET_SIZE_LIMIT</code> (in module <code>tardis.default_settings.frontend</code>), 120		
<code>registerReader()</code> (tardis.apps.oaipmh.server.ProxyingMetadataRegistry method), 82	<code>RENDER_IMAGE_SIZE_LIMIT</code> (in module <code>tardis.default_settings.frontend</code>), 121		
<code>registerWriter()</code> (tardis.apps.oaipmh.server.ProxyingMetadataRegistry method), 82	<code>register_cache()</code> (in module <code>tardis.tardis_portal.util</code>), 235		
<code>REGISTRATION_OPEN</code> (in module <code>tardis.default_settings.auth</code>), 118	<code>render_public_access_badge()</code> (in module <code>tardis.tardis_portal.util</code>), 235		
<code>registration_processor()</code> (in module <code>tardis.tardis_portal.context_processors</code>), 222	<code>render_response_index()</code> (in module <code>tardis.tardis_portal.shortcuts</code>), 234		
<code>RegistrationForm</code> (class in <code>tardis.tardis_portal.forms</code>), 229	<code>render_success_message()</code> (in module <code>tardis.apps.push_to.views</code>), 98		
<code>related_models</code> (tardis.apps.search.documents.DataFileDocument attribute), 105	<code>render_to_file()</code> (in module <code>tardis.tardis_portal.shortcuts</code>), 234		
<code>related_models</code> (tardis.apps.search.documents.DatasetDocument attribute), 105	<code>replaces</code> (tardis.tardis_portal.migrations.0001_squashed_0011_auto_2013_03_11_17_00 migration), 131		
<code>related_models</code> (tardis.apps.search.documents.ExperimentDocument attribute), 106	<code>ReplicaAppResource</code> (class in <code>tardis.apps.s3utils.api</code>), 101		
<code>RelatedInfoForm</code> (class in <code>tardis.apps.related_info.forms</code>), 100	<code>ReplicaAppResource.Meta</code> (class in <code>tardis.apps.s3utils.api</code>), 101		
<code>remote_hosts</code> (tardis.apps.push_to.models.Credential attribute), 91	<code>ReplicaResource</code> (class in <code>tardis.tardis_portal.api</code>), 220		
<code>remote_user</code> (tardis.apps.push_to.models.Credential attribute), 91	<code>ReplicaResource.Meta</code> (class in <code>tardis.tardis_portal.api</code>), 220		
<code>RemoteHost</code> (class in <code>tardis.apps.push_to.models</code>), 94	<code>ReplicaResourceTest</code> (class in <code>tardis.tardis_portal.tests.api.test_replica_resource</code>), 187		
<code>RemoteHost.DoesNotExist</code> , 95	<code>REQUIRE_DATAFILE_CHECKSUMS</code> (tardis.default_settings attribute), 46		
<code>RemoteHost.MultipleObjectsReturned</code> , 95	<code>REQUIRE_DATAFILE_SIZES</code> (tardis.default_settings attribute), 46		
<code>RemoteHostAdmin</code> (class in <code>tardis.apps.push_to.models</code>), 96	<code>REQUIRE_SSL_TO_GENERATE_KEY</code> (in module <code>tardis.apps.sftp.default_settings</code>), 109		
<code>remove_auth_method()</code> (in module <code>tardis.tardis_portal.auth.authentication</code>), 123	<code>REQUIRE_VALIDATION_ON_INGESTION</code> (tardis.default_settings attribute), 46		
<code>remove_csrf_token()</code> (in module <code>tardis.tardis_portal.views.utils</code>), 208	<code>requires_admin_approval()</code> (in module <code>tardis.apps.social_auth.auth.social_auth</code>), 117		
<code>remove_licenses()</code> (in module <code>tardis.tardis_portal.migrations.0017_add_cc_licenses</code>), 134	<code>resource_name</code> (tardis.apps.s3utils.api.ReplicaAppResource.Meta attribute), 101		
<code>RemovedInMyTardis42Warning</code> , 223			

[attribute](#)), 101
[resource_name](#) ([tardis.apps.search.api.AdvanceSearchAppResourceMeta](#) [class in](#) [tardis.apps.oaipmh.provider.experiment](#)),
[attribute](#)), 104
[resource_name](#) ([tardis.apps.search.api.SearchAppResourceMeta](#) [class in](#) [tardis.apps.oaipmh.provider.experiment](#)),
[attribute](#)), 104
[resource_name](#) ([tardis.apps.sftp.api.SFTPPublicKeyAppResourceMeta](#) [class in](#) [tardis.apps.oaipmh.provider.experiment](#)),
[attribute](#)), 108
[resource_name](#) ([tardis.tardis_portal.api.DataFileResourceMeta](#) [class in](#) [tardis.tardis_portal.publish.provider.rifcsprovider](#)),
[attribute](#)), 214
[restart](#) () ([tardis.tardis_portal.tests.slapd.Slapd](#) [class in](#) [tardis.apps.related_info.tests.test_oaipmh](#)),
[method](#)), 192
[RestfulExperimentParameterSet](#) ([class in](#) [tardis.tardis_portal.shortcuts](#)), 234
[retrieve_access_list_group_readonly](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)),
203
[retrieve_access_list_user_readonly](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)),
203
[retrieve_group_list](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)),
203
[retrieve_group_list_by_user](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)), 203
[retrieve_group_userlist_readonly](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)),
203
[retrieve_licenses](#) () ([in module](#) [tardis.tardis_portal.views.ajax_json](#)), 202
[retrieve_owned_exps_list](#) () ([in module](#) [tardis.tardis_portal.views.ajax_pages](#)), 202
[retrieve_shared_exps_list](#) () ([in module](#) [tardis.tardis_portal.views.ajax_pages](#)), 202
[retrieve_user_list](#) () ([in module](#) [tardis.tardis_portal.views.authorisation](#)),
203
[return_response_error](#) () ([in module](#) [tardis.tardis_portal.shortcuts](#)), 234
[return_response_error_message](#) () ([in module](#) [tardis.tardis_portal.shortcuts](#)), 234
[return_response_not_found](#) () ([in module](#) [tardis.tardis_portal.shortcuts](#)), 234
[REUSE_DATASET_STORAGE_BOX](#) ([in module](#) [tardis.default_settings.storage](#)), 122
[reverse_func](#) () ([in module](#) [tardis.tardis_portal.migrations.0017_add_cc_licenses](#)),
134
[RFC](#)
[RFC 3339](#), 233
[rfc3339](#) () ([in module](#) [tardis.tardis_portal.rfc3339](#)),
233
[RifCsExperimentProvider](#) ([class in](#) [tardis.apps.oaipmh.provider.experiment](#)),
79
[RifCsExperimentProvider.ExperimentWriter](#)
[RifCsExperimentProviderTestCase](#) ([class in](#) [tardis.apps.oaipmh.tests.provider.test_experiment](#)),
80
[RifCsProvider](#) ([class in](#) [tardis.tardis_portal.publish.provider.rifcsprovider](#)),
180
[RifCsTestCase](#) ([class in](#) [tardis.apps.related_info.tests.test_oaipmh](#)),
98
[RightsForm](#) ([class in](#) [tardis.tardis_portal.forms](#)), 229
[RightsForm.Meta](#) ([class in](#) [tardis.tardis_portal.forms](#)), 229
[RightsFormTestCase](#) ([class in](#) [tardis.tardis_portal.tests.test_forms](#)), 196
[RightsTestCase](#) ([class in](#) [tardis.tardis_portal.tests.views.test_auth_views](#)),
190
[RmExperimentTestCase](#) ([class in](#) [tardis.tardis_portal.tests.management.test_rmexperiment](#)),
189
[rollback_migration](#) () ([in module](#) [tardis.apps.openid_migration.utils](#)), 89

S

[S3_SIGNED_URL_EXPIRY](#) ([in module](#) [tardis.apps.s3utils.default_settings](#)), 102
[S3UtilsAppApiTestCase](#) ([class in](#) [tardis.apps.s3utils.tests.test_api](#)), 100
[S3UtilsAppChecksumsTestCase](#) ([class in](#) [tardis.apps.s3utils.tests.test_checksums](#)), 101
[S3UtilsConfig](#) ([class in](#) [tardis.apps.s3utils.apps](#)),
102
[S3UtilsConfigTestCase](#) ([class in](#) [tardis.apps.s3utils.tests.test_app_config](#)),
101
[safe](#) ([tardis.tardis_portal.models.experiment.Experiment](#) [attribute](#)), 151
[sanitize_html](#) () ([in module](#) [tardis.tardis_portal.templatetags.formfieldfilters](#)),
183
[save](#) () ([tardis.apps.push_to.models.KeyPair](#) [method](#)),
93
[save](#) () ([tardis.tardis_portal.forms.ExperimentForm](#) [method](#)), 227
[save](#) () ([tardis.tardis_portal.forms.RegistrationForm](#) [method](#)), 229
[save](#) () ([tardis.tardis_portal.models.access_control.UserAuthentication](#) [method](#)), 138
[save](#) () ([tardis.tardis_portal.models.datafile.DataFile](#) [method](#)), 142

[save \(\) \(tardis.tardis_portal.models.datafile.DataFileObjectSchemaManager \(class in tardis.tardis_portal.managers\)\), 233](#)
[save \(\) \(tardis.tardis_portal.models.datafile.DataFileObjectSchemaResource \(class in tardis.tardis_portal.api\), 220\)](#)
[save \(\) \(tardis.tardis_portal.models.dataset.DatasetSchemaResource \(class in tardis.tardis_portal.api\), 220\)](#)
[save \(\) \(tardis.tardis_portal.models.experiment.ExperimentSchemaResource \(class in tardis.tardis_portal.api\), 220\)](#)
[save \(\) \(tardis.tardis_portal.models.experiment.ExperimentSchemaResourceTest \(class in tardis.tardis_portal.tests.api.test_schema_resource\), 187\)](#)
[save \(\) \(tardis.tardis_portal.models.facility.FacilitySearchFields \(tardis.tardis_portal.admin.DatafileAdmin attribute\), 209\)](#)
[save \(\) \(tardis.tardis_portal.models.instrument.InstrumentSearchFields \(tardis.tardis_portal.admin.DatasetAdmin attribute\), 210\)](#)
[save \(\) \(tardis.tardis_portal.models.parameters.ExperimentParameterSearchFields \(tardis.tardis_portal.admin.ExperimentAdmin attribute\), 210\)](#)
[save \(\) \(tardis.tardis_portal.models.parameters.ParameterSetSearchFields \(tardis.tardis_portal.admin.FacilityAdmin attribute\), 210\)](#)
[save_datafile_add_form \(\) \(in module tardis.tardis_portal.forms\), 230](#)
[save_datafile_edit_form \(\) \(in module tardis.tardis_portal.forms\), 230](#)
[save_license \(\) \(tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler search_fields \(tardis.tardis_portal.admin.ObjectACLAdmin attribute\), 211\)](#)
[save_m2m \(\) \(tardis.tardis_portal.forms.ExperimentForm.FullExperimentForm search_fields \(tardis.tardis_portal.admin.ParameterNameAdmin attribute\), 211\)](#)
[save_with_random_token \(\) \(tardis.tardis_portal.models.token.Token search_fields \(tardis.tardis_portal.admin.SchemaAdmin attribute\), 212\)](#)
[Schema \(class in tardis.tardis_portal.models.parameters\), search_fields \(tardis.tardis_portal.admin.StorageBoxAdmin attribute\), 212\)](#)
[Schema \(class in tardis.tardis_portal.models.parameters\), search_fields \(tardis.tardis_portal.admin.UserAuthenticationAdmin attribute\), 214\)](#)
[schema \(tardis.tardis_portal.creativecommonshandler.CreativeCommonsHandler \(class in tardis.apps.search.api\), 104\)](#)
[schema \(tardis.tardis_portal.models.parameters.DatafileParameterSetAppResource.Meta \(class in tardis.apps.search.api\), 104\)](#)
[schema \(tardis.tardis_portal.models.parameters.DatasetParameterSetConfig \(class in tardis.apps.search.apps\), 105\)](#)
[schema \(tardis.tardis_portal.models.parameters.ExperimentParameterSet searchEntities \(\) \(tardis.tardis_portal.auth.authservice.AuthService attribute\), 125\)](#)
[schema \(tardis.tardis_portal.models.parameters.ExperimentParameterSet searchGroups \(\) \(tardis.tardis_portal.auth.authservice.AuthService attribute\), 125\)](#)
[schema \(tardis.tardis_portal.models.parameters.InstrumentParameterSet searchGroups \(\) \(tardis.tardis_portal.auth.interfaces.GroupProvider attribute\), 127\)](#)
[schema \(tardis.tardis_portal.models.parameters.ParameterName searchGroups \(\) \(tardis.tardis_portal.auth.localdb_auth.DjangoGroupProvider attribute\), 170\)](#)
[schema \(tardis.tardis_portal.models.parameters.ParameterSet searchGroups \(\) \(tardis.tardis_portal.auth.token_auth.TokenGroupProvider attribute\), 170\)](#)
[schema \(tardis.tardis_portal.shortcuts.RestfulExperimentParameterSet searchGroups \(\) \(tardis.tardis_portal.tests.test_authservice.MockGroupProvider attribute\), 234\)](#)
[Schema.DoesNotExist, 171](#)
[Schema.MultipleObjectsReturned, 171](#)
[Schema.UnsupportedType, 171](#)
[schema_id \(tardis.tardis_portal.models.parameters.ParameterNameUsers \(\) \(tardis.tardis_portal.auth.authservice.AuthService attribute\), 170\)](#)
[schema_id \(tardis.tardis_portal.models.parameters.ParameterSetUsers \(\) \(tardis.tardis_portal.auth.interfaces.UserProvider attribute\), 171\)](#)
[SchemaAdmin \(class in tardis.tardis_portal.admin\), SearchView \(class in tardis.apps.search.views\), 106](#)
[SECRET_KEY, 45](#)

send_admin_email() (in module attribute), 106
 tardis.apps.social_auth.auth.social_auth), setUp() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCa
 117 method), 80
 serializer(tardis.apps.search.api.AdvanceSearchAppResource.Meta(tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExpe
 attribute), 104 method), 81
 serializer(tardis.apps.search.api.SearchAppResource.Meta(tardis.apps.oaipmh.tests.test_oai.EndpointTestCase
 attribute), 104 method), 81
 serializer(tardis.tardis_portal.api.MyTardisModelResource.Meta(tardis.apps.openid_migration.tests.test_forms.OpenIDMigration
 attribute), 219 method), 84
 serializer(tardis.tardis_portal.api.UserResource.Meta(tardis.apps.openid_migration.tests.test_migration.OpenIDMigr
 attribute), 222 method), 85
 SerializerTest (class in setUp() (tardis.apps.openid_migration.tests.test_models.ModelTestCase
 tardis.tardis_portal.tests.api.test_serializer), method), 85
 187 setUp() (tardis.apps.openid_migration.tests.test_views.OpenIDMigration
 service (in module tardis.analytics.tracker), 75 method), 85
 session_ended() (tardis.apps.sftp.sftp.MyTSFTPServiceInterface(tardis.apps.push_to.tests.test_models.ModelsTestCase
 method), 112 method), 90
 session_started() setUp() (tardis.apps.related_info.tests.test_oaipmh.RifCSTestCase
 (tardis.apps.sftp.sftp.MyTSFTPServiceInterface method), 98
 method), 112 setUp() (tardis.apps.related_info.tests.tests.CreateTestCase
 method), 98
 set_debug() (tardis.tardis_portal.tests.slapi.Slapd setUp() (tardis.apps.related_info.tests.tests.DeleteTestCase
 method), 192 method), 99
 set_dn_suffix() (tardis.tardis_portal.tests.slapi.Slapd setUp() (tardis.apps.related_info.tests.tests.GetTestCase
 method), 192 method), 99
 set_param() (tardis.tardis_portal.ParameterSetManager.ParameterSetManager.setUp() (tardis.apps.related_info.tests.tests.ListTestCase
 method), 208 method), 99
 set_param_list() (tardis.tardis_portal.ParameterSetManager.ParameterSetManager.setUp() (tardis.apps.related_info.tests.tests.TabTestCase
 method), 209 method), 99
 set_params_from_dict() setUp() (tardis.apps.related_info.tests.tests.UpdateTestCase
 (tardis.tardis_portal.ParameterSetManager.ParameterSetManager method), 99
 method), 209
 set_port() (tardis.tardis_portal.tests.slapi.Slapd setUp() (tardis.apps.s3utils.tests.test_api.S3UtilsAppApiTestCase
 method), 193 method), 100
 set_root_cn() (tardis.tardis_portal.tests.slapi.Slapd setUp() (tardis.apps.s3utils.tests.test_checksums.S3UtilsAppChecksumsT
 method), 193 method), 101
 set_root_password() setUp() (tardis.apps.search.tests.test_api.SimpleSearchTest
 (tardis.tardis_portal.tests.slapi.Slapd method), method), 103
 193 setUp() (tardis.apps.search.tests.test_index.IndexExperimentTestCase
 method), 103
 set_slapi_debug_level() setUp() (tardis.apps.sftp.sftp.MyTSFTPRequestHandler
 (tardis.tardis_portal.tests.slapi.Slapd method), method), 111
 193
 set_tmpdir() (tardis.tardis_portal.tests.slapi.Slapd setUp() (tardis.apps.sftp.tests.test_sftp.SFTPTTest
 method), 193 method), 107
 set_token() (in module setUp() (tardis.tardis_portal.tests.api.MyTardisResourceTestCase
 tardis.apps.push_to.oauth_tokens), 96 method), 188
 set_value() (tardis.tardis_portal.models.parameters.Parameter method) (tardis.tardis_portal.tests.api.test_datafile_resource.DataFileRes
 method), 167 method), 184
 setPost() (tardis.tardis_portal.tests.test_authservice.MockRequest(tardis.tardis_portal.tests.api.test_dataset_metadata_resources.L
 method), 194 method), 185
 settings(tardis.apps.search.documents.DataFileDocumentIndex) (tardis.tardis_portal.tests.api.test_dataset_resource.DatasetReso
 attribute), 105 method), 185
 settings(tardis.apps.search.documents.DatasetDocumentIndex) (tardis.tardis_portal.tests.api.test_experiment_resource.Experim
 attribute), 105 method), 186
 settings(tardis.apps.search.documents.ExperimentDocumentIndex) (tardis.tardis_portal.tests.api.test_schema_resource.SchemaReso
 method), 186

method), 187

setUp () (tardis.tardis_portal.tests.management.test_collectstatic.CollectStaticTest method), 188

setUp () (tardis.tardis_portal.tests.management.test_dumpschemas.DumpSchemasTestCase method), 189

setUp () (tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase method), 193

setUp () (tardis.tardis_portal.tests.test_authorisation.ObjectACLTest method), 193

setUp () (tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase method), 194

setUp () (tardis.tardis_portal.tests.test_copy_move.CopyMoveTestCase method), 195

setUp () (tardis.tardis_portal.tests.test_download.DownloadTestCase method), 195

setUp () (tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTestCase method), 195

setUp () (tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase method), 196

setUp () (tardis.tardis_portal.tests.test_forms.RightsFormTestCase method), 196

setUp () (tardis.tardis_portal.tests.test_iiif.ExtraTestCases method), 196

setUp () (tardis.tardis_portal.tests.test_iiif.Level0TestCase method), 196

setUp () (tardis.tardis_portal.tests.test_iiif.Level1TestCase method), 197

setUp () (tardis.tardis_portal.tests.test_iiif.Level2TestCase method), 197

setUp () (tardis.tardis_portal.tests.test_ldap.LDAPTest method), 197

setUp () (tardis.tardis_portal.tests.test_models.ModelTestCase method), 198

setUp () (tardis.tardis_portal.tests.test_parameters.ParametersTestCase method), 198

setUp () (tardis.tardis_portal.tests.test_parametersets.EditableSetTestCase method), 199

setUp () (tardis.tardis_portal.tests.test_parametersets.ParametersetManagerTestCase method), 199

setUp () (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase method), 200

setUp () (tardis.tardis_portal.tests.test_storage.ModelTestCase method), 200

setUp () (tardis.tardis_portal.tests.test_tar_download.TarDownloadTestCase method), 200

setUp () (tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase method), 200

setUp () (tardis.tardis_portal.tests.test_tokens.TokenTestCase method), 201

setUp () (tardis.tardis_portal.tests.views.test_auth_views.UserGroupListTestCase method), 190

setUp () (tardis.tardis_portal.tests.views.test_auth_views.UserListTestCase method), 190

setUp () (tardis.tardis_portal.tests.views.test_contextual_views.ContextualViewTest method), 190

setUp () (tardis.tardis_portal.tests.views.test_experiment_views.ExperimentListTestCase method), 190

setUp () (tardis.tardis_portal.tests.views.test_template_contexts.ExperimentTemplateContextTestCase method), 191

setUp () (tardis.tardis_portal.tests.views.test_template_contexts.ViewTemplateContextTestCase method), 191

setUp () (tardis.tardis_portal.tests.views.test_upload_views.UploadTestCase method), 191

setUp () (in module tardis.apps.sftp.views), 116

setUp () (in module tardis.apps.sftp.views), 116

SFTP_USERNAME_ATTRIBUTE (in module tardis.apps.sftp.default_settings), 109

SFTPAuthorization (class in tardis.apps.sftp.models), 108

SFTPConfig (class in tardis.apps.sftp.apps), 108

SFTPOverviewTestCase (class in tardis.apps.sftp.tests.test_sftp), 107

SFTTPublicKey (class in tardis.apps.sftp.models), 109

SFTTPublicKey.DoesNotExist, 109

SFTTPublicKey.MultipleObjectsReturned, 110

SFTTPublicKeyAppResource (class in tardis.apps.sftp.api), 108

SFTTPublicKeyAppResource.Meta (class in tardis.apps.sftp.api), 108

SFTPTest (class in tardis.apps.sftp.tests.test_sftp), 107

sha512sum (tardis.tardis_portal.models.datafile.DataFile attribute), 142

share () (in module tardis.tardis_portal.views.authorisation), 203

setUp () (in module tardis.tardis_portal.views.pages), 206

setUp () (tardis.tardis_portal.managers.ExperimentManager method), 232

setUp () (in module tardis.apps.push_to.utils), 97

setUp () (tardis.apps.sftp.sftp.MyTSFTPTCPServer method), 113

sign_certificate () (in module tardis.apps.push_to.ssh_authz), 96

simple_search_public_data () (in module tardis.apps.search.api), 104

SimpleSearchTest (class in tardis.apps.search.tests.test_api), 103

SINGLE_SEARCH_ENABLED (in module tardis.apps.push_to.settings.search), 121

single_search_processor () (in module tardis.tardis_portal.context_processors), 222

setUp () (in module tardis.tardis_portal.views.ContextualViewTest) (in module

[tardis.tardis_portal.views.pages](#)), 206
[site_settings\(\)](#) (in module [tardis.tardis_portal.views.machine](#)), 204
[SITE_TITLE](#) (in module [tardis.default_settings.site_customisations](#)), 122
[size](#) ([tardis.tardis_portal.models.datafile.DataFile](#) attribute), 142
[size\(\)](#) (in module [tardis.tardis_portal.templatetags.formfield_filters](#)), 183
[Slapd](#) (class in [tardis.tardis_portal.tests.slapd](#)), 192
[SocialAuthConfig](#) (class in [tardis.apps.social_auth.apps](#)), 117
[Span](#) (class in [tardis.tardis_portal.widgets](#)), 235
[split_path\(\)](#) (in module [tardis.tardis_portal.util](#)), 235
[SPONSORED_TEXT](#) (in module [tardis.default_settings.site_customisations](#)), 122
[start\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#) method), 193
[start_server\(\)](#) (in module [tardis.apps.sftp.sftp](#)), 115
[start_time](#) ([tardis.tardis_portal.models.experiment.Experiment](#) attribute), 151
[started\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#) method), 193
[stat\(\)](#) ([tardis.apps.sftp.sftp.MyTSFTPHandle](#) method), 111
[stat\(\)](#) ([tardis.apps.sftp.sftp.MyTSFTPServerInterface](#) method), 112
[STATIC_ROOT](#) ([tardis.default_settings](#) attribute), 48
[STATIC_URL](#) ([tardis.default_settings](#) attribute), 48
[StaticField](#) (class in [tardis.tardis_portal.forms](#)), 230
[stats\(\)](#) (in module [tardis.tardis_portal.views.pages](#)), 207
[status](#) ([tardis.tardis_portal.models.datafile.DataFile](#) attribute), 142
[status](#) ([tardis.tardis_portal.models.storage.StorageBox](#) attribute), 176
[status_code](#) ([tardis.tardis_portal.views.utils.HttpResponseMethodNotAllowed](#) attribute), 208
[status_code](#) ([tardis.tardis_portal.views.utils.HttpResponseServerError](#) attribute), 208
[stop\(\)](#) ([tardis.tardis_portal.tests.slapd.Slapd](#) method), 193
[storage_box](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#) attribute), 144
[storage_box](#) ([tardis.tardis_portal.models.parameters.DataFileParameterSet](#) attribute), 159
[storage_box](#) ([tardis.tardis_portal.models.parameters.DatasetParameterSet](#) attribute), 161
[storage_box](#) ([tardis.tardis_portal.models.parameters.ExperimentParameterSet](#) attribute), 163
[storage_box](#) ([tardis.tardis_portal.models.parameters.InstrumentParameterSet](#) attribute), 166
[storage_box](#) ([tardis.tardis_portal.models.parameters.ParameterSet](#) attribute), 171
[storage_box](#) ([tardis.tardis_portal.models.storage.StorageBoxAttribute](#) attribute), 177
[storage_box](#) ([tardis.tardis_portal.models.storage.StorageBoxOption](#) attribute), 178
[storage_box_id](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#) attribute), 145
[storage_box_id](#) ([tardis.tardis_portal.models.storage.StorageBoxAttribute](#) attribute), 177
[storage_box_id](#) ([tardis.tardis_portal.models.storage.StorageBoxOption](#) attribute), 178
[storage_type](#) ([tardis.tardis_portal.models.datafile.DataFileObject](#) attribute), 145
[storage_type](#) ([tardis.tardis_portal.models.storage.StorageBox](#) attribute), 176
[StorageBox](#) (class in [tardis.tardis_portal.models.storage](#)), 173
[StorageBox.DoesNotExist](#), 173
[StorageBox.MultipleObjectsReturned](#), 173
[StorageBoxAdmin](#) (class in [tardis.tardis_portal.admin](#)), 212
[StorageBoxAttribute](#) (class in [tardis.tardis_portal.models.storage](#)), 176
[StorageBoxAttribute.DoesNotExist](#), 177
[StorageBoxAttribute.MultipleObjectsReturned](#), 177
[StorageBoxAttributeInline](#) (class in [tardis.tardis_portal.admin](#)), 212
[StorageBoxAttributeInlineForm](#) (class in [tardis.tardis_portal.admin](#)), 212
[StorageBoxAttributeInlineForm.Meta](#) (class in [tardis.tardis_portal.admin](#)), 212
[StorageBoxAttributeResource](#) (class in [tardis.tardis_portal.api](#)), 221
[StorageBoxAttributeResource.Meta](#) (class in [tardis.tardis_portal.api](#)), 221
[StorageBoxAttributeResourceTest](#) (class in [tardis.tardis_portal.tests.api.test_storagebox_resources](#)), 187
[StorageBoxForm](#) (class in [tardis.tardis_portal.admin](#)), 212
[StorageBoxForm.Meta](#) (class in [tardis.tardis_portal.admin](#)), 213
[StorageBoxOption](#) (class in [tardis.tardis_portal.models.storage](#)), 177
[StorageBoxOption.DoesNotExist](#), 177
[StorageBoxOption.MultipleObjectsReturned](#), 177
[StorageBoxOptionInline](#) (class in [tardis.tardis_portal.admin](#)), 213
[StorageBoxOptionInlineForm](#) (class in [tardis.tardis_portal.admin](#)), 213

`tardis.tardis_portal.admin`), 213
`StorageBoxOptionInlineForm.Meta` (class in `tardis.tardis_portal.admin`), 213
`StorageBoxOptionResource` (class in `tardis.tardis_portal.api`), 221
`StorageBoxOptionResource.Meta` (class in `tardis.tardis_portal.api`), 221
`StorageBoxOptionResourceTest` (class in `tardis.tardis_portal.tests.api.test_storagebox_resources`), 187
`StorageBoxResource` (class in `tardis.tardis_portal.api`), 221
`StorageBoxResource.Meta` (class in `tardis.tardis_portal.api`), 221
`StorageBoxResourceTest` (class in `tardis.tardis_portal.tests.api.test_storagebox_resources`), 187
`streaming_download_datafiles()` (in module `tardis.tardis_portal.download`), 224
`STRING` (`tardis.tardis_portal.models.parameters.ParameterName` attribute), 168
`STRING` (`tardis.tardis_portal.models.storage.StorageBoxOption` attribute), 178
`string_value` (`tardis.tardis_portal.models.parameters.Parameter` attribute), 167
`subtype` (`tardis.tardis_portal.models.parameters.Schema` attribute), 173
`suite()` (in module `tardis.tardis_portal.tests.tests`), 201
`sum_sizes()` (`tardis.tardis_portal.models.datafile.DataFile` class method), 142
`supports_anonymous_user` (`tardis.tardis_portal.auth.authorisation.ACLAwareBackend` attribute), 124
`supports_object_permissions` (`tardis.tardis_portal.auth.authorisation.ACLAwareBackend` attribute), 124
`SYSTEM_OWNED` (`tardis.tardis_portal.models.access_control.ObjectACL` attribute), 136
`system_owned_groups()` (`tardis.tardis_portal.managers.ExperimentManager` method), 232

T
`TabTestCase` (class in `tardis.apps.related_info.tests.tests`), 99
`tag` (`tardis.tardis_portal.widgets.Label` attribute), 235
`tag` (`tardis.tardis_portal.widgets.Span` attribute), 235
`TAPE` (`tardis.tardis_portal.models.storage.StorageBox` attribute), 173
`tardis` (module), 238
`tardis.analytics` (module), 76
`tardis.analytics.apps` (module), 75
`tardis.analytics.ga` (module), 75
`tardis.analytics.tracker` (module), 75

`tardis.app_config` (module), 237
`tardis.apps` (module), 117
`tardis.apps.deep_storage_download_mapper` (module), 76
`tardis.apps.deep_storage_download_mapper.mapper` (module), 76
`tardis.apps.deep_storage_download_mapper.urls` (module), 76
`tardis.apps.dl_mapper_df_dir_only` (module), 77
`tardis.apps.dl_mapper_df_dir_only.mapper` (module), 76
`tardis.apps.dl_mapper_df_dir_only.urls` (module), 77
`tardis.apps.filepicker` (module), 77
`tardis.apps.filepicker.filepicker_settings` (module), 77
`tardis.apps.filepicker.urls` (module), 77
`tardis.apps.filepicker.utils` (module), 77
`tardis.apps.filepicker.views` (module), 77
`tardis.apps.oaipmh` (module), 84
`tardis.apps.oaipmh.models` (module), 82
`tardis.apps.oaipmh.provider` (module), 80
`tardis.apps.oaipmh.provider.base` (module), 77
`tardis.apps.oaipmh.provider.experiment` (module), 79
`tardis.apps.oaipmh.server` (module), 82
`tardis.apps.oaipmh.tests` (module), 82
`tardis.apps.oaipmh.tests.provider` (module), 81
`tardis.apps.oaipmh.tests.provider.test_base` (module), 80
`tardis.apps.oaipmh.tests.provider.test_experiment` (module), 81
`tardis.apps.oaipmh.tests.test_oai` (module), 81
`tardis.apps.oaipmh.urls` (module), 84
`tardis.apps.oaipmh.views` (module), 84
`tardis.apps.openid_migration` (module), 89
`tardis.apps.openid_migration.apps` (module), 85
`tardis.apps.openid_migration.context_processors` (module), 85
`tardis.apps.openid_migration.default_settings` (module), 86
`tardis.apps.openid_migration.email_text` (module), 86
`tardis.apps.openid_migration.forms` (module), 86
`tardis.apps.openid_migration.migration` (module), 86
`tardis.apps.openid_migration.migrations` (module), 84

[tardis.apps.openid_migration.migrations.0001_initial \(module\)](#), 84
[tardis.apps.openid_migration.migrations.0002_auto20150518_1953 \(module\)](#), 84
[tardis.apps.openid_migration.models \(module\)](#), 86
[tardis.apps.openid_migration.tasks \(module\)](#), 89
[tardis.apps.openid_migration.tests \(module\)](#), 85
[tardis.apps.openid_migration.tests.test_forms \(module\)](#), 84
[tardis.apps.openid_migration.tests.test_migrations \(module\)](#), 84
[tardis.apps.openid_migration.tests.test_models \(module\)](#), 85
[tardis.apps.openid_migration.tests.test_views \(module\)](#), 85
[tardis.apps.openid_migration.urls \(module\)](#), 89
[tardis.apps.openid_migration.user_menu_builder \(module\)](#), 89
[tardis.apps.openid_migration.utils \(module\)](#), 89
[tardis.apps.openid_migration.views \(module\)](#), 89
[tardis.apps.push_to \(module\)](#), 98
[tardis.apps.push_to.apps \(module\)](#), 90
[tardis.apps.push_to.exceptions \(module\)](#), 91
[tardis.apps.push_to.migrations \(module\)](#), 90
[tardis.apps.push_to.migrations.0001_initial \(module\)](#), 90
[tardis.apps.push_to.migrations.0002_auto20150518_1953 \(module\)](#), 90
[tardis.apps.push_to.models \(module\)](#), 91
[tardis.apps.push_to.oauth_tokens \(module\)](#), 96
[tardis.apps.push_to.ssh_authz \(module\)](#), 96
[tardis.apps.push_to.tasks \(module\)](#), 97
[tardis.apps.push_to.tests \(module\)](#), 90
[tardis.apps.push_to.tests.test_models \(module\)](#), 90
[tardis.apps.push_to.urls \(module\)](#), 97
[tardis.apps.push_to.utils \(module\)](#), 97
[tardis.apps.push_to.views \(module\)](#), 97
[tardis.apps.related_info \(module\)](#), 100
[tardis.apps.related_info.forms \(module\)](#), 100
[tardis.apps.related_info.models \(module\)](#), 100
[tardis.apps.related_info.settings \(module\)](#), 100
[tardis.apps.related_info.tests \(module\)](#), 99
[tardis.apps.related_info.tests.test_oaipmh \(module\)](#), 98
[tardis.apps.related_info.tests.tests \(module\)](#), 98
[tardis.apps.related_info.urls \(module\)](#), 100
[tardis.apps.related_info.views \(module\)](#), 100
[tardis.apps.s3utils \(module\)](#), 103
[tardis.apps.s3utils.api \(module\)](#), 101
[tardis.apps.s3utils.apps \(module\)](#), 102
[tardis.apps.s3utils.default_settings \(module\)](#), 102
[tardis.apps.s3utils.tests \(module\)](#), 101
[tardis.apps.s3utils.tests.test_api \(module\)](#), 100
[tardis.apps.s3utils.tests.test_app_config \(module\)](#), 101
[tardis.apps.s3utils.tests.test_checksums \(module\)](#), 101
[tardis.apps.s3utils.urls \(module\)](#), 102
[tardis.apps.s3utils.utils \(module\)](#), 102
[tardis.apps.search \(module\)](#), 106
[tardis.apps.search.api \(module\)](#), 103
[tardis.apps.search.apps \(module\)](#), 105
[tardis.apps.search.documents \(module\)](#), 105
[tardis.apps.search.tests \(module\)](#), 103
[tardis.apps.search.tests.test_api \(module\)](#), 103
[tardis.apps.search.tests.test_index \(module\)](#), 103
[tardis.apps.search.urls \(module\)](#), 106
[tardis.apps.search.views \(module\)](#), 106
[tardis.apps.sftp \(module\)](#), 116
[tardis.apps.sftp.admin \(module\)](#), 108
[tardis.apps.sftp.api \(module\)](#), 108
[tardis.apps.sftp.apps \(module\)](#), 108
[tardis.apps.sftp.default_settings \(module\)](#), 109
[tardis.apps.sftp.forms \(module\)](#), 109
[tardis.apps.sftp.management \(module\)](#), 107
[tardis.apps.sftp.management.commands \(module\)](#), 107
[tardis.apps.sftp.management.commands.sftpd \(module\)](#), 106
[tardis.apps.sftp.migrations \(module\)](#), 107
[tardis.apps.sftp.migrations.0001_initial \(module\)](#), 107
[tardis.apps.sftp.models \(module\)](#), 109
[tardis.apps.sftp.sftp \(module\)](#), 110
[tardis.apps.sftp.tests \(module\)](#), 107
[tardis.apps.sftp.tests.test_sftp \(module\)](#), 107
[tardis.apps.sftp.urls \(module\)](#), 115

[tardis.apps.sftp.user_menu_modifiers \(module\)](#), 115
[tardis.apps.sftp.views \(module\)](#), 116
[tardis.apps.social_auth \(module\)](#), 117
[tardis.apps.social_auth.apps \(module\)](#), 117
[tardis.apps.social_auth.auth \(module\)](#), 117
[tardis.apps.social_auth.auth.social_auth \(module\)](#), 116
[tardis.apps.social_auth.default_settings \(module\)](#), 117
[tardis.celery \(module\)](#), 238
[tardis.default_settings \(module\)](#), 122
[tardis.default_settings.admins \(module\)](#), 117
[tardis.default_settings.analytics \(module\)](#), 117
[tardis.default_settings.apps \(module\)](#), 117
[tardis.default_settings.auth \(module\)](#), 118
[tardis.default_settings.caches \(module\)](#), 118
[tardis.default_settings.celery_settings \(module\)](#), 118
[tardis.default_settings.custom_views \(module\)](#), 118
[tardis.default_settings.database \(module\)](#), 119
[tardis.default_settings.debug \(module\)](#), 119
[tardis.default_settings.downloads \(module\)](#), 119
[tardis.default_settings.email \(module\)](#), 120
[tardis.default_settings.filters \(module\)](#), 120
[tardis.default_settings.frontend \(module\)](#), 120
[tardis.default_settings.i18n \(module\)](#), 121
[tardis.default_settings.localisation \(module\)](#), 121
[tardis.default_settings.logging \(module\)](#), 121
[tardis.default_settings.middlewares \(module\)](#), 121
[tardis.default_settings.publication \(module\)](#), 121
[tardis.default_settings.search \(module\)](#), 121
[tardis.default_settings.sharing \(module\)](#), 121
[tardis.default_settings.site_customisation \(module\)](#), 122
[tardis.default_settings.static_files \(module\)](#), 122
[tardis.default_settings.storage \(module\)](#), 122
[tardis.default_settings.templates \(module\)](#), 122
[tardis.default_settings.uploads \(module\)](#), 122
[tardis.default_settings.urls \(module\)](#), 122
[tardis.tardis_portal \(module\)](#), 236, 238
[tardis.tardis_portal.admin \(module\)](#), 209
[tardis.tardis_portal.api \(module\)](#), 214
[tardis.tardis_portal.auth \(module\)](#), 129
[tardis.tardis_portal.auth.authentication \(module\)](#), 123
[tardis.tardis_portal.auth.authorisation \(module\)](#), 123
[tardis.tardis_portal.auth.authservice \(module\)](#), 124
[tardis.tardis_portal.auth.decorators \(module\)](#), 125
[tardis.tardis_portal.auth.fix_circular \(module\)](#), 126
[tardis.tardis_portal.auth.interfaces \(module\)](#), 127
[tardis.tardis_portal.auth.localdb_auth \(module\)](#), 128
[tardis.tardis_portal.auth.token_auth \(module\)](#), 128
[tardis.tardis_portal.auth.utils \(module\)](#), 129
[tardis.tardis_portal.constants \(module\)](#), 222
[tardis.tardis_portal.context_processors \(module\)](#), 222
[tardis.tardis_portal.creativecommons_handler \(module\)](#), 223
[tardis.tardis_portal.deprecations \(module\)](#), 223
[tardis.tardis_portal.download \(module\)](#), 224
[tardis.tardis_portal.email \(module\)](#), 224
[tardis.tardis_portal.errors \(module\)](#), 225
[tardis.tardis_portal.fields \(module\)](#), 225
[tardis.tardis_portal.forms \(module\)](#), 225
[tardis.tardis_portal.iiif \(module\)](#), 230
[tardis.tardis_portal.logging_middleware \(module\)](#), 230
[tardis.tardis_portal.management \(module\)](#), 131
[tardis.tardis_portal.management.commands \(module\)](#), 131
[tardis.tardis_portal.management.commands.createuser \(module\)](#), 129
[tardis.tardis_portal.management.commands.dumpschema \(module\)](#), 130
[tardis.tardis_portal.management.commands.loadschema \(module\)](#), 130

(module), 130
 tardis.tardis_portal.management.commands and experiments_portal.models.facility
 (module), 130 (module), 152
 tardis.tardis_portal.managers (module), tardis.tardis_portal.models.hooks (mod-
 231 ule), 154
 tardis.tardis_portal.migrations (module), tardis.tardis_portal.models.instrument
 135 (module), 154
 tardis.tardis_portal.migrations.0001_initi and tardis.tardis_portal.models.jti (module),
 (module), 131 155
 tardis.tardis_portal.migrations.0001_squashed and tardis.tardis_portal.models.license
 (module), 131 (module), 156
 tardis.tardis_portal.migrations.0002_auth and tardis.tardis_portal.models.parameters
 (module), 131 (module), 157
 tardis.tardis_portal.migrations.0003_auth and tardis.tardis_portal.models.storage
 (module), 131 (module), 173
 tardis.tardis_portal.migrations.0004_storage and tardis.tardis_portal.models.token (mod-
 (module), 132 ule), 178
 tardis.tardis_portal.migrations.0005_data and tardis.tardis_portal.models.tokenparameter
 (module), 132 (module), 208
 tardis.tardis_portal.migrations.0006_data and tardis.tardis_portal.models.tokenparameter
 (module), 132 (module), 180
 tardis.tardis_portal.migrations.0007_remove and tardis.tardis_portal.publish.provider
 (module), 132 (module), 180
 tardis.tardis_portal.migrations.0008_string and tardis.tardis_portal.publish.provider.rifcsprovider
 (module), 132 (module), 181
 tardis.tardis_portal.migrations.0009_auto_2016 and tardis.tardis_portal.publish.publishservice
 (module), 133 (module), 180
 tardis.tardis_portal.migrations.0010_auth and tardis.tardis_portal.rfc3339 (module), 233
 (module), 133 234
 tardis.tardis_portal.migrations.0011_auth and tardis.tardis_portal.signals (module), 234
 (module), 133 tardis.tardis_portal.storage (module), 180
 tardis.tardis_portal.migrations.0012_user and tardis.tardis_portal.storage.file_system
 (module), 133 (module), 180
 tardis.tardis_portal.migrations.0013_auth and tardis.tardis_portal.tasks (module), 234
 (module), 133 tardis.tardis_portal.templatetags (mod-
 tardis.tardis_portal.migrations.0014_auto_2018 and ule), 184
 (module), 133 tardis.tardis_portal.templatetags.approved_user_tag
 tardis.tardis_portal.migrations.0015_dataset and tardis.tardis_portal.templatetags.basiccomparisonf
 (module), 134 (module), 181
 tardis.tardis_portal.migrations.0016_add_time and tardis.tardis_portal.templatetags.bleach_tag
 (module), 134 (module), 181
 tardis.tardis_portal.migrations.0017_add_cc_li and tardis.tardis_portal.templatetags.capture
 (module), 134 (module), 181
 tardis.tardis_portal.migrations.0018_make_defa and tardis.tardis_portal.templatetags.default_box_status_online
 (module), 134 (module), 181
 tardis.tardis_portal.models (module), 179, (module), 182
 236, 238 tardis.tardis_portal.templatetags.dynurl
 tardis.tardis_portal.models.access_control (module), 182
 (module), 135 tardis.tardis_portal.templatetags.experiment_tags
 tardis.tardis_portal.models.datafile (module), 182
 (module), 140 tardis.tardis_portal.templatetags.experimentstats
 tardis.tardis_portal.models.dataset (module), 183
 (module), 145 tardis.tardis_portal.templatetags.facility_tags
 tardis.tardis_portal.models.experiment (module), 183

(module), 191	tearDown() (tardis.apps.s3utils.tests.test_checks.S3UtilsAppCheckSumTest), 101
tardis.tardis_portal.tests.views.test_upload_views (module), 191	tearDown() (tardis.tardis_portal.tests.api.test_dataset_metadata_resource.DatasetMetadataResourceTest), 185
tardis.tardis_portal.util (module), 234	tearDown() (tardis.tardis_portal.tests.api.test_schema_resource.SchemaResourceTest), 187
tardis.tardis_portal.views (module), 208, 236, 238	tearDown() (tardis.tardis_portal.tests.management.test_collectstatic.CollectorsTest), 188
tardis.tardis_portal.views.ajax_actions (module), 202	tearDown() (tardis.tardis_portal.tests.management.test_dumpschemas.DumpschemasTest), 189
tardis.tardis_portal.views.ajax_json (module), 202	tearDown() (tardis.tardis_portal.tests.test_authorisation.ObjectACLTest), 193
tardis.tardis_portal.views.ajax_pages (module), 202	tearDown() (tardis.tardis_portal.tests.test_authservice.AuthServiceTest), 194
tardis.tardis_portal.views.authentication (module), 202	tearDown() (tardis.tardis_portal.tests.test_copy_move.CopyMoveTestCase), 195
tardis.tardis_portal.views.authorisation (module), 203	tearDown() (tardis.tardis_portal.tests.test_download.DownloadTestCase), 195
tardis.tardis_portal.views.facilities (module), 203	tearDown() (tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownloadTest), 195
tardis.tardis_portal.views.images (module), 204	tearDown() (tardis.tardis_portal.tests.test_ldap.LDAPTest), 197
tardis.tardis_portal.views.machine (module), 204	tearDown() (tardis.tardis_portal.tests.test_parameters.ParametersTestCase), 198
tardis.tardis_portal.views.pages (module), 204	tearDown() (tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest), 199
tardis.tardis_portal.views.parameters (module), 207	tearDown() (tardis.tardis_portal.tests.test_parametersets.ParameterSetModificationTest), 199
tardis.tardis_portal.views.upload (module), 207	tearDown() (tardis.tardis_portal.tests.test_storage.ModelTestCase), 200
tardis.tardis_portal.views.utils (module), 208	tearDown() (tardis.tardis_portal.tests.test_tar_download.TarDownloadTest), 200
tardis.tardis_portal.widgets (module), 235	tearDown() (tardis.tardis_portal.tests.test_tokens.TokenTestCase), 201
tardis.tardis_portal.xmlwriter (module), 235	tearDown() (tardis.tardis_portal.tests.views.test_auth_views.UserGroupTest), 190
tardis.test_on_mysql_settings (module), 238	tearDown() (tardis.tardis_portal.tests.views.test_auth_views.UserListTest), 190
tardis.test_on_postgresql_settings (module), 238	tearDown() (tardis.tardis_portal.tests.views.test_contextual_views.ContextualViewsTest), 190
tardis.test_settings (module), 238	tearDown() (tardis.tardis_portal.tests.views.test_template_contexts.ExperimentTemplateContextTest), 191
tardis.views (module), 238	tearDown() (tardis.tardis_portal.tests.views.test_template_contexts.ViewTemplateContextTest), 191
TarDownloadTestCase (class in tardis.tardis_portal.tests.test_tar_download), 200	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tarinfo_for_df() (tardis.tardis_portal.download.UncachedTarStream), 224	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tearDown() (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTest), 80	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tearDown() (tardis.apps.oaipmh.tests.provider.test_experiment.ExperimentProviderTest), 81	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tearDown() (tardis.apps.oaipmh.tests.provider.test_experiment.ExperimentProviderTest), 81	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tearDown() (tardis.apps.oaipmh.tests.test_oai.EndpointTest), 81	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191
tearDown() (tardis.apps.s3utils.tests.test_api.S3UtilsAppAPITest), 100	tearDown() (tardis.tardis_portal.tests.views.test_upload_views.UploadTest), 191

`template_name` (*tardis.tardis_portal.views.pages.IndexView*, `test_create_index()`
`attribute`), 206 (*tardis.apps.search.tests.test_index.IndexExperimentTestCase*
`TEMPORARY` (*tardis.tardis_portal.models.storage.StorageBox*, `method`), 103
`attribute`), 173 (`test_create_token()`
`test_add_datafile_params()` (*tardis.tardis_portal.tests.test_tokens.TokenTestCase*
`(tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest, 201
method), 199 (test_create_user_automatically_generate_api_key()
test_add_dataset_params() (tardis.tardis_portal.tests.test_models.ModelTestCase
(tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest, 198
method), 199 (test_credential_generation()
test_add_experiment_params() (tardis.apps.push_to.tests.test_models.ModelsTestCase
(tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest, 190
method), 199 (test_cyberduck_connection_window()
test_advance_search_authenticated_user() (tardis.apps.sftp.tests.test_sftp.SFTPTest
(tardis.apps.search.tests.test_api.SimpleSearchTest, method), 107
method), 103 (test_datafile() (tardis.tardis_portal.tests.test_models.ModelTestCase
test_advance_search_unauthenticated_user() method), 198
(tardis.apps.search.tests.test_api.SimpleSearchTest, test_dataset() (tardis.tardis_portal.tests.test_models.ModelTestCase
method), 103 method), 198
test_apikey_authentication() (test_dataset_json()
(tardis.tardis_portal.tests.api.test_auth.MyTardisAuthenticationTest, tardis.tardis_portal.tests.views.test_experiment_views.Experiment
method), 184 method), 191
test_app_config() (test_dataset_view()
(tardis.apps.s3utils.tests.test_app_config.S3UtilsConfigTest, tardis.tardis_portal.tests.views.test_template_contexts.ViewTemp
method), 101 method), 191
test_authenticate() (test_debug_serializer()
(tardis.tardis_portal.tests.test_ldap.LDAPTest, tardis.tardis_portal.tests.api.test_serializer.SerializerTest
method), 197 method), 187
test_authors() (tardis.tardis_portal.tests.test_models.ModelTestCase, test_expiry()
method), 198 (tardis.tardis_portal.tests.test_tokens.TokenTestCase
test_bad_credentials() method), 201
(tardis.tardis_portal.tests.api.test_auth.MyTardisAuthenticationTest, test_get_dfo_without_uri()
method), 184 (tardis.tardis_portal.tests.test_models.ModelTestCase
test_cache() (tardis.tardis_portal.tests.test_copy_move.CopyMoveTest, 198
method), 195 (test_details_display()
test_checksums() (tardis.apps.s3utils.tests.test_checksums.S3UtilsAppChecksumsTest, tardis.tardis_portal.tests.views.test_contextual_views.Contextual
method), 101 method), 190
test_collectstatic() (test_djangoauth()
(tardis.tardis_portal.tests.management.test_collectstatic.CollectStaticTest, tardis.tardis_portal.tests.test_authentication.AuthenticationTest
method), 188 method), 193
test_copy() (tardis.tardis_portal.tests.test_copy_move.CopyMoveTest, test_authentication()
method), 195 (tardis.apps.openid_migration.tests.test_migration.OpenIDMigra
test_create_and_edit() method), 85
(tardis.tardis_portal.tests.views.test_experiment_views.ExperimentTestCase, test_key()
method), 191 (tardis.tardis_portal.tests.test_download_apikey.ApiKeyDownload
test_create_dataset_pset() method), 195
(tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterSetResourceTest
method), 185 (tardis.apps.s3utils.tests.test_api.S3UtilsAppApiTestCase
test_create_dataset_pset_no_auth() method), 100
(tardis.tardis_portal.tests.api.test_dataset_metadata_resources.DatasetParameterSetResourceTest
method), 185 (tardis.tardis_portal.tests.api.test_datafile_resource.DataFileReso
test_create_df_for_staging() method), 184
(tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest, test_file_params()
method), 184 (tardis.tardis_portal.tests.test_parametersets.EditParameterSetTest`

`method`), 199
`test_edit_dataset_params()`
 (`tardis.tardis_portal.tests.test_parametersets.EditParameterSetTestCase`
`method`), 199
`test_edit_experiment_params()`
 (`tardis.tardis_portal.tests.test_parametersets.EditParameterSetTestCase`
`method`), 199
`test_ensures_suitable_license()`
 (`tardis.tardis_portal.tests.test_forms.RightsFormTestCase`
`method`), 196
`test_existing_parameterset()`
 (`tardis.tardis_portal.tests.test_parametersets.ParameterSetTestCase`
`method`), 199
`test_experiment()`
 (`tardis.tardis_portal.tests.test_models.ModelTestCase`
`method`), 198
`test_experiment_parameter_get()`
 (`tardis.tardis_portal.tests.test_parameters.ParametersTestCase`
`method`), 198
`test_experiment_view()`
 (`tardis.tardis_portal.tests.views.test_template_contexts.ViewTemplateContextsTestCase`
`method`), 191
`test_facility_overview_datafile_list()`
 (`tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase`
`method`), 196
`test_facility_overview_experiments()`
 (`tardis.tardis_portal.tests.test_facility_overview.FacilityOverviewTestCase`
`method`), 196
`test_file_upload()`
 (`tardis.tardis_portal.tests.views.test_upload_views.UploadViewTestCase`
`method`), 191
`test_get_allowed_signing_services()`
 (`tardis.apps.push_to.tests.test_models.ModelsTestCase`
`method`), 90
`test_get_dataset_files()`
 (`tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTestCase`
`method`), 185
`test_get_dataset_filter_instrument()`
 (`tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTestCase`
`method`), 185
`test_get_dataset_no_instrument()`
 (`tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTestCase`
`method`), 185
`test_get_dataset_with_instrument()`
 (`tardis.tardis_portal.tests.api.test_dataset_resource.DatasetResourceTestCase`
`method`), 185
`test_get_experiment()`
 (`tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTestCase`
`method`), 186
`test_get_experiment_author()`
 (`tardis.tardis_portal.tests.api.test_experiment_resource.ExperimentResourceTestCase`
`method`), 186
`test_get_facility_by_id()`
 (`tardis.tardis_portal.tests.api.test_facility_resource.FacilityResourceTestCase`
`method`), 186
`test_get_facility_by_manager_group_id()`
 (`tardis.tardis_portal.tests.api.test_facility_resource.FacilityResourceTestCase`
`method`), 186
`test_get_facility_by_name()`
 (`tardis.tardis_portal.tests.api.test_facility_resource.FacilityResourceTestCase`
`method`), 186
`test_get_group_by_id()`
 (`tardis.tardis_portal.tests.api.test_group_resource.GroupResourceTestCase`
`method`), 186
`test_get_group_by_name()`
 (`tardis.tardis_portal.tests.api.test_group_resource.GroupResourceTestCase`
`method`), 186
`test_get_group_list()`
 (`tardis.tardis_portal.tests.views.test_auth_views.UserGroupListsTestCase`
`method`), 190
`test_get_instrument_by_id()`
 (`tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTestCase`
`method`), 186
`test_get_instrument_by_name()`
 (`tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTestCase`
`method`), 186
`test_get_receiving_box()`
 (`tardis.tardis_portal.tests.test_storage.ModelTestCase`
`method`), 200
`test_get_schema_by_id()`
 (`tardis.tardis_portal.tests.api.test_schema_resource.SchemaResourceTestCase`
`method`), 187
`test_get_schema_by_namespace()`
 (`tardis.tardis_portal.tests.api.test_schema_resource.SchemaResourceTestCase`
`method`), 187
`test_get_session_expiry()`
 (`tardis.tardis_portal.tests.test_tokens.TokenTestCase`
`method`), 201
`test_get_session_expiry_expired_token()`
 (`tardis.tardis_portal.tests.test_tokens.TokenTestCase`
`method`), 201
`test_get_session_expiry_near_expiry()`
 (`tardis.tardis_portal.tests.test_tokens.TokenTestCase`
`method`), 201
`test_get_storage_box_attr_list_from_box_id()`
 (`tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxResourcesTestCase`
`method`), 187
`test_get_storage_box_by_id()`
 (`tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxResourcesTestCase`
`method`), 187
`test_get_storage_box_option_by_id()`
 (`tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxResourcesTestCase`
`method`), 187
`test_get_storage_box_option_list_from_box_id()`
 (`tardis.tardis_portal.tests.api.test_storagebox_resources.StorageBoxResourcesTestCase`
`method`), 187
`test_get_user_by_id()`
 (`tardis.tardis_portal.tests.api.test_user_resource.UserResourceTestCase`
`method`), 186

method), 188
test_get_user_by_username() (*tardis.tardis_portal.tests.api.test_user_resource.UserResourceTest* confirmation() *method*), 191
method), 188
test_get_user_list() (*tardis.tardis_portal.tests.views.test_auth_views.UserGroupListsTestCase* reset() *method*), 196
method, 190
test_get_user_list() (*tardis.tardis_portal.tests.views.test_auth_views.UserListTestCase* UserMigration_creation() *method*), 199
method, 190
test_getgroupbyid() (*tardis.tardis_portal.tests.test_ldap.LDAPTest* test_parameter() (*tardis.tardis_portal.tests.test_models.ModelTestCase* *method*), 197
method), 197
test_getgroups() (*tardis.tardis_portal.tests.test_ldap.LDAPTest* parameterset_as_string() *method*), 197
method, 197
test_getgroupsforentity() (*tardis.tardis_portal.tests.test_ldap.LDAPTest* test_permissions_checks() *method*), 197
method, 197
test_getuserbyid() (*tardis.tardis_portal.tests.test_ldap.LDAPTest* test_pkey_to_credential() *method*), 197
method, 197
test_image_filename_parameters() (*tardis.tardis_portal.tests.test_parameters.ParametersTestCase* test_dataset() *method*), 198
method, 198
test_init() (*tardis.apps.openid_migration.tests.test_forms.OpenIDMigrationFormTestCase* *method*), 84
method, 84
test_instrument() (*tardis.tardis_portal.tests.test_models.ModelTestCase* test_post_dataset_with_params() *method*), 198
method, 198
test_is_expired() (*tardis.tardis_portal.tests.test_tokens.TokenTestCase* test_post_experiment() *method*), 201
method, 201
test_keys_from_private_key_only() (*tardis.apps.push_to.tests.test_models.ModelsTestCase* test_post_instrument() *method*), 90
method, 90
test_link_parameter_type() (*tardis.tardis_portal.tests.test_parametersets.ParameterSetMutationTestCase* test_post_single_file() *method*), 199
method, 199
test_link_parameter_type_extra() (*tardis.tardis_portal.tests.test_parametersets.ParameterSetMutationTestCase* test_pretty_serializer() *method*), 199
method, 199
test_link_urls() (*tardis.tardis_portal.tests.test_parameters.ParametersTestCase* test_rename_instrument() *method*), 198
method, 198
test_login() (*tardis.tardis_portal.tests.tests.UserInterfaceTestCase* test_retrieve_access_list_tokens() *method*), 201
method, 201
test_manage_account() (*tardis.tardis_portal.tests.views.test_auth_views.ManageAccountTestCase* test_require_valid_owner() *method*), 190
method, 190
test_migrate_accounts() (*tardis.apps.openid_migration.tests.test_views.OpenIDMigrationViewTestCase* *method*), 85
method, 85
test_move() (*tardis.tardis_portal.tests.test_copy_move.CopyMoveTestCase* test_search_random_token() *method*), 195
method, 195
test_mydata_view() (*tardis.tardis_portal.tests.test_tokens.TokenTestCase* *method*), 201
method, 201

test_save_with_random_token_failures() (*tardis.tardis_portal.tests.test_tokens.TokenTestCase*
 method), 201
 test_save_with_random_token_gives_up() (*tardis.tardis_portal.tests.test_tokens.TokenTestCase*
 method), 201
 test_search() (*tardis.tardis_portal.tests.test_ldap.LDAPTest*
 method), 197
 test_search() (*tardis.tardis_portal.tests.test_ldap.LDAPTest*
 method), 197
 test_searchgroups() (*tardis.tardis_portal.tests.test_ldap.LDAPTest*
 method), 197
 test_sftp() (*tardis.apps.sftp.tests.test_sftp.SFTPTTest*
 method), 107
 test_sftp_dynamic_docs_dataset() (*tardis.apps.sftp.tests.test_sftp.SFTPTTest*
 method), 107
 test_sftp_dynamic_docs_experiment() (*tardis.apps.sftp.tests.test_sftp.SFTPTTest*
 method), 107
 test_sftp_key_connect() (*tardis.apps.sftp.tests.test_sftp.SFTPTTest*
 method), 107
 test_shared_fs_many_files() (*tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest*
 method), 184
 test_shared_fs_single_file() (*tardis.tardis_portal.tests.api.test_datafile_resource.DataFileResourceTest*
 method), 184
 test_shared_view() (*tardis.tardis_portal.tests.views.test_template_contexts.ExperimentallyTest*
 method), 191
 test_simple_search_authenticated_user() (*tardis.apps.search.tests.test_api.SimpleSearchTest*
 method), 103
 test_simple_search_unauthenticated_user() (*tardis.apps.search.tests.test_api.SimpleSearchTest*
 method), 103
 test_storageboxoption() (*tardis.tardis_portal.tests.test_storage.ModelTestCase*
 method), 200
 test_tar_experiment_download() (*tardis.tardis_portal.tests.test_tar_download.TarDownloadTestTask*
 method), 200
 test_token_delete() (*tardis.tardis_portal.tests.test_tokens.TokenTestCase*
 method), 201
 test_tz_aware_date_handling() (*tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase*
 method), 199
 test_tz_naive_date_handling() (*tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase*
 method), 199
 test_unauthorized_instrument_access_attempt() (*tardis.tardis_portal.tests.api.test_instrument_resource.InstrumentResourceTest*
 method), 186
 test_unresolvable_link_parameter() (*tardis.tardis_portal.tests.test_parametersets.ParameterSetManagerTestCase*
 method), 199
 test_upload_complete() (*tardis.tardis_portal.tests.views.test_upload_views.UploadTestCases*
 method), 191
 test_urls() (*tardis.tardis_portal.tests.tests.UserInterfaceTestCase*
 method), 201
 test_urls_with_some_content() (*tardis.tardis_portal.tests.tests.UserInterfaceTestCase*
 method), 201
 TEST_UTILS_DIR (*tardis.tardis_portal.tests.slapi.Slapd*
 attribute), 192
 test_wrong_size_verification() (*tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase*
 method), 200
 testAccessWithoutReadPerms() (*tardis.apps.related_info.tests.tests.TabTestCase*
 method), 99
 testAccessWithReadPerms() (*tardis.apps.related_info.tests.tests.TabTestCase*
 method), 99
 testAuthFileResourceTest() (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
 testAuthFileResourceTest() (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
 testCanDelete() (*tardis.apps.related_info.tests.tests.DeleteTestCase*
 method), 98
 testCanGetInfoAsJSON() (*tardis.tardis_portal.tests.test_iiif.Level0TestCase*
 method), 196
 testCanGetInfoAsXML() (*tardis.tardis_portal.tests.test_iiif.Level0TestCase*
 method), 196
 testCanGetJpegFormat() (*tardis.tardis_portal.tests.test_iiif.Level1TestCase*
 method), 197
 testCanGetOriginalImage() (*tardis.tardis_portal.tests.test_iiif.Level0TestCase*
 method), 196
 testCanGetRequiredFormats() (*tardis.tardis_portal.tests.test_iiif.Level2TestCase*
 method), 197
 testCantEditLockedExperiment() (*tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase*
 method), 199
 testChangeUserPermissions() (*tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase*
 method), 199
 testContext() (*tardis.tardis_portal.tests.test_publishservice.PublishServiceTestTask*
 method), 199

method), 200
testDatasetFile ()
 (*tardis.tardis_portal.tests.test_download.DownloadTestCase*
 method), 195
testDetectsBadInput ()
 (*tardis.apps.related_info.tests.tests.CreateTestCase*
 method), 98
testDetectsBadInput ()
 (*tardis.apps.related_info.tests.tests.UpdateTestCase*
 method), 99
testDownload () (*tardis.tardis_portal.tests.test_download.DownloadTestCase*
 method), 195
testDumpSchemas ()
 (*tardis.tardis_portal.tests.management.test_dumpschemas.DumpSchemaTestCase*
 method), 189
testExistsInOaipmh ()
 (*tardis.apps.related_info.tests.test_oaipmh.RifCSTestCase*
 method), 98
testGetGroupsForEntity ()
 (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
testGetRecord () (*tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase*
 method), 80
testGetRecord () (*tardis.apps.oaipmh.tests.provider.test_experiment.ExperimentProviderTestCase*
 method), 81
testGetRecord () (*tardis.apps.oaipmh.tests.provider.test_experiment.ExperimentProviderTestCase*
 method), 81
testGetRecord () (*tardis.apps.oaipmh.tests.test_oai.EndpointTestCase*
 method), 82
testGetRecordHandlesInvalidIdentifiers ()
 (*tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase*
 method), 81
testGroupProvider ()
 (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
testGroupSearch ()
 (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
testHandleRegions ()
 (*tardis.tardis_portal.tests.test_iiif.Level1TestCase*
 method), 197
testHandleRotation ()
 (*tardis.tardis_portal.tests.test_iiif.Level1TestCase*
 method), 197
testHandlesEmptySet ()
 (*tardis.apps.related_info.tests.tests.ListTestCase*
 method), 99
testHandlesFound ()
 (*tardis.apps.related_info.tests.tests.GetTestCase*
 method), 99
testHandleSizing ()
 (*tardis.tardis_portal.tests.test_iiif.Level1TestCase*
 method), 197
testHandleSizing ()
 (*tardis.tardis_portal.tests.test_iiif.Level2TestCase*
 method), 197
testHandlesMultipleEntries ()
 (*tardis.apps.related_info.tests.tests.ListTestCase*
 method), 99
testHandlesNotFound ()
 (*tardis.apps.related_info.tests.tests.GetTestCase*
 method), 99
testHandlesSingleEntry ()
 (*tardis.apps.related_info.tests.tests.ListTestCase*
 method), 99
testIdentify () (*tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase*
 method), 80
testIdentify () (*tardis.apps.oaipmh.tests.provider.test_experiment.ExperimentProviderTestCase*
 method), 81
testIdentify () (*tardis.apps.oaipmh.tests.test_oai.EndpointTestCase*
 method), 82
testImageCacheControl ()
 (*tardis.tardis_portal.tests.test_iiif.ExtraTestCases*
 method), 196
testImageHasEtags ()
 (*tardis.tardis_portal.tests.test_iiif.ExtraTestCases*
 method), 196
testInitialisation ()
 (*tardis.tardis_portal.tests.test_authservice.AuthServiceTestCase*
 method), 194
testInitialisation ()
 (*tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase*
 method), 200
testInitialisationNoProvider ()
 (*tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase*
 method), 200
testInteractive ()
 (*tardis.tardis_portal.tests.management.test_createuser.CreateUserTestCase*
 method), 188
testList () (*tardis.tardis_portal.tests.management.test_rmexperiment.RemoveExperimentTestCase*
 method), 189
testListIdentifiers ()
 (*tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase*
 method), 80
testListIdentifiers ()
 (*tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase*
 method), 81
testListIdentifiers ()
 (*tardis.apps.oaipmh.tests.test_oai.EndpointTestCase*
 method), 82
testListIdentifiersDoesNotHandleSets ()
 (*tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase*
 method), 81
testListMetadataFormats ()
 (*tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase*
 method), 80

method), 80
 testListMetadataFormats ()
 (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase
 method), 81
 testListMetadataFormats ()
 (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase
 method), 82
 testListRecords ()
 (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase
 method), 80
 testListRecords ()
 (tardis.apps.oaipmh.tests.provider.test_experiment.DcExperimentProviderTestCase
 method), 81
 testListRecords ()
 (tardis.apps.oaipmh.tests.provider.test_experiment.RifCsExperimentProviderTestCase
 method), 81
 testListRecords ()
 (tardis.apps.oaipmh.tests.test_oai.EndpointTestCase
 method), 82
 testListSets () (tardis.apps.oaipmh.tests.provider.test_base.BaseProviderTestCase
 method), 81
 testListSets () (tardis.apps.oaipmh.tests.provider.test_experiment.AbstractExperimentProviderTestCase
 method), 81
 testLoadSchemas ()
 (tardis.tardis_portal.tests.management.test_loadschemas.LowSideLoadTestCase
 method), 189
 testLocalFile () (tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase
 method), 200
 testManageAuthMethods ()
 (tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase
 method), 193
 testManageRifCsCheckContent ()
 (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase
 method), 200
 testManageRifCsCreateAndRemove ()
 (tardis.tardis_portal.tests.test_publishservice.PublishServiceTestCase
 method), 200
 testMustHaveWrite ()
 (tardis.apps.related_info.tests.tests.CreateTestCase
 method), 98
 testMustHaveWrite ()
 (tardis.apps.related_info.tests.tests.DeleteTestCase
 method), 99
 testMustHaveWrite ()
 (tardis.apps.related_info.tests.tests.UpdateTestCase
 method), 99
 testNoInput () (tardis.tardis_portal.tests.management.test_createuser.CreateUserTestCase
 method), 189
 testOwnedExperiments ()
 (tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase
 method), 194
 testReadAccess () (tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase
 method), 194
 testRemove () (tardis.tardis_portal.tests.management.test_removeexperiment.RemoveExperimentTestCase
 method), 189
 testSFTPWithoutHostKey ()
 (tardis.apps.sftp.provider.test_sftp.SFTPManagementTestCase
 method), 107
 testSimpleAuthenticate ()
 (tardis.tardis_portal.tests.test_authentication.AuthenticationTestCase
 method), 193
 testView () (tardis.tardis_portal.tests.test_download.DownloadTestCase
 method), 195
 testWriteAccess ()
 (tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase
 method), 195
 timeout (tardis.apps.sftp.sftp.MyTSFTPRequestHandler
 attribute), 111
 to_json () (tardis.apps.search.api.PrettyJSONSerializer
 method), 104
 to_json () (tardis.tardis_portal.api.PrettyJSONSerializer
 method), 126
 todatetime () (in module
 tardis.tardis_portal.tests.test_tasks.BackgroundTaskTestCase), 183
 Token (class in tardis.tardis_portal.models.token), 178
 token (tardis.tardis_portal.models.token.Token at-
 tribute), 179
 Token.DoesNotExist, 178
 token_delete () (in module
 tardis.tardis_portal.views.authorisation), 203
 token_set (tardis.tardis_portal.models.experiment.Experiment
 attribute), 151
 TokenServiceTestCase (class in
 tardis.tardis_portal.auth.token_auth), 128
 TokenGroupProvider (class in
 tardis.tardis_portal.auth.token_auth), 128
 TokenTestCase (class in
 tardis.tardis_portal.tests.test_tokens), 201
 oxmldatetime () (in module
 tardis.tardis_portal.templatetags.xmldate), 183
 track_download () (in module tardis.analytics.ga), 75
 track_login () (in module tardis.analytics.ga), 75
 track_logout () (in module tardis.analytics.ga), 75
 type (tardis.tardis_portal.models.parameters.Schema
 attribute), 178
 TYPE_CHOICES (tardis.tardis_portal.models.storage.StorageBoxOption
 attribute), 176
 UserACLTestCase (tardis.tardis_portal.models.storage.StorageBox
 attribute), 176
 UserACLTestCase (tardis.tardis_portal.models.storage.StorageBox
 attribute), 173
 types (tardis.tardis_portal.models.storage.StorageBox
 attribute), 173

attribute), 173

U

UncachedTarStream (class in *tardis.tardis_portal.download*), 224

units (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 170

unpickled_value (*tardis.tardis_portal.models.storage.StorageBox* attribute), 178

UnsupportedSearchQueryTypeError, 225

update_all_files() (*tardis.apps.sftp.sftp.DynamicTree* method), 111

update_dataset_files() (*tardis.apps.sftp.sftp.DynamicTree* method), 111

update_datasets() (*tardis.apps.sftp.sftp.DynamicTree* method), 111

update_detail() (*tardis.tardis_portal.api.ACLAuthorization* method), 214

update_experiments() (*tardis.apps.sftp.sftp.DynamicTree* method), 111

update_list() (*tardis.tardis_portal.api.ACLAuthorization* method), 214

update_mimetype() (*tardis.tardis_portal.models.datafile.DataFile* method), 143

update_nothing() (*tardis.apps.sftp.sftp.DynamicTree* method), 111

update_time (*tardis.tardis_portal.models.experiment.Experiment* attribute), 151

UpdateTestCase (class in *tardis.apps.related_info.tests.tests*), 99

upload_auth() (in module *tardis.tardis_portal.auth.decorators*), 126

upload_complete() (in module *tardis.tardis_portal.views.upload*), 207

UPLOAD_METHOD (in module *tardis.default_settings.uploads*), 122

UploadTestCase (class in *tardis.tardis_portal.tests.views.test_upload_views*), 191

uri (*tardis.tardis_portal.models.datafile.DataFileObject* attribute), 145

url (*tardis.tardis_portal.models.experiment.Experiment* attribute), 151

url (*tardis.tardis_portal.models.experiment.ExperimentAuth* attribute), 152

url (*tardis.tardis_portal.models.license.License* attribute), 156

URL (*tardis.tardis_portal.models.parameters.ParameterName* attribute), 168

urls (*tardis.tardis_portal.tests.test_authorisation.ObjectACLTestCase* attribute), 194

urls (*tardis.tardis_portal.tests.test_tokens.TokenTestCase* attribute), 201

USE_FILTERS (in module *tardis.default_settings.filters*), 120

use_rapid_connect() (in module *tardis.tardis_portal.views.pages*), 207

user (*tardis.apps.push_to.models.Credential* attribute), 92

user (*tardis.apps.sftp.models.SFTPPublicKey* attribute), 110

user (*tardis.tardis_portal.models.access_control.GroupAdmin* attribute), 135

user (*tardis.tardis_portal.models.access_control.UserProfile* attribute), 139

user (*tardis.tardis_portal.models.token.Token* attribute), 179

user_acls() (*tardis.tardis_portal.managers.ExperimentManager* method), 232

user_details_processor() (in module *tardis.tardis_portal.context_processors*), 222

user_guide() (in module *tardis.tardis_portal.views.pages*), 207

user_id (*tardis.apps.push_to.models.Credential* attribute), 92

user_id (*tardis.apps.sftp.models.SFTPPublicKey* attribute), 110

user_id (*tardis.tardis_portal.models.access_control.GroupAdmin* attribute), 135

user_id (*tardis.tardis_portal.models.access_control.UserProfile* attribute), 139

user_id (*tardis.tardis_portal.models.token.Token* attribute), 179

USER_MENU_MODIFIERS (in module *tardis.default_settings.apps*), 117

user_menu_processor() (in module *tardis.tardis_portal.context_processors*), 222

user_migration (*tardis.apps.openid_migration.models.OpenidACLMig* attribute), 87

user_migration_id (*tardis.apps.openid_migration.models.OpenidACLMigration* attribute), 87

user_migration_obj() (*tardis.apps.openid_migration.models.OpenidACLMigrationAdm* method), 87

user_owned_groups() (*tardis.tardis_portal.managers.ExperimentManager* method), 232

UserAuthentication (class in *tardis.tardis_portal.models.access_control*), 137

UserAuthentication.DoesNotExist, 138
 UserAuthentication.MultipleObjectsReturned, 138
 userauthentication_set (tardis.tardis_portal.models.access_control.UserProfile attribute), 139
 UserAuthenticationAdmin (class in tardis.tardis_portal.admin), 214
 UserGroupListsTestCase (class in tardis.tardis_portal.tests.views.test_auth_views), 190
 UserInterfaceTestCase (class in tardis.tardis_portal.tests.tests), 201
 UserListTestCase (class in tardis.tardis_portal.tests.views.test_auth_views), 190
 username (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 138
 UserProfile (class in tardis.tardis_portal.models.access_control), 138
 userProfile (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 138
 UserProfile.DoesNotExist, 139
 UserProfile.MultipleObjectsReturned, 139
 userProfile_id (tardis.tardis_portal.models.access_control.UserAuthentication attribute), 138
 UserProvider (class in tardis.tardis_portal.auth.interfaces), 127
 UserResource (class in tardis.tardis_portal.api), 221
 UserResource.Meta (class in tardis.tardis_portal.api), 221
 UserResourceTest (class in tardis.tardis_portal.tests.api.test_user_resource), 188
 users () (tardis.tardis_portal.managers.ExperimentManager method), 232
V
 validate_remote_path () (in module tardis.apps.push_to.views), 98
 validation (tardis.apps.sftp.api.SFTPPublicKeyAppResource.Meta attribute), 108
 value (tardis.tardis_portal.models.storage.StorageBoxAttribute attribute), 177
 value (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 178
 value_from_datadict () (tardis.tardis_portal.widgets.CommaSeparatedInput method), 235
 value_type (tardis.tardis_portal.models.storage.StorageBoxOption attribute), 178
 verbose_name (tardis.analytics.apps.AnalyticsConfig attribute), 75
 verbose_name (tardis.apps.openid_migration.apps.OpenidMigrationConfig attribute), 85
 verbose_name (tardis.apps.push_to.apps.PushToConfig attribute), 90
 verbose_name (tardis.apps.search.apps.SearchConfig attribute), 105
 verbose_name (tardis.apps.sftp.apps.SFTPConfig attribute), 108
 verbose_name (tardis.apps.social_auth.apps.SocialAuthConfig attribute), 117
 verified (tardis.tardis_portal.models.datafile.DataFile attribute), 143
 verified (tardis.tardis_portal.models.datafile.DataFileObject attribute), 145
 verify () (tardis.tardis_portal.models.datafile.DataFile method), 143
 verify_file () (tardis.tardis_portal.api.DataFileResource method), 215
 verify_remote_access () (tardis.tardis_portal.api.DataFileResource method), 215
 verify_remote_access () (tardis.tardis_portal.models.datafile.DataFile method), 143
 version (tardis.tardis_portal.models.datafile.DataFile attribute), 143
 view_functions (tardis.tardis_portal.shortcuts.RestfulExperimentParameter attribute), 234
 ViewTemplateContextsTest (class in tardis.tardis_portal.tests.views.test_template_contexts), 191
W
 wait () (tardis.tardis_portal.tests.slapped.Slapped method), 193
 which () (in module tardis.tardis_portal.tests.slapped), 193
 widget (tardis.tardis_portal.forms.StaticField attribute), 230
 widgets (tardis.apps.push_to.models.CredentialForm.Meta attribute), 92
 widgets (tardis.tardis_portal.admin.DatafileAdminForm.Meta attribute), 210
 widgets (tardis.tardis_portal.admin.DataFileObjectInlineForm.Meta attribute), 209
 widgets (tardis.tardis_portal.admin.StorageBoxAttributeInlineForm.Meta attribute), 212
 widgets (tardis.tardis_portal.admin.StorageBoxForm.Meta attribute), 213
 widgets (tardis.tardis_portal.admin.StorageBoxOptionInlineForm.Meta attribute), 213
 widgets (tardis.tardis_portal.forms.RightsForm.Meta attribute), 230

```
write() (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
        method), 80
write_permissions_required() (in module
                              tardis.tardis_portal.auth.decorators), 126
write_template_to_dir()
    (tardis.tardis_portal.xmlwriter.XMLWriter
     static method), 235
write_template_to_file()
    (tardis.tardis_portal.xmlwriter.XMLWriter
     static method), 236
write_xml_to_file()
    (tardis.tardis_portal.xmlwriter.XMLWriter
     static method), 236
writeExperimentMetadata()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider
     static method), 80
writeMetadata() (tardis.apps.oaipmh.provider.base.BaseProvider
                 method), 79, 243
writeMetadata() (tardis.apps.oaipmh.server.ProxyingMetadataRegistry
                 method), 82
writeRegistryObjectsWrapper()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
     method), 80
writeRelatedAuthor()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
     method), 80
writeRelatedInfo()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
     method), 80
writeRelatedUser()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
     method), 80
writeSubject() (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider.ExperimentWriter
                method), 80
writeUserMetadata()
    (tardis.apps.oaipmh.provider.experiment.RifCsExperimentProvider
     static method), 80
```

X

```
XMLWriter (class in tardis.tardis_portal.xmlwriter),
          235
```